

County Surveyor's Record, Douglas County, Oregon

18796

Subdivision of Section 13,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="margin-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 6° 06' W., 80.7 lks. dist., with brass cap mkd. RM CE 1/16 S13 53.3 FT TO COR 1989 and an arrow pointing to the corner.</p> <p style="margin-left: 40px;">The marks BX0 chiseled in a sandstone outcrop, 4 ft. wide, 2 ft. high, bears N. 0¼° W., 13½ lks. dist.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Corner is located on small spur, slopes E.</p> <p>From this point, a point established as an approximate center E 1/16 sec. cor. of sec. 13 by C.W. Worthylake et al., employees of Davidson Industries, Inc., in 1968, record held by Davidson Industries, Inc., Mapleton Oregon, bears N. 87° 05' W., 0.964 chs. dist., monumented with an iron pipe, ¼ in. diam., firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Worthylake et al:</p> <p style="margin-left: 40px;">A fir, 13 ins. diam., bears N. 85° W., 27 lks. dist., with healed blaze.</p> <p>Ascend E. slope, over steep rock bluff.</p>
20.30	Enter timber, edge bears E. and S.
20.90	Top of rock bluff, edge bears N. 30° E. and S. 30° W.
24.50	Divide between Siuslaw and Smith river drainages, bears N. and S.; desc. NW. slope.
26.60	U.S. Forest Service Road No. 4890, gravel, 20 lks. wide, bear N. 20° E. and S. 40° W., in a curve; desc. broken N. slope.
38.730	The center ¼ sec. cor. of sec. 13.
	Ascend NE. slope.
39.50	Spur, slopes N. 60° W.; desc. broken SW. slope.
75.70	Spur, slopes N. 50° W.; desc. SW. slope.
77.730	The ¼ sec. cor. of secs. 13 and 14.
	<hr style="border: 0.5px solid black;"/> <p>From the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 3° 48' 00" E., on the N. and S. center line of the SE¼ of sec. 13.</p> <p>Descend broken NE. slope, through logged area.</p>
22.50	Overgrown rock road, 15 lks. wide, bears N. 60° W. and E.; asc. SW. slope.
23.225	Point for the SE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SE¼.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S13 1989</p>
	from which