

County Surveyor's Record, Douglas County, Oregon

18798

Subdivision of Section 24,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS													
	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 77° E., 5½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 20½° W., 19½ lks. dist., mkd. C¼ S24 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend S. slope, through logged area.</p>												
47.10	Spur, slopes S. 70° E.; desc. broken N. slope.												
69.705	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td style="text-align: center;">N 1/16</td><td style="text-align: center;"> </td><td style="text-align: center;">S 24</td></tr> <tr><td></td><td style="text-align: center;">C</td><td></td></tr> <tr><td></td><td style="text-align: center;">1989</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 89° 44'E., 81.1 lks. dist., with brass cap mkd. RM CN 1/16 53.5 FT TO COR S24 1989 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 60¼° W., 10½ lks. dist., mkd. CN 1/16 S24 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend broken S. slope.</p>		C		N 1/16		S 24		C			1989	
	C												
N 1/16		S 24											
	C												
	1989												
92.70	Ravine, drains S. 30° E.; asc. SW. slope.												
93.040	The ¼ sec. cor. of secs. 13 and 24.												
	<p>From the ¼ sec. cor. of sec. 24 only, on the E. bdy. of the Tp. N. 89° 12' 00" W., on the E. and W. center line of sec. 24. Over North Fork Smith River.</p>												
0.70	Right bank North Fork Smith River, bears N. 40° E. and S. 30° W., 60 lks. wide, course S. 40° W.; asc. broken SE. slope, through timber.												
38.500	The center ¼ sec. cor. of sec. 24.												
	Descend broken S. slope, through logged area.												
57.700	<p>Point for the center W 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr><td style="text-align: center;">C</td><td style="text-align: center;">W 1/16</td><td style="text-align: center;">C</td></tr> <tr><td></td><td style="text-align: center;"> </td><td></td></tr> <tr><td></td><td style="text-align: center;">S 24</td><td></td></tr> <tr><td></td><td style="text-align: center;">1989</td><td></td></tr> </table> </div> <p>from which</p>	C	W 1/16	C					S 24			1989	
C	W 1/16	C											
	S 24												
	1989												