

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 24,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18799

CHAINS	
	A fir, 5 ins. diam., bears N. 77 $\frac{1}{4}$ ° E., 19 $\frac{1}{2}$ lks. dist., mkd. CW 1/16 S24 BT.
	A fir, 4 ins. diam., bears S. 24 $\frac{1}{2}$ ° E., 7 lks. dist., mkd. XBT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend S. slope, through logged area.
60.30	Spur, slopes S. 30° W.; desc. over broken SW. slope, enter timber, edge bears N. 30° E. and S. 30° W.
73.10	Spur, slopes S. 50° E.; desc. over S. slope.
76.900	The $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	From the N 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp. S. 89° 23' 00" W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 24.
	Descend NW. slope, through timber, posting true line.
2.60	Toe of hill, edge bears N. 70° E. and S. 70° W.; over flood plain and abandoned river channels.
4.70	Left bank of the North Fork Smith River, bears N. 40° E. and S. 40° W.; 100 lks. wide, course S. 40° W.
6.10	Right bank of the North Fork Smith River, bears N. 40° E. and S. 40° W.; over a flood plain.
8.50	Toe of hill, edge bears N. and S.; asc. over E. slope, through logged area.
14.90	Spur, slopes S. 80° E.; continue ascent over E. slope.
21.30	Rock road, 20 lks. wide, bears N. 20° E. and S. 20° W.
22.60	Spur, slopes S. 30° E.; desc. over SW. slope.
24.10	Same road, bears N. 40° W. and S. 40° E.
30.50	Creek, 1 lk. wide, course S. 20° E.; asc. over E. slope.
37.30	Spur, slopes S. 40° E.; desc. over S. slope.
38.530	The center N 1/16 sec. cor. of sec. 24.
	From the center W 1/16 sec. cor. of sec. 24.
	N. 3° 55' 30" E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 24.
	Ascend S. slope, through logged area.
4.00	Spur, slopes S. 40° W., enter timber, edge bears N. 40° E. and S. 40° W.; asc. SW. slope.
6.30	Spur, slopes S. 40° E.; desc. over broken NE. slope.
21.70	Spur, slopes S. 40° E.; desc. over E. slope.
23.185	Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd: