

County Surveyor's Record, Douglas County, Oregon 36

18800

Subdivision of Section 24,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	NW 1/16 S24 1989
	<p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 9° W., 54 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 49° W., 39 lks. dist., mkd. NW 1/16 S24 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as an approximate NW 1/16 sec. cor. of sec. 24 by C.E. Worthylake et al., employees of Davidson Industries, Inc., in 1968, record held by Davidson Industries, Inc., Mapleton, Oregon, and perpetuated as a working corner by a U.S. Forest Service cutting boundary agreement survey in 1974, record held at Mapleton Ranger Station, bears S. 78° 46' W., 0.570 chs. dist.; monumented with a 3/4 in. angle iron, top portion bent, lower portion firmly set, projecting 12 ins. above ground, from which the remains of a bearing tree mkd. by Worthylake et al:</p> <p style="padding-left: 40px;">A partially uprooted hemlock snag, 21 ins. diam., 10 ft. high, bears N. 41° W., 11 lks. dist., mkd. with a yellow tag.</p> <p>and the remains of bearing trees mkd. in 1974</p> <p style="padding-left: 40px;">A hemlock stump, 20 ins. diam., 10 ft. high, bears S. 53° W., 33 lks. dist., mkd. with a yellow tag.</p> <p style="padding-left: 40px;">A hemlock stump, 17 ins. diam., 10 ft. high, bears S. 24° E., 62 lks. dist., mkd. with nails.</p> <p>Ascend SE. slope, posting true line.</p>
24.80	Spur, slopes S. 30° E.; over E. slope.
27.00	Ravine, drains S. 40° E.; asc. over S. slope.
29.70	Spur, slopes S. 70° E.; desc. over NE. slope.
31.90	Ravine, drains S. 80° E.; asc. over SE. changing to E. slope.
41.30	U.S. Forest Service Road No. 48-910, gravel, 25 lks. wide, bears N. 70° E. and S. 40° W.; in a curve; asc. over S. slope.
43.30	Spur, slopes S. 40° E.; desc. over E. slope.
45.10	Creek, 1 lk. wide, course S. 40° E.; asc. over S. slope.
45.90	Spur, slopes S. 40° E.; desc. over E. slope.
46.370	The W 1/16 sec. cor. of secs. 13 and 24.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 24.</p> <p>N. 89° 38' 30" W., on the E. and W. center line of the NW 1/4 of sec. 24.</p> <p>Descend S. slope, through logged area, posting true line.</p>
1.40	Slope changes to desc. W. slope.
5.10	Ravine, drains S. 50° W.; asc. over S. slope.
6.10	Spur, slopes S. 40° W.; desc. over SW. slope.