

County Surveyor's Record, Douglas County, Oregon 37

Subdivision of Section 24,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18801

CHAINS

7.90 A dry creek, course S. 20° E.; asc. over E. slope.

11.20 Spur, slopes S. 40° E.; desc. over rolling S. slope.

16.20 Ravine, drians S. 30° E.; asc. over E. slope.

19.270 The NW 1/16 sec. cor. of sec.24.

Ascend broken E. slope.

38.535 The N 1/16 sec. cor. of secs. 23 and 24.

Subdivision of Section 27,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 27 and 34.

N. 0° 36' 00" W., on the N. and S. center line of sec. 27.

Ascend broken SE. slope, through timber.

21.90 U.S. Forest Service Road No. 48-922, gravel, 25 lks.wide, bears N. 70° E. and S. 70° W.; asc. over S. slope, through logged area.

22.470 Point for the center S 1/16 sec.cor.of sec. 27.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd:

C
S 1/16 | S 27
C
1989

from which

A fir stump, 42 ins. diam., bears N.35° 10' E., 36.9 lks. dist. to a railroad spike driven in top, mkd.
CS 1/16 S27 BT.

A fir, 33 ins. diam., bears S. 57° E., 182 lks. dist., mkd. CS 1/16 S27 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

44.30 Enter timber, edge bears N.80° W. and S. 70° E.; over level ground.

44.940 Point for the center 1/4 sec. cor. of sec.27, at intersection with the E. and W. center line.

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd:

T19S R10W
C 1/4 S 27
1989

from which

A fir, 38 ins. diam., bears S. 26° W., 25 lks. dist., mkd. C 1/4 S27 BT.

A hemlock, 17 ins. diam., bears N. 45 1/2° W., 80 lks.dist., mkd. C 1/4 S27 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.