

County Surveyor's Record, Douglas County, Oregon 38

18802

Subdivision of Section 27,
T. 19 S., R. 10 W., Willamette Meridian, Oregon

CHAINS	
	Descend gradually over nearly level spur.
49.70	Begin steep descent over NW. slope.
55.10	U.S. Forest Service Road No.48, asphalt, 25 lks. wide, bears N. 40° E. and S. 40° W.
56.20	Peach Creek, 5 lks. wide, course S. 60° W.; asc. over SW. slope, through logged area.
56.90	Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.; asc. over broken SW. slope.
90.220	The ¼ sec. cor. of secs. 22 and 27.
	<hr/> From the ¼ sec. cor. of secs. 26 and 27.
	N. 89° 20' 30" W., on the E. and W. center line of sec. 27.
	Descend SW. slope, through timber.
1.20	Ravine, drains S. 10° E.; asc. over E. slope.
3.10	Spur, slopes S.; desc. over SW. slope.
5.10	Creek, 2 lks. wide, course S.; asc. over SE. slope.
6.50	U.S. Forest Service Road No. 48, asphalt, 25 lks. wide, bears N. 40° E. and S. 30° W., in a curve.
6.90	Top of ascent, slopes S.; desc. over rolling S. slope.
19.430	Point for the center E 1/16 sec. cor. of sec. 27.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:
	$\begin{array}{c} C \quad E \ 1/16 \quad C \\ \quad \quad S \ 27 \\ \quad \quad 1989 \end{array}$
	from which
	A hemlock, 7 ins. diam., bears S. 72½° E., 12 lks. dist., mkd. CE 1/16 S27 BT.
	A fir, 25 ins. diam., bears N. 65° W., 20 lks. dist., mkd. CE 1/16 S27 BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
31.80	U.S. Forest Service Road No. 48, asphalt, 25 lks. wide, bears N. 10° E. and S. 10° E., in a curve; desc. over broken W. slope.
38.860	The center ¼ sec. cor. of sec. 27.
	Over level ground.
47.20	U.S. Forest Service Road No. 48, asphalt, 25 lks. wide, bears N. 30° E. and S. 20° W., in a curve, desc. over W. slope.
47.90	West Branch North Fork Smith River, 20 lks. wide, course S. 20° W.; asc. over E. slope.
58.90	Spur, slopes S. 10° E.; desc. over broken SW. slope.
76.80	Creek, 2 lks. wide, course N. 20° W.; asc. over NE. slope.
77.280	The ¼ sec. cor. of secs. 27 and 28.