

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 27,  
T. 19 S., R. 10 W., Willamette Meridian, Oregon

18803

CHAINS	
	From the E 1/16 sec. cor. of secs. 27 and 34.
	N. 1° 06' 30" W., on the N. and S. center line of the SE¼ of sec. 27.
	Over level ground, through timber, posting true line.
2.50	U.S. Forest Service Road No. 23, asphalt, 25 lks. wide, bears N. 70° W. and E.; in a curve.
2.70	Barbed wire fence, bears N. 70° W. and E., 6 lks. dist. to corner of fences bearing N. and W.; desc. over N. slope.
3.10	Creek, 2 lks. wide, course N. 70° W.; over level ground.
6.30	Barbed wire fence, bears N. 50° E. and S. 40° W., on top of creek bank; desc. over NW. slope.
6.70	Left bank of the North Fork Smith River, bears N. 50° E. and S. 50° W., 90 lks. wide, course S. 50° W.
8.00	Right bank of the North Fork Smith River, bears N. 60° E. and S. 60° W.; asc. over SW. slope.
11.90	Graveled road, 20 lks. wide, bears N. 70° E. and S. 70° W.
12.10	Top of ascent, slopes S. 70° W.; over level ground.
13.00	Enter logged area, edge bears E. and W.
18.30	Begin ascent over SW. slope.
19.30	Enter timber, edge bears E. and W.
22.525	Point for the SE 1/16 sec. cor. of sec. 27, at intersection with the E. and W. center line of the SE¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd:
	SE 1/16 S27 1989
	from which
	A fir, 50 ins. diam., bears S. 44° W., 35 lks. dist., mkd. SE 1/16 S27 BT.
	A fir, 47 ins. diam., bears N. 17° W., 87 lks. dist., mkd. X BT.
	Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
	From this point, a point established as a working SE 1/16 sec. cor. of sec. 27 by a U.S. Forest Service cutting boundary agreement survey in 1977, record held at the Mapleton Ranger Station, bears S. 5° 29' E., 2.860 chs. dist., monumented with a ¾ in. angle iron, firmly set, projecting 18 ins. above ground, from which the bearing trees mkd. in 1977:
	A fir, 35 ins. diam., bears N. 15° E., 31 lks. dist., with an aluminum tag.
	A fir, 42 ins. diam., bears S. 59½° W., 42 lks. dist., with an aluminum tag.
32.70	U.S. Forest Service Road No. 48-922, gravel, 25 lks. wide, bears N. 60° W. and S. 60° E.
33.10	Spur, slopes N. 60° W.; desc. over broken N. slope