

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 18,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

18807

CHAINS	
	<p>A fir, 11 ins. diam., bears N. 38° E., 19 lks. dist., with healed blaze.</p> <p>A fir, 10 ins. diam., bears S. 72½° W., 15 lks. dist., with healed blaze.</p> <p>N. 0° 27' 00" E., on the N. and S. center line of sec. 18.</p> <p>Descend over broken N. slope, through scattering timber and dense undergrowth.</p>
3.35	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
6.80	Same Road, 15 lks wide, bears N. 30° E. and S. 30° W.
9.00	Slope changes to broken NW.; continue to descend.
22.80	Power transmission line, 3 wires, bears N. 40° W. and S. 40° E.
23.70	Power transmission line, 3 wires, bears N. 40° W. and S. 40° E.
27.50	Power transmission line, 3 wires, bears N. 25° W. and S. 25° E.
31.90	Creek, 3 lks. wide, course N. 70° W.; asc. over S. slope.
32.70	Spur, slopes N. 20° W.; desc. over broken NW. slope.
33.70	Creek, 4 lks. wide, course N. 80° W.; asc. over broken SW. slope.
39.765	<p>Point for the centr ¼ sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 4 ft. base, to top, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S R 4 W</p> <p> C ¼</p> <p> S 18</p> <p> 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears S. 38° E., 84 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="margin-left: 40px;">A cedar, 15 ins. diam., bears S. 35° W., 86½ lks. dist., mkd. C ¼ S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue over broken SW. slope.</p>
45.10	Dirt road, 15 lks. wide, bers N. 25° W. and S. 25° E.
50.50	Spur, slopes W.; desc. over NW. slope.
56.80	Ravine, drains W.; asc. over broken SW. slope.
59.10	Spur, slopes N. 50° W.; desc. over NW. slope.
59.395	<p>Point for the center N. 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p> C</p> <p>N 1/16 S 18</p> <p> C</p> <p> 1989</p> </div>