

County Surveyor's Record, Douglas County, Oregon

18809

Subdivision of Section 18,
T. 28 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
19.715	<p>Point for the center E 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin: 10px 0;"> <p>C <u>E 1/16</u> C</p> <p> S 18</p> <p> 1989</p> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 73½° E., 31 lks. dist., mkd. CE 1/16 S18 BT.</p> <p style="margin-left: 40px;">A cedar, 9 ins. diam., bears N. 44¾° W., 65 lks. dist., mkd. CE 1/16 S18 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Continue over steep W. slope.</p>
29.60	Creek, 2 lks. wide, course S. 40° W.; desc. over SW. slope.
37.40	Dirt road, 15 lks. wide, bears N. 40° W. and S. 40° E.
39.430	The center ¼ sec. cor. of sec. 18.
44.60	Power transmission line, 3 wires, bears N. 25° W. and S. 25° E.
52.40	Power transmission line, 3 wires, bears N. 40° W. and S. 40° E.
54.00	Power transmission line, 3 wires, bears N. 40° W. and S. 40° E.
57.70	Melton Creek, 5 lks. wide, course N. 60° W.; asc. over broken NE. slope.
78.575	<p>The ¼ sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 28 S</p> <p>R 5 W R 4 W</p> <p> ¼</p> <p> S 13 S 18</p> <p> 1974</p> </div> <p>from which bearing trees mkd. by Popken</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears N. 24° E., 72½ lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 32½° W., 31 lks. dist., with healed blaze.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the center E 1/16 sec. cor. of sec. 18.</p> <p>N. 0° 52' 00" E., on the N. and S. center line of the NE¼ of sec. 18.</p> <p>Ascend over broken SW. slope, through scattering timber and dense undergrowth.</p>
8.40	Spur, slopes W.; desc. over broken NW. slope.
19.20	Bottom of descent, slopes W.; asc. over gentle SW. slope.
19.680	Point for the NE 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the NE¼.