

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

18815

CHAINS

T 29 S R 7 W
S 32 | S 33
1924

from which the remains of a bearing tree mkd. by Mensch

A sawed fir stump, 14 ins. diam., bears N. 72° W.,
16 lks. dist., with fragmentary scribe marks visible
on opened blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor,
in 1962

A fir, 17 ins. diam., bears N. 33½° E., 86 lks. dist.,
with healed double blaze.

A fir, 20 ins. diam., bears N. 30° W., 133 lks. dist.,
with healed blaze.

N. 89° 18' 30" W., on the S. bdy. of sec. 32.

Descend over broken NW. slope, through heavy timber and dense
undergrowth.

30.680

The ¼ sec. cor. of sec. 32 only, T. 29½ S. R. 7 W., perpetuated and
recorded by Ben B. Irving, Deputy County Surveyor, in 1954, and
further perpetuated and recorded by James W. Byron, Deputy County
Surveyor, in 1962; monumented with an iron post, 1 in. diam., firmly
set, projecting 6 ins. above ground, with brass cap mkd.

¼ S 32
T 29½ S
1924

from which the remains of the original bearing trees

A sawed fir stump, 19 ins. diam., bears S. 41° E.,
22 lks. dist., with healed blaze.

A sawed fir stump, 10 ins. diam., bears S. 52° W., 30 lks.
dist., no marks visible on partially healed blaze.

and the remains of a bearing tree mkd. by Irving

A fir snag, 26 ins. diam., bears South, 136 lks. dist.,
with healed double blaze.

and the remains of a bearing tree mkd. by Byron

A broken top cedar, 16 ins. diam., bears S. 53° E.,
64 lks. dist., with healed double blaze.

and new bearing trees

A fir, 10 ins. diam., bears S. 25° E., 19 lks. dist.,
mkd. ¼ S32 BT.

A cedar, 14 ins. diam., bears S. 6° W., 20 lks. dist.,
mkd. ¼ S32 BT.

N. 89° 18' 30" W., beginning new measurement.

Descend over broken NW. slope.

7.805

The ¼ sec. cor. of sec. 32 only, T. 29 S., R. 7 W., perpetuated and
recorded by Ben B. Irving, Deputy County Surveyor, in 1954, and
further perpetuated and recorded by James W. Byron, Deputy County
Surveyor, in 1962; monumented with an iron post, 1 in. diam., firmly
set, projecting 12 ins. above ground, with brass cap mkd.