

# County Surveyor's Record, Douglas County, Oregon

18816

Dependent Resurvey of a Portion of the South Boundary,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

1/4 S32  
1924

from which the remains of bearing trees mkd. by Irving

A fir, 18 ins. diam., bears N. 50 $\frac{1}{4}$ ° E., 18 $\frac{1}{2}$  lks. dist.,  
with healed double blaze.

A rotted fir stob, 8 ins. diam., bears N. 20° W.,  
7 lks. dist., with scribe marks BT visible.

and a bearing tree mkd. by Byron

A fir, 14 ins. diam., bears N. 63° W., 32 lks. dist.,  
with healed double blaze.

---

S. 88° 16' 30" W., beginning new measurement.

Descend over broken NW. slope.

- 0.95 Ditch, 15 lks. wide, bears NE. and S. 60° E.
- 10.25 Olalla Creek, 25 lks. wide, course N. 35° E.; asc. over SE. slope.
- 11.600 Point for the W 1/16 sec. cor. of sec. 32 only, T. 29 $\frac{1}{2}$  S., R. 7 W.  
Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 24 ins. in  
the ground, with brass cap mkd:

W 1/16 S 32  
1988

from which

A cedar, 12 ins. diam., bears S. 33 $\frac{1}{2}$ ° E., 64 $\frac{1}{2}$  lks.  
dist., mkd. W 1/16 S32 BT.

A fir, 10 ins. diam., bears S. 23 $\frac{1}{2}$ ° W., 41 lks. dist.,  
mkd. W 1/16 S32 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel  
post.

From this point a corner established and recorded by Russell B.  
Bass, Registered Land Surveyor No. 558, in 1976, bears S. 82° 24'  
E., 0.015 chs. dist., monumented with a stainless steel pipe, 1 $\frac{1}{4}$   
ins. diam., loosely set, projecting 24 ins. above ground, from which  
a bearing tree mkd. by Bass:

A fir, 28 ins. diam., bears S. 39° W., 53 lks. dist.,  
with healed blaze.

This point was established using improper procedure and is not  
utilized in this survey.

Ascend over SE. slope.

- 12.30 Olalla Creek County Road No.38, tarred surface, 30 lks. wide, bears  
N. 40° E. and SW.
- 30.995 The true point for the closing cor. of secs. 31 and 32, T. 29 $\frac{1}{2}$  S.,  
R. 7 W., hereinafter described.  
Ascend over NE. slope, through young timber and light undergrowth.
- 38.680 The cor. of secs. 31 and 32 only, T. 29 S., R. 7 W., monumented with  
an iron post, 2 ins. diam., firmly set, projecting 12 ins. above  
ground, with brass cap mkd.