

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 7 W., Willamette Meridian, Oregon

18817

CHAINS

T 29 S R 7 W
S 31 | S 32
1924

from which the only remaining bearing tree mkd. by Mensch

A white fir, 31 ins. diam., bears N.70° E., 82 lks.
dist., with healed blaze.

No other suitable trees available

Dependent Resurvey of a portion of the South Boundary,
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars, in 1882,
and the resurvey by Fred Mensch, in 1924)

From the ¼ sec. cor. of secs. 5 and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 9 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 29½ S R 7 W
¼ S 32
S 5
T 30 S
1962

from which the remains of the original bearing trees

A rotted oak stump, 18 ins. diam., bears S. 24° W.,
27 lks. dist., no marks visible.

A rotted oak stump, 22 ins. diam., bears N.83° W., 39
lks. dist., no marks visible. (Record, N. 86° W., 42 lks.)

and bearing trees mkd. by Mensch

A ponderosa pine, 37 ins. diam., bears N. 34° E.,
210 lks. dist., with fragmentary scribe marks visible
on partially healed blaze.

A fir, 20 ins. diam., bears S. 12° E., 15 lks. dist.,
with healed blaze.

and a bearing tree mkd. by Byron

A fir, 8 ins. diam., bears N. 66½° W., 20 lks. dist.,
with healed double blaze.

S. 87° 35' 00" W., bet. secs. 5 and 32, marking and blazing the true line.

Descend over broken NW. slope, through heavy timber and light undergrowth.

17.20 Slope changes to SW.

19.420 Point for the W 1/16 sec. cor. of secs. 5 and 32.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd:

W 1/16 S 32
S 5
1988