

County Surveyor's Record, Douglas County, Oregon

18818

Dependent Resurvey of a Portion of the South Boundary,
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 13 ins. diam., bears S. 75° E., 100 lks. dist.,
mkd. W 1/16 S5 BT.

A fir, 20 ins. diam., bears N. 78° W., 40 lks. dist.,
mkd. W 1/16 S32 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Descend over SW. slope.

22.25 Ditch, 15 lks. wide, bears N. and S.

28.30 Olalla Creek, 35 lks. wide, course N. 10° W.; asc. over SE. slope.

29.70 Olalla Creek County Road No. 38, gravel, 30 lks. wide, bears
N. 15° E. and S. 15° W.

31.70 Spur, slopes N. 20° E.; desc. over NW. slope.

32.75 Creek, 4 lks. wide, course N. 10° E.; asc. over E. slope.

38.840 The cor. of secs. 5, 6, 31, and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with a sandstone, firmly set 24 x 18 x 9 ins. above a mound of stone, 4 ft. base, 1 ft. high, plainly mkd. with 5 notches on E. face, 1 notch on the W. face, and X on top, from which the remains of the original bearing trees:

A fir, 26 ins. diam., bears N. 42° E., 14 lks. dist.,
with healed double blaze.

A live oak, 6 ins. diam., bears S. 46° E., 10 lks. dist.,
with partially healed rotted blaze. (Record, 12 lks.)

A fir, 43 ins. diam., bears S. 45° W., 76 lks. dist., with
healed blaze and fragmentary scribe marks visible on bark.

A fir, 52 ins. diam., bears N. 44° W., 65 lks. dist.,
with healed blaze. (Record, 56 lks.)

and a bearing tree mkd. by Byron

A fir, 8 ins. diam., bears S. 11° E., 46 lks. dist.,
with healed double blaze.

Due to the rocky, steep slope and the permanency and excellent condition of the stone monument, it was left to mark the corner position.

From this point, United States Coast and Geodetic Survey triangulation station "BUCK MOUNTAIN" bears S. 50° 03' 01" E., 201.182 chs. dist., monumented with a brass tablet, 3½ ins. diam., firmly set flush with bedrock, mkd. BUCK MTN 1942 and a triangle.

(Restoring the survey by Fred Mensch, in 1924)

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, and further perpetuated and recorded by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1984; monumented with a brass tablet, 2 ins. diam., firmly set flush in solid rock, with top mkd.

T 29½ S
S32 | S33 R
5 | 4 7
1984

LS 498 T 30 S