

County Surveyor's Record, Douglas County, Oregon

18820

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A maple snag, 9 ins. diam., bears S. 29° W., 52 lks. dist., with scribe marks T29 R W 3 BT visible on partially healed blaze.</p> <p>and a bearing tree recorded by Wofford, Popken, and Carlson</p> <p style="text-align: center;">A fir, 60 ins. diam., bears S. 63° W., 24 lks. dist., with healed blaze.</p> <p>Corner lies on a N. slope.</p> <p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp. N. 0° 02' 30" W., bet. secs. 31 and 32.</p> <p>Ascend over broken SE. slope, through heavy timber and light undergrowth.</p>
3.40	Base of rock bluff, 60 feet high.
9.980	<p>Point for the S-S 1/64 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin-left: 100px;"> S S 1/64 S 31 S 32 1988 </div> <p>from which</p> <p style="text-align: center;">A cedar, 26 ins. diam., bears S. 70° E., 10½ lks dist., mkd. SS 1/64 S32 BT.</p> <p style="text-align: center;">A fir, 41 ins. diam., bears S. 51° W., 48 lks. dist., mkd. SS 1/64 S31 BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p>
19.960	<p>Point for the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <div style="text-align: center; margin-left: 100px;"> S 1/16 S 31 S 32 1988 </div> <p>from which</p> <p style="text-align: center;">A fir, 12 ins. diam., bears N. 46¼° E., 53 lks. dist., mkd. S 1/16 S32 BT.</p> <p style="text-align: center;">A fir, 4 ins. diam., bears N. 51½° W., 48 lks. dist., mkd. X BT.</p> <p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p>
22.95	Spur, slopes N. 60° E.; desc. over N. slope.
28.220	<p>True point for the closing cor. of secs. 31 and 32, at intersection with the S. bdy. of T. 29 S., R. 7 W.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd:</p>