

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, 18921
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 29 S R 7 W
 $\frac{S 32}{S 31 | S 32}$
 C C
 T 29½ S R 7 W
 1988

from which

A fir, 8 ins. diam., bears S.84° E., 21 lks. dist.,
mkd. T29½S R7W S32 CC BT.

A fir, 7 ins. diam., bears S. 17° W., 27 lks. dist.,
mkd. T29½S R7W S31 CC BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the original closing cor. of secs. 31 and 32, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, bears N. 0° 02' 30" W., 0.070 chs. dist., monumented with an iron post, 1¼ ins. diam., firmly set flush with the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T29½S R 7 W S31 S32 1962, from which the remains of an original bearing tree:

A root hole, bears S. 53° W., 41 lks. dist., with a down and rotted fir alongside, 12 ins. diam., no marks visible on rotted blaze.

and a bearing tree mkd. by Byron

A yew, 22 ins. diam., bears S. 66° E., 35 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A fir, 8 ins. diam., bears S. 77° W., 16 lks. dist., mkd. T29½S R7W S31 BT.

From this same point, the cor. of secs. 31 and 32 only, T. 29 S., R. 7 W., bears S. 88° 16' 30" W., 7.685 chs. dist., hereinbefore described.

Subdivision of Section 32,
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

From the ¼ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.

N. 0° 06' 30" W., on the N. and S. center line of sec. 32.

Descend over broken NW. slope, through heavy timber and light undergrowth.

20.045 Point for the center S 1/16 sec. cor. of sec. 32.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

C
 $\frac{S 1/16 | S 32}{C}$
 1988

from which

A fir, 18 ins. diam., bears N. 55¼° E., 54 lks.
mkd. X BT.

A fir, 15 ins. diam., bears S. 4¾° E., 56 lks. dist.,
mkd. CS 1/16 S32 BT.