

County Surveyor's Record, Douglas County, Oregon

18922

Subdivision of Section 32,
T. 29½ S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a corner established and recorded by Russell B. Bass, Registered Land Surveyor No. 558, bears North, 0.002 chs. dist., monumented with a stainless steel pipe, 1¼ ins. diam., firmly set, projecting 9 ins. above ground, from which a bearing tree mkd. by Bass:</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 39° W., 17 lks. dist., with healed blaze.</p> <p>This point was established using improper procedure and is not utilized in this survey.</p> <p>Descend over broken NW. slope.</p>
27.435	<p>The ¼ sec. cor. of sec. 32 only, on the N. bdy. of the Tp.</p> <hr style="border: 0.5px solid black;"/> <p>From the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>S. 87° 44' 00" W., on the E. and W. center line of the SE¼ of sec. 32.</p> <p>Descend over broken NW. slope, through heavy timber and dense underground.</p>
39.380	<p>The center S 1/16 sec. cor. of sec. 32.</p> <hr style="border: 0.5px solid black;"/> <p>From the W 1/16 sec. cor. of sec. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 05' 00" W., on the N. and S. center line of the SW¼ of sec. 32.</p> <p>Ascend over SW. slope, through heavy timber and light undergrowth.</p>
2.90	<p>Spur, slopes N. 50° W.; desc. over NE. slope.</p>
9.995	<p>Point for the center S-SW 1/64 sec. cor. of secs. 32.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 32 C S SW 1/64 1988</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 79½° E., 5 lks. dist., mkd. C S SW 1/64 S32 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 21¼° W., 52 lks. dist., mkd. X BT.</p>
19.990	<p>Deposit white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NW. slope.</p> <p>Point for the SW 1/16 sec. cor. of sec. 32, at intersection with the E. and W. center line of the SW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:</p> <p style="text-align: center;">SW 1/16 S 32 1988</p>