

CHAINS

DUPLICATE

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
AND SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF SECTIONS 14, 23, AND 35,
TOWNSHIP 20 SOUTH, RANGE 7 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Wayne L. Rogers, Cadastral Surveyor

Under Special Instructions dated July 20, 1989, approved July 21, 1989,
and Supplemental Special Instructions dated April 24, 1990,
approved April 25, 1990,
which provided for the surveys included under Group No. 1502,
and Assignment Instructions dated July 28, 1989, and May 9, 1990.

Survey commenced August 28, 1989

Survey completed April 18, 1991

T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of sections 14, 23, and 35, township 20 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The north boundary and a portion of the subdivisional lines of township 21 south, range 7 west was surveyed by Laban H. Wheeler, U. S. Deputy Surveyor, in 1883.

The survey of the subdivisional lines of township 21 south, range 7 west was completed by William P. Wright, U. S. Deputy Surveyor, in 1884.

The south boundary was resurveyed and the subdivisional lines of township 20 south, range 7 west were surveyed by Thomas E. Todd, U. S. Deputy Surveyor, in 1891.

A portion of the subdivisional lines was dependently resurveyed by Harvey E. Wofford and Lester E. Fischer, Cadastral Surveyors, in 1976-1978.

A portion of the south boundary and subdivisional lines was resurveyed by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, in 1983-1984.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 20, 1989, and Supplemental Special Instructions dated April 24, 1990, for Group No. 1502, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding public lands were blazed. All lines not forming a closure were measured twice.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weight 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the ¼ section corner of sections 11 and 14, as determined from a tie to Geodetic Control Station No. EC 41049, established by the Bureau of Land Management, is as follows:

Latitude 43° 50' 16.22" N. Longitude 123° 29' 54.85" W.

T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The geographic position (NAD 1927) of the corner of sections 35 and 36, as determined from a traverse tie to Geodetic Control Station No. EC 41050, established by the Bureau of Land Management, is as follows:

Latitude 43° 46' 51.16" N. Longitude 123° 29' 20.36" W.

The mean magnetic declination is 18½° East.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the survey by Laban H. Wheeler, in 1883,
and the resurvey by Thomas E. Todd in 1891)

Beginning at the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp., perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, year unknown, further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1962, as recorded in Douglas County Surveyors Office Corner Renewal File No. 31, determined at record bearing and distance from the remains of an original bearing tree:

A sawed fir stump, 50 ins. diam., bears N. 6° W., 45 lks. dist., with scribe marks 7W S visible on opened blaze.

and the remains of a bearing tree mkd. by Haines

A sawed fir stump, 34 ins. diam., bears N. 33° W., 104 lks. dist., no marks visible.

and a bearing tree mkd. by Godfrey

A madrone, 19 ins. diam., bears N. 51° E., 78 lks. dist., no marks visible.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T20S R7W

S35 S36

S2

T21S R7W

1990

from which new bearing trees

A fir, 4 ins. diam., bears N. 59° E., 47 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears N. 67° W., 10 lks. dist., mkd. T20S R7W S35 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	<p>The corner is located in the cutbank of a graveled road, 20 lks. wide, bears N. 60° W. and S. 60° E.</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41050, at latitude 43° 46' 57.245" N., longitude 123° 29' 25.276" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N. 30° 19' 00" W., 10.822 chs. dist., monumented with an aluminum cap, 2½ ins. diam., firmly set flush with the ground, in a gravel filled perforated pipe, 4 ins. diam., with top mkd. EC 41050 GPS 1990.</p> <p>S. 88° 17' 00" W., on the S. bdy. of sec. 35.</p> <p>Descend over broken SW. slope through heavy timber and dense undergrowth.</p>
0.40	Graveled road, 20 lks. wide, bears N. 60° W. and S. 60° E.
21.05	Amberson Creek, 3 lks. wide, course N.; asc. over NE. slope.
21.505	<p>Point for the ¼ sec. cor. of sec. 2 only, T. 21 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <u>T20S R7W</u> ¼ S2 T21S R7W 1990 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 52½° E., 18 lks. dist., mkd. ¼ S2 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 65° W., 8 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over NE. slope.</p>
28.65	Spur, slopes N. 15° W.; desc. over NW. slope.
32.65	Ravine, drains N. 35° E.; asc. over NE. slope.
39.455	<p>Point for the ¼ sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <u>T20S R7W</u> ¼ S35 T21S R7W 1990 </div>

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 77° E., 62 lks. dist., mkd. ¼ S35 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 9° W., 45 lks. dist., mkd. ¼ S35 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over NE. slope.</p>
40.05	Ridge, bears NW. and S. 30° E.; desc. over SW. slope.
48.90	Bottom of descent, drains S.; asc. over SE. slope.
57.45	Spur, slopes SW.; desc. over NW. slope.
61.400	<p>Point for the cor. of secs. 2 and 3 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <u>T20S R7W</u> S3 S2 T21S R7W 1990 </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 14° E., 13½ lks. dist., mkd. T21S R7W S2 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 74° W., 21 lks. dist., mkd. T21S R7W S3 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located at the edge of a landing with a graveled road, 15 lks. wide, bears S. 15° E.</p> <p>Descend over broken NW. slope.</p>
78.910	<p>The cor. of secs. 34 and 35 only, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;"> <u>T20S R7W</u> <u>S34 S35</u> S3 T21S R7W 1983 </p> <p>from which bearing trees mkd. by Rogers and Bishop</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 78½° E., 20 lks. dist., with healed blaze.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

A fir, 13 ins. diam., bears N. 38½° W., 28 lks. dist., with healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the survey by Thomas E. Todd, in 1891, and the
resurvey by Harvey E. Wofford and Lester E. Fischer in 1976-1978)

From the cor. of secs. 35 and 36 only, on the S. bdy. of the Tp.
N. 0° 27' 00" W., bet. secs. 35 and 36.

Ascend over SW. slope through heavy reproduction timber and dense undergrowth.

0.40	Spur, slopes NW.; desc. over NE. slope.
9.80	Creek, 3 lks. wide, course N. 40° W.; asc. over broken SW. slope.
32.65	Spur, slopes W.; desc. over NW. slope.
39.260	The ¼ sec. cor. of secs. 35 and 36, perpetuated but not recorded by Wilford N. Haines, Registered Land Surveyor No. 239, year unknown, monumented with the original stone, 30 x 20 x 10 ins., loosely set, with ¼ S visible on W. face (alongside of which is a "T" shaped iron rod, 1 in. diam., firmly set, projecting 24 ins. above ground, with washer mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE), from which the remains of the original bearing trees: <p style="margin-left: 40px;">A sawed fir stump, 65 ins. diam., bears S. 5° E., 10 lks. dist., with scribe marks ¼ visible on opened blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 74 ins. diam., bears N. 8° W., 114 lks. dist., no marks visible. (Record, 120 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T20S R7W ¼ S35 S36 1990 </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A maple, 6 ins. diam., bears N. 45° E., 12 lks. dist., mkd. ¼ S36 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 77° W., 26 lks. dist., mkd. ¼ S35 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Deposit a white "DEEP-1" magnetic marker and T iron at the base and the original stone alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 20' 00" W., beginning new measurement.</p> <p>Descend over NW. slope.</p> <p>0.45 Ravine, drains W.; asc. over SW. slope.</p> <p>10.45 Spur, slopes W.; desc. over N. slope.</p> <p>12.75 Ravine, drains N. 60° W.; asc. over broken SW. slope.</p> <p>31.30 Spur, slopes N. 35° W.; desc. over NE. slope.</p> <p>37.60 Top of spur, in saddle, slopes from N. 30° E. and S. 30° W.; asc. along SW. slope.</p> <p>39.840 The cor. of secs. 25, 26, 35, and 36, perpetuated but not recorded by Leo J. Martin, Registered Land Surveyor No. 363, year unknown, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 3, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE</p> <table style="margin-left: auto; margin-right: auto; border: none;"> <tr> <td style="padding-right: 20px;">FD. OK by</td> <td>T20S</td> </tr> <tr> <td>D. Edwards</td> <td><u>S26</u> <u>S25</u></td> </tr> <tr> <td>6/1998</td> <td>S35 S36</td> </tr> <tr> <td>M130-2</td> <td>R7W</td> </tr> <tr> <td></td> <td>1958</td> </tr> </table> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, 14 ins. diam., bears N. 54° E., 6 lks. dist., with scribe marks BT visible on overgrowth.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 61° W., 9 lks. dist., with axe marks visible on decayed blaze.</p> <p style="padding-left: 40px;">A fir snag, 20 ins. diam., bears N. 21° W., 19 lks. dist., with healed blaze. (Record, N. 40° W.)</p> <p>and the remains of the bearing trees mkd. by Martin</p> <p style="padding-left: 40px;">A fir snag, 24 ins. diam., bears N. 64° E., 13 lks. dist., with scribe marks 363 T20S R7W S25 BT visible on bark blaze.</p> <p style="padding-left: 40px;">A fir snag, 28 ins. diam., bears S. 29° E., 21 lks. dist., with scribe marks T20S R7W S36 BT CS visible on open blaze.</p> <p style="padding-left: 40px;">A fir snag, 32 ins. diam., bears S. 18° W., 24 lks. dist., with healed blaze.</p> <p>and new bearing trees</p>	FD. OK by	T20S	D. Edwards	<u>S26</u> <u>S25</u>	6/1998	S35 S36	M130-2	R7W		1958
FD. OK by	T20S										
D. Edwards	<u>S26</u> <u>S25</u>										
6/1998	S35 S36										
M130-2	R7W										
	1958										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

A fir, 5 ins. diam., bears N. 83° E., 27 lks. dist., mkd. T20S R7W S25 BT.

A fir, 5 ins. diam., bears S. 51½° E., 22 lks. dist., mkd. T20S R7W S36 BT.

A fir, 4 ins. diam., bears S. 58° W., 28 lks. dist., mkd. X BT.

A fir, 4 ins. diam., bears N. 27½° W., 13½ lks. dist., mkd. X BT.

From the cor. of secs. 23, 24, 25, and 26, perpetuated but not recorded by Wilford N. Haines, Registered Land Surveyor No. 239, year unknown, further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 7, and further perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 41, monumented with "T" shaped iron rod, 1 in. diam., firmly set, projecting 1 in. above ground, with washer mkd. WILFORD N HAINES RLS 239 SURVEY PT DRAIN ORE, from which the remains of the original bearing trees:

A sawed fir stump, 36 ins. diam., bears N. 3° E., 18 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 18° E.).

A fir snag, 25 ins. diam., bears S. 14° W., 27 lks. dist., with healed blaze. (Record, S. 20° W.)

A fir snag, 36 ins. diam., bears N. 26° W., 16 lks. dist., with healed blaze. (Record, N. 2° W., 20 lks.)

and the remains of a bearing tree mkd. by Byron

A fir snag, 29 ins. diam., bears S. 38° E., 27 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and the remains of bearing trees mkd. by Godfrey

A cedar, 13 ins. diam., bears S. 25° W., 92 lks. dist., with scribe marks T20S R7W S23 B visible on bark blaze.

A cedar snag, 28 ins. diam., bears N. 68° W., 73 lks. dist., with scribe marks W S26 B visible on opened blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground directly atop T iron, with brass cap mkd.

Fd. Ok by	T20S R7W
R. Ward	<u>S23 S24</u>
3/2001	S26 S25
M 136-60 & C.S. 65/36-17B	1989

from which new bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 12 ins. diam., bears N. 89° E., 58 lks. dist., mkd. T20S R7W S24 BT.</p> <p>A hemlock, 6 ins. diam., bears S. 20° E., 48 lks. dist., mkd. T20S R7W S25 BT.</p> <p>An alder, 10 ins. diam., bears N. 20° W., 30 lks. dist., mkd. T20S R7W S23 BT on bark.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>N. 1° 10' 00" E., bet. secs. 23 and 24, marking and blazing the true line.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
2.90	Dirt road, 20 lks. wide, bears N. 15° W. and S. 15° E.
39.260	<p>The ¼ sec. cor. of secs. 23 and 24, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 6, monumented with the original sandstone, 36 x 28 ins. (record, 40 x 30 ins.), firmly set, mkd. X on top and ¼ on W. face, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A decayed fir snag, 30 ins. diam., bears N. 86° E., 26 lks. dist., no marks visible. (Record, 30 lks.)</p> <p style="padding-left: 40px;">A decayed fir snag, 20 ins. diam., bears S. 40° W., 21 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 61° E., 77 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 45 ins. diam., bears N. 65½° W., 97 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a brass tablet, 3½ ins. diam., 3¼ in. stem, cemented flush in drill hole in the center of the X on the corner stone, with top mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T20S R7W</p> <p style="margin-left: 40px;">¼</p> <p>S23 S24</p> <p>1989</p> <hr style="width: 20%; margin: 0 auto;"/> </div> <p>N. 0° 22' 00" E., beginning new measurement.</p> <p>Ascend over SW. slope.</p>
1.75	Spur, slopes S. 40° E.; desc. along broken NE. slope.
4.95	Spur, slopes N. 50° E.; desc. over broken NW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
23.70	Ravine, drains E.; asc. over SE. slope.
31.35	Spur, slopes N. 75° E.; desc. over N. slope.
36.15	Ravine, drains E.; asc. over SE. slope.
38.970	<p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T20S <u>S14</u> <u>S13</u> S23 S24 R7W 1958</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears N. 47° E., 10 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 60 ins. diam., bears S. 40° W., 35 lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1958, as recorded in Douglas County Surveyor's Office Corner File No. 2</p> <p style="padding-left: 40px;">A sawed cedar stump, 36 ins. diam., bears N. 2½° E., 62 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A hemlock, 23 ins. diam., bears N. 18° W., 123½ lks. dist., with healed blaze.</p> <p>and the bearing trees mkd. by Wofford and Fischer</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 62° E., 17 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears N. 21° W., 66 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 49° E., 17 lks. dist., mkd. T20S R7W S24 BT.</p> <hr/> <p>N. 0° 12' 30" E., bet. secs. 13 and 14.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
9.10	Ridge, bears W. and S. 75° E.; desc. over NW. slope.
16.55	Ravine, drains E.; asc. over broken SE. slope.
34.70	Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E., also, ridge, bears N. 60° W. and S. 80° E.; desc. over NW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
39.140	<p>The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T20S R7W ¼ S14 S13 1977</p> <p>from which bearing trees mkd. by Wofford and Fischer</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 6° E., 49 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 80° W., 60 lks. dist., with healed blaze.</p> <hr/> <p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>S. 88° 24' 00" W., bet. secs. 26 and 35.</p> <p>Descend over broken SW. slope through heavy timber and dense undergrowth.</p>
3.90	Ravine, drains N. 55° W.; asc. over broken NE. slope.
10.60	Spur, slopes N.; desc. over broken NW. slope.
26.25	Dirt road, 20 lks. wide, bears N. 60° W. and S. 60° E.
28.70	Graveled road, 20 lks. wide, bears N. 30° W. and S. 30° E.
39.135	<p>The ¼ sec. cor. of secs. 26 and 35, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 66, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 16 ins. above ground, from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A cedar, 46 ins. diam., bears S. 30° W., 15 lks. dist., with weathered blaze.</p> <p>and the remains of a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A maple snag, 48 ins. diam., bears N. 22° W., 65 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p>Fd. Ok by T20S R7W 6/1998 S26 M130-2 ¼ S35 1990</p> <p>from which a new bearing tree</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS											
	<p>An ash, 13 ins. diam., bears N. 69° E., 67 lks. dist., mkd. ¼ S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 87° 49' 00" W., bet. secs. 23 and 26.</p> <p>Descend over SW. slope through heavy timber and dense undergrowth.</p>										
0.90	Creek, 5 lks. wide, course S. 20° E.; asc. over SE. slope.										
34.10	Spur, slopes N. 75° E.; desc. over NW. slope.										
38.65	Head of ravine, drains N. 30° E.; asc. over SE. slope.										
39.030	<p>Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Fd. Ok by</td> <td style="width: 50%;">T20S R7W</td> </tr> <tr> <td>D. Edwards</td> <td>S23</td> </tr> <tr> <td>6/1998</td> <td>¼</td> </tr> <tr> <td>M130-2</td> <td>S26</td> </tr> <tr> <td></td> <td>1989</td> </tr> </table> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 66° W., 18 lks. dist., mkd. ¼ S26 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 55° W., 74 lks. dist., mkd. ¼ S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p>	Fd. Ok by	T20S R7W	D. Edwards	S23	6/1998	¼	M130-2	S26		1989
Fd. Ok by	T20S R7W										
D. Edwards	S23										
6/1998	¼										
M130-2	S26										
	1989										
41.40	Ridge, bears N. 35° W. to saddle, and S. 35° E.; desc. over SW. slope changing to NW. slope.										
58.40	Ravine, drains S. 65° W.; asc. over SE. slope.										
58.545	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%;">S23</td> </tr> <tr> <td style="width: 50%; text-align: center;">W 1/16</td> <td style="width: 50%;"></td> </tr> <tr> <td style="width: 50%;"></td> <td style="width: 50%;">S26</td> </tr> <tr> <td style="width: 50%;"></td> <td style="width: 50%;">1989</td> </tr> </table> <p>from which</p>		S23	W 1/16			S26		1989		
	S23										
W 1/16											
	S26										
	1989										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS																	
	<p>A fir, 26 ins. diam., bears N. 38° E., 37 lks. dist., mkd. W 1/16 S23 BT.</p> <p>A fir, 35 ins. diam., bears S. 84° E., 39 lks. dist., mkd. W 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over SE. slope.</p>																
61.35	Spur, slopes S.; desc. over SW. slope.																
65.50	Graveled road, 25 lks. wide, bears N. 20° W. and S. 20° E.																
70.25	Haney Creek, 15 lks. wide, course S. 55° E.; asc. over NE. slope.																
76.40	Spur, slopes N. 30° E.; desc. over NW. slope.																
78.060	<p>The cor. of secs. 22, 23, 26, and 27, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 71, and further perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1976, as recorded in Douglas County Surveyor's Office Corner Renewal File No. 81; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground (alongside of which is the original stone, 14 x 12 x 10 ins. [record, 18 x 14 x 10 ins.], mkd. X on top, and an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground), with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;">Fd. OK by</td> <td>T20S</td> <td>R7W</td> <td>WM</td> </tr> <tr> <td>D. Edwards</td> <td><u>S22</u></td> <td><u>S23</u></td> <td></td> </tr> <tr> <td>6/1998</td> <td>S27</td> <td>S26</td> <td></td> </tr> <tr> <td>M130-2</td> <td></td> <td>1976</td> <td></td> </tr> </table> <p>from which the remains of the original bearing trees</p> <p>A fir, 49 ins. diam., bears N. 9½° E., 84 lks. dist., no marks visible on opened, axed blaze. (Record, N. 7° E., 95 lks.)</p> <p>A cedar stub, size indeterminate, bears S. 70° E., 60 lks. dist., no marks visible. (Record, S. 66° E., 54 lks.)</p> <p>A cedar, 46 ins. diam., bears N. 55° W., 113 lks. dist., with open, burned blaze. (Record, 118 lks.)</p> <p>and bearing trees mkd. by Shaner</p> <p>A fir, 18 ins. diam., bears N. 16 3/4° E., 114 lks. dist., with healed blaze.</p> <p>A fir, 27 ins. diam., bears S. 86½° E., 144 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 31 ins. diam., bears S. 85¼° W., 37 lks. dist., with healed blaze.</p>	Fd. OK by	T20S	R7W	WM	D. Edwards	<u>S22</u>	<u>S23</u>		6/1998	S27	S26		M130-2		1976	
Fd. OK by	T20S	R7W	WM														
D. Edwards	<u>S22</u>	<u>S23</u>															
6/1998	S27	S26															
M130-2		1976															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 29 ins. diam., bears N. 28¼° W., 51 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <hr/> <p>From the ¼ sec. cor. of secs. 22 and 23, perpetuated and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, as recorded in Douglas County Surveyor's Office Map File No. M35-3, from original evidence no longer in existence; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above gravel bar in Haney Creek, from which the bearing trees mkd. by Haines:</p> <p style="padding-left: 40px;">An alder, 27 ins. diam., bears N. 83° E., 41 lks. dist., with scribe marks ¼ S23 BT visible on bark blaze.</p> <p style="padding-left: 40px;">A maple, 39 ins. diam., bears S. 82° W., 109 lks. dist., with scribe marks ¼ S22 BT visible on opened, double blaze.</p> <p>and a reference monument of which I have no record</p> <p style="padding-left: 40px;">An iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, bears N. 88° 15' E., 0.265 chs. dist.</p> <p>and a new reference monument</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 30° W., 37.9 lks. dist., with brass cap mkd. RM ¼ S22 25 FT 1989 and an arrow pointing to the corner.</p> <p>N. 1° 04' 00" E., bet. secs. 22 and 23.</p> <p>Ascend along nearly level creek bottom.</p>
1.05	Haney Creek, 20 lks. wide, course S. from SW.; continue along creek bottom.
2.30	Haney Creek, 20 lks. wide, course S. 60° E.; continue along creek bottom.
7.65	Haney Creek, 20 lks. wide, course S. 10° W.; continue along creek bottom.
10.10	Haney Creek, 20 lks. wide, course S. 50° E. from S. 55° W.; continue along creek bottom.
12.50	Haney Creek, 20 lks. wide, course S. 60° E.; continue along creek bottom.
13.80	Haney Creek, 20 lks. wide, course S. 55° W.; continue along creek bottom.
19.955	<p>The N 1/16 sec. cor. of secs. 22 and 23, established and recorded by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, as recorded in Douglas County Surveyor's Office Map File No. M35-3, further perpetuated and recorded by Stephen J. Flause, Deputy County Surveyor, in 1981, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., loosely set, projecting 6 ins. above ground, from which a bearing tree mkd. by Haines:</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS									
	<p>An alder, 29 ins. diam., bears N. 2° W., 39 lks. dist., with scribe marks 1/16 S22 BT visible on bark blaze.</p> <p>and a bearing tree mkd. by Flauser</p> <p>An alder, 14 ins. diam., bears S. 1° W., 32 lks. dist., with scribe marks 1/16 S22 CS BT visible on bark blaze.</p> <p>and a new reference monument</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 85° E., 60.6 lks. dist., with brass cap mkd. RM N 1/16 S23 40 FT 1990 and an arrow pointing to the corner.</p> <p>The corner is located at the top of an undercut creek bank.</p> <p style="text-align: center;">_____</p> <p>N. 0° 58' 00" E., beginning new measurement. Continue along nearly level creek bottom.</p>								
1.40	Haney Creek, 20 lks. wide, course S. 15° E.; continue along creek bottom.								
1.75	Haney Creek, 20 lks. wide, course S. 35° W.; continue along creek bottom.								
13.50	Haney Creek, 20 lks. wide, course SE.; continue along creek bottom.								
15.40	Haney Creek, 10 lks. wide, course SW.; continue along creek bottom.								
16.45	Haney Creek, 10 lks. wide, course S. 80° E.; continue along creek bottom.								
19.945	<p>The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td>T20S</td> <td>R7W</td> </tr> <tr> <td><u>S15</u></td> <td><u>S14</u></td> </tr> <tr> <td>S22</td> <td>S23</td> </tr> <tr> <td colspan="2">1977</td> </tr> </table> </div> <p>from which the remains of the bearing trees mkd. by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, as recorded in Douglas County Surveyor's Office Map File No. M35-3</p> <p>A fir snag, 22 ins. diam., bears N. 83° E., 61½ lks. dist., with healed double blaze.</p> <p>An alder, 25 ins. diam., bears S. 72° E., 48½ lks. dist., with scribe marks T20S R7W S23 BT visible on bark blaze.</p> <p>A fir, 23 ins. diam., bears S. 2° W., 100 lks. dist., with healed double blaze.</p> <p>A cedar, 19 ins. diam., bears N. 33° W., 65 lks. dist., with healed double blaze.</p>	T20S	R7W	<u>S15</u>	<u>S14</u>	S22	S23	1977	
T20S	R7W								
<u>S15</u>	<u>S14</u>								
S22	S23								
1977									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	and a new bearing tree
	A maple, 12 ins. diam., bears N. 55° E., 82 lks. dist., mkd. T20S R7W S14 BT.
	From the cor. of secs. 13, 14, 23, and 24.
	S. 89° 00' 00" W., bet. secs. 14 and 23.
	Ascend over SE. slope through heavy timber and dense undergrowth.
3.90	Spur, slopes S.; desc. over SW. slope.
9.05	Ravine, drains S. 30° E.; asc. over SE. slope.
19.440	Point for the E 1/16 sec. cor. of secs. 14 and 23.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S14 E 1/16 S23 1989
	from which
	A fir, 5 ins. diam., bears S. 44° W., 16 lks. dist., mkd. X BT.
	A fir, 7 ins. diam., bears N. 16° W., 5½ lks. dist., mkd. E 1/16 S14 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over SE. slope.
20.75	Ridge, in saddle, bears N. 20° E. and S. 20° W.; desc. along broken SW. slope.
37.60	Spur, slopes S. 55° W.; desc. over NW. slope.
38.880	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20S R7W S14 ¼ S23 1989
	from which
	A fir, 28 ins. diam., bears N. 46° E., 57 lks. dist., mkd. ¼ S14 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 83 ins. diam., bears S. 40° E., 40 lks. dist., mkd. ¼ S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
39.30	Head of ravine, drains N.; asc. over NE. slope.
43.65	Top of ascent, slopes N.; desc. over NW. slope.
48.35	Ravine, drains N. 10° E.; asc. over NE. slope.
51.50	Spur, slopes N.; desc. over NW. slope.
56.80	Spur, slopes N.; desc. over NW. slope.
58.320	Point for the W 1/16 sec. cor. of secs. 14 and 23.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S14 W 1/16 S23 1989</p> <p>from which</p> <p>A fir, 22 ins. diam., bears N. 32° E., 33 lks. dist., mkd. W 1/16 S14 BT.</p> <p>A fir, 26 ins. diam., bears S. 89° E., 11 lks. dist., mkd. W 1/16 S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
60.90	Ravine, drains N. 30° W.; asc. over NE. slope.
63.40	Top of ascent, slopes N.; desc. over NW. slope.
74.20	Ravine, drains S. 70° W.; asc. over SE. slope.
75.85	Spur, slopes S. 40° W.; desc. over SW. slope.
76.55	Dirt road, 15 lks. wide, bears N. and S.
77.760	The cor. of secs. 14, 15, 22, and 23.
	<hr/> <p>Subdivision of Section 14, T. 20 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/>

**Subdivision of Section 14,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	N. $0^{\circ} 22' 00''$ W., on the N. and S. center line of sec. 14.
	Descend over NW. slope through heavy timber and dense undergrowth.
4.80	Ravine, drains S. 80° W.; asc. over broken SW. slope.
15.60	Spur, slopes S. 80° W.; desc. over NE. slope.
33.80	Creek, 2 lks. wide, course N. 85° W.; asc. over SW. slope.
39.255	Point for the center $\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T20S R7W C $\frac{1}{4}$ S14 1989
	from which
	A fir, 8 ins. diam., bears S. 71° E., 35 lks. dist., mkd. X BT.
	A fir, 14 ins. diam., bears N. 25° W., 13 lks. dist., mkd. C $\frac{1}{4}$ S14 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over SW. slope.
49.55	Graveled road, 25 lks. wide, bears N. 85° E. and N. 50° W.
55.75	Spur, slopes N. 40° W.; desc. over broken NW. slope.
69.20	Creek, 3 lks. wide, course S. 80° W.; asc. over SE. slope.
78.705	The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.
	T20S R7W S11 $\frac{1}{4}$ S14 1977
	from which the remains of the original bearing trees
	A fir stump, 24 ins. diam., bears N. 25° E., 94 lks. dist., no marks visible on burned, decayed blaze.
	A fir stump, 28 ins. diam., bears S. 20° E., 47 lks. dist., no marks visible on burned, decayed blaze.
	and bearing trees mkd. by Wofford and Fischer

**Subdivision of Section 14,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over broken SW. slope.
68.10	Creek, 5 lks. wide, course S. 10° W.; asc. over E. slope.
68.35	Spur, slopes S.; desc. over W. slope.
68.50	Creek, 3 lks. wide, course S. 20° E.; asc. over broken SE. slope.
78.475	The ¼ sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.
	T20S R7W ¼ S15 S14 1977
	from which bearing trees mkd. by Wofford and Fischer
	A fir, 29 ins. diam., bears S. 70° E., 7 lks. dist., with healed blaze.
	A fir, 34 ins. diam., bears S. 59½° W., 97 lks. dist., with healed blaze.
	<hr/>
	From the E 1/16 sec. cor. of secs. 14 and 23.
	N. 0° 03' 00" W., on the N. and S. center line of the SE¼ of sec. 14.
	Ascend over broken SE. slope, through heavy timber and dense undergrowth.
3.25	Ridge, bears E. and N. 35° W.; desc. over broken NE. slope changing to N. slope.
16.45	Ravine, drains N. 55° W.; asc. over SW. slope.
31.70	Spur, slopes N. 55° W.; desc. over NE. slope.
39.200	The center E 1/16 sec. cor. of sec. 14.
	<hr/> Subdivision of Section 23, T. 20 S., R. 7 W., Willamette Meridian, Oregon <hr/>
	From the ¼ sec. cor. of secs. 23 and 26.
	N. 0° 52' 30" E., on the N. and S. center line of sec. 23.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
13.75	Ridge, bears N. 30° E. and S.; desc. along NW. slope.
29.80	Spur, slopes W.; desc. over broken NW. slope.
34.90	Spur, slopes N. 30° W.; desc. over NE. slope.

**Subdivision of Section 23,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
39.635	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 23, at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20S R7W C$\frac{1}{4}$ S23 1989</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. 38° E., 153 lks. dist., mkd. C$\frac{1}{4}$ S23 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 85° W., 83 lks. dist., mkd. C$\frac{1}{4}$ S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
40.90	Ravine, drains N. 35° W.; asc. over broken SW. slope.
55.60	Spur, slopes W.; desc. over NW. slope.
59.350	<p>Point for the center N $\frac{1}{16}$ sec. cor. of sec. 23. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N $\frac{1}{16}$ S23 C 1989</p> <p>from which</p> <p style="padding-left: 40px;">A maple, 14 ins. diam., bears N. 36° E., 45 lks. dist., mkd. CN $\frac{1}{16}$ S23 BT.</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears N. 59° W., 39 lks. dist., mkd. CN $\frac{1}{16}$ S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NW. slope.</p>
63.85	Creek, 5 lks. wide, course W.; asc. over SW. slope.
77.90	Spur, slopes N. 55° E. to saddle; desc. over NW. slope.
79.065	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	<hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>S. $88^{\circ} 19' 00''$ W., on the E. and W. center line of sec. 23.</p>

**Subdivision of Section 23,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over broken SW. slope, through heavy timber and dense undergrowth.
10.00	Dirt road, 25 lks. wide, bears N. 35° W. and S. 35° E.
22.25	Ravine, drains S. 20° E.; asc. over broken SE. slope.
31.85	Ridge, bears N. 35° E. and S. 35° W.; desc. over broken NW. slope.
38.05	Ravine, drains NW.; asc. over NE. slope.
39.210	The center ¼ sec. cor. of sec. 23.
	Ascend over NE. slope.
41.85	Spur, slopes N. 30° W.; desc. over NW. slope.
45.10	Ravine, drains N. 25° W.; asc. over NE. slope.
49.85	Spur, slopes N. 30° W.; desc. over NW. slope.
55.10	Ravine, drains N. 35° W.; asc. over NE. slope.
58.705	Point for the center W 1/16 sec. cor. of sec. 23.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 C C S23 1989
	from which
	A fir, 15 ins. diam., bears S. 75° E., 26 lks. dist., mkd. CW 1/16 S23 BT.
	A fir, 42 ins. diam., bears S. 41° W., 9½ lks. dist., mkd. CW 1/16 S23 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over NE. slope.
58.95	Spur, slopes N. 15° W.; desc. over NW. slope.
65.10	Creek, 5 lks. wide, course S. 40° W.; asc. over SE. slope.
72.15	Spur, slopes S. 40° W.; desc. over W. slope.
76.35	Dirt road, 15 lks. wide, bears N. 15° W. and S. 15° E.
78.200	The ¼ sec. cor. of secs. 22 and 23.
	From the W 1/16 sec. cor. of secs. 23 and 26.

**Subdivision of Section 23,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
	N. 0° 54' 00" E., on the N. and S. center line of the SW¼ of sec. 23.
	Ascend over SW. slope, through heavy timber and dense undergrowth.
11.15	Spur, slopes S. 65° W.; desc. over NW. slope.
18.85	Creek, 3 lks. wide, course S. 65° W.; asc. over S. slope.
31.60	Spur, slopes SW.; desc. over NE. slope.
39.820	The center W 1/16 sec. cor. of sec. 23.
<hr/>	
	N. 0° 58' 30" E., on the N. and S. center line of the NW¼ of sec. 23.
	Descend over NE. slope through heavy timber and dense undergrowth.
6.50	Creek, 5 lks. wide, course S. 80° W.; asc. over SE. slope changing to SW. slope.
19.840	Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E. and W. center line of the NW¼. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. NW 1/16 S23 1989
	from which
	A fir, 20 ins. diam., bears S. 20° E., 9 lks. dist., mkd. NW 1/16 S23 BT.
	A fir, 9 ins. diam., bears N. 31° W., 29 lks. dist., mkd. NW 1/16 S23 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend over SW. slope.
33.50	Spur, slopes N. 55° W.; desc. over broken NW. slope.
39.675	The W 1/16 sec. cor. of secs. 14 and 23.
<hr/>	
	From the center N 1/16 sec. cor. of sec. 23.
	S. 88° 41' 00" W., on the E. and W. center line of the NW¼ of sec. 23.
	Descend over NW. slope through heavy timber and dense undergrowth.
7.70	Creek, 3 lks. wide, course S. 35° W.; asc. over NE. slope changing to SE. slope.
18.10	Top of ascent, slopes SE.; desc. SW. slope.

**Subdivision of Section 23,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
19.470	The NW 1/16 sec. cor. of sec. 23. Descend over SW. slope changing to NW. slope.
36.65	Dirt road, 15 lks. wide, bears N. and S.
38.75	Haney Creek, 30 lks. wide, course S. 30° W.; thence along creek bottom.
38.920	The N 1/16 sec. cor. of secs. 22 and 23.
<hr/> Subdivision of Section 35, T. 20 S., R. 7 W., Willamette Meridian, Oregon <hr/>	
	From the ¼ sec. cor. of sec. 35 only, on the S. bdy. of the Tp. N. 0° 08' 00" W., on the N. and S. center line of sec. 35. Descend over broken NE. slope through scattering timber and dense undergrowth.
7.60	Ravine, drains E.; asc. over SE. slope.
14.95	Spur, slopes N. 60° E.; desc. along NW. slope.
20.80	Spur, slopes N. 30° W.; desc. along NE. slope.
23.85	Spur, slopes NE.; desc. along broken NW. slope.
39.495	Point for the center ¼ sec. cor. of sec. 35 at intersection with the E. and W. center line. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T20S R7W C¼ S35 1990
	from which <div style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 64¼° E., 42 lks. dist., mkd. C¼ S35 BT.</div> <div style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 64¼° W., 56½ lks. dist., mkd. C¼ S35 BT.</div>
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend along NW. slope.
40.00	Spur, slopes N. 25° W.; desc. over NE. slope.
65.10	Amberson Creek, 10 lks. wide, course N. 70° W.; thence along creek bottom.

**Subdivision of Section 35,
T. 20 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
79.205	The ¼ sec. cor. of secs. 26 and 35.
	<hr/>
	From the ¼ sec. cor. of secs. 35 and 36.
	S. 88° 35' 30" W., on the E. and W. center line of sec. 35.
	Descend over NW. slope through heavy timber and dense undergrowth.
2.30	Ravine, drains N. 10° W.; asc. over NE. slope.
7.20	Spur, slopes N. 30° W.; desc. over broken NW. slope.
12.55	Dirt road, 20 lks. wide, bears N. 10° E. and S. 15° W.
13.05	Amberson Creek, 15 lks. wide, course N.; asc. over broken NE. slope.
39.00	Spur, slopes N. 25° W.; desc. over broken NW. slope.
39.245	The center ¼ sec. cor. of sec. 35.
	Descend over broken NW. slope.
57.30	Creek, 10 lks. wide, course N. 30° W.; asc. over NE. slope.
64.55	Spur, slopes N.; desc. over NW. slope.
72.80	Ravine, drains N. 30° E.; asc. over E. slope.
76.40	Top of ascent, slopes N. 30° E.; desc. over NW. slope.
78.945	The ¼ sec. cor. of secs. 34 and 35, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with aluminum cap mkd.
	T20S R7W ¼ S34 S35 1984
	from which bearing trees mkd. by Rogers and Bishop
	A fir, 7 ins. diam., bears S. 61½° E., 10 lks. dist., with healed, double blaze.
	A fir, 8 ins. diam., bears S. 67½° W., 36 lks. dist., with healed, double blaze.
	<hr/> GENERAL DESCRIPTION <hr/>
	The lands included in the foregoing resurvey are located in Lane and Douglas Counties approximately 14 miles northwesterly of Drain, Oregon. The east and west center line of section 14 is the county line. The elevations range from approximately 1,480 feet above sea level near the corner of sections 2 and 3 only, to about 640 feet above sea level at the quarter section corner of sections 26 and 35.

T. 20 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The area is drained by Haney Creek, Panther Creek, Amberson Creek with numerous small and seasonal drainages flowing into the Smith River, and Haight Creek, Bear Creek, and numerous small and seasonal drainages flowing northerly into the Siuslaw River. The soil consists of a rocky clay. The lands are forested with fir, cedar, hemlock, yew, alder, cherry, maple, madrone, willow, ash, and chinquapin. Undergrowth consists of ferns, poison oak, vine maple, arrowwood, hazel, Oregon grape, salal, huckleberry, blackberry, thimbleberry, salmonberry, currant, wild rose, ceanothus, devils club, rhododendron, manzanita, and young timber.

Access is gained via a paved road along the South Fork of Smith River, with numerous graveled and dirt roads branching from it into the area surveyed.

There were no mineral deposits noted along the lines resurveyed. The land is used primarily for timber production and recreation.

The mean magnetic declination is $18\frac{1}{2}^{\circ}$ East, with a range of $0\frac{1}{2}^{\circ}$ in local attraction.