

CHAINS

DUPLICATE

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF SECTIONS 3, 10, AND 15,
TOWNSHIP 30 SOUTH, RANGE 5 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Wayne L. Rogers, Cadastral Surveyor

Under Special Instructions dated August 7, 1990, approved August 8, 1990,
which provided for the surveys included under Group No. 1565,
and Assignment Instructions dated August 15, 1990.

Survey commenced August 28, 1990

Survey completed July 11, 1991

T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 3, 10, and 15, township 30 south, range 5 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south, west, and north boundaries and a portion of the subdivisional lines were surveyed by Nathaniel Ford, U. S. Deputy Surveyor, in 1854.

The donation land claims were surveyed by Josiah A. Burnett and Elliott N. Bowman, U. S. Deputy Surveyors, between 1855 and 1860.

Portions of the east and north boundaries and subdivisional lines were surveyed by Oscar F. Thiel, U. S. Deputy Surveyor, in 1896.

Portions of the north boundary and subdivisional lines were resurveyed by Lynn M. Roseberry and James E. Jelley, Cadastral Surveyors, in 1967-69.

A portion of the subdivisional lines was correctively resurveyed and certain original corner points were remonumented without survey by Wayne L. Rogers, Cadastral Surveyor, in 1986.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions dated August 7, 1990, for Group No. 1565, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the northwest one-sixteenth section corner of section 10, as determined from a tie to Geodetic Control Station No. 41072, established by the Bureau of Land Management in 1990, is as follows:

Latitude: 42° 58' 49.19" N. Longitude: 123° 16' 45.23" W.

The mean magnetic declination is 19° 00' East.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	<p>Beginning at the S 1/16 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 15 * S 14 1969</p> <p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 31 3/4° E., 19½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 62½° W., 34 lks. dist., with healed blaze.</p> <p>N. 0° 50' 30" E., bet. secs. 14 and 15, marking and blazing the true line.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p> <p>0.40 Woven wire fence, extends E. and W.</p> <p>2.90 Graveled road, 25 lks. wide, bears E. and W.</p> <p>19.905 The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R5W 1/4 S 15 * S 14 1969</p> <p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears N. 51½° E., 35 lks. dist., with healed blaze. (Record, 39 lks.)</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 60½° W., 32 lks. dist., with healed blaze.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R5W S 10 * S 11))))3)))) S 15 * S 14 1969</p> <p>from which the remains of bearing trees mkd. by John H. Markam Jr., Registered Engineer No. 2880, in 1958</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 27¼° E., 69 lks. dist., with healed blaze.</p>
--------	--

**Lines, Dependent Resurvey of a Portion of the Subdivisional
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A root hole, bears N. 87¼° E., 62 lks. dist., with a down fir alongside, 14 ins. diam., no marks visible on decayed tree.</p>
	<p>A fir, 19 ins. diam., bears S. 65¼° W., 50 lks. dist., with healed blaze. (Record S. 71° W.)</p>
	<p>A fir, 29 ins. diam., bears N. 21½° W., 27 lks. dist., with scribe marks S10 X visible on bark blaze.</p>
	<p>and a bearing tree mkd. by Roseberry and Jelley</p>
	<p>A fir, 25 ins. diam., bears S. 34 3/4° E., 117 lks. dist., with healed, double blaze. (Record 108 lks.)</p>
	<p>The corner is located 20 lks. W. of a ravine, drains S.</p>
	<p>S. 89° 12' 30" W., bet. secs. 10 and 15, marking and blazing the true line.</p>
	<p>Ascend over SE. slope, changing to NE slope; through heavy timber and dense undergrowth.</p>
12.70	<p>Dirt road, 15 lks. wide, bears N. 5° E. and S. 10° W.</p>
19.980	<p>The E 1/16 sec. cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 10 E 1/16))))) S 15 1969</p>
	<p>from which bearing trees mkd. by Roseberry and Jelley</p>
	<p>A fir, 22 ins. diam., bears S. 21° W., 61 lks. dist., with healed blaze.</p>
	<p>A fir snag, 20 ins. diam., bears N. 69° W., 93 lks. dist., with healed blaze.</p>
	<p>and a new bearing tree</p>
	<p>A fir, 11 ins. diam., bears N. 7° E., 53 lks. dist., mkd. E 1/16 S10 BT.</p>
	<p>From the W 1/16 sec. cor. of secs. 3 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 3 W 1/16))))) S 10 1969</p>
	<p>from which the bearing trees mkd. by Roseberry and Jelley</p>
	<p>A fir, 36 ins. diam., bears S. 64° E., 77½ lks. dist., with healed blaze. (Record S. 74° E.)</p>

**Lines, Dependent Resurvey of a Portion of the Subdivisional
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 19 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ W., 41$\frac{1}{2}$ lks. dist., with healed blaze. (Record N. $21\frac{1}{2}^{\circ}$ W.)</p> <p>N. $88^{\circ} 41' 30''$ W., bet. secs. 3 and 10.</p> <p>Descend over broken SW. slope, through heavy timber and moderate undergrowth.</p>
11.95	Spur, slopes S. 60° W.; desc. over NW. slope.
19.875	The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">COUNTY SURVEYORS OFFICE S 4 * S 3)))))3))))) S 9 * S 10 T30S R5W 1959</p> <p>from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1959</p> <p>A fir, 14 ins. diam., bears N. $61\frac{1}{4}^{\circ}$ E., 12 lks. dist., with healed double blaze.</p> <p>A fir, 19 ins. diam., bears S. $57\frac{3}{4}^{\circ}$ E., 37 lks. dist., with healed double blaze.</p> <p>A fir, 26 ins. diam., bears S. $4\frac{3}{4}^{\circ}$ W., 22$\frac{1}{2}$ lks. dist., with healed double blaze.</p> <p>A fir, 21 ins. diam., bears N. $25\frac{1}{2}^{\circ}$ W., 65$\frac{1}{2}$ lks. dist., with healed double blaze.</p>
	<p>Subdivision of Section 3, T. 30 S., R. 5 W., Willamette Meridian, Oregon</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, determined at record bearing and distance from the bearing trees mkd. by Roseberry and Jelley:</p> <p>A fir, 19 ins. diam., bears N. 62° E., 161 lks. dist., with healed blaze.</p> <p>A maple, 28 ins. diam., bears N. 22° W., 175 lks. dist., with scribe marks $\frac{1}{4}$ S3 BT visible on open blaze.</p> <p>At the corner point</p> <p>Set an stainless steel post, $2\frac{1}{2}$ ins. diam., 28 ins. long, 26 ins. in the ground with brass cap mkd.</p>

**Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	T30S R5W S 3 1/4))))) S 10 1990
	from which a new bearing tree
	A fir, 10 ins. diam., bears S. 27° W., 131 lks. dist., mkd. 1/4 S10 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located in an old logging landing at the end of a dirt road, bears SE.
	N. 0° 01' 00" E., on the N. and S. center line of sec. 3.
	Descend over NE. slope, through moderate timber and dense undergrowth.
1.55	Ravine, drains S. 50° E.; asc. over broken SW. slope.
17.00	Graveled road, 20 lks. wide, bears N. 80° W. and S. 80° E.
19.615	Point for the center S 1/16 sec. cor. of sec. 3.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C S 1/16 * S 3 C 1990
	from which
	A fir, 7 ins. diam., bears S. 42° E., 16 lks. dist., mkd. CS 1/16 S3 BT.
	A fir, 15 ins. diam., bears N. 5° W., 16½ lks. dist., mkd. CS 1/16 S3 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SW. slope.
24.25	Ridge, bears N. 60° W. and S. 60° E.; desc. over broken NE. slope, also, dirt road, 10 lks. wide, bears N. 60° W. and S. 60° E.
32.15	Graveled road, 25 lks. wide, bears E. and W.
39.230	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	T30S R5W C 1/4 S 3 1990
	from which
	A fir, 11 ins. diam., bears S. 63° E., 24½ lks. dist., mkd. C 1/4 S3 BT.
	A maple, 10 ins. diam., bears S. 20½° W., 48 lks. dist., mkd. C 1/4 S3 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over NE. slope.
42.05	Ravine, drains N. 35° E.; asc. over broken SE. slope.
62.55	Spur, slopes SE.; asc. over SE. slope.
66.60	Spur, slopes N. 65° E.; desc. over broken NE. slope, also, dirt road, 15 lks. wide, bears N. 65° E. and S. 65° W.
80.660	The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
))))) 1/4 S 3 T30S R5W 1969
	from which bearing trees mkd. by Roseberry and Jelley
	A fir, 37 ins. diam., bears S. 6° E., 91 lks. dist., with healed blaze.
	A fir, 15 ins. diam., bears S. 7½° W., 88½ lks. dist., with healed blaze.
	From the 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	T30S R5W 1/4 S 3 * S 2 1969
	from which the remains of an original bearing tree
	A fir, 31 ins. diam., bears N. 42½° W., 20 lks. dist., with healed blaze and rescribed by Markam with scribe marks 1/4 S3 visible on bark blaze.
	and the remains of a bearing tree mkd. by John H. Markam Jr., Registered Engineer No. 2880, in 1951

**Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir snag, 16 ins. diam., bears S. 46 3/4° E., 9 lks. dist., with scribe marks 1/4 S T30S R5W 2880 visible on partially healed blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963</p> <p>A fir, 22 ins. diam., bears N. 3° E., 14 lks. dist., with healed blaze.</p> <p>N. 89° 28' 00" W., on the E. and W. center line of sec. 3.</p> <p>Descend over NW. slope, through heavy timber and dense undergrowth.</p>
8.65	Ravine, drains N. 30° E.; asc. over steep NE. slope.
19.580	<p>Point for the center E 1/16 sec. cor. of sec. 3.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C))))))) C S 3 1990</p> <p>from which</p> <p>A fir, 20 ins. diam., bears N. 48¼° E., 23 lks. dist., mkd. CE 1/16 S3 BT.</p> <p>A fir, 23 ins. diam., bears N. 41 3/4° W., 37½ lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over NE. slope.</p>
20.00	Spur, slopes N. 30° E.; desc. over NW. slope.
28.35	Ravine, drains N. 20° E.; asc. over NE. slope.
35.70	Spur, slopes N. 30° E.; desc. over NW. slope.
39.160	<p>The center 1/4 sec. cor. sec. 3.</p> <p>Descend over NW. slope.</p>
41.05	Ravine, drains NE.; asc. over NE. slope.
46.65	Graveled road, 25 lks. wide, bears N. 5° E. and S. 20° E.
49.80	Spur, slopes N.; desc. over broken SW. slope.
78.655	The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

**Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T30S 1/4 S 4 * S 3 R5W 1963</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A burned fir snag, 32 ins. diam., bears S. 45° E., 9 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 45° W., 33 lks. dist., no marks visible. (Record, N. 35° W.)</p> <p>and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears South, 33 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A burned maple snag, 17 ins. diam., bears N. 13° W., 73 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 64° W., 91 lks. dist., mkd. 1/4 S4 BT.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 3 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 E 1/16))))) S 10 1969</p> <p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears S. 28° W., 25½ lks. dist., with healed blaze. (Record S. 21° W.)</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 64° W., 15 lks. dist., with healed blaze. (Record N. 74° W.)</p> <p>N. 0° 19' 30" W., on the N. and S. center line of the SE 1/4 of sec. 3.</p> <p>Descend along broken E. slope, through heavy timber and dense undergrowth.</p> <p>7.45 Ravine, drains S. 35° E.; asc. over SW. slope.</p> <p>19.715 Point for the SE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
--------	---

**Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">SE 1/16 S3 1990</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 52° E., 23 lks. dist., mkd. SE 1/16 S3 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 73° W., 33½ lks. dist., mkd. SE 1/16 S3 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SW. slope.</p> <p>24.80 Ridge, bears E. and W.; desc. over NE. slope.</p> <p>39.465 The center E 1/16 sec. cor. of sec. 3.</p>
	<p>From the S 1/16 sec. cor. of secs. 2 and 3, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 3 * S 2 1969</p> <p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 19° E., 35 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 5° W., 15½ lks. dist., with healed blaze.</p> <p>N. 89° 04' 30" W., on the E. and W. center line of the SE¼ of sec. 3.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p> <p>2.55 Ravine, drains S. 20° W.; asc. over SE. slope.</p> <p>6.80 Spur, slopes S.; desc. over SW. slope.</p> <p>11.50 Ravine, drains S.; asc. over SE. slope.</p> <p>19.715 The SE 1/16 sec. cor. of sec. 3.</p> <p>Ascend over SE. slope.</p> <p>19.90 Spur, slopes S.; desc. over SW. slope.</p> <p>25.15 Ravine, drains S. 10° W.; asc. over NE. slope.</p> <p>32.90 Graveled road, 30 lks. wide, bears N. 50° E. and S. 50° W.</p> <p>35.10 Spur, slopes S. 30° E.; desc. over SW. slope.</p>

**Subdivision of Section 3,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
39.420	The center S 1/16 sec. cor. of sec. 3.
	<p>Subdivision of Section 10, T. 30 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T30S S 10 1/4))))) S 15 R5W 1963</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears N. 45° W., 16 lks. dist., with down pine stump alongside, size indeterminate, no marks visible.</p> <p>and the remains of bearing trees mkd. by John H. Markam Jr., Registered Engineer No. 2880, in 1958</p> <p style="padding-left: 40px;">A madrone, 36 ins. diam., bears N. 28° E., 51½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A root crown, size indeterminate, bears N. 59° E., 47 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A madrone root crown, size indeterminate, bears S. 26° E., 70 lks. dist., no marks visible. (Record, 76 lks.)</p> <p>and the remains of a bearing tree mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A root hole, bears S. 70 ¾° E., 29½ lks. dist., with down fir stump alongside, 48 ins. diam., with healed blaze.</p> <p>and a bearing tree mkd. by Rogers</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 47° E., 64 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>N. 0° 29' 30" W., on the N. and S. center line of sec. 10.</p> <p>Descend over NE. slope, through heavy timber and dense undergrowth.</p>
3.80	Ravine, drains N. 50° E.; asc. over SE. slope.
19.565	The center S 1/16 sec. cor. of sec. 10, established by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1986, recorded in County Map File No. M103-1, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 16 ins. above ground, with an aluminum cap, 2 ins. diam., mkd.

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	T30S R5W SEC 10 CS 1/16 1986 LS 498
	from which the bearing trees mkd. by Johnstone
	A fir, 13 ins. diam., bears N. 3° E., 36½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	A fir, 19 ins. diam., bears N. 48° E., 39½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	<hr/>
	N. 0° 29' 00" W., beginning a new measurement.
	Ascend over SE. slope.
8.40	Spur, slopes N. 40° E.; desc. over broken NE. slope.
19.555	The center 1/4 sec. cor. of sec. 10, established by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1986, recorded in County Map File No. M103-1, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 14 ins. above ground, with an aluminum cap, 2 ins. diam., mkd.
	T30S R5W SEC 10 C 1/4 1986 LS 498
	from which the bearing trees mkd. by Johnstone
	A fir, 10 ins. diam., bears S. 62° W., 28 lks. dist., with healed blaze.
	A fir, 7 ins. diam., bears N. 46° W., 15 lks. dist., with healed blaze.
	<hr/>
	N. 0° 43' 00" W., beginning new measurement.
	Descend over NE. slope.
4.35	Morgan Creek, 5 lks. wide, course N. 65° E.; asc. over broken SE. slope.
16.15	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
18.895	Point for the center N 1/16 sec. cor. of sec. 10.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C N 1/16 * S 10 C 1991

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 58° E., 24 lks. dist., mkd. CN 1/16 S10 BT.</p> <p style="padding-left: 40px;">A madrone, 5 ins. diam., bears S. 14½° E., 24½ lks. dist., mkd. CN 1/16 S10 BT on bark.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p> <p>21.25 Spur, slopes S. 70° E.; desc. over broken NE. slope.</p> <p>37.790 The 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>From the 1/4 sec. cor. of secs. 10 and 11, monumented with the original corner tree, a maple, 24 ins. diam., with an opened decayed blaze on W. face (with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above ground, on N. side of tree), from which the remaining original bearing tree:</p> <p style="padding-left: 40px;">A maple, 22 ins. diam., bears N. 88° W., 63 lks. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by John H. Markam Jr., Registered Engineer No. 2880, in 1958</p> <p style="padding-left: 40px;">A yew, 16 ins. diam., bears S. 47½° W., 105 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A root hole, bears N. 54° W., 63 lks. dist., with down fir alongside, 8 ins. diam., with scribe marks 1/4 S10 BT visible on decayed double blaze.</p> <p style="padding-left: 40px;">A maple, 16 ins. diam., bears N. 31 3/4° W., 95 lks. dist., with axe marks on bark and center decayed.</p> <p>and a reference monument by Roseberry and Jelley</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, bears N. 45° E., 10 lks. dist., with brass cap mkd. T30SR5W 1/4 S11 RM 1969 and an arrow pointing to the corner.</p> <p>and bearing trees mkd. by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1986</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 39° E., 20 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 25° W., 25 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>N. 88° 52' 00" W., on the E. and W. center line of sec. 10.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	<p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 77° E., 20 lks. dist., mkd. CW 1/16 S10 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 73° W., 13 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p> <p>27.35 Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>35.55 Dirt road, 15 lks. wide, bears N. 55° E. and S. 55° W.</p> <p>36.50 Ridge, bears N. 35° E. and S. 35° W.; desc. over broken NW. slope, also graveled road, 25 lks. wide, bears N. 35° E. and S. 35° W.</p> <p>39.670 The 1/4 sec. cor. of secs. 9 and 10, monumented with the remains of the original corner tree, a decayed fir snag, 18 ins. diam., with fragmentary scribe marks visible on opened blaze on W. face, from which the remains of bearing trees mkd. by Roseberry and Jelley:</p> <p style="padding-left: 40px;">A decayed fir stump, 11 ins. diam., bears S. 34¼° E., 87½ lks. dist., with scribe marks 1/4 S10 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears N. 85½° W., 196½ lks. dist., with healed blaze.</p> <p>and a bearing tree recorded by Rogers</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., bears S. 78½° E., 16 lks. dist., with scribe marks BT visible on opened blaze.</p> <p>and a bearing tree mkd. by Rogers</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 54° E., 39 lks. dist., with healed blaze.</p> <p>From this point, a local corner established by James W. Byron, Deputy County Surveyor, in 1959, bears South, 0.020 chs. dist., monumented with an iron post, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S * S 1/4 9 * 10 T30S R5W 1959</p> <p>from which the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir snag, 10 ins. diam., bears N. 46° E., 67 lks. dist., with healed double blaze.</p>
--------	--

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	<p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 30' 30" W., on the N. and S. center line of the SE¼ of sec. 10.</p> <p>Descend over NE. slope, changing to NW. slope, through heavy timber and dense undergrowth.</p>
19.230	<p>The SE 1/16 sec. cor. of sec. 10, established by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1986, recorded in County Map File No. M103-1, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, with an aluminum cap, 2 ins. diam., mkd.</p> <p style="text-align: center;">T30S RRCO R5W SE 1/16 S10 LS 498 1986</p> <p>from which the bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears N. 72° E., 24 lks. dist., with scribe marks SE 1/16 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 60° W., 37 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>The corner is located in the bottom of descent, drains N. 10° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 32' 30" W., beginning new measurement.</p> <p>Descend over NE. slope.</p>
2.40	<p>Creek, 5 lks. wide, course N. 60° E.; asc. over broken SE. slope.</p>
15.25	<p>Spur, slopes N. 50° E.; desc. over broken NE. slope.</p>
19.210	<p>The center E 1/16 sec. cor. of sec. 10.</p>
	<p>From the S 1/16 sec. cor. of secs. 10 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 10 * S 11 1969</p> <p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 47 3/4° E., 75 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 6½° W., 93 lks. dist., with healed blaze.</p> <p>The corner is located at the base of a rootwad, 8 ft. high.</p>

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	N. 89° 51' 00" W., on the E. and W. center line of the SE¼ of sec. 10.
	Descend over NW. slope, through heavy timber and dense undergrowth.
7.10	Creek, 1 lk. wide, course N. 10° W.; asc. over NE. slope.
11.15	Spur, slopes N.; desc. over NW. slope.
17.10	Creek, 1 lk. wide, course N. 30° W.; asc. over NE. slope.
19.925	The SE 1/16 sec. cor. of sec. 10.

	N. 89° 51' 00" W., beginning new measurement.
	Ascend over NE. slope.
3.20	Spur, slopes N.; desc. over NW. slope.
3.70	Creek, 5 lks. wide, course N. 20° E.; asc. over broken SE. slope.
19.945	The center S 1/16 sec. cor. of sec. 10.
	From the W 1/16 sec. cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	S 10 W 1/16))))) S 15 1986
	from which the bearing trees mkd. by Rogers
	A fir, 52 ins. diam., bears S. 14° E., 29 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	A fir, 29 ins. diam., bears N. 8° W., 25 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	N. 0° 38' 00" W., on the N. and S. center line of the SW¼ of sec. 10.
	Ascend over broken SW. slope, changing to SE. slope, through heavy timber and moderate undergrowth.
17.05	Ridge, bears S. 75° E. and S. 80° W.; desc. over broken NE. slope, also dirt road, 15 lks. wide, bears S. 75° E. and S. 80° W.
18.65	Graveled road, 20 lks. wide, bears N. 75° W. and S. 55° E.
19.630	The SW 1/16 sec. cor. of sec. 10, established by Howard W. Johnstone, Registered Land Surveyor No. 498, in 1986, recorded in County Map File No. M103-1, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 16 ins. above ground, with aluminum cap, 2 ins. diam., mkd.

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	RRCO T30S R5W SW 1/16 1986 SEC 10 LS 498
	from which the bearing trees mkd. by Johnstone
	A fir, 7 ins. diam., bears S. 45½° E., 19 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	A fir, 11 ins. diam., bears S. 23½° E., 16½ lks. dist., with fragmentary scribe marks visible on partially healed blaze.

	N. 0° 38' 00" W., beginning new measurement.
	Descend over NE. slope.
17.15	Morgan Creek, 3 lks. wide, course N. 40° E.; asc. over SE. slope.
18.50	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
19.615	The center W 1/16 sec. cor. of sec. 10.

	From the center S 1/16 sec. cor. of sec. 10.
	N. 88° 59' 30" W., on the E. and W. center line of the SW¼ of sec. 10.
	Ascend over broken SE. slope, through heavy timber and dense undergrowth.
8.10	Spur, slopes N. 40° E.; asc. over broken NE. slope.
19.775	The SW 1/16 sec. cor. of sec. 10.

	N. 88° 59' 30" W., beginning new measurement.
	Ascend over broken NE. slope.
16.45	Graveled road, 30 lks. wide, bears N. 55° W. and S. 35° E.
19.740	The S 1/16 sec. cor. of secs. 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	S 1/16 S 9 * S 10 1969
	from which the bearing trees mkd. by Roseberry and Jelley
	A fir, 16 ins. diam., bears S. 14½° E., 53 lks. dist., with healed blaze.
	A fir, 20 ins. diam., bears N. 56½° W., 29 lks. dist., with healed blaze.

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>The corner is located on top of a ridge, bears N. 20° W. and S. 20° E.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 10.</p> <p>N. 0° 42' 30" W., on the N. and S. center line of the NW¼ of sec. 10.</p> <p>Ascend over broken SE. slope, through heavy timber and dense undergrowth.</p>
9.60	Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.
17.25	Ridge, bears N. 50° E. and S. 50° W.; desc. over NW. slope, also dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.
18.940	<p>Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S10 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 42° E., 105 lks. dist., mkd. NW 1/16 S10 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 37° W., 59 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41072, at latitude 42° 59' 04.774" N., longitude 123° 16' 44.476" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N. 2° 02' 02" E., 23.919 chs. dist., monumented with an aluminum cap, 2½ ins. diam., firmly set flush with the ground, set in concrete, 18 ins. diam., with top mkd. EC 41072 GPS 1990.</p> <p>Descend over NW. slope.</p>
20.80	Graveled road, 25 lks. wide, bears N. 30° E. and S. 40° W.
32.25	Ravine, drains S. 60° W.; asc. over SW. slope.
37.800	The W 1/16 sec. cor. of secs. 3 and 10.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 10.</p> <p>N. 88° 44' 00" W., on the E. and W. center line of the NW¼ of sec. 10.</p>

**Subdivision of Section 10,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	Ascend over broken SE. slope, through heavy timber and dense undergrowth.
2.50	Spur, slopes S.; continue to asc. over broken SE. slope.
18.25	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
18.40	Ridge, bears N. 30° E. and S. 30° W.; desc. over NW. slope.
19.835	The NW 1/16 sec. cor. of sec. 10. Descend over broken NW. slope.
36.90	Spur, slopes NW.; desc. over SW. slope.
39.660	The N 1/16 sec. cor. of secs. 9 and 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.
	N 1/16 S 9 * S 10 1969
	from which the bearing trees mkd. by Roseberry and Jelley
	A fir, 16 ins. diam., bears N. 50° E., 53½ lks. dist., with healed blaze.
	A fir, 22 ins. diam., bears N. 45° W., 85 lks. dist., with healed blaze.
	<hr/> Subdivision of Section 15, T. 30 S., R. 5 W., Willamette Meridian, Oregon <hr/>
	From the 1/4 sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remains of an original bearing tree:
	A root hole, bears S. 45° E., 12 lks. dist.
	and the remains of bearing trees mkd. by Roseberry and Jelley
	A fir root crown, size indeterminate, bears N. 45½° E., 13 lks. dist., no marks visible.
	An oak stump, 31 ins. diam., bears S. 81½° W., 17 lks. dist., no marks visible.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R5W S 15 1/4))))) S 22 1991
	from which new bearing trees

**Subdivision of Section 15,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A madrone, 7 ins. diam., bears S. 19° E., 131 lks. dist., mkd. 1/4 S22 BT on bark.</p> <p>An oak, 11 ins. diam., bears N. 74½° W., 42 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post and set a steel fence post S. of the corner.</p> <p>N. 1° 02' 30" E., on the N. and S. center line of sec. 15.</p> <p>Ascend over nearly level land, through scattering timber and moderate undergrowth.</p>
16.90	Ravine, drains S. 20° W.; asc. over SW. slope.
20.080	<p>Point for the center S 1/16 sec. cor. of sec. 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 * S 15 C 1991</p> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 52° E., 56 lks. dist., mkd. CS 1/16 S15 BT.</p> <p>A fir, 11 ins. diam., bears S. 53½° E., 44 lks. dist., mkd. CS 1/16 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a fence corner bears N. 3° 30' 00" E., 2.09 chs. dist., with fences extending N., S., and E.</p> <p>Ascend over SE. slope.</p>
21.10	Spur, slopes S. 5° E.; asc. over SE. slope.
36.15	Spur, slopes S. 10° W.; desc. over NW. slope.
40.160	<p>Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R5W C 1/4 S 15 1991</p> <p>from which</p> <p>A fir, 8 ins. diam., bears S. 67° E., 51 lks. dist., mkd. C 1/4 S15 BT.</p>

**Subdivision of Section 15,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 14 ins. diam., bears N. 13° W., 81 lks. dist., mkd. C 1/4 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, an iron pipe, 1/2 in. diam., firmly set, projecting 4 ins. above ground, bears S. 18° 14' 00" E., 0.365 chs. dist., established by person(s) unknown. This point is located in a fence extending N. 35° W. and S. 35° E., and is not used in this survey.</p> <p>Descend over NW. slope.</p>
41.50	Head of ravine, drains S. 80° W.; asc. over broken SW. slope.
61.50	Spur, slopes S. 85° W.; desc. over broken NW. slope.
69.95	Ravine, drains S. 70° W.; asc. over broken SW. slope.
74.20	Graveled road, 25 lks. wide, bears N. 55° W. and S. 55° E.
75.30	Spur, slopes W.; desc. over NE. slope.
79.140	The 1/4 sec. cor. of secs. 10 and 15.
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>N. 89° 40' 30" W., on the E. and W. center line of sec. 15.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
1.80	Spur, slopes S. 10° W.; desc. over broken SW. slope, also graveled road, 25 lks. wide, bears N. 15° E. and S. 30° W.
18.05	Ravine, drains S. 15° W.; asc. over broken SE. slope.
26.15	Spur, slopes S. 10° E.; asc. over SE. slope.
35.35	Spur, slopes S. 35° W.; desc. over broken NW. slope, also dirt road, 15 lks. wide, bears N. 35° E. and S. 35° W.
39.945	The center 1/4 sec. cor. of sec. 15.
	Descend over NW. slope.
45.40	Ravine, drains S. 80° W.; desc. over broken SW. slope.
55.60	Creek, 5 lks. wide, course S.; asc. over SE. slope.
59.725	Point for the center W 1/16 sec. cor. of sec. 15.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p>W 1/16 C))))))) C S 15 1991</p>

**Subdivision of Section 15,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 22 3/4° E., 42½ lks. dist., mkd. CW 1/16 S15 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 39½° W., 32 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above ground, bears N. 65° 21' 00" E., 0.120 chs. dist., established by person(s) unknown. This point was not used in this survey.</p> <p>Ascend over SE. slope.</p>
63.60	Spur, slopes S. 5° W.; desc. over broken SW. slope.
67.15	Ravine, drains S. 25° W.; asc. over broken SE. slope.
73.75	Creek, 5 lks. wide, course S. 10° E.; asc. over broken NE. slope.
79.505	The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<p>T30S R5W 1/4 S 16 * S 15 1969</p>
	<p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 57° E., 39 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears N. 45° W., 30 lks. dist., with healed blaze.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>N. 89° 57' 30" W., on the E. and W. center line of the SE¼ of sec. 15.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
10.75	One strand electric fence, extends N. and S., 1.20 chs. S. of woven wire fence, extending E. and W.
11.70	Spur, slopes S.; desc. over SW. slope.
17.70	Creek, 1 lk. wide, course S. 5° E.; asc. over SE. slope.
33.60	Spur, slopes S. 20° W.; desc. over SW. slope.
38.65	Ravine, drains S. 10° W.; asc. over SE. slope.

**Subdivision of Section 15,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

<p>CHAINS 39.90</p>	<p>Spur, slopes S. 5° E.; desc. over SW. slope.</p>
<p>40.020</p>	<p>The center S 1/16 sec. cor. of sec. 15.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the W 1/16 sec. cor. of secs. 15 and 22, determined at record bearing and distance from the remains of the bearing trees mkd. by Roseberry and Jelley:</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. 34½° E., 54½ lks. dist., with scribe marks W 1/16 S22 visible on opened blaze.</p> <p style="padding-left: 40px;">A root hole, bears N. 73¼° W., 108 lks. dist., with down fir alongside, 12 ins. diam., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>S 15 W 1/16))))) S 22 1991</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears N. 80½° W., 557 lks. dist., mkd. W 1/16 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on a SE. slope in open pastureland.</p> <p>N. 1° 03' 00" E., on the N. and S. center line of the SW¼ of sec. 15.</p> <p>Ascend over broken SE. slope, through open pasture.</p>
<p>19.865</p>	<p>Point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> <p>SW 1/16 S15 1991</p> </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears S. 47½° E., 9½ lks. dist., mkd. SW 1/16 S15 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 85° W., 26½ lks. dist., mkd. SW 1/16 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>

**Subdivision of Section 15,
T. 30 S., R. 5 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, an iron pipe, 1/2 in. diam., firmly set, projecting 6 ins. above ground, bears S. 73° 04' 00" E., 0.025 chs. dist., established by person(s) unknown. This point was not used in this survey.</p> <p>Ascend over SE. slope.</p>
25.20	Creek, 5 lks. wide, course S. 50° E.; asc. over broken SE. slope.
39.735	The center W 1/16 sec. cor. of sec. 15.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 15.</p> <p>N. 89° 04' 00" W., on the E. and W. center line of the SW¼ of sec. 15.</p> <p>Descend over SW. slope, through heavy timber and dense undergrowth.</p>
0.60	Ravine, drains S. 10° E.; asc. over SE. slope.
7.55	Spur, slopes S.; desc. over SW. slope.
16.00	Dirt road, 15 lks. wide, bears N. 5° E. and S. 5° W.
17.00	Creek, 6 lks. wide, course S. 10° W.; asc. over SE. slope.
19.785	The SW 1/16 sec. cor. of sec. 15.
	Ascend over SE. slope, changing to NE. slope.
36.55	Spur, slopes S. 10° E.; desc. over W. slope; also dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E.; also Natural Gas Line right-of-way, bears same.
39.640	The S 1/16 sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	<p>S 1/16 S 16 * S 15 1969</p>
	<p>from which the bearing trees mkd. by Roseberry and Jelley</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 58° E., 85 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 58° W., 2½ lks. dist., with healed blaze.</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, bears N. 52° 30' 00" E., 0.380 chs. dist., established by person(s) unknown. This point was not used in this survey.</p> <hr/>

T. 30 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

GENERAL DESCRIPTION

The lands included in the foregoing resurvey are located in mountainous country approximately four miles north of Canyonville, Oregon. The elevation ranges from approximately 920 feet above sea level near the quarter section corner of sections 15 and 22, to about 2,120 feet above sea level near the center south one-sixteenth section corner of section 3.

The area is drained by South Myrtle Creek to the north, Morgan Creek to the east, and Small Creek to the southeast, which all flow into the South Umpqua River, with numerous other small and seasonal drainages flowing into them. The soil consists of a rocky clay in the higher elevations to a clay loam in the lower elevations. The timber consists of fir, pine, yew, alder, maple, oak, willow, cascara, ash, dogwood, madrone, chinquapin and cedar. The undergrowth is mainly salal, poison oak, Oregon grape, manzanita, arrowwood, vine maple, blackberry, salmonberry, huckleberry, and young timber.

Access is gained via Gazely Road, with numerous graveled and dirt roads branching from it into the area.

No mineral deposits were noted along the lines resurveyed. The area is used primarily for timber with farms located in the southern part of section 15.

The average of readings over the area gives a value of 19° 00' East for the mean magnetic declination, with a range of 0° 45' due to local attraction.