

CHAINS

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF SECTIONS 3 AND 11,
TOWNSHIP 30 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Dale T. Bedell, Cadastral Surveyor

Under Special Instructions dated June 13, 1990,
approved June 14, 1990,
which provided for the surveys included under Group No. 1551,
and Assignment Instructions dated June 20, 1990.

Survey commenced August 21, 1990

Survey completed July 8, 1991

T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of sections 3 and 11, township 30 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1854, Nathaniel Ford, U.S. Deputy Surveyor, surveyed the east and north boundaries of the township.

In 1855, Addison R. Flint, U.S. Deputy Surveyor, resurveyed the east boundary and surveyed the south and west boundaries and subdivisional lines.

In 1958 and 1959, Hans W. Thielsen and C. Albert White, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines, and remonumented certain original corners in T. 29 S., R. 6 W.

In 1967, Lynn W. Roseberry, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1988, Wayne L. Rogers, Cadastral Surveyor, subdivided sections 10 and 15.

The survey was executed in accordance with the specifications as set forth in the *Manual of Surveying Instructions, 1973*, and the Special Instructions dated June 13, 1990, for Group No. 1551, Oregon.

The directions of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding public lands were blazed. All lines not forming a closure were measured twice.

Detectable Electronically Energized Particles (DEEP-1™) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the corner of sections 2, 3, 10, and 11, as determined from a tie to Geodetic Control Station No. EC 41056, established by the Bureau of Land Management, is as follows:

Latitude 42° 59' 06.46" N. Longitude 123° 23' 05.96" W.

The mean magnetic declination is 20° East.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	(Restoring the survey by Addison R. Flint in 1855)
	<p>Beginning at the cor. of secs. 11, 12, 13, and 14, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1929, from original evidence no longer in existence, recorded in Map File 1-61 and Survey File Volume 3, pages 294, 295, and 296, Douglas County Records, further perpetuated by John M. Powell, Deputy County Surveyor, in 1969, recorded in Douglas County Corner Renewal Records, and further perpetuated by William J. Ruppert, Registered Land Surveyor No. 866, in 1981, recorded in Map File 87-79, Douglas County Records, monumented with an iron pipe, 1½ ins. diam., firmly set flush with the ground, with a steel rod, 26 ins. long, 7/8 in. diam., set alongside, from which a bearing tree mkd. by Irving:</p> <p style="padding-left: 40px;">A white oak, 30 ins. diam., bears S. 17½° W., 88 lks. dist., with healed blaze.</p> <p>and a bearing tree recorded by Powell</p> <p style="padding-left: 40px;">A maple, 30 ins. diam., bears N. 35° E., 210 lks. dist., with healed blaze.</p> <p>and the remains of a bearing tree mkd. by Powell</p> <p style="padding-left: 40px;">A maple snag, 38 ins. diam., bears S. 76° E., 203 lks. dist., with scribe marks T30S R6W S13 CS BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T30S R6W <u>S11 * S12</u> S14 * S13 1990</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A white oak, 25 ins. diam., bears S. 72° E., 264 lks. dist., mkd. T30S R6W S13 BT.</p> <p style="padding-left: 40px;">A black oak, 10 ins. diam., bears N. 83¼° W., 26 lks. dist., mkd. T30S R6W S11 BT.</p> <p>Deposit the steel rod alongside the stainless steel post.</p> <p>N. 0° 36' 00" E., bet. secs. 11 and 12.</p> <p>Cross level creek bottom land.</p>
1.35	Lane Creek, dry, 10 lks. wide, drains N. 80° E.; asc. over gentle SE. slope through open pastureland.
6.90	Graveled road, 30 lks. wide, bears N. 30° E. and S. 30° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
20.125	<p>Point for the S 1/16 sec. cor. of secs. 11 and 12. There is no remaining evidence of the corner established by W. F. Briggs, County Surveyor, in 1885, recorded in Volume 1, page 62, Douglas County Records.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S11 * S12 1991</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 34° E., 37 lks. dist., mkd. S 1/16 S12 BT.</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 80° W., 39 lks. dist., mkd. S 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the corner of an old wire fence, bears S. 86° W., 14 lks. dist. The fences extend E. and S. for 20 lks.; thence W.</p> <p>Continue over SE. slope.</p>
20.60	Wire fence, bears E. and W.; enter heavy timber and dense undergrowth.
39.10	Spur, slopes E.; desc. over NE. slope.
40.250	<p>The ¼ sec. cor. of secs. 11 and 12, reestablished by W. F. Briggs, County Surveyor, in 1873, recorded in Volume 00, page 113, Douglas County Records, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1929, recorded in Map File M1-61 and Survey File Volume 3, pages 294, 295, and 296, Douglas County Records, and further perpetuated by James W. Byron, Deputy County Surveyor, in 1964, recorded in Douglas County Corner Renewal Records; there is no remaining evidence of the original corner, therefore, this position is accepted as the corner, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T30S ¼ S11 * S12 R6W 1964</p> <p>from which bearing trees mkd. by Irving</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears S. 46° E., 83 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">The northerly trunk of a double trunked cedar, 18 ins. diam., bears S. 15° W., 88 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 0° 25' 00" E., beginning new measurement.
	Descend over NE. slope.
8.70	Graveled road, 20 lks. wide, bears N. 40° W. and S. 40° E.
12.10	Judd Creek, 20 lks. wide, course S. 20° E.; asc. over broken SW. slope.
17.90	Spur, slopes W.; desc. broken NW. slope.
20.175	Point for the N 1/16 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	N 1/16 S11 * S12 1991
	from which
	A pine, 15 ins. diam., bears S. 10° E., 49 lks. dist., mkd. N 1/16 S12 BT.
	A pine, 8 ins. diam., bears S. 36° W., 59 lks. dist., mkd. N 1/16 S11 BT.
	Continue descent over gentle NW. slope.
30.50	Enter creek bottom land, edge bears N. 10° E. and S. 10° W.
40.350	Point for the cor. of secs. 1, 2, 11, and 12, at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T30S R6W <u>S2 * S1</u> S11 * S12 1991
	from which
	A cedar, 7 ins. diam., bears N. 28½° E., 27 lks. dist., mkd. T30S R6W S1 BT.
	A cedar, 9 ins. diam., bears S. 55° E., 60 lks. dist., mkd. T30S R6W S12 BT.
	A myrtle, 7 ins. diam., bears S. 74° W., 20 lks. dist., mkd. T30S R6W S11 BT.
	A fir, 16 ins. diam., bears N. 20½° W., 47½ lks. dist., mkd. T30S R6W S2 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

From this point, a point established as the cor. of secs. 1, 2, 11, and 12 by Ben B. Irving, Deputy County Surveyor, in 1929, recorded in Map File 1-61 and Survey File Volume 3, pages 294, 295, and 296, Douglas County Records, and perpetuated by James W. Byron, Deputy County Surveyor, in 1964, recorded in Douglas County Corner Renewal Records, bears S. 3° 10' 00" E., 4.480 chs. dist., monumented with an iron pipe, 3/4 in. diam., in a collar of stone, projecting 2 ins. above the ground, from which the remains of bearing trees, not of record, found by Irving:

A pine, 35 ins. diam., bears N. 54½° E., 93 lks. dist., with scribe mark C visible on previously opened blaze.

A root hole, bears S. 86° E., 113 lks. dist., with a down pine alongside, 30 ins. diam., with scribe mark C visible on previously opened blaze and BT on newly opened blaze.

and bearing trees mkd. by Irving

A fir, 22 ins. diam., bears S. 1° W., 47 lks. dist., with healed blaze.

A fir, 21 ins. diam., bears N. 75° W., 39 lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A fir, 14 ins. diam., bears N. 41° E., 36 lks. dist., with healed blaze.

A fir, 19 ins. diam., bears S. 85° E., 27 lks. dist., with healed blaze.

This point was determined by Irving at the intersection of the facing of the two bearing trees of unknown origin or record, it is not harmoniously related with identified existing original corners in the area, and is not utilized in this survey.

From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., perpetuated by Ben B. Irving, Deputy County Surveyor, in 1929, from original evidence no longer in existence, recorded in Map File 1-61 and Survey File 1-65A, Douglas County Records, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Corner Renewal Records, and further perpetuated by Larry E. Monrean of the County Surveyors Office in 1979, recorded in Douglas County Corner Renewal Records, monumented with an iron rod, 1¼ ins. diam., firmly set 30 ins. below the ground surface, with an iron rod, 3/4 in. diam., set 24 ins. below the ground surface, alongside, from which a bearing tree and reference monument mkd. by Byron:

An oak, 14 ins. diam., bears S. 58½° W., 215½ lks. dist., with healed double blaze.

An iron rod, 3/4 in. diam., projecting 12 ins. above the ground, bears N. 66° W., 75½ lks. dist.

and a reference monument and bearing object mkd. by Monrean

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

An angle iron, 1½ x 1½ ins., projecting 12 ins. above ground,
bears S. 88° W., 90½ lks. dist.

The mark X with marks B0 alongside, in a concrete headwall,
bears N. 34½° W., 219 lks. dist.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins.
in the ground, flush with the surface and directly over the iron
rods, with brass cap mkd.

T30S
R6W * R5W
S1 *
----- S6
S12 *
1991

From this point, the cor. of secs. 6 and 7 only, T. 30 S., R. 5
W., bears S. 2° 04' 00" E., 3.970 chs. dist., perpetuated by Floyd
C. Frear, Deputy County Surveyor, in 1917, from original evidence
no longer in existence, recorded in Douglas County Corner Renewal
Records, further perpetuated by Ben B. Irving, Deputy County
Surveyor, in 1919, recorded in Douglas County Corner Renewal
Records, further perpetuated by James W. Byron, Deputy County
Surveyor, in 1963, recorded in Douglas County Corner Renewal
Records, and further perpetuated by Larry E. Monrean of the County
Surveyors Office, in 1979, recorded in Douglas County Corner
Renewal Records, monumented with an iron post, 1 in. diam., firmly
set 18 ins. below the ground surface, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T30S
R R
6 * S6 5
 S12 -----
W * S7 W
1979

from which bearing trees mkd. by Frear

An oak, 23 ins. diam., bears S. 38° W., 407 lks. dist., with
healed double blaze.

An oak, 25 ins. diam., bears N. 62° W., 326 lks. dist., with
healed double blaze.

and the remains of a bearing tree mkd. by Byron

An oak stump, 16 ins. diam., bears S. 30° E., 323 lks. dist.,
no marks remaining.

N. 89° 01' 00" W., bet. secs. 1 and 12.

Cross nearly level open pastureland.

0.90

Wire fence, bears N. 40° E. and S. 40° W.; asc. steep broken E.
slope through heavy timber and dense undergrowth.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
3.00	Railroad tracks, bears N. 40° E. and S. 40° W.
5.30	Asphalt road, 30 lks. wide, bears N. 20° E. and S. 20° W.
39.10	Ridge, bears N. 50° E. and S. 50° W.; desc. NW. slope through scattering timber and light undergrowth.
40.560	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to solid rock, supported in a mound of stone, 8 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T30S R6W S1 ¼ ----- S12 1991</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears N. 82° E., 60 lks. dist., mkd. ¼ S1 BT.</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears S. 42¼° W., 76 lks. dist., mkd. ¼ S12 BT.</p> <p>From this point, a point established as the ¼ sec. cor. of secs. 1 and 12 by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1965, recorded in Map File 22-65 and Survey File 53-117, Douglas County Record, bears S. 3° 12' 00" E., 2.220 chs. dist., determined from bearing trees mkd. by Rogers:</p> <p style="padding-left: 40px;">A pine, 19 ins. diam., bears N. 35½° E., 224 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 1½° W., 130 lks. dist., with healed double blaze.</p> <p>The point was established using improper control and is not utilized in this survey.</p> <p>From this same point, a bearing tree not of record found by Ben B. Irving, Deputy County Surveyor, in 1929, recorded in Map File 1-61 and Survey File Volume 3, pages 294, 295, and 296, Douglas County Records, bears S. 9° 40' 00" E., 3.920 chs. dist.; an oak, 28 ins. diam., with scribe mark C visible on opened rotted blaze, facing E.</p> <p>Continue to descend over broken W. slope.</p>
55.00	Ravine, drains S. 30° W.; asc. over SE. slope.
65.00	Spur, slopes S. 30° W.; desc. over steep W. slope.
81.120	The cor. of secs. 1, 2, 11, and 12.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 1° 21' 00" E., bet. secs. 1 and 2.
	Along W. slope through creek bottom land with scattering timber and undergrowth.
12.00	Creek, 10 lks. wide, course S. 35° W.; asc. SE. slope.
32.30	Spur, slopes E.; desc. over NE. slope.
37.00	Creek, 10 lks. wide, course S. 50° E.; asc. rocky SW. slope.
39.85	Rocky spur, slopes S. 80° W.; desc. NW. slope.
40.360	The ¼ sec. cor. of secs. 1 and 2, determined at record bearing and distance from the remains of the original bearing trees: <p style="margin-left: 40px;">A decayed oak snag, 14 ins. diam., bears S. 10° E., 6 lks. dist., with rotted out upper blaze and scribe mark B in reverse visible on overgrowth removed from rotted lower blaze.</p> <p style="margin-left: 40px;">A madrone, 16 ins. diam., bears S. 75° W., 25 lks. dist., no marks remaining on rotted out blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> T30S R6W ¼ S2 * S1 1991 </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears N. 39¼° E., 59 lks. dist., mkd. ¼ S1 BT.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 39½° W., 29 lks. dist., mkd. ¼ S2 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 50%; margin-left: 0;"/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 88° 54' 00" W., bet. secs. 11 and 14.</p> <p>Ascend gentle SE. slope through open pastureland.</p>
1.90	Lane Creek, dry, 10 lks. wide, drains N. 35° E.
3.40	Graveled road, 30 lks. wide, bears N. 30° E. and S. 30° W.
20.15	End of old fence line, extending N.
20.270	Point for the E 1/16 sec. cor. of secs. 11 and 14.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

S11
E 1/16 -----
S14
1991

from which

An oak, 4 ins. diam., bears N. 41° E., 24 lks. dist., mkd. X BT.

A cedar, 18 ins. diam., bears S. 25° W., 147 lks. dist., mkd. E 1/16 S14 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located 20 lks. N. of a graveled road, 30 lks. wide, bearing E. and S. 80° W.

Continue to ascend over broken SE. slope.

40.540

The ¼ sec. cor. of secs. 11 and 14, perpetuated by Frank Cain, Deputy County Surveyor, in 1920, recorded in Douglas County Corner Renewal Records, and further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Corner Renewal Records, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T30S
S11
¼ -----
S14
R6W
1963

from which the remaining original bearing tree

A black oak, 42 ins. diam., bears N. 40° W., 373 lks. dist., with healed blaze. (Record, 380 lks.)

and a bearing tree mkd. by Cain

A white oak, 38 ins. diam., bears S. 41° W., 233 lks. dist., with healed blaze.

The corner is located 4 lks. W. of a wire fence, extending N. and S. for 20 lks.; thence W.

From the cor. of secs. 10, 11, 14, and 15, perpetuated by James W. Byron, Deputy County Surveyor, in 1964, recorded in Douglas County Corner Renewal Records, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	COUNTY SURVEYORS OFFICE T30S $\frac{S10 * S11}{S15 * S14}$ R6W 1964
	from which the remains of an original bearing tree A rotted oak stump, 20 ins. diam., bears N. 50° E., 254 lks. dist., no marks remaining. and bearing trees mkd. by Byron A madrone, 11 ins. diam., bears N. 58° E., 45 lks. dist., with healed blaze. A madrone, 13 ins. diam., bears S. 5° E., 79 lks. dist., with illegible scribe marks on partially healed blaze. A madrone, 7 ins. diam., bears S. 29° W., 82½ lks. dist., with healed blaze. A madrone, 18 ins. diam., bears N. 75° W., 50 lks. dist., with healed blaze. The corner is located 2 lks. S. of a wire fence, bearing E. and W. N. 1° 05' 30" E., bet. secs. 10 and 11. Ascend SE. slope, through scattering timber and dense undergrowth. 2.80 Spur, slopes E.; desc. over NE. slope. 10.80 Ravine, drains E.; asc. over SE. slope. 19.570 Point for the S 1/16 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. $\frac{S 1/16}{S10 * S11}$ 1991 from which A pine, 11 ins. diam., bears S. 65° E., 41 lks. dist., mkd. S 1/16 S11 BT. A pine, 13 ins. diam., bears N. 10° W., 130 lks. dist., mkd. S 1/16 S10 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Continue over SE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
19.90	Dirt road, 20 lks. wide, on a curve, bears N. 35° E. and W.; along broken E. slope.
27.10	Sanderson Creek, 2 lks. wide, course S. 60° E.; asc. steep S. slope.
36.50	Spur, slopes SW.; along broken W. slope.
39.140	The ¼ sec. cor. of secs. 10 and 11, perpetuated by Randall Smith of the County Surveyors Office, in 1989, recorded in Douglas County Corner Renewal Records, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T30S ¼ * S10 * S11 R6W 1989 1963
	from which the remaining original bearing tree
	A pine, 40 ins. diam., bears S. 25° W., 164 lks. dist., with scribe marks ¼S on opened upper blaze and BT on opened lower blaze.
	and the remains of the bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963
	A pine, 16 ins. diam., bears S. 20° E., 36½ lks. dist., with healed double blaze.
	A root hole, bears N. 26° W., 85 lks. dist., with a down pine alongside, size indeterminate, with scribe marks ¼ S10 CS BT on open blaze.
	and a bearing tree mkd. by Rogers
	A pine, 10 ins. diam., bears N. 59° W., 46 lks. dist., with scribe marks ¼ S10 BT visible on partially healed blaze.
	and a bearing tree mkd. by Smith
	A pine, 18 ins. diam., bears N. 3½° E., 8½ lks. dist., with scribe marks ¼ S11 CS BT visible on open blaze at breast height.
	<hr style="width: 20%; margin: 0 auto;"/> N. 0° 36' 30" E., beginning new measurement.
	Ascend over broken SW. slope, through scattering timber and undergrowth.
8.30	Ridge, bears N. 35° W. and S. 35° E.; along broken E. slope.
21.30	Spur, slopes NE.; desc. N. slope.
35.80	Bottom of descent, slopes NE.; asc. SE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS
40.465

The cor. of secs. 2, 3, 10, and 11, perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, recorded in Survey File 42-274, Douglas County Records, monumented with an iron pipe, 24 ins. long, 2½ ins. diam., firmly set, projecting 8 ins. above ground, from which the remaining original bearing trees:

A madrone, 35 ins. diam., bears S. 15° E., 19 lks. dist., with healed blaze. (Record, S. 20° E.)

A fir, 55 ins. diam., bears N. 57° W., 29 lks. dist., with healed blaze. (Record, N. 80° W.)

and the remains of bearing trees mkd. by Markham

A madrone, 32 ins. diam., bears N. 16° E., 54 lks. dist., with healed blaze.

A black oak, 32 ins. diam., bears S. 10° E., 130 lks. dist., with healed blaze.

A root hole, bears S. 86° W., 87 lks. dist., with a down madrone alongside, 30 ins. diam., with illegible scribe marks visible on partially healed blaze.

A madrone, 24 ins. diam., bears N. 50° W., 84½ lks. dist., with scribe marks R6 S2 visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T30S} \quad \text{R6W} \\ \hline \text{S3} \quad * \quad \text{S2} \\ \hline \text{S10} \quad * \quad \text{S11} \\ 1990 \end{array}$$

from which a new bearing tree

A fir, 7 ins. diam., bears S. 23° W., 109 lks. dist., mkd. T30S R6W S10 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the iron pipe alongsidethe stainless steel post.

The corner is located at the corner of fences, extending E., W., and S.

From this point, the Bureau of Land Management Geodetic Control Station No. EC 41056, at latitude 42° 58' 53.756" N., longitude 123° 23' 16.850" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 32° 11' 00" W., 23.018 chs. dist. (mean bearing and sea level distance), monumented with an aluminum tablet, 3 ins. diam., set in cement flush with the ground, mkd. EC 41056 GPS 1990.

From the cor. of secs. 1, 2, 11, and 12.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	S. 89° 58' 00" W., bet. secs. 2 and 11.
	Descend gentle W. slope through creek bottom land.
1.10	Creek, 10 lks. wide, course S. 20° E.; asc. steep E. slope through scattering timber and dense undergrowth.
8.80	Spur, slopes S. 20° E.; desc. broken SW. slope.
20.170	Point for the E 1/16 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	S2 E 1/16 ---- S11 1991
	from which
	A pine, 11 ins. diam., bears N. 5 3/4° E., 90 lks. dist., mkd. E 1/16 S2 BT.
	A pine, 10 ins. diam., bears S. 46° W., 100½ lks. dist., mkd. E 1/16 S11 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue to descend broken SW. slope.
37.30	Judd Creek, 10 lks. wide, course SE.; asc. over NE. slope.
40.340	Point for the ¼ sec. cor. of secs. 2 and 11 at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T30S R6W S2 ¼----- S11 1991
	from which
	A fir, 19 ins. diam., bears N. 34° E., 26½ lks. dist., mkd. ¼ S2 BT.
	A fir, 13 ins. diam., bears S. 9° E., 8½ lks. dist., mkd. ¼ S11 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, a point established as the $\frac{1}{4}$ sec. cor. of secs. 2 and 11 by Herbert L. Northcraft, Registered Land Surveyor No. 750, in 1974, recorded in Map File 54-13, Douglas County Records, bears S. $3^{\circ} 12' 00''$ E., 2.250 chs. dist., monumented with a steel rod, $\frac{5}{8}$ in. diam., projecting 7 ins. above ground, from which bearing trees mkd. by Northcraft:</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. $47\frac{1}{4}^{\circ}$ E., 167 lks. dist., with scribe marks $\frac{1}{4}$ S11 T30S R6W BT 750 visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. $36\frac{1}{2}^{\circ}$ W., 49 lks. dist., with scribe marks $\frac{1}{4}$ S2 T30S R6W BT 750 visible on partially healed blaze.</p> <p>This point was established using improper control and is not utilized in this survey.</p> <p>Continue ascent over broken NE. slope.</p>
59.10	Graveled road, 30 lks. wide, bears N. 55° W. and S. 55° E.
66.50	Top of ascent, slopes N.; desc. NW. slope.
70.70	Creek, 2 lks. wide, course N. 60° E.; asc. broken SE. slope.
80.680	The cor. of secs. 2, 3, 10, and 11.
	<hr/> <p>N. $1^{\circ} 55' 00''$ E., bet. secs. 2 and 3.</p> <p>Ascend SE. slope; through heavy timber and dense undergrowth.</p>
2.10	Spur, slopes E.; desc. over broken NE. slope.
22.10	Judd Creek, 10 lks. wide, course SE.; asc. over broken SW. slope.
38.735	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T30S R6W $\frac{1}{4}$ S3 * S2 1990</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 87° E., 43 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears N. 15° W., 20 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue to ascend broken SW. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
44.90	Spur, slopes S. 60° W.; desc. over broken NW. slope.
61.60	Creek, 10 lks. wide, course S. 30° W.; asc. over broken SE. slope.
75.065	The cor. of secs. 2, 3, 34, and 35 on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	<p align="center">T29S R6W S34 * S35 S3 * S2 T30S R6W 1958</p>
	from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1956
	<p align="center">A fir stump, 10 ins. diam., bears N. 32° E., 85 lks. dist., no visible marks. (Record, N. 32¼° E., 84 lks.)</p>
	<p align="center">A fir, 34 ins. diam., bears S. 10½° E., 42 lks. dist., with healed blaze. (Record, S. 10 3/4° E., 52 lks.)</p>
	and the remains of bearing trees mkd. by Thielsen and White
	<p align="center">A root hole, bears S. 25 3/4° W., 53 lks. dist., with a down cedar alongside, 27 ins. diam., no visible marks.</p>
	<p align="center">A fir stump, 37 ins. diam., bears N. 60½° W., 72 lks. dist., with healed blaze.</p>
	and new bearing trees
	<p align="center">A fir, 10 ins. diam., bears N. 54° E., 85 lks. dist., mkd. T29S R6W S35 BT.</p>
	<p align="center">A fir, 12 ins. diam., bears S. 79½° W., 33 lks. dist., mkd. T30S R6W S3 BT.</p>
	<p align="center">A fir, 15 ins. diam., bears N. 80° W., 39 lks. dist., mkd. T29S R6W S34 BT.</p>
	<hr/> <p align="center">Subdivision of Section 3, T. 30 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>
	From the ¼ sec. cor. of secs. 3 and 10, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	<p align="center">COUNTY SURVEYORS OFFICE T30S S3 ¼ ----- S10 R6W 1963</p>
	from which the remains of an original bearing tree

Subdivision of Section 3,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A root hole, bears S. 30° W., 5 lks. dist., with a down decayed fir alongside, size indeterminate, no visible marks.</p> <p>and the remains of bearing trees mkd. by John Markham, Jr., Registered Engineer No. 2880, in 1957</p> <p>A sawed fir stump, 16 ins. diam., bears N. 36° E., 57½ lks. dist., no visible marks.</p> <p>A sawed fir stump, 26 ins. diam., bears N. 63° E., 54 lks. dist., with scribe marks BT visible on open blaze.</p> <p>A sawed fir stump, 37 ins. diam., bears N. 13° W., 51 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Roseberry</p> <p>A cedar, 12 ins. diam., bears N. 73° W., 61 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Rogers</p> <p>A fir, 9 ins. diam., bears S. 60° E., 6½ lks. dist., with scribe marks ¼ S10 BT visible on partially healed blaze.</p> <p>The corner is located 15 lks. N. of an E. and W. fence line.</p> <p>N. 4° 26' 00" E., on the N. and S. center line of sec. 3.</p> <p>Descend over steep broken N. slope; through heavy timber and dense undergrowth.</p>
20.50	Creek, 5 lks. wide, course S. 70° E.; asc. over S. slope.
25.00	Spur, slopes E.; desc. over NE. slope.
29.80	Creek, 5 lks. wide, course SE.; asc. over broken SE. slope.
39.150	<p>Point for the center ¼ sec. cor. of sec. 3, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T30S R6W C¼ S3 1990</p> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 55½° E., 84 lks. dist., mkd. C¼ S3 BT.</p> <p>A madrone, 10 ins. diam., bears S. 58 ¾° E., 109 lks. dist., mkd. C¼ S3 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue to ascend over broken S. slope.</p>

Subdivision of Section 3,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
44.10	Graveled road, 20 lks. wide, bears N. 80° E. and S. 80° W.
59.20	Spur, slopes S. 70° E.; desc. over broken NE. slope.
66.50	Bottom of descent, slopes E.; along E. slope.
71.50	Begin to ascend over broken SE. slope.
75.610	The ¼ sec. cor. of secs. 3 and 34 on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	T29S R6W S34 ¼ ----- S3 T30S R6W 1958
	from which the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1956
	A root hole, bears N. 37° E., 34½ lks. dist., with a down fir stump alongside, 40 ins. diam., with scribe marks ¼ S34 CS BT visible on the bark.
	A root hole, bears S. 59½° E., 57 lks. dist., with a down fir alongside, 45 ins. diam., with scribe marks visible on the bark.
	and new bearing trees
	A Douglas fir, 12 ins. diam., bears N. 46° E., 14 lks. dist., mkd. ¼ S34 BT.
	A white fir, 12 ins. diam., bears S. 20° W., 18 lks. dist., mkd. ¼ S3 BT.
	The corner is located 15 lks. E. of an abandoned dirt road, 20 lks. wide, bearing N. 30° E. and S. 30° W.

	From the ¼ sec. cor. of secs. 2 and 3.
	N. 89° 35' 00" W., on the E. and W. center line of sec. 3.
	Descend over broken W. slope through heavy timber and dense undergrowth.
10.40	Judd Creek, 10 lks. wide, course S. 10° E.; asc. over broken NE. slope.
24.50	Spur, slopes SE., along broken S. slope.
41.330	The center ¼ sec. cor. of sec. 3. Descend over broken SW. slope.
48.70	Ravine, drains S.; asc. over SE. slope.

**Subdivision of Section 3,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
54.40	Graveled road, 30 lks. wide, bears N. and S.
55.50	Spur, slopes SE.; along S. slope.
68.30	Ravine, drains SE.; asc. SE. slope.
74.10	Rocky spur, slopes S.; desc. SW. slope.
77.10	Ravine, drains S.; asc. over broken E. slope.
81.640	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	$\frac{1}{4}$ S4 * S3 T30S R6W 1967
	from which the remains of bearing trees recorded by John Markham, Jr., Registered Engineer No. 2880, in 1952
	A fir, 28 ins. diam., bears S. 62 $\frac{1}{2}$ ° E., 13 lks. dist., with rotted blaze.
	A madrone stump, 25 ins. diam., bears S. 1 $\frac{1}{4}$ ° W., 22 $\frac{1}{2}$ lks. dist., no visible marks.
	and the remains of a bearing tree mkd. by Markham
	A root crown, 14 ins. diam., bears N. 40 $\frac{1}{2}$ ° W., 36 lks. dist., no visible marks.
	and the remains of a bearing tree mkd. by Roseberry
	A fir snag, 24 ins. diam., bears West, 15 lks. dist., with scribe marks S4 BT visible on partially healed blaze. (Record, N. 85° E.)
	and a new bearing tree
	A fir, 12 ins. diam., bears N. 52° W., 8 $\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	<hr/> Subdivision of Section 11, T. 30 S., R. 6 W., Willamette Meridian, Oregon <hr/>
	From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
	N. 0° 41' 30" E., on the N. and S. center line of sec. 11.
	Ascend broken S. slope through scattering timber and undergrowth.
19.695	Point for the center S $\frac{1}{16}$ sec. cor. of sec. 11.
	Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

Subdivision of Section 11,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	C S 1/16 * S11 C 1991
	from which
	A pine, 20 ins. diam., bears N. 61° E., 20 lks. dist., mkd. CS 1/16 S11 BT.
	A pine, 16 ins. diam., bears N. 15° W., 8½ lks. dist., mkd. CS 1/16 S11 BT.
	From this point, the corner of wire fences extending N. 20° W. and S., bears N. 10° W., 8 lks. dist.
	Ascend over broken SW. slope.
27.50	Spur, slopes S. 35° E.; asc. over broken SE. slope.
39.390	Point for the center ¼ sec. cor. of sec. 11, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T30S R6W C¼ S11 1991
	from which
	A cedar, 23 ins. diam., bears S. 40½° E., 57½ lks. dist., mkd. T30S R6W C¼ S11 BT.
	A pine, 20 ins. diam., bears S. 62¼° W., 55 lks. dist., mkd. T30S R6W C¼ S11 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue over SE. slope.
43.90	Ridge, bears N. 40° E. and S. 40° W.; desc. over broken NW. slope.
59.600	Point for the center N 1/16 sec. cor. of sec. 11.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	C N 1/16 * S11 C 1991
	A cedar, 18 ins. diam., bears S. 30° E., 8 lks. dist., mkd. CN 1/16 S11 BT.
	A pine, 20 ins. diam., bears N. 82° W., 55 lks. dist., mkd. CN 1/16 S11 BT.

Subdivision of Section 11,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue over NW. slope.
65.20	Graveled road, 30 lks. wide, bears N. 35° E. and S. 35° W.
67.70	Creek, 2 lks. wide, course NE.; asc. over SE. slope.
73.20	Spur, slopes E.; desc. over NE. slope.
79.810	The ¼ sec. cor. of secs. 2 and 11.
	<hr/>
	From the ¼ sec. cor. of secs. 11 and 12.
	S. 89° 54' 30" W., on the E. and W. center line of sec. 11.
	Ascend over broken NE. slope through scattering timber and undergrowth.
16.70	Ridge, bears N. 50° W. and S. 50° E.; along broken S. slope.
20.245	Point for the center E 1/16 sec. cor. of sec. 11.
	Set an aluminum rod, 10 ins. long, ½ in. diam., 6 ins. into solid rock, in cement, with an aluminum cap mkd.
	E 1/16 C ----- C S11 1991
	from which
	A pine, 22 ins. diam., bears N. 65 3/4° E., 49½ lks. dist., mkd. CE 1/16 S11 BT.
	A pine, 8 ins. diam., bears N. 16½° W., 51 lks. dist., mkd. CE 1/16 S11 BT.
	Ascend over broken SE. slope.
40.490	The center ¼ sec. cor. of sec. 11.
	Continue over SE. slope.
50.80	Ridge, bears N. and S. turning SW.; along broken N. slope.
58.70	Same ridge, bears N. 35° W. and S. 35° E.; along broken S. slope.
78.70	Spur, slopes S. 20° W.; desc. SW. slope.
80.790	The ¼ sec. cor. of secs. 10 and 11.
	<hr/>
	From the center E 1/16 sec. cor. of sec. 11.
	N. 0° 33' 00" E., on the N. and S. center line of the NE¼ of sec. 11.

Subdivision of Section 11,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Ascend over S. slope through scattering timber and undergrowth.
0.50	Ridge, bears N. 50° W. and S. 50° E.; desc. over broken NE. slope.
11.80	Ravine, drains N. 70° E.; asc. over SE. slope.
20.190	Point for the NE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the NE¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	NE 1/16 S11 1991
	from which
	A pine, 21 ins. diam., bears N. 35½° E., 16 lks. dist., mkd. NE 1/16 S11 BT.
	A cedar, 16 ins. diam., bears N. 25¼° W., 36 lks. dist., mkd. NE 1/16 S11 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	The corner is located on top of a spur, sloping NE.
	Descend over broken NW. slope.
27.80	Graveled road, 25 lks. wide, bears N. 70° E. and S. 70° W.
29.70	Judd Creek, 10 lks. wide, course SE.; asc. over SW. slope.
40.385	The E 1/16 sec. cor. of secs. 2 and 11.
	<hr/>
	From the N 1/16 sec. cor. of secs. 11 and 12.
	S. 89° 56' 00" W., on the E. and W. center line of the NE¼ of sec. 11.
	Descend over SW. slope through scattering timber and undergrowth.
4.30	Creek, 5 lks. wide, course S. 15° W.; along S. slope.
7.80	Judd Creek, 10 lks. wide, course SE.; asc. broken E. slope.
11.70	Graveled road, 30 lks. wide, bears N. 50° E. and S. 50° W.
20.210	The NE 1/16 sec. cor. of sec. 11.
	Along broken N. slope.
29.80	Begin ascent over broken NE. slope.
39.50	Spur, slopes NE.; desc. over NW. slope.

Subdivision of Section 11,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
40.410	<p>The center N 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0° 38' 30" E., on the N. and S. center line of the SE¼ of sec. 11.</p> <p>Ascend over broken SE. slope through open pastureland.</p>
19.910	<p>Point for the SE 1/16 sec. cor. of secs. 11, at intersection with the E. and W. center line of the SE¼. There is no remaining evidence of the corner established by W. F. Briggs, County Surveyor, in 1885, recorded in Volume 1, page 62, Douglas County Records, or the corner established by Frank Cain, Deputy County Surveyor, in 1920, recorded in Volume 2, page 273, Douglas County Records.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S11 1991</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears N. 88½° W., 193 lks. dist., mkd. SE 1/16 S11 BT.</p> <p style="padding-left: 40px;">An oak, 29 ins. diam., bears N. 10 3/4° W., 274 lks. dist., mkd. SE 1/16 S11 BT.</p> <p>No suitable trees available within limits S. or E. of the corner.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend broken SE. slope through scattering timber and undergrowth.</p>
39.825	<p>The center E 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89° 29' 30" W., on the E. and W. center line of the SE¼ of sec. 11.</p> <p>Ascend over broken SE. slope through scattering timber and undergrowth.</p>
20.255	<p>The SE 1/16 sec. cor. of sec. 11.</p> <p>Continue over broken SE. slope.</p>
37.60	<p>Spur, slopes S.; desc. over SW. slope.</p>
40.505	<p>The center S 1/16 sec. cor. of sec. 11.</p> <hr/>

Subdivision of Section 11,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	N. 89° 53' 30" W., on the E. and W. center line of the SW¼ of sec. 11.
	Along broken S. slope through scattering timber and undergrowth.
14.80	Ravine, drains S. 10° W.; asc. over SE. slope.
29.20	Spur, slopes S.; desc. over broken SW. slope.
34.10	Sanderson Creek, 10 lks. wide, course S. 20° E.; asc. over broken E. slope.
36.10	Graveled road, 20 lks. wide, bears N. 30° W. and S. 30° E.
40.430	The S 1/16 sec. cor. of secs. 10 and 11.
GENERAL DESCRIPTION	
<p>The lands included in the foregoing survey are located in Douglas County approximately two miles northwest of the town of Riddle, Oregon. The terrain is mountainous with elevations ranging from 800 feet above sea level to 1,800 feet above sea level.</p>	
<p>The drainage is southeasterly by numerous small creeks flowing into Judd Creek. The soil is rocky clay. The lands are forested with fir, cedar, hemlock, pine, myrtle, maple, oak, madrone, and willow, with undergrowth of blackberry, huckleberry, salal, Oregon grape, arrowwood, poison oak, manzanita, buckbrush, and ferns.</p>	
<p>Access is via secondary roads branching from County Highway No. 263.</p>	
<p>There were no mineral deposits noted along the lines of survey. The land is primarily used for timber production and cattle and sheep ranching.</p>	
<p>The average of a number of readings along the lines surveyed gives a value of 20° East for the mean magnetic declination. There is a range of 1° due to local attraction.</p>	