

T. 23 S., R. 13 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of a dependent resurvey of the Fifth Standard Parallel South through Range 13 West, portions of the east boundary, subdivisional lines, and adjusted record meanders, and the subdivision of sections 13, 14, 22, 23, and 26, the survey of Parcel A and traverse of a portion of the mean high water line of Maud Lake in section 34, township 23 south, range 13 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is:

The north and east boundaries, meanders of the Pacific Ocean, and portions of the south boundary and subdivisional lines were surveyed by Harvey Gordon, U.S. Deputy Surveyor, in 1857.

The remaining portions of the south boundary and subdivisional lines were surveyed by William Hall, U.S. Deputy Surveyor, in 1883.

The west tier of sections of T. 23 S., R. 12 W., including the north boundary of section 6, were surveyed by Simon B. Cathcart, U.S. Deputy Surveyor, in 1891, changing the original corner of Tps. 22 and 23 S., Rs. 12 and 13 W., to serve for Tps. 22 and 23 S., R. 13 W. only.

Exchange survey number 256, encompassing a parcel in section 13, was surveyed by George W. Williams, Forester, U.S. Forest Service, in 1950.

A portion of the south boundary and subdivisional lines was resurveyed by Peter A. Peterson, Cadastral Surveyor, in 1976.

The corner of sections 2, 3, 34, and 35, on the south boundary of the township, established by Harvey Gordon in 1857, was remonumented in 1980 by Glenn F. Godson and John P. Lee, Cadastral Surveyors, during the resurvey of a portion of the subdivisional lines of T. 24 S., R. 13 W.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 23, 1980, and Supplemental Special Instructions dated June 25, 1982, under Group Number 1037, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice.

The geographic position of the corner of sections 26, 27, 34, and 35, as determined by a tie to triangulation station "GRASS", established by the Oregon State Highway Department in 1968, and recovered by the United States Geological Survey in 1970, in the northwest quarter of section 9, T. 24 S., R. 13 W., is: