

T. 23 S., R. 13 W., Willamette Meridian, Oregon

CHAINS

Latitude 43° 32' 19.8" N. Longitude 124° 13' 16.0" W.
The mean magnetic declination is 19½° E.

Dependent Resurvey of the Fifth Standard Parallel South
Through R. 13 W., Willamette Meridian, Oregon

(Restoring the survey by Harvey Gordon in 1857)

Beginning at the standard cor. of Tps. 22 and 23 S., R. 13 W., perpetuated by J.M. Gearhart, County Surveyor, in 1949, subsequently perpetuated and recorded by Russell F. Torbeck, County Surveyor, in 1974, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 22 S	T 23 S
R 13 W	R 12 W
36	
1	6
T 23 S	
R 13 W	

from which the remains of the original bearing trees

A stump hole, bears N. 41° E., 10 lks. dist.

A fir, rotten windfall, 18 ins. diam., bears
S. 22° E., 48 lks. dist., mkd. with axe blaze.

A fir, rotten windfall, 24 ins. diam., bears
S. 85° W., 11 lks. dist., with a cross section
sawed out. (Torbeck has reported removing a
section of this tree with blaze and visible
scribe marks.)

A stump hole, bears N. 6° W., 42 lks. dist.

and bearing trees mkd. by Gearhart

A fir, 25 ins. diam., bears S. 86° W., 26½ lks.
dist., mkd. with a healed blaze.

A fir, 34 ins. diam., bears N. 30° W., 74 lks.
dist., mkd. with a healed blaze.

and a bearing tree mkd. by Torbeck

A cedar, 13 ins. diam., bears N. 83½° E., 34½
lks. dist., with scribe marks T23 R12 S6 BT
visible on a partially healed blaze.

From this point, mostly downed woven wire fence, bears
S., 10 lks. dist., extending N. 25° E. and S. 25° W.

West, on record bearing bet. secs. 1 and 36.

Descend 80 ft. over NW. slope, through heavy timber and
dense undergrowth.

2.60 Old Highway No. 101, 31 lks. wide, asphalt surfaced,
bears N. 45° E. and S. 25° W., on a curve.

7.55 Creek, 10 lks. wide, course S. 45° W.; asc. 70 ft. over
SE. slope.