

Dependent Resurvey, Fifth Stan. Par. S.,
R. 13 W., Willamette Meridian, Oregon

CHAINS	
	Descend 115 ft. over open rolling sand dunes.
38.50	Enter scattered scrub pines and moderate undergrowth, edge bears N. and S.
40.00	Point for the standard $\frac{1}{4}$ sec. cor. of secs. 2 and 35, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{4}$ ins. diam., 21 ins. in the ground, in concrete, with brass cap mkd.
	$\begin{array}{r} S C \\ T 22 S R 13 W \\ \frac{1}{4} \frac{S 35}{S 2} \\ T 23 S \\ 1980 \end{array}$
	No suitable trees available.
	Set a 5 ft. steel fence post alongside the iron post.
	Cross rolling sand dunes.
56.00	Point for the meander cor. of secs. 2 and 35, at record distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{4}$ ins. diam., 22 ins. in the ground, in concrete, with brass cap mkd.
	$\begin{array}{r} T 22 S \\ MC \frac{S 35}{S 2} R 13 W \\ T 23 S \\ 1980 \end{array}$
	No suitable trees available.
	Set a 5 ft. steel fence post alongside the iron post.
	This cor. is located E., 1.30 chs. dist. from the line of mean high tide of the Pacific Ocean which bears N. 15° E. and S. 15° W.
	Land, rolling. Soil, sand. Timber, scrub pine; undergrowth, ceanothus and beach grass.
Dependent Resurvey of a Portion of the East Boundary, T. 23 S., R. 13 W., Willamette Meridian, Oregon	
(Restoring the survey by Harvey Gordon in 1857, and the survey by Simon B. Cathcart in 1891)	
Beginning at the cor. of secs. 13, 18, 19, and 24, reestablished by person(s) unknown, subsequently perpetuated and recorded by Clifford A. Stephens, Registered Land Surveyor No. 238, Oregon, in 1948, and by Russell F. Torbeck, County Surveyor, in 1974, and accepted as the best available evidence of the position of the original	

COOS COUNTY