

CHAINS

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
AND
THE SUBDIVISION OF SECTION 29,
TOWNSHIP 25 SOUTH, RANGE 2 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Wayne L. Rogers, Cadastral Surveyor
Robert H. Browning, Surveying Technician

Under Special Instructions dated August 6, 1992,
and approved August 7, 1992,
which provided for the surveys included under Group No. 1659,
and Assignment Instructions dated August 19, 1992.

Survey commenced June 21, 1993

Survey completed July 28, 1993

T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivision of section 29, township 25 south, range 2 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1900, Hezekiah H. Johnson, U.S. Deputy Surveyor, surveyed the subdivisional lines.

in 1962, Floyd A. Brooks, Cadastral Surveyor, remonumented certain original corner points without survey.

Between 1972 and 1975, Harvey E. Wofford, Daniel L. Berry, and G. Steven Popken, Cadastral Surveyors, and Glenn S. Baughman, Registered Land Surveyor No. 536, Oregon, resurveyed a portion of the subdivisional lines and subdivided sections 31 and 32.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated August 6, 1992, for Group No. 1659, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the corner of sections 19, 20, 29, and 30, as determined by a tie to Geodetic Control Station EC 41167, established by the Bureau of Land Management in 1992, is as follows:

Latitude 43° 22' 23.68" N. Longitude 122° 58' 18.30" W.

The mean magnetic declination is 18° East.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">(Restoring the survey by Hezekiah E. Johnson in 1900, the remonumentation by Floyd A. Brooks in 1962, and the resurvey by Harvey E. Wofford, Daniel L. Berry, G. Steven Popken, and Glenn S. Baughman in 1972-75)</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set flush with the ground, with original basalt stone alongside, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 29 * S 28 T25S R2W 1962 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed hemlock stump, 24 ins. diam., bears N. 39° E., 31 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A decayed fir snag, 18 ins. diam., bears S. 84° W., 59 lks. dist., no marks visible.</p> <p>and the bearing object and remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">The west face of a rock outcrop with overhang, bears S. $70\frac{1}{4}^{\circ}$ E., $36\frac{1}{2}$ lks. dist., mkd. BXO.</p> <p style="padding-left: 40px;">A sawed cedar stump, 15 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., $42\frac{1}{2}$ lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears N. 21° W., 100 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>N. $0^{\circ} 37' 00''$ E., bet. secs. 28 and 29.</p> <p>Descend over broken NW. slope through heavy timber and dense undergrowth.</p>
13.80	<p>The west edge of landing, with a dirt road, 15 lks. wide, bears S. 80° E., also spur, slopes N. 80° W.; desc. over broken NE. slope.</p>
20.705	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 28 and 29.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> N $\frac{1}{16}$ S 29 * S 28 1993 </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 77° E., 11 lks. dist., mkd. N $\frac{1}{16}$ S28 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 13 ins. diam., bears N. 5° W., 21 lks. dist., mkd. N 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over broken NE. slope.</p>
32.30	Graveled road, 25 lks. wide, bears S. 85° E. and S. 75° W.
41.410	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;"> T25S R2W <u>S 20 * S 21</u> S 29 * S 28 1962 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 45° E., 10 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 50 ins. diam., bears S. 13° W., 29 lks. dist., with scribe marks T25S R2W S29 visible on opened blaze.</p> <p>and bearing trees mkd. by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1957, as recorded in Douglas County Surveyor's Office Survey File No. CS 42/308</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 13½° W., 91 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears West, 52 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 81° E., 57 lks. dist., mkd. T25S R2W S21 BT.</p> <p>The corner is located on a spur, sloping N. 30° E., 20 lks. S. of a creek, 10 lks. wide, course S. 75° W., and 20 lks. W. of the same creek, 10 lks. wide, course North.</p> <hr/> <p>From the ¼ sec. cor. of secs. 29 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> S 29 1/4 ----- S 32 T25S R2W 1962 </p> <p>from which the original bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 35 ins. diam., bears S. 43° E., 12 lks. dist., with healed blaze.</p> <p>A fir, 37 ins. diam., bears N. 18° W., 112 lks. dist., with healed blaze.</p> <p>N. 89° 43' 00" W., bet. secs. 29 and 32.</p> <p>Descend over broken SW. slope through heavy timber and dense undergrowth.</p>
14.55	Conley Creek, 10 lks. wide, course N. 50° W.; asc. over NE. slope.
20.025	<p>The W 1/16 sec. cor. of secs. 29 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 29 W 1/16 ----- S 32 1972</p> <p>from which the bearing trees mkd. by Wofford, Berry, Popken, and Baughman</p> <p>A fir, 10 ins. diam., bears N. 71° E., 14 lks. dist., with healed double blaze.</p> <p>A hemlock, 13 ins. diam., bears S. 22° W., 33 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 37' 30" W., beginning a new measurement.</p> <p>Ascend over NE. slope.</p>
19.980	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T25S R2W <u>S 30 * S 29</u> S 31 * S 32 1962</p> <p>from which the remains of the original bearing trees</p> <p>A decayed chinquapin stump, size indeterminate, bears N. 36° E., 36 lks. dist., with decayed remains alongside, no marks visible.</p> <p>A chinquapin snag, 15 ins. diam., bears S. 44½° E., 33 lks. dist., with healed blaze.</p> <p>A roothole, bears S. 13° W., 41 lks. dist., with a down chinquapin alongside, 16 ins. diam., with healed blaze.</p> <p>A fir, 30 ins. diam., bears N. 12½° W., 51 lks. dist., with healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>and a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 78° E., 21 lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Wofford, Berry, Popken, and Baughman</p> <p style="padding-left: 40px;">A sawed hemlock stump, 19 ins. diam., bears S. 3° E., 55 lks. dist., with partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 17° W., 94 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 4 ins. diam., bears S. 29½° E., 40 lks. dist., mkd. X BT.</p> <p>The corner is located on a spur, sloping N. 20° E.</p> <hr/> <p>N. 1° 05' 00" E., bet. secs. 29 and 30.</p> <p>Descend along broken NW. slope along timber edge, with clearcut to the west.</p>
16.60	Graveled road, 25 lks. wide, bears E. and N. 65° W.
20.300	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 30 * S 29 1993</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 7 ins. diam., bears N. 44° E., 33 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 32° E., 115 lks. dist., mkd. S 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in the edge of timber, with clearcut to the west.</p> <p>Descend over broken NW. slope.</p>
31.55	Rock Creek, 100 lks. wide, course N. 65° W.; asc. over broken S. slope.
40.600	The ¼ sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set flush with the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	1/4 S 30 * S 29 T25S R2W 1962
	from which the remains of the original bearing trees
	A white fir snag, 28 ins. diam., bears S. 72½° E., 52 lks. dist., with scribe marks BT visible on opened blaze.
	A fir stump, 42 ins. diam., bears N. 56¼° W., 126½ lks. dist., with healed blaze.
	and the remains of a bearing tree mkd. by Brooks
	A fir stump, 15 ins. diam., bears N. 15° W., 50 lks. dist., with healed blaze.
	and bearing trees mkd. by Randall Smith and Stephen J. Flause, Deputy County Surveyors, in 1986, as recorded in Douglas County Surveyor's Office C.S. File No. 62/31 and Corner Renewal Notes T. 25 S., R. 2 W., No. 120
	An ash, 13 ins. diam., bears S. 5° E., 21 lks. dist., with scribe marks ¼ S29 CS BT visible on open double blaze.
	A maple, 11 ins. diam., bears S. 88° W., 21 lks. dist., with scribe marks S30 CS BT visible on partially healed double blaze.
	A cedar, 12 ins. diam., bears N. 10° W., 54 lks. dist., with scribe marks S30 CS BT visible on partially healed double blaze.

	N. 0° 25' 00" W., beginning new measurement.
	Ascend over broken S. slope.
11.45	Rock Creek Road, County Road No. 78A, paved, 30 lks. wide, bears N. 60° E. and N. 70° W.
31.80	Graveled road, 30 lks. wide, bears N. 75° W. and S. 75° E.
39.935	The cor. of secs. 19, 20, 29, and 30, perpetuated by James W. Byron, Deputy County Surveyor, in 1959, as recorded in Douglas County Surveyor's Office C.S. File No. 49/102 and Corner Renewal T. 25 S., R. 2 W., No. 40; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 10 ins. above a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.
	COUNTY SURVEYORS OFFICE <u>S 19 * S 20</u> S 30 * S 29 T25S R2W 1959
	from which the remains of the original bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A chinquapin stump, 20 ins. diam., bears N. 65° E., 27 lks. dist., no marks visible.</p> <p>A chinquapin, 14 ins. diam., bears S. 69° E., 21 lks. dist., with decayed partially healed blaze.</p> <p>A cedar stump, 37 ins. diam., bears S. 24° W., 30 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Byron</p> <p>A fir, 21 ins. diam., bears N. 3° E., 24 lks. dist., with healed blaze.</p> <p>A cedar, 16 ins. diam., bears S. 39° E., 32 lks. dist., with healed double blaze.</p> <p>A fir, 27 ins. diam., bears N. 4½° W., 43 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>A hemlock, 13 ins. diam., bears S. 78° W., 22 lks. dist., mkd. T25S R2W S30 BT.</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41167, at latitude 43° 22' 32.581" N., longitude 122° 58' 15.522" W. (NAD 1927), determined by the NAVSTAR Global Positional System, bears N. 28° 13' 54" E., 16.498 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap set flush with the ground, mkd. EC 41167 GPS 1992 and a triangle.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89° 46' 00" W., bet. secs. 20 and 29.</p> <p>Descend over broken NW. slope through heavy timber and dense undergrowth.</p>
3.60	Creek, 10 lks. wide, course S. 20° W.; desc. over broken W. slope.
6.40	Creek, 10 lks. wide, course N. 40° W.; continue over creek bottom.
7.10	Creek, 10 lks. wide, course S. 30° W.; continue over creek bottom.
11.35	Creek, 10 lks. wide, course N. 50° W.; continue over creek bottom.
20.285	Point for the E 1/16 sec. cor. of secs. 20 and 29.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 20 E 1/16 ----- S 29 1993</p> <p>from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 7 ins. diam., bears N. 36 3/4° E., 44 lks. dist., mkd. E 1/16 S20 BT.</p> <p>A fir, 7 ins. diam., bears S. 26½° E., 33 lks. dist., mkd. E 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue over creek bottom.</p>
23.00	Rock Creek, 130 lks. wide, course S.; asc. over nearly level creek bottom.
35.90	Rock Creek Road, County Road No. 78A, paved, 30 lks. wide, bears N. 60° E. and S. 60° W.; begin ascent over broken SE. slope.
40.570	<p>The ¼ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 20 1/4 ----- S 29 T25S R2W 1962</p> <p>from which the remains of the original bearing trees</p> <p>A fir stump, 18 ins. diam., bears N. 27° E., 67 lks. dist., with scribe marks S BT visible on decayed blaze.</p> <p>A fir snag, 18 ins. diam., bears S. 50° E., 54 lks. dist., with healed blaze.</p> <p>and the remains of a bearing tree mkd. by Brooks</p> <p>A fir stump, 11 ins. diam., bears N. 49½° W., 20 lks. dist., with decayed snag lying alongside, with healed blaze.</p> <p>and bearing trees mkd. by Randall Smith and Stephen J. Flause, Deputy County Surveyors, in 1986, as recorded in Douglas County Surveyor's Office C.S. File No. 62/31 and Corner Renewal T. 25 S., R. 2 W., No. 119</p> <p>A fir, 7 ins. diam., bears N. 18° E., 35 lks. dist., with healed blaze.</p> <p>A chinquapin, 8 ins. diam., bears N. 75° E., 43 lks. dist., with scribe marks 1/4 S20 CS BT visible on open blaze.</p> <p>A fir, 7 ins. diam., bears S. 25° W., 44 lks. dist., with healed double blaze.</p> <p>A fir, 11 ins. diam., bears S. 85° W., 33 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89° 28' 30" W., beginning new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over broken SE. slope.
18.50	Spur, slopes SE.; desc. over SW. slope.
20.340	The W 1/16 sec. cor. of secs. 20 and 29, established by Donald L. Peel, Registered Land Surveyor No. 752, in 1981, as recorded in Douglas County Surveyor's Office C.S. File No. 58/256, and is accepted as the corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the bearing trees mkd. by Peel:
	A fir, 19 ins. diam., bears S. 12° W., 24 lks. dist., with healed blaze.
	A fir, 13 ins. diam., bears N. 23° W., 12 lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 20 W 1/16----- S 29 1993
	Deposit a white "DEEP-1" magnetic marker at the base and an iron pipe alongside the stainless steel post.

	S. 89° 28' 30" W., beginning new measurement.
	Descend over SW. slope.
2.55	Creek, 3 lks. wide, course SW.; asc. over broken SE. slope.
13.25	Dirt road, 20 lks. wide, bears N. 30° W. and S. 10° E.
19.85	Spur, slopes N. 70° E.; desc. over SW. slope.
20.340	The cor. of secs. 19, 20, 29, and 30.

	Subdivision of Section 29, T. 25 S., R. 2 W., Willamette Meridian, Oregon

	From the ¼ sec. cor. of secs. 29 and 32.
	N. 0° 47' 00" E., on the N. and S. centerline of sec. 29.
	Ascend over SW. slope through heavy timber and dense undergrowth.
2.20	Spur, slopes N. 80° W.; desc. over broken NW. slope.
20.100	Point for the center S 1/16 sec. cor. of sec. 29.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	C S 1/16 * S 29 C 1993
	from which A fir, 5 ins. diam., bears N. 67¼° E., 37 lks. dist., CS 1/16 S29 BT. A fir, 18 ins. diam., bears S. 43¼° E., 41½ lks. dist., mkd. CS 1/16 S29 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend over broken NW. slope.
33.40	Graveled road, 25 lks. wide, bears N. 35° E. and SW.
40.200	Point for the center ¼ sec. cor. of sec. 29, at intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd. T25S R2W C¼ S 29 1993
	from which A cedar, 8 ins. diam., bears S. 26 3/4° E., 45 lks. dist., mkd. C¼ S29 BT. A hemlock, 13 ins. diam., bears S. 68½° W., 15 lks. dist., mkd. C¼ S29 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend over broken NW. slope.
60.670	Point for the center N 1/16 sec. cor. of sec. 29. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. C N 1/16 * S 29 C 1993
	from which A fir, 3 ins. diam., bears N. 61 3/4° E., 59 lks. dist., mkd. X BT. A fir, 6 ins. diam., bears S. 29¼° E., 48 lks. dist., mkd. CN 1/16 S29 BT.

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Descend over broken NW. slope.
67.50	Rock Creek, 50 lks. wide, course S. 70° W.; asc. over SE. slope.
77.95	Rock Creek Road, County Road No. 78A, paved 30 lks. wide, bears N. 50° E. and S. 50° W.
81.140	The ¼ sec. cor. of secs. 20 and 29.
<hr/>	
	From the ¼ sec. cor. of secs. 28 and 29.
	N. 89° 03' 30" W., on the E. and W. centerline of sec. 29.
	Descend over broken NW. slope through heavy timber and dense undergrowth.
9.60	Spur, slopes N. 20° W.; desc. over NW. slope.
20.355	Point for the center E 1/16 sec. cor. of sec. 29.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	E 1/16 C ----- C S 29 1993
	from which
	A fir, 8 ins. diam., bears N. 7° E., 20 lks. dist., mkd. X BT.
	A fir, 9 ins. diam., bears S. 54½° E., 4 lks. dist., mkd. CE 1/16 S29 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Descend over NW. slope.
25.95	Graveled road, 30 lks. wide, bears N. 15° E. and S. 15° W.
32.55	Graveled road, 15 lks. wide, bears N. 55° E. and S. 55° W.
40.710	The center ¼ sec. cor. of sec. 29.
	Descend over NW. slope.
48.20	Creek, 2 lks. wide, course N. 50° W.; continue descent over NW. slope.
54.70	Rock Creek, 50 lks. wide, course SW.; continue over nearly level creek bottom.
60.620	Point for the center W 1/16 sec. cor. of sec. 29.

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ----- C S 29 1993</p> <p>from which</p> <p style="padding-left: 40px;">An alder, 9 ins. diam., bears N. 39° W., 72 lks. dist., mkd. CW 1/16 S29 BT on the bark.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 4° W., 122 lks. dist., mkd. CW 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue over creek bottom.</p>
78.20	Old creek channel, 15 lks. wide, bears N. 50° E. and S. 50° W.; continue over creek bottom.
80.530	The ¼ sec. cor. of secs. 29 and 30.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 29.</p> <p>N. 0° 43' 00" E., on the N. and S. centerline of the NE¼ of sec. 29.</p> <p>Descend over broken NW. slope through heavy timber and dense undergrowth.</p>
9.90	Graveled road, 25 lks. wide, bears N. 5° E. and S. 30° W.
13.10	Bottom of descent, slopes S. 85° W.; asc. over SW. slope.
13.70	Graveled road, 20 lks. wide, bears N. 15° E. and S. 30° W.
17.15	Spur, slopes N. 55° W.; desc. over broken NE. slope.
20.585	<p>Point for the NE 1/16 sec. cor. of sec. 29, at intersection with the E. and W. centerline of the NE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 29 1993</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 53° E., 26 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 78° W., 17 lks. dist., mkd. NE 1/16 S29 BT.</p>

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Descend over NE. slope.
26.00	Creek, 5 lks. wide, course N. 40° W.; asc. over SW. slope.
30.20	Spur, slopes N. 50° W.; desc. over NW. slope.
35.05	Ravine, drains S. 80° W.; continue over creek bottom.
41.170	The E 1/16 sec. cor. of secs. 20 and 29.
<hr/>	
	From the N 1/16 sec. cor. of secs. 28 and 29.
	N. 89° 24' 30" W., on the E. and W. centerline of the NE¼ of sec. 29.
	Ascend over broken NE. slope, through heavy timber and dense undergrowth.
4.00	Spur, slopes N. 30° W.; desc. over broken NW. slope changing to SW. slope.
14.40	Graveled road, 25 lks. wide, bears N. 20° W. and S. 20° E.
17.15	Creek, 3 lks. wide, course N. 20° W.; asc. over broken NE. slope.
20.320	The NE 1/16 sec. cor. of sec. 29.
	Ascend over NE. slope.
21.40	Spur, slopes N. 10° W.; desc. over broken NW. slope.
40.640	The center N 1/16 sec. cor. of sec. 29.
<hr/>	
	From the W 1/16 sec. cor. of secs. 29 and 32.
	N. 0° 57' 30" E., on the N. and S. centerline of the SW¼ of sec. 29.
	Descend over NE. slope through heavy timber and dense undergrowth.
6.50	Conley Creek, 15 lks. wide, course N. 60° W.; asc. over SW. slope.
12.50	Spur, slopes W.; desc. over NW. slope.
19.60	Conley Creek, 15 lks. wide, course N. 10° E.; desc. along NE. slope.
20.220	Point for the SW 1/16 sec. cor. of sec. 29, at intersection with the E. and W. centerline of the SW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	SW 1/16 S29 1993

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 69½° W., 50 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 15 ¾° W., 33 lks. dist., mkd. SW 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend over NE. slope.</p>
21.75	Conley Creek, 15 lks. wide, course N. 60° W.; desc. over broken N. slope.
24.40	Graveled road, 15 lks. wide, bears NE. and SW.
34.45	Rock Creek, 60 lks. wide, course S. 65° W.; continue along creek bottom.
40.420	The center W 1/16 sec. cor. of sec. 29.
	<hr/> <p>From the center S 1/16 sec. cor. of sec. 29.</p> <p>N. 89° 22' 00" W., on the E. and W. centerline of the SW¼ of sec. 29.</p> <p>Descend over broken NW. slope, through scattering timber and moderate undergrowth.</p>
19.75	Conley Creek, 15 lks. wide, course N. 10° E.; asc. over broken NE. slope.
19.965	The SW 1/16 sec. cor. of sec. 29.
	Ascend over broken NE. slope.
24.95	Spur, slopes N. 10° W.; desc. over NW. slope.
30.30	Graveled road, 15 lks. wide, bears N. 60° E. and S. 60° W.
31.55	Bottom of descent, drains N.; asc. over NE. slope.
38.45	Top of ascent, slopes N.; desc. over NW. slope.
39.910	The S 1/16 sec. cor. of secs. 29 and 30.
	<hr/> <p>From the center W 1/16 sec. cor. of sec. 29.</p> <p>N. 0° 11' 00" E., on the N. and S. centerline of the NW¼ of sec. 29.</p> <p>Ascend over creek bottom, changing to a SW. slope, through scattering timber and moderate undergrowth.</p>
14.20	Spur, slopes N. 80° E.; desc. over NE. slope.

Subdivision of Section 29,
T. 25 S., R. 2 W., Willamette Meridian, Oregon

CHAINS	
22.95	Ravine, drains N. 85° E.; asc. over SE. slope.
27.15	Rock Creek Road, County Road No. 78A, paved, 30 lks. wide, bears N. 85° E. and S. 80° W.
36.10	Creek, 5 lks. wide, course S. 30° E.; asc. over SW. slope.
40.435	The W 1/16 sec. cor. of secs. 20 and 29.
<hr/> <p>GENERAL DESCRIPTION</p>	
<p>The area surveyed is situated eight miles northwesterly of the town of Glide, Oregon. Access is provided by Rock Creek Road with several graveled and dirt roads branching from it into the area.</p>	
<p>The elevations range from approximately 1,880 feet above sea level at the ¼ section corner of sections 28 and 29, to about 1,020 feet above sea level at the center W 1/16 section corner of section 29. The soil is mainly a rocky clay, with a sandy loam in the creek bottoms.</p>	
<p>The area is drained by Rock Creek, Conley Creek, and several other small and seasonal drainage.</p>	
<p>The timber consists primarily of fir, hemlock, cedar, maple, ash, yew, willow, oak, and alder. Undergrowth is made up of vine maple, salmonberry, blackberry, salal, Oregon grape, huckleberry, hazel, devils club, poison oak, rhododendron, arrowwood, fern, and young timber.</p>	
<p>There were no mineral deposits noted along the lines surveyed.</p>	
<p>The mean magnetic declination as shown on the United States Geological Survey 7½ minute quadrangle map "OLD FAIRVIEW, OREGON," Provisional Edition, in 1989, is 18° East.</p> <hr/>	