

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
CORRECTIVE DEPENDENT RESURVEY OF A PORTION OF
THE SOUTH, EAST, AND WEST BOUNDARIES AND SUBDIVISIONAL LINES,
THE CORRECTIVE SURVEY OF SECTIONS 20 AND 26,
THE DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY
(FIFTH STANDARD PARALLEL SOUTH),
EAST AND SOUTH BOUNDARIES AND SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF SECTIONS 1, 25, AND 28,
TOWNSHIP 23 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

**Wayne L. Rogers, Cadastral Surveyor
Boyd W. Peterson, Cadastral Surveyor
Philip G. Griffin, Cadastral Surveyor
Dale T. Bedell, Cadastral Surveyor
Robert H. Browning, Surveying Technician**

Under Special Instructions dated April 19, 1985, approved April 24, 1985;
Amendment to Special Instructions dated May 22, 1986, approved May 23,
1986;
Supplemental Special Instructions dated March 10, 1987, approved
March 11, 1987; and Second Supplemental Special Instructions dated
April 8, 1994, approved April 11, 1994, which provided for the surveys
included under Group No. 1266; Special Instructions dated February 21,
1992,
approved February 24, 1992, which provided for the surveys included under
Group No. 1637; and Special Instructions dated April 8, 1993, approved
April 9, 1993, which provided for the surveys included under Group No.
1688;
and Assignment Instructions dated June 9, 1986; March 27, 1987; March 25,
1992; February 12, 1993; April 20, 1993; October 20, 1993; and April 11,
1994.

**Survey commenced June 9, 1986
Survey completed August 22, 1995**

T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the corrective dependent resurvey of portions of the south, east, and west boundaries and subdivisional lines, the corrective survey of sections 20 and 26, the dependent resurvey of a portion of the north boundary (Fifth Standard Parallel South), south and east boundaries and subdivisional lines, and the subdivision of sections 1, 25, and 28, township 23 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1853, Robert Elder and Henry S. Gile, U.S. Deputy Surveyors, surveyed the south and east boundaries of T. 23 S., R. 6 W. and the west boundary of T. 24 S., R. 6 W., establishing a corner for Tps. 23 and 24 S., Rs. 6 and 7 W.

In 1855, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the north boundary (Fifth Standard Parallel South).

In 1879, William Thiel, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1881, William R. Whipple, U.S. Deputy Surveyor, retraced a portion of the south boundary.

In 1881, William H. Byars, U.S. Deputy Surveyor, surveyed a portion of the south boundary and the east boundary of T. 23 S., R. 7 W., establishing a new corner of Tps. 23 S., Rs. 6 and 7 W., without reference to the Elder and Gile township corner.

In 1883, John A. McQuinn, U.S. Deputy Surveyor, completed the survey of the subdivisional lines.

From 1943 to 1957, Otis O. Gould, Cadastral Engineer, and Joseph S. Gawron and Orville N. Eggen, Cadastral Surveyors, resurveyed the boundaries and subdivisional lines of T. 23 S., R. 6 W. During this resurvey they were instructed by the Area Cadastral Engineering Officer to reestablish a single corner for Tps. 23 and 24 S., Rs. 6 and 7 W., by the double proportion method (memorandum dated July 31, 1957).

In 1957, Orville N. Eggen, Cadastral Surveyor, resurveyed the east boundary of section 1, T. 24 S., R. 7 W., and the south boundary of section 36, T. 23 S., R. 7 W. This resurvey was suspended March 6, 1964.

In 1964, Floyd A. Brooks, Cadastral Surveyor, correctively resurveyed the east boundary of section 1, T. 24 S., R. 7 W., the south boundary of section 36, T. 23 S., R. 7 W., and the south and west boundaries of section 31, T. 23 S., R. 6 W.

In 1982-83, James E. Jelley, Wayne L. Rogers, and Lance J. Bishop, Cadastral Surveyors, correctively resurveyed and surveyed a portion of the subdivisional lines and subdivided sections 20 and 26.

T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

During the execution of this survey acceptable closures could not be achieved using the 1943-57 resurvey data. Subsequent investigations revealed several corners were erroneously positioned during the 1943-57 resurvey by Gould, Gawron, and Eggen, requiring the corrective action herein. The corner corrections necessitate correcting the corrective survey by Brooks in 1964 and the survey and corrective survey by Jelley, Rogers, and Bishop in 1982-83.

In 1992, the Douglas County Surveyor notified this office of a chaining error existing on the south boundary of section 36, T. 23 S., R. 7 W., as resurveyed by Floyd A. Brooks, Cadastral Surveyor, in 1964. This error was verified and original corners were recovered necessitating further corrective action of the south and west boundaries of section 31.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated April 19, 1985, Amendment to Special Instructions dated May 22, 1986, Supplemental Special Instructions dated March 10, 1987, and Second Supplemental Special Instructions dated April 8, 1994, for Group No. 1266, Special Instructions dated February 21, 1992, for Group No. 1637, and the Special Instructions dated April 8, 1993, for Group No. 1688, Oregon

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions unless already suitably remonumented. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice.

The field notes of the township boundaries and subdivisional lines are prepared in sequential order. A notation is made at each point where a change is made from a dependent resurvey to a corrective resurvey and vice-versa.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the corner of sections 21, 22, 27, and 28, as determined by a tie to United States Geological Survey triangulation station "YELLOW 1904," is as follows:

Latitude 43° 32' 52.72" N. Longitude 123° 24' 16.50" W.

T. 23 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The geographic position (NAD 1927) of the corner of sections 9, 10, 15, and 16, as determined by a tie to Geodetic Control Station EC 41179, established by the Bureau of Land Management in 1993, is as follows:

Latitude 43° 34' 33.33" N. Longitude 123° 24' 07.08" W.

The geographic position (NAD 1927) of the corner of townships 23 and 24 south, ranges 6 and 7 west, as determined by a tie to the erroneous township corner, geodetic coordinates established by Douglas County in 1992 is as follows:

Latitude 43° 31' 10.18" N. Longitude 123° 27' 52.89" W.

The geographic position (NAD 1927) of the ¼ section corner of sections 19 and 24 on the east boundary of the township, as determined by a tie to Geodetic Control Station EC 41179, established by the Bureau of Land Management in 1993, is as follows:

Latitude 43° 33' 20.39" N. Longitude 123° 20' 42.00" W.

The mean magnetic declination is 19° East.

**Dependent Resurvey of a Portion of the North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

(Restoring the survey by Harvey Gordon and Charles T. Gardner in 1853, and the resurvey by Otis O. Gould, Joseph S. Gawron, and Orville N. Eggen in 1943 to 1957)

From the standard ¼ sec. cor. of sec. 1 only, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

¼ S1
SC
1943

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A sawed fir stump, 25 ins. diam., bears S. 68° E., 106 lks. dist., with healed blaze.

A sawed fir stump, 35 ins. diam., bears S. 65½° W., 36 lks. dist., with healed blaze.

and new bearing trees

A fir, 16 ins. diam., bears S. 44¼° E., 47 lks. dist., mkd. ¼ S1 SC BT.

A fir, 5 ins. diam., bears S. 20¼° W., 53 lks. dist., mkd. X BT.

**Dependent Resurvey of a Portion of the North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	N. 89° 52' 00" W., on the N. bdy. of sec. 1.								
	Ascend over broken E. slope through heavy timber and dense undergrowth.								
5.55	Spur, slopes S. 30° E.; desc. over SW. slope.								
7.65	Ravine, drains S. 30° E.; asc. over E. slope.								
21.070	<p>The standard W 1/16 sec. cor. of sec. 1 only, established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1974, recorded in County Survey No. M49-60, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which a bearing tree mkd. by Bentz:</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears South, 2 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 10%; margin: 0 auto;"/> W 1/16 S1 1986 </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 63½° W., 32 lks. dist., mkd. W 1/16 S1 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located N. 80½° E., 0.86 chs. dist. from a fence corner, fence lines extending E., S., and N. 66° W.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> N. 89° 51' 00" W., beginning new measurement. </div> <p>Continue ascent over E. slope.</p>								
21.060	<p>The standard cor. of secs. 1 and 2, perpetuated and recorded by Milo E. Godfrey, Deputy County Surveyor, in 1964, as indicated in Government Corner Renewal No. 45; monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S2</td> <td style="padding: 0 5px;">S1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">T23S</td> <td style="padding: 0 5px;">R6W</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">SC</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1943</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p>	S2	S1	T23S	R6W	SC		1943	
S2	S1								
T23S	R6W								
SC									
1943									

**Dependent Resurvey of a Portion of the North Boundary
(Fifth Standard Parallel South),
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

A fir, 48 ins. diam., bears S. $13\frac{1}{4}^{\circ}$ E., 109 lks. dist., with healed blaze. (Record, S. $26\frac{1}{2}^{\circ}$ E.)

A root hole, bears S. 67° W., 203 lks. dist., alongside of which is lying a sawed fir stump, 54 ins. diam., with healed blaze.

and bearing trees mkd. by Godfrey

A fir, 16 ins. diam., bears S. $65\frac{3}{4}^{\circ}$ E., 23 lks. dist., with healed blaze.

A fir, 17 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ W., 41 lks. dist., with healed blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

(Restoring the survey by Robert Elder and Henry Gile in 1853, the resurvey by William R. Whipple in 1891, restoring or correcting the resurvey by Otis Gould, Joseph Gawron, and Orville Eggen in 1943-57, and correcting the resurvey by Floyd A. Brooks in 1964)

(Dependent Resurvey)

Beginning at the cor. of secs. 3, 4, 33, and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above a collar of stone (with T iron alongside), with brass cap mkd.

T 23 S	R 6 W
S33	S34
S4	S3
T 24 S	R 6 W
1957	

from which remains of an original bearing tree

A fir stump, 48 ins. diam., bears S. 71° W., 17 lks. dist., with scribe marks R6W T24 visible on open blaze.

and bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 12 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., $49\frac{1}{2}$ lks. dist., with healed blaze.

A fir, 28 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ E., 47 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 49° W., 58 lks. dist., with healed blaze.

and a bearing tree not of record

A fir, 30 ins. diam., bears N. 13° W., 26 lks. dist., with healed blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 89° 33' 30" W., bet. secs. 4 and 33.
1.75	Creek, 4 lks. wide, course S.; asc. broken SE. slope through heavy timber and light undergrowth.
40.390	The ¼ sec. cor. of secs. 4 and 33, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T 23 S R 6 W S33 ¼ ——— S4 T 24 S R 6 W 1957
	from which an original bearing tree
	A fir, 44 ins. diam., bears N. 50 ¾° W., 50 lks. dist., with axe marks visible on opened blaze.
	and bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 11 ins. diam., bears N. 25¼° E., 61 lks. dist., with healed blaze.
	A fir, 26 ins. diam., bears S. 76½° E., 91 lks. dist., with healed blaze.
	(Corrective Dependent Resurvey)
	S. 89° 44' 30" W., bet. secs. 4 and 33.
	Descend gradually over SW. slope.
5.30	Ravine, drains S. 20° E.; asc. broken SE. slope.
40.815	Point for the cor. of secs. 4, 5, 32, and 33 at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T23S R6W S32 S33 S5 S4 T24S 1994
	from which bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 22 ins. diam., bears N. 78 ¾° E., 19 lks. dist., with healed blaze.
	A fir, 15 ins. diam., bears S. 4½° E., 92 lks. dist., with healed blaze.
	A fir, 25 ins. diam., bears S. 58° W., 70 lks. dist., with healed blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 14° W., 45 lks. dist., mkd. T23S R6W S32 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on steep SE. slope.</p> <p>From this point, the cor. of secs. 4, 5, 32, and 33, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 16° 57' 30" W., 0.357 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above a mound of stone, 2½ ft. base, 1 ft. high, with brass cap marked and witnessed as described in the official record, except the NW. bearing tree is now a snag. Amended the marks on the brass cap to read AM 1994 1957, reset the monument, inverted, and obliterated the marks on the NW. bearing tree snag.</p> <hr/> <p>S. 89° 44' 30" W., bet. secs. 5 and 32.</p> <p>Ascend steep SE. slope, over sandstone ledges.</p>
1.50	<p>Spur, slopes S.; desc. SW. slope.</p>
40.815	<p>The ¼ sec. cor. of secs. 5 and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T23S R6W S32 ¼ ——— S5 T24S R6W 1957</p> </div> <p>from which the remains of bearing trees mkd. by Whipple</p> <p style="padding-left: 40px;">A sawed fir stump, 66 ins. diam., bears N. 48° E., 59 lks. dist., with knife marks ¼S visible on open blaze facing S.</p> <p style="padding-left: 40px;">A root hole, bears S. 72° E., 59 lks. dist., alongside of which is lying a fir, 30 ins. diam., no marks visible on open blaze.</p> <p>and a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A hemlock, 28 ins. diam., bears S. 61° W., 79½ lks. dist., with healed double blaze. (Record, fir.)</p> <p>and the remains of bearing trees mkd. by Vernon Tracy, Deputy County Surveyor, in 1966, as indicated in Government Corner Renewal No. 55</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 40½° E., 46½ lks. dist., with healed blaze.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS											
	<p>A rootwad, bears N. 38° W., 131 lks. dist., alongside of which is lying a rotted fir log, 10 ins. diam., with fragmentary scribe marks visible on rotted blaze.</p> <p>and a new bearing tree</p> <p>A fir, 10 ins. diam., bears N. 41° W., 12 lks. dist., mkd. ¼ S32 BT.</p> <hr/> <p style="text-align: center;">(Dependent Resurvey)</p> <p>N. 89° 58' 30" W., bet. secs. 5 and 32.</p> <p>Descend SW. slope.</p>										
9.30	Graveled road, 20 lks. wide, bears N. 15° W. and S. 15° E.; thence descend, cross creek, and ascend.										
40.435	<p>The cor. of secs. 5, 6, 31, and 32, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T23S</td> <td style="padding: 0 5px;">R6W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S31</td> <td style="padding: 0 5px;">S32</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S6</td> <td style="padding: 0 5px;">S5</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">T24S</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1957</td> </tr> </table> </div> <p>from which an original bearing tree</p> <p>A fir, 30 ins. diam., bears N. 22° E., 53 lks. dist., with illegible scribe marks visible on open blaze.</p> <p>and bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A hemlock, 18 ins. diam., bears S. 63° E., 35 lks. dist., with healed blaze.</p> <p>A hemlock, 17 ins. diam., bears S. 30° W., 17 lks. dist., with scribe marks S6 24S R6W visible on partially healed blaze. (Record, S. 3° W.)</p> <p>A fir, 40 ins. diam., bears N. 74° W., 57 lks. dist., with healed blaze.</p> <hr/> <p style="text-align: center;">(Corrective Dependent Resurvey)</p> <p>N. 89° 27' 00" W., bet. secs. 6 and 31.</p> <p>Descend broken NW. slope, through heavy timber and dense undergrowth.</p>	T23S	R6W	S31	S32	S6	S5	T24S		1957	
T23S	R6W										
S31	S32										
S6	S5										
T24S											
1957											
2.70	Creek, 5 lks. wide, course N. 70° E.; asc. broken SE. slope.										
10.70	Spur, slopes N. 70° E.; continue ascending broken NE. slope.										
25.80	Spur, slopes S. 40° E.; desc. SW. slope.										

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS 40.445	
	<p>The ¼ sec. cor. of secs. 6 and 31, determined at record bearing and distance from the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A fir snag, 57 ins. diam., bears S. 38° W., 53 lks. dist., with scribe marks ¼ S BT and a chaining notch visible on opened blaze.</p> <p>From this point, the ¼ sec. cor. of secs. 6 and 31, erroneously reestablished by Brooks in 1964, bears S. 64° 59' 30" E., 2.090 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap marked and witnessed as described in the official record. Remove the iron post, obliterate the marks on the bearing trees, and at the true corner point:</p> <p>Reset the iron post, 30 ins. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T23S R6W S31 ¼ ——— S6 T24S 1957 1993</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 48° E., 42 lks. dist., mkd. ¼ S6 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 55° W., 27 lks. dist., mkd. ¼ S31 BT.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>S. 88° 22' 30" W., beginning new measurement.</p> <p>Descend broken SW. slope.</p>
20.40	Creek, 10 lks. wide, course S. 20° E.; asc. broken NE. slope.
36.00	Spur, slopes S. 60° E.; continue ascending SE. slope.
36.90	Dirt road, 20 lks. wide, bears N. 40° W. and S., curving SW.
37.795	<p>Point for the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> <p>T23S R7W R6W S36 S31 S1 S6 R7W R6W T24S 1993</p> </div>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the South Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

from which

A fir, 9 ins. diam., bears N. 33° E., 18½ lks. dist., mkd.
T23S R6W S31 BT.

A fir, 7 ins. diam., bears S. 35° E., 32 lks. dist., mkd.
T24S R6W S6 BT.

A fir, 7 ins. diam., bears S. 28° W., 16 lks. dist., mkd.
T24S R7W S1 BT.

A fir, 7 ins. diam., bears N. 67° W., 16½ lks. dist., mkd.
T23S R7W S36 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W., at latitude 43° 31' 09.776" N. and longitude 123° 27' 52.045" W. (NAD 1927), determined by Douglas County Surveyor's Office in 1992, erroneously reestablished by Brooks in 1964, bears S. 56° 53' 00" E., 1.130 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. T23S R7W R6W S36 S31 S1 S6 R7W R6W T24S 1957 RESET 1977. This monument had been referenced and removed for road construction and then reset at the same position by the Douglas County Surveyor's Office in 1977 (Douglas County Corner Renewal Record, T. 24 S., R. 7 W., No. 132), from which a bearing tree mkd. by Gould, Gawron, and Eggen:

A fir, 30 ins. diam., bears N. 74¼° W., 176 lks. dist., with healed blaze.

and bearing trees mkd. by Brooks

A fir, 14 ins. diam., bears N. 62° E., 112 lks. dist., with healed blaze.

A cedar, 22 ins. diam., bears S. 86° E., 163 lks. dist., with healed blaze.

and a bearing tree mkd. by Gary L. Langlitz, Douglas County Surveyor's Office, in 1992 (Douglas County Corner Renewal Record, T. 24 S., R. 7 W., No. 164)

A fir, 7 ins. diam., bears S. 43¼° W., 29 lks. dist., with scribe marks T24S R7W S1 CS BT visible on an open blaze.

Amended the brass cap to read T23S R7W R6W S36 S31 S1 S6 R7W R6W T24S 1957 RESET 1977 AMENDED 1993, reset the monument flush with the ground surface, and obliterated the marks on the bearing trees.

The south and west control for the township corner is described in the corrective dependent resurvey of a portion of the N. and E. bdrs. of T. 24 S., R. 7 W., executed concurrently under Group No. 1637.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

(Restoring the survey by Robert Elder and Henry S. Gile in 1853, and restoring or correcting the resurvey by Otis O. Gould, Joseph S. Gawron, and Orville N. Eggen in 1943 to 1957)

(Dependent Resurvey)

From the cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T23S	
R6W	R5W
S25	S30
S36	S31
1943	

from which the remains of an original bearing tree

An oak snag, 24 ins. diam., bears N. 34° E., 185 lks. dist., no marks visible.

and bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 20 ins. diam., bears S. 25° E., 303 lks. dist., with healed blaze. (Record, S. 23° E., 307 lks.)

An oak, 24 ins. diam., bears S. 61° W., 445 lks. dist., with healed blaze.

and new bearing trees

An oak, 10 ins. diam., bears N. 51° E., 21 lks. dist., mkd. T23S R5W S30 BT.

A fir, 11 ins. diam., bears N. 27° W., 97 lks. dist., mkd. T23S R6W S25 BT.

N. 0° 06' 00" E., bet. secs. 25 and 30.

Ascend over SE. slope through heavy timber and dense undergrowth.

11.35 Spur, slopes S. 70° E.; desc. over NE. slope.

20.040 The S 1/16 sec. cor. of secs. 25 and 30, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1961, and recorded in County Survey No. M 20-46, and is accepted as the corner; monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Haines:

A cedar, 20 ins. diam., bears S. 53° W., 47 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	S 1/16 S25 S30 1986
	from which a new bearing tree
	A fir, 8 ins. diam., bears S. 10½° E., 156 lks. dist., mkd. S 1/16 S30 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

	N. 0° 05' 00" E., beginning new measurement.
0.15	Creek, 1 lk. wide, course E.
7.05	Blackberry Canyon Creek, 2 lks. wide, course S. 80° E.; asc. over SW. slope.
20.030	The ¼ sec. cor. of secs. 25 and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	¼ S25 S30 1943
	from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen
	A sawed fir stump, 30 ins. diam., bears N. 37° E., 30 lks. dist., with scribe marks ¼ S30 BT visible on open blaze.
	A sawed fir stump, 28 ins. diam., bears N. 40½° W., 48 lks. dist., with healed blaze.
	and new bearing trees
	A fir, 22 ins. diam., bears N. 52½° E., 69 lks. dist., mkd. ¼ S30 BT.
	A fir, 10 ins. diam., bears N. 63° W., 24½ lks. dist., mkd. ¼ S25 BT.

	N. 0° 09' 00" E., beginning new measurement.
	Ascend over broken SW. slope.
19.900	The N 1/16 sec. cor. of secs. 25 and 30, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1961, and recorded in County Survey No. M20-46, and is accepted as the corner; monumented with a 1 in. "T" shaped iron rod, firmly set, with top 4 ins. below surface of road, from which bearing trees mkd. by Haines:
	A fir, 18 ins. diam., bears S. 16° E., 292 lks. dist., with healed double blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 25 ins. diam., bears N. 55° W., 144 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, the top 8 ins. below road surface, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S25 S30 1986</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron rod inside the stainless steel post.</p> <p>The corner is located in center of dirt road, 15 lks. wide, bears NW. and S. 30° E.</p> <p style="text-align: center;">_____</p> <p>N. 0° 08' 00" E., beginning new measurement.</p> <p>Ascend over broken SW. slope.</p>
1.30	Spur, slopes SE.; desc. over NE. slope.
12.50	Ravine, drains S. 50° E.; asc. over SE. slope.
17.55	Spur, slopes E.; desc. over NE. slope.
19.870	<p>The cor. of secs. 19, 24, 25, and 30, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W R5W S24 S19 S25 S30 1943</p> <p>from which the remains of the original bearing trees</p> <p>A sawed fir stump, 48 ins. diam., bears S. 28° E., 141 lks. dist., no marks visible on opened blaze. (Record, S. 19° E., 109 lks.)</p> <p>A fir, 65 ins. diam., bears S. 65½° W., 104 lks. dist., with blaze chopped open and rehealed. (Record, S. 66½° W., 112 lks.)</p> <p>and the remains of a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p>A root hole, bears S. 22° E., 46 lks. dist., alongside of which is lying a fir, 22 ins. diam., with healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 78½° E., 38 lks. dist., mkd. T23S R5W S19 BT.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 10 ins. diam., bears S. 51½° E., 56 lks. dist., mkd. T23S R5W S30 BT.</p> <p>A maple, 14 ins. diam., bears N. 44° W., 42½ lks. dist., mkd. T23S R6W S24 BT.</p> <hr/> <p>N. 0° 01' 30" E., bet. secs. 19 and 24.</p> <p>Ascend over SE. slope, through heavy timber and dense undergrowth.</p>
2.15	Spur, slopes S. 85° E.; desc. over NE. slope.
8.40	Creek, 5 lks. wide, course S. 35° E.; asc. over SE. slope.
22.70	Spur, slopes N. 25° E. to saddle; desc. over broken NW. slope, also graveled road, 15 lks. wide, bears N. 15° E. and S. 15° W., to landing.
23.70	Graveled road, 30 lks. wide, bears N. 35° E. and S. 35° W.
39.580	The 1/4 sec. cor. of secs. 19 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S\ 24 \mid S\ 19 \\ 1943 \end{array}$
	<p>from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A sawed fir stump, 27 ins. diam., bears N. 72 3/4° E., 61 lks. dist., with healed blaze. (Record, S. 33° E., 67 lks.)</p> <p>A sawed fir stump, 38 ins. diam., bears N. 68½° W., 141 lks. dist., with healed blaze. (Record, N. 70° W., 144 lks.)</p> <p>and new bearing trees</p> <p>A fir, 10 ins. diam., bears S. 21 3/4° E., 14 lks. dist., mkd. 1/4 S19 BT.</p> <p>A fir, 12 ins. diam., bears N. 66° W., 27 lks. dist., mkd. 1/4 S24 BT.</p> <p>From this point, Bureau of Land Management Geodetic Control Station No. EC 41179, at latitude 43° 33' 31.936" N. and longitude 123° 23' 27.852" W. (NAD 1927), determined by the NAVSTAR Global Position System, bears N. 84° 31' 10" W., 185.892 chs. dist. (mean bearing and sea level distance), monumented with an aluminum cap set flush with the ground, mkd. EC 41179 GPS 1993 and a triangle.</p> <hr/> <p style="text-align: center;">(Corrective Dependent Resurvey)</p> <p>N. 0° 11' 30" W., beginning new measurement.</p> <p>Descend over NW. slope.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
11.85	Creek, 5 lks. wide, course S. 70° W.; asc. over SW. slope.
18.95	Spur, slopes W.; desc. over NW. slope.
24.40	Creek, 5 lks. wide, course S. 50° W.; asc. over SE. slope.
29.40	Graveled road, 15 lks. wide, bears N. 85° E. and S. 85° W.
33.50	Ridge, bears E. and W.; desc. over NW. slope.
40.300	The cor. of secs. 13, 18, 19, and 24, perpetuated by Donald S. Peel, Registered Land Surveyor No. 752, in 1993 (recorded in Douglas County Surveyor's Office Corner Renewal No. 139), monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	<pre> T23S R6W R5W S 13 S 18 ----- ----- S 24 S 19 1993 </pre>
	from which the remains of the original bearing trees
	<p>A decayed fir root crown, size indeterminate, bears S. 58° E., 18 lks. dist., no marks visible. (Record, S. 53° E., 14 lks.)</p> <p>A fir stump, 36 ins. diam., bears S. 63° W., 26 lks. dist., with scribe marks T23S S24 visible on opened blaze.</p> <p>A decayed fir root crown, size indeterminate, bears N. 82° W., 25 lks. dist., no marks visible.</p>
	and bearing trees mkd. by Peel
	<p>A fir, 11 ins. diam., bears N. 49° E., 42½ lks. dist., with scribe marks T23S R5W S18 BT visible on open blaze.</p> <p>A fir, 14 ins. diam., bears S. 28° E., 41½ lks. dist., with scribe marks T23S R5W S19 BT visible on open blaze.</p> <p>A fir, 20 ins. diam., bears S. 35° W., 19½ lks. dist., with scribe marks T23S R6W S24 BT visible on open blaze.</p> <p>A fir, 15 ins. diam., bears N. 82° W., 36½ lks. dist., with scribe marks T23S R6W S13 BT visible on open blaze.</p>
	From this point, the cor. of secs. 13, 18, 19, and 24, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 31° 38' 00" E., 0.260 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap marked and witnessed as described in the official record, except the SW. bearing tree is a snag, bears S. 34° W. (record, S. 45° W.)

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Change marks on brass cap to now read AM 17.2 FT TO COR 1943 1995 and an arrow pointing to the true corner location. Destroy the marks on the snag.

	N. 0° 25' 30" W., bet. secs. 13 and 18.
	Descend over NW. slope, through heavy timber and dense undergrowth.
15.25	Creek, 1 lk. wide, course N. 60° W.; asc. over SW. slope.
18.35	Spur, slopes N. 80° W.; desc. over NW. slope.
20.75	Ravine, drains N. 70° W.; asc. over SE. slope.
25.80	Spur, slopes W.; desc. over NW. slope.
29.60	Creek, 5 lks. wide, course N. 65° W.; asc. over SW. slope.
39.685	The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ S\ 13\ \ S\ 18 \\ 1943 \end{array}$
	from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 64 ins. diam., bears S. 18° E., 155 lks. dist., with healed blaze.
	A sawed fir stump, 36 ins. diam., bears N. 30° W., 84 lks. dist., with healed blaze. (Record, N. 29½° W., 82 lks.)
	and a new bearing tree
	A fir, 8 ins. diam., bears N. 59½° W., 8 lks. dist., mkd. 1/4 S13 BT.

	(Dependent Resurvey)
	N. 0° 09' 00" W., beginning new measurement.
	Descend broken NW. slope.
17.40	Spur, slopes N. 80° W.; continue descending broken NW. slope.
25.95	Ridge, bears N. 35° W. and S. 20° E.; desc. over broken NE. slope.
30.20	Ravine, drains N. 35° E.
39.790	The cor. of secs. 7, 12, 13, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

T23S	
R6W	R5W
S 12	S 7

S 13	S 18
1943	

from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A roothole, bears N. 23½° E., 223 lks. dist., alongside of which is lying a fir, 40 ins. diam., with healed blaze.

A fir, 26 ins. diam., bears S. 38° W., 106 lks. dist., with healed blaze. (Record, S. 42° W., 109 lks.)

A sawed fir stump, 23 ins. diam., bears N. 49° W., 50 lks. dist., with healed blaze. (Record, N. 50° W., 61 lks.)

and new bearing trees

A fir, 13 ins. diam., bears N. 18° E., 67 lks. dist., mkd. T23S R5W S7 BT.

A fir, 11 ins. diam., bears S. 10° E., 24 lks. dist., mkd. T23S R5W S18 BT.

No suitable tree available in sec. 12.

N. 0° 14' 00" E., bet. secs. 7 and 12.

Descend over broken NE. slope, changing to NW. slope, across clearcut.

39.825

The 1/4 sec. cor. of secs. 7 and 12, reset by Randall Smith and Stephen Flause, Deputy County Surveyors, in 1990 (recorded in Douglas County Surveyor's Office Corner Renewal No. 79), monumented with an iron post, 1 in. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

1/4	
Reset	
S 12	S 7

1943	
1990	

from which a bearing tree mkd. by Gould, Gawron, and Eggen

A cedar, 14 ins. diam., bears N. 44° E., 33 lks. dist., no marks visible on decayed, open blaze.

and the remains of bearing trees mkd. by Smith and Flause

A hemlock, 14 ins. diam., bears S. 82½° E., 57 lks. dist., with scribe marks 1/4 S7 CS BT visible on open blaze.

A fir stump, 25 ins. diam., bears S. 73° W., 43 lks. dist., with scribe marks 1/4 S12 CS BT visible on open double blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS											
	<p>A hemlock, 13 ins. diam., bears N. 31° W., 64 lks. dist., with scribe marks 1/4 S12 CS BT visible on opened double blaze.</p> <p>The corner is located in a creek, 5 lks. wide, course N. 25° E. from S. 15° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' 30" E., beginning new measurement.</p> <p>Descend along NE. slope.</p>										
11.70	Flagler Creek, 35 lks. wide, course S. 85° W.; asc. over broken SE. slope.										
14.10	Graveled road, 25 lks. wide, bears N. 65° W. and S. 65° E.										
39.850	<p>The cor. of secs. 1, 6, 7, and 12, perpetuated by Larry E. Monrean, Deputy County Surveyor, in 1977, as indicated in Government Corner Renewal No. 69; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td colspan="2">T23S</td></tr> <tr><td>R6W</td><td>R5W</td></tr> <tr><td style="border-right: 1px solid black;">S1</td><td>S6</td></tr> <tr><td style="border-right: 1px solid black;">S12</td><td>S7</td></tr> <tr><td colspan="2">1943</td></tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole, bears N. 40° E., 41 lks. dist., alongside of which is lying a fir, size indeterminate, with decayed blaze.</p> <p>and the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A roothole, bears N. 49° E., 49 lks. dist., alongside of which is lying a fir, 43 ins. diam., with scribe marks T23S R5W S6 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 21° E., 48 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 55° W., 72 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Monrean</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 55° E., 75 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 66° W., 29 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' 00" W., bet. secs. 1 and 6.</p>	T23S		R6W	R5W	S1	S6	S12	S7	1943	
T23S											
R6W	R5W										
S1	S6										
S12	S7										
1943											

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over broken SW. slope, through heavy timber and dense undergrowth.
15.80	Ridge, bears N. 30° E. and S. 30° W.; desc. over broken NW. slope.
19.845	The S 1/16 sec. cor. of secs. 1 and 6, established by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1973, recorded in County Survey No. M 48-3, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Hosford: <p style="margin-left: 40px;">A cedar, 30 ins. diam., bears N. 19¼° E., 38 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A cedar, 14 ins. diam., bears N. 52° W., 10 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin-left: 100px;"> S 1/16 S1 S6 1986 </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01' 00" W., beginning new measurement.</p> <p>Descend along W. slope.</p>
8.90	Spur, slopes N. 35° W.; continue descent over N. slope.
19.845	The ¼ sec. cor. of secs. 1 and 6, perpetuated by Larry E. Monrean, Deputy County Surveyor, in 1977, as indicated on Government Corner Renewal No. 70; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. <div style="text-align: center; margin-left: 100px;"> ¼ 1 6 1943 </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A rotted sawed fir stump, 28 ins. diam., bears S. 48° E., 57 lks. dist., no marks visible.</p> <p style="margin-left: 40px;">A rotted sawed fir stump, 24 ins. diam., bears S. 35° W., 48 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>and the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="margin-left: 40px;">A rotted fir snag, 22 ins. diam., bears N. 84° E., 30 lks. dist., no marks visible.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the East Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A rotted sawed fir stump, 29 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ W., 70 lks. dist., no marks visible on opened blaze.</p> <p>and bearing trees mkd. by Monrean</p> <p>A fir, 13 ins. diam., bears S. 63° E., $31\frac{1}{2}$ lks. dist., with healed double blaze.</p> <p>A black oak, 19 ins. diam., bears S. 68° W., 50 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <hr/> <p style="text-align: center;">Corrective Dependent Resurvey of a Portion of the West Boundary, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the survey by William H. Byars in 1881, and correcting the corrective resurvey by Floyd A. Brooks in 1964)</p> <hr/> <p>From the cor. of Tps. 23 and 24 S., Rs. 6 and 7 W. N. $2^{\circ} 28' 00''$ E., bet. secs. 31 and 36. Ascend gentle SE. slope, through heavy timber and dense undergrowth.</p> <p>0.30 Dirt road, 20 lks. wide, bears N. 80° W. and S. 80° E., on a spur sloping S. 80° E.; desc. steep NE. slope.</p> <p>10.60 Creek, 4 lks. wide, course E.; asc. steep broken SW. slope.</p> <p>27.10 Graveled road, 30 lks. wide, bears N. 65° W. and S. 65° E.; enter logged area, edge bears N. and S. 65° E.</p> <p>30.80 Ridge, bears E. and W.; desc. broken NW. slope.</p> <p>39.900 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, determined from the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir stump, 40 ins. diam., bears N. 40° E., 84 lks. dist. (to the blaze), with scribe marks BT visible through a hollow center.</p> <p style="padding-left: 40px;">A fir stump, 42 ins. diam., bears S. 57° W., 46 lks. dist. (to the blaze), with scribe mark S visible on partially opened blaze.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 31 and 36 erroneously reestablished by Brooks in 1964, bears S. $55^{\circ} 23' 00''$ W., 1.325 chs. dist., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is a stump. Remove the iron post, obliterate the marks on the stump, and at the true corner point:</p> <p>Reset the iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Corrective Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	T23S R7W R6W $\frac{1}{4}$ S36 S31 1993
	from which a bearing tree mkd. by Brooks
	A hemlock, 13 ins. diam., bears S. 61½° W., 144 lks. dist., with healed blaze.
	The corner is located in a clearcut logging area with no other suitable bearing trees available.

	N. 0° 49' 00" W., beginning new measurement.
	Descend broken NW. slope through logged area.
0.90	Ravine, drains N. 60° W.; asc. SW. slope.
14.40	Spur, slopes S. 30° W., at the northerly edge of the clearcut logging area, bears NE. and SW.; desc. broken NW. slope through heavy timber and dense undergrowth.
33.80	Creek, 5 lks. wide, course N. 15° W.; asc. broken SW. slope.
38.860	The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	T23S R7W R6W <u>S25 S30</u> <u>S36 S31</u> 1957
	from which the remains of the original bearing trees
	A root hole, bears N. 80° E., 35 lks. dist., alongside of which is lying a fir, 26 ins. diam., no visible marks.
	A root hole, bears S. 62° W., 29 lks. dist.
	A root hole, bears N. 21° W., 62 lks. dist., alongside of which is lying a cedar, 32 ins. diam., no visible marks.
	and bearing trees mkd. by Brooks
	A fir, 24 ins. diam., bears N. 73½° E., 78 lks. dist., with healed blaze.
	A fir, 16 ins. diam., bears S. 33½° E., 44 lks. dist., with healed blaze.
	A cedar, 24 ins. diam., bears S. 37° W., 85 lks. dist., with healed blaze.
	A cedar, 34 ins. diam., bears N. 12° W., 17 lks. dist., with healed blaze.

**Corrective Dependent Resurvey of a Portion of the West Boundary,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>The corner is located on a steep W. slope, approximately 1 ch. E. of a creek, 5 lks. wide, course N.</p> <hr/> <p align="center">Dependent Resurvey and Corrective Dependent Resurvey of a Portion of the Subdivisional Lines, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>(Restoring the survey by William Thiel in 1879, the retracement, resurvey, and survey by John A. McQuinn in 1883, restoring or correcting the resurvey by Otis O. Gould, Joseph S. Gawron, and Orville N. Eggen in 1943 to 1957, correcting the corrective resurvey by Floyd A. Brooks in 1964, and correcting the corrective resurvey by James E. Jelley, Wayne L. Rogers, and Lance J. Bishop in 1982-83)</p> <hr/> <p align="center">(Dependent Resurvey)</p> <p>From the cor. of secs. 25, 30, 31, and 36, on the E. bdy. of the Tp.</p> <p>S. 89° 26' 00" W., bet. secs. 25 and 36.</p> <p>Ascend over SE. slope through scattering timber and moderate undergrowth.</p>								
8.75	Spur, slopes S.; desc. over SW. slope.								
19.85	Ravine, drains S. 20° W.; asc. over SE. slope.								
22.655	<p>Point for the E 1/16 sec. cor. of secs. 25 and 36.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td></td><td>S25</td></tr> <tr><td>E 1/16</td><td>-----</td></tr> <tr><td></td><td>S36</td></tr> <tr><td></td><td>1986</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 50¼° E., 76 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A cedar, 13 ins. diam., bears S. 82¼° E., 367 lks. dist., mkd. E 1/16 S36 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in open pasture.</p> <p>Ascend over SE. slope.</p>		S25	E 1/16	-----		S36		1986
	S25								
E 1/16	-----								
	S36								
	1986								
22.80	Spur, slopes S. 10° W.; desc. over SW. slope.								
28.25	Ravine, drains S. 35° E.; asc. over NE. slope.								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
41.30	Spur, slopes S. 75° E.; desc. over SW. slope.
45.310	<p>The ¼ sec. cor. of secs. 25 and 36, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S25 ¼ ——— S36 1957 1943</p> </div> <p>from which the original bearing trees</p> <p>An oak, 30 ins. diam., bears S. 82° E., 116 lks. dist., no marks visible.</p> <p>A madrone, 39 ins. diam., bears N. 46½° W., 28 lks. dist., with scribe marks ¼ visible on opened blaze.</p> <p>and bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A fir, 18 ins. diam., bears S. 23° W., 19 lks. dist., with healed blaze.</p> <p>A chinquapin, 12 ins. diam., bears N. 15½° W., 50 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <hr/> <p>From the cor. of secs. 19, 24, 25, and 30 on the E. bdy. of the Tp.</p> <p>S. 87° 51' 00" W., bet. secs. 24 and 25.</p> <p>Ascend over broken NE. slope through heavy timber and dense undergrowth.</p>
8.55	Spur, slopes S. 50° E.; desc. over SW. slope.
15.35	Head of ravine, drains S.; asc. over broken SE. slope.
19.430	<p>The E 1/16 sec. cor. of secs. 24 and 25, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S24 E 1/16 ——— S25 1957</p> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A maple, 20 ins. diam., bears N. 12½° E., 186 lks. dist., with healed blaze.</p> <p>A fir, 24 ins. diam., bears S. 71° E., 21 lks. dist., with healed blaze.</p> <hr/>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	S. 87° 32' 00" W., beginning new measurement.
	Ascend over SE. slope.
0.60	Ridge, bears N. 50° E. and S. 80° W.; desc. over broken SW. slope.
5.50	Dirt road, 25 lks. wide, bears N. 50° W. and S. 50° E.
9.65	Head of ravine, drains S. 20° E.; asc. along ridgetop.
13.00	Ridge, bears N. 70° E. and S. 70° W.; desc. over NW. slope.
19.390	The ¼ sec. cor. of secs. 24 and 25, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	T23S R6W S24 ¼ ——— S25 1957
	from which bearing trees mkd. by Gould, Gawron, and Eggen
	A maple, 20 ins. diam., bears N. 26½° E., 13 lks. dist., with healed blaze.
	A maple, 19 ins. diam., bears S. 71° W., 82 lks. dist., with healed blaze.
	—————
	S. 87° 34' 00" W., beginning new measurement.
	Descend over NW. slope.
4.15	Ravine, drains N. 5° W.; asc. over NE. slope.
6.10	Spur, slopes N. 35° W.; desc. over NW. slope.
11.60	Graveled road, 30 lks. wide, bears N. 20° E. and S. 20° W.
13.40	Dirt road, 30 lks. wide, bears N. 30° E. and S. 35° W.
14.60	Creek, 2 lks. wide, course N. 20° W.; asc. over NE. slope.
16.10	Dirt road, 30 lks. wide, bears NW. and S. 60° E.
17.35	Spur, slopes N. 20° E.; desc. over broken NW. slope, changing to broken SW. slope.
27.45	Dirt road, 30 lks. wide, bears N. 35° E. and S. 30° W.
38.825	The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T23S R6W S23 S24 S26 S25 1957

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears East, 80 lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A sawed fir stump, 12 ins. diam., bears N. 12° E., 37 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed fir stump, 32 ins. diam., bears S. 66° E., 5 lks. dist., with scribe marks R6W S25 BT visible on opened blaze.</p> <p style="padding-left: 40px;">A chinquapin, 23 ins. diam., bears S. 14° W., 64 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A root hole, bears N. 15° W., 40 lks. dist., alongside of which is lying a fir, 14 ins. diam., with healed blaze.</p> <p>and bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 77° E., 35 lks. dist., with scribe marks T23S R6W S24 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 52° E., 65 lks. dist., with scribe marks T23S R6W S25 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 8° W., 10½ lks. dist., with scribe marks X BT visible on partially healed double blaze.</p> <hr/> <p>From the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp. S. 81° 53' 00" W., bet. secs. 1 and 12.</p> <p>Descend over SW. slope through heavy timber and dense undergrowth.</p>
3.95	Ravine, drains S. 10° E.; asc. over E. slope.
10.05	Spur, slopes S.; desc. over W. slope.
20.630	<p>The E 1/16 sec. cor. of secs. 1 and 12, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, and recorded in County Survey No. M35-11, and is accepted as the corner; monumented with an iron rod, ½ in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Haines:</p> <p style="padding-left: 40px;">A double fir, 23 ins. diam., bears N. 20½° E., 66 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 25¼° E., 20½ lks. dist., with healed blaze.</p> <p>At the corner point</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">S1 E 1/16 ——— S12 1986</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 81° 52' 00" W., beginning new measurement.</p> <p>Descend over W. slope.</p>
15.45	<p>County Road No. 71A, gravel surface, 30 lks. wide, bears N. 10° W. and S. 35° E., at junction with side road, bears S. 45° W.</p>
20.35	<p>Flagler Creek, 23 lks. wide, course N. 15° W. from S. 60° E.; asc. over E. slope.</p>
20.600	<p>The ¼ sec. cor. of secs. 1 and 12, determined at record bearing and distance from a bearing tree mkd. by Gould, Gawron, and Eggen:</p> <p style="padding-left: 40px;">A fir, 43 ins. diam., bears N. 51° W., 473 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an aluminum rod, 72 ins. long, ¾ in. diam., 70 ins. in the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">T23S R6W S1 ¼ ——— S12 1986</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A maple, 12 ins. diam., bears S. 5½° W., 60 lks. dist., mkd. ¼ S12 BT.</p> <p>From this point, a witness corner established by Gregory Quibell, Deputy County Surveyor, in 1982, as indicated in Government Corner Renewal No. 76, bears West, 1.290 chs. dist.; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. DOUGLAS CO. SURVEYOR T23S R6W WIT. COR. ¼ S1 S12 85 FT. EAST TO ¼ COR 1982, from which bearing trees mkd. by Quibell:</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 46° W., 78 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 55¼° W., 318 lks. dist., with healed double blaze.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS													
	<p>A fir, 18 ins. diam., bears N. 86½° W., 250 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 81° 53' 00" W., beginning new measurement.</p> <p>Ascend over E. slope.</p>												
3.55	Graveled road, 10 lks. wide, bears N. and S.												
17.80	Spur, slopes N. 65° E.; desc. over NW. slope.												
20.520	Point for the W 1/16 sec. cor. of secs. 1 and 12.												
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td></td><td>S1</td><td></td></tr> <tr><td>W 1/16</td><td>—</td><td></td></tr> <tr><td></td><td>S12</td><td></td></tr> <tr><td></td><td>1986</td><td></td></tr> </table> </div> <p>from which</p> <p>A fir, 12 ins. diam., bears S. 47° W., 67 lks. dist., mkd. W 1/16 S12 BT.</p> <p>A fir, 28 ins. diam., bears N. 43 3/4° W., 44 lks. dist., mkd. W 1/16 S1 BT.</p> <p>From this point, a point established as the W 1/16 sec. cor. of secs. 1 and 12 by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, recorded in County Survey No. M35-11, bears S. 20° 56' 00" E., 0.200 chs. dist.; monumented with an iron rod, ½ in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Haines:</p> <p>A fir, 15 ins. diam., bears N. 76 3/4° E., 58 lks. dist., with healed blaze.</p> <p>A fir, 21 ins. diam., bears S. 9¼° E., 54 lks. dist., with healed blaze.</p> <p>This corner is improperly positioned and is not utilized in this survey.</p> <p>Ascend over NE. slope.</p>		S1		W 1/16	—			S12			1986	
	S1												
W 1/16	—												
	S12												
	1986												
28.40	Spur, slopes S. 55° E.; continue ascent over broken NE. slope.												
39.65	Ridge, bears N. 60° E. and S. 65° W.; desc. NW. slope.												
41.040	<p>The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T23S</td><td>R6W</td></tr> <tr><td>S2</td><td>S1</td></tr> <tr><td>S11</td><td>S12</td></tr> <tr><td colspan="2">1943</td></tr> </table> </div>	T23S	R6W	S2	S1	S11	S12	1943					
T23S	R6W												
S2	S1												
S11	S12												
1943													

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A cedar snag, 44 ins. diam., bears N. 50° E., 62 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears N. 23¼° E., 46 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 39 ins. diam., bears S. 25½° E., 283 lks. dist., with healed double blaze. (Record, S. 35° E., 273 lks.)</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. 62° W., 136 lks. dist., with healed blaze. (Record, 37 lks.)</p> <p style="padding-left: 40px;">A fir, 50 ins. diam., bears N. 27½° W., 98 lks. dist., with healed blaze. (Record, N. 33° W.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 59 3/4° E., 20 lks. dist., mkd. T23S R6W S12 BT.</p> <hr/> <p>N. 1° 03' 00" E., bet. secs. 1 and 2.</p> <p>Descend over NE. slope through heavy timber and dense undergrowth.</p> <p>7.10 Spur, slopes N. 10° E.; desc. NW. slope.</p> <p>18.20 Ravine, drains N. 35° W.; asc. over SW. slope.</p> <p>22.800 The S 1/16 sec. cor. of secs. 1 and 2, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, recorded in County Survey No. M35-11, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, from which bearing trees mkd. by Haines:</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 17° E., 38 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 62½° W., 25 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>S 1/16</p> <p>S2 S1</p> <p>1986</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron rod alongside the stainless steel post.</p> <hr/> <p>N. 1° 09' 00" E., beginning new measurement.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over SW. slope.
2.05	Spur, slopes N. 60° W.; desc. over N. slope.
10.40	Andrews Creek, 14 lks. wide, course N. 80° E.; asc. over S. slope.
15.50	County Road No. 71, gravel surface, 35 lks. wide, bears N. 75° E. and S. 75° W.
19.25	Spur, slopes S.; desc. over NE. slope.
22.800	The ¼ sec. cor. of secs. 1 and 2, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.
	$\begin{array}{c} \frac{1}{4} \\ S2 \quad \quad S1 \\ 1943 \end{array}$
	from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen
	A sawed fir stump, 36 ins. diam., bears N. 64° E., 52 lks. dist., with healed blaze. (Record, 57 lks.)
	A cedar, 32 ins. diam., bears N. 80° W., 7 lks. dist., with healed blaze.
	and a new bearing tree
	A fir, 10 ins. diam., bears S. 17 3/4° E., 26 lks. dist., mkd. ¼ S1 BT.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 1° 09' 00" E., beginning new measurement.
	Descend over NE. slope.
1.40	Creek, 4 lks. wide, course S. 30° E.; asc. over SW. slope.
22.680	The N 1/16 sec. cor. of secs. 1 and 2, established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1974, and recorded in County Survey No. M49-60, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Bentz:
	A fir, 15 ins. diam., bears N. 81¼° E., 23 lks. dist., with healed blaze.
	A fir, 13 ins. diam., bears N. 31½° W., 37 lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.
	$\begin{array}{c} N \ 1/16 \\ S2 \quad \quad S1 \\ 1986 \end{array}$

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 1° 03' 00" E., beginning new measurement.</p> <p>Ascend over SE. slope.</p>								
2.90	Dirt road, 20 lks. wide, bears N. 65° E. and S. 70° W.								
22.930	The standard cor. of secs. 1 and 2, on the N. bdy. of the Tp.								
	<hr/> <p>(Corrective Dependent Resurvey)</p>								
	<p>From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground (with T bar, projecting 18 ins. above the ground, with brass washer mkd. WILFORD HAINES 239 alongside), with brass cap mkd.</p>								
	<table style="margin: auto;"> <tr> <td>T23S</td> <td>R6W</td> </tr> <tr> <td>S27</td> <td>S26</td> </tr> <tr> <td>S34</td> <td>S35</td> </tr> <tr> <td colspan="2">1957</td> </tr> </table>	T23S	R6W	S27	S26	S34	S35	1957	
T23S	R6W								
S27	S26								
S34	S35								
1957									
	<p>from which remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears S. 80° E., 16 lks. dist.</p> <p>and the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A maple stump, 32 ins. diam., bears N. 87° E., 215 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 50° E., 49 lks. dist., alongside of which is lying a cedar, 30 ins. diam., with burned blaze.</p> <p style="padding-left: 40px;">A cedar snag, 46 ins. diam., bears S. 34 3/4° W., 138 lks. dist., with burned blaze.</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears N. 47¼° W., 316 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1962, as indicated in Government Corner Renewal No. 41</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears S. 30° E., 137 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A maple, 36 ins. diam., bears S. 89° W., 195 lks. dist., no marks visible.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">An alder, 10 ins. diam., bears N. 14° E., 24 lks. dist., with scribe marks T23S R6W S26 BT visible on partially healed blaze.</p>								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A steel fence post is alongside the iron post.</p> <p>N. 6° 52' 00" W., bet. secs. 26 and 27.</p> <p>Over level bottom land through heavy timber and dense undergrowth.</p>
1.75	<p>Yellow Creek, 20 lks. wide, course S. 80° W.; asc. steep SE. slope along W. edge of logged area.</p>
37.860	<p>Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p> ¼</p> <p>S27 S26</p> <p> 1994</p> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 70° E., 81 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 86½° W., 52½ lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on steep E. slope at NW. corner of logged area.</p> <p>From this point, the ¼ sec. cor. of secs. 26 and 27, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 63° 04' 00" W., 0.139 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Continue along E. slope.</p>
56.790	<p>Point for the N 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S27 S26</p> <p> 1994</p> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 84½° W., 48 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 35° W., 18 lks. dist., with healed blaze.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 3° W., 21 lks. dist., mkd. N 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker and a railroad spike at the base of the stainless steel post.</p> <p>From this point, the N 1/16 sec. cor. of secs. 26 and 27, erroneously established by Gould, Gawron, and Eggen in 1943-57, bears N. 61° 07' 30" W., 0.188 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument, inverted.</p>								
59.50	Dirt road, 20 lks. wide, bears N. 20° W. and S. 20° E.								
60.75	Ravine, drains S. 30° E.								
62.20	Dirt road, 30 lks. wide, bears N. 80° W. and S. 80° E.; asc. steep S. slope through heavy timber and light undergrowth.								
75.720	<p>Point for the cor. of secs. 22, 23, 26, and 27, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T23S</td> <td style="padding: 0 5px;">R6W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1994</td> </tr> </table> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 44½° E., 16½ lks. dist., with healed blaze. Add the marks X at breast height and BT at the base, facing corner position.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 87° W., 34 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 59¼° W., 39 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 68½° E., 22 lks. dist., mkd. T23S R6W S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the cor. of secs. 22, 23, 26, and 27, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 60° 32' 30" W., 0.293 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the bearing to the NE. bearing tree is N. 26° E.</p>	T23S	R6W	S22	S23	S27	S26	1994	
T23S	R6W								
S22	S23								
S27	S26								
1994									

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>(record, N. 35° E.), and the tree is now a snag. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the NE. bearing tree snag.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 88° 56' 00" W., bet. secs. 23 and 26.</p>
20.340	<p>Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S23 E 1/16 ——— S26 1994</p> </div> <p>from which a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 16° W., 12½ lks. dist., with healed blaze.</p> <p>and a bearing tree reported and a bearing tree mkd. by Jelley, Rogers, and Bishop</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 76 3/4° W., 37 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 18½° W., 27 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located in a shallow ravine, drains N. 30° W.</p> <p>From this point, the E 1/16 sec. cor. of secs. 23 and 26, erroneously established by Gould, Gawron, and Eggen in 1943-57, bears N. 61° 29' 30" W., 0.092 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p>
21.75	<p>Spur, slopes N. 30° W.; desc. gradual NW. slope to Yellow Creek; thence ascend steep SE. slope through heavy timber and moderate undergrowth.</p>
40.680	<p>Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W S23 ¼ ——— S26 1994</p> </div>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>from which</p> <p>A fir, 9 ins. diam., bears S. 41 3/4° E., 16½ lks. dist., mkd. ¼ S26 BT.</p> <p>A fir, 8 ins. diam., bears N. 71 3/4° W., 16 lks. dist., mkd. X at breast height and BT at base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 23 and 26, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 67° 04' 00" W., 0.198 chs. dist.; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the bearing trees.</p>								
42.00	Spur, slopes S. 30° E.; enter logged area and continue along S. slope.								
61.020	<p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td></td><td>S23</td></tr> <tr><td>W 1/16</td><td>-----</td></tr> <tr><td></td><td>S26</td></tr> <tr><td></td><td>1994</td></tr> </table> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A fir, 15 ins. diam., bears S. 49° W., 24 lks. dist., with healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 50½° W., 54 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the W 1/16 sec. cor. of secs. 23 and 26, erroneously established by Gould, Gawron, and Eggen in 1943-57, bears N. 48° 12' 00" W., 0.342 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Continue along S. slope through heavy timber and light undergrowth.</p>		S23	W 1/16	-----		S26		1994
	S23								
W 1/16	-----								
	S26								
	1994								
80.60	Spur, slopes SE.								
81.360	The cor. of secs. 22, 23, 26, and 27.								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 4° 31' 00" E., bet. secs. 22 and 23.
	Ascend S. slope.
0.80	Spur, slopes SE.; continue along E. edge of logged area.
18.850	Point for the S 1/16 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 1/16 S22 S23 1994
	from which a bearing tree mkd. by Gary Langlitz, Deputy County Surveyor, in 1975, as indicated on government Corner Renewal No. 67
	A fir, 18 ins. diam., bears N. 26° W., 133 lks. dist., with healed double blaze.
	and a new bearing tree
	A fir, 21 ins. diam., bears N. 65½° E., 113 lks. dist., mkd. S 1/16 S23 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	From this point, the S 1/16 sec. cor. of secs. 22 and 23, erroneously established by Gould, Gawron, and Eggen in 1943-57, bears N. 29° 59' 30" W., 0.142 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is a snag, bears N. 53½° E. (record, N. 67½° E.), and the SW. bearing tree is gone. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the bearing tree snag.
	Descend steep N. slope.
19.50	Ravine, drains N. 30° W.
20.65	Spur, slopes NW.
21.55	Ravine, drains N. 70° W.; desc. steep, broken NW. slope through heavy timber and light undergrowth.
37.700	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate distance. There is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T23S R6W ¼ S22 S23 1994

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 85½° E., 21 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 35° W., 37 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Gary L. Langlitz, Deputy County Surveyor, in 1975, as indicated in Government Corner Renewal No. 66</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 32° W., 44 lks. dist., with healed double blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 22 and 23, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 51° 57' 00" W., 0.058 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NW. bearing tree is 32 lks. dist. (record, 34 lks.) Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Descend gradual NW. slope along E. edge of logged area.</p>								
42.00	Creek, 10 lks. wide, course N. 80° E.; asc. steep SE. slope.								
73.20	Graveled road, 20 lks. wide, bears N. 80° W. and S. 80° E.								
74.00	Top of Prince Albert Mountain, bears NW. and SE.; desc. NE. slope.								
75.400	<p>Point for the cor. of secs. 14, 15, 22, and 23, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T23S</td> <td style="padding: 0 10px;">R6W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S15</td> <td style="padding: 0 5px;">S14</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">1994</td> </tr> </table> </div> <p>from which remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A sawed fir stump, 15 ins. diam., bears N. 57° E., 46 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 50° E., 70 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A chinquapin, 10 ins. diam., bears S. 80½° W., 133 lks. dist., mkd. T23S R6W S22 BT.</p>	T23S	R6W	S15	S14	S22	S23	1994	
T23S	R6W								
S15	S14								
S22	S23								
1994									

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

A fir, 16 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ W., 237 lks. dist., mkd.
T23S R6W S15 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 14, 15, 22, and 23, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. $86^{\circ} 23' 30''$ E., 0.111 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above the ground, and in a collar of stone, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is now a sawed stump, 37 lks. dist. (record, 38 lks.), the SW. bearing tree is uprooted, and the NW. bearing tree is now a sawed stump, bears N. 9° W., 55 lks. dist. (record, N. 10° W., 65 lks.) Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the remains of the SW. and NW. bearing trees.

From the cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T23S	R6W
<u>S14</u>	<u>S13</u>
S23	S24
1943	

from which the original bearing trees

A fir, 60 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ E., 113 lks. dist., with scribe marks T23 R6 visible on bark blaze.

A fir, 48 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ W., 49 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. $22\frac{1}{2}^{\circ}$ W., 40 lks. dist., with scribe marks T 2 visible on opened blaze.

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 54 ins. diam., bears N. 48° E., 108 lks. dist., with axe marks visible.

A sawed fir stump, 56 ins. diam., bears S. 80° E., 75 lks. dist., with axe marks visible.

and a bearing tree not of record

A hemlock, 17 ins. diam., bears S. 85° E., 5 lks. dist., with healed blaze.

S. $86^{\circ} 50' 00''$ W., bet. secs. 14 and 23.

Ascend E. slope through heavy timber and dense undergrowth.

34.80

Creek, 10 lks. wide, course S. 30° E.; asc. steep E. slope.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
35.660	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p>S14</p> <p>$\frac{1}{4}$ ———</p> <p>S23</p> <p>1994</p> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 23° E., 70 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 1° E., 26 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. $86^{\circ} 21' 00''$ E., 0.094 chs. dist.; monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Ascend steep E. slope along S. edge of logged area.</p>
70.25	Graveled road, 20 lks. wide, bears NW. and S., in a curve.
71.320	The cor. of secs. 14, 15, 22, and 23.
	<hr/> <p>N. $3^{\circ} 40' 00''$ W., bet. secs. 14 and 15.</p> <p>Descend NE. slope across logged area.</p>
0.95	Graveled road, 20 lks. wide, bears NW. and SE.
3.20	Ravine, drains E.
6.80	Graveled road, 20 lks. wide, bears N. 80° E. and S. 80° W., on a ridge, sloping N. 60° E.
8.00	Begin steep descent of NE. slope along W. edge of logged area.
37.660	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	T23S R6W $\frac{1}{4}$ S15 S14 1994
	<p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 27 3/4° E., 65 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears S. 60½° W., 24 lks. dist., with healed, double blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a steep NE. slope, 15 lks. W. of Snail Canyon Creek, 3 lks. wide, course irregularly N.</p> <p>From this point, the ¼ sec. cor. of secs. 14 and 15, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears East, 0.159 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the SE. bearing tree bears S. 14° E., 59 lks. dist. (record, N. 61° E., 51 lks.), and the SW. bearing tree bears S. 72° W., 39 lks. dist. (record, N. 61° W., 55 lks.). Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Descend along creek.</p>
75.320	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> T23S R6W S10 S11 S15 S14 1943 </p> <p>from which the remaining original bearing trees</p> <p style="padding-left: 40px;">A fir, 51 ins. diam., bears N. 35 3/4° E., 97 lks. dist., with healed blaze. (Record, N. 38° E., 100 lks.)</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears S. 5½° E., 25 lks. dist., with scribe marks 2 R S15 BT visible on bark blaze. (Record, S. 3° E., 28 lks.)</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears N. 64¼° W., 15 lks. dist., with healed blaze. (Record, N. 67° W., 19 lks.)</p> <p>and a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 68 ins. diam., bears S. 41° W., 61 lks. dist., with healed blaze. (Record, 65 lks.)</p> <hr/> <p>From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 14° 11' 30" E., bet. secs. 33 and 34.
	Ascend SE. slope.
40.370	Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate distance. There is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T23S R6W ¼ S33 S34 1994
	from which a bearing tree mkd. by Gould, Gawron, and Eggen
	A fir, 26 ins. diam., bears N. 15 ¾° W., 36 lks. dist., with healed blaze.
	and a bearing object mkd. by person(s) unknown
	An X chiselled in the NE. corner of sandstone boulder, 13 x 6 x 3 ft. above the ground, bears N. 64° W., 7 lks. dist.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	From this point, the ¼ sec. cor. of secs. 33 and 34, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 6° 54' 00" W., 0.158 chs. dist.; monumented with an iron post, 2½ ins. diam., loosely set, projecting 12 ins. above a mound of stone, 3 ft. base, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is now a sawed stump. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the stump.
	Continue along steep E. slope along W. edge of logged area.
43.05	Ravine, drains SE.; asc. steep S. slope.
56.00	Spur, slopes S. 60° E.; desc. steep N. slope.
78.00	Spur, slopes S. 70° E.; desc. steep NE. slope.
80.740	Point for the cor. of secs. 27, 28, 33, and 34, at proportionate distance. There is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T23S R6W S28 S27 S33 S34 1994
	from which bearing trees mkd. by Gould, Gawron, and Eggen

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 25 ins. diam., bears N. 62° E., 33 lks. dist., with healed blaze.</p> <p>A fir, 8 ins. diam., bears S. 84° E., 42 lks. dist., with healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 20° W., 80 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. in 1986 under this group</p> <p>A fir, 22 ins. diam., bears N. 49° W., 29 lks. dist., mkd. T23S R6W S28 BT. (In 1994 this is a healed blaze.)</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the cor. of secs. 27, 28, 33, and 34, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 49° 33' 00" E., 0.125 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the SE. bearing tree bears S. 69° E. (record, S. 72° E.), and the NW. bearing tree is dead and down, bears N. 47° W., 35 lks. dist. (record, N. 44° W., 36 lks.) Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the dead and down NW. bearing tree.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>S. 89° 01' 00" W., bet. secs. 27 and 34.</p> <p>Across flat bottom land, through heavy timber and dense undergrowth.</p>
2.35	Yellow Creek, 25 lks. wide, course S.; asc. SE. slope.
30.60	Dirt road, 25 lks. wide, bears NW. and S., in a curve.
35.345	<p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T23S R6W</p> <p>S27</p> <p>¼ —————</p> <p>S34</p> <p>1994</p> </div> <p>from which a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p>A fir, 29 ins. diam., bears N. 22½° W., 33 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 7 ins. diam., bears S. $12\frac{1}{2}^{\circ}$ E., 16 lks. dist., mkd. $\frac{1}{4}$ S34 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 27 and 34, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. $16^{\circ} 57' 30''$ E., 0.171 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted. Do not reuse the SW. bearing tree and unable to remove the marks.</p> <p>Descend SW. slope.</p>
37.70	Creek, 6 lks. wide, course SE.; asc. steep NE. slope.
70.690	The cor. of secs. 27, 28, 33, and 34.
	<hr/> <p>N. $13^{\circ} 30' 00''$ W., bet. secs. 27 and 28.</p> <p>Descend steep N. slope through heavy timber and light undergrowth.</p>
38.50	Spur, slopes E.
40.250	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p>$\frac{1}{4}$</p> <p>S28 S27</p> <p>1994</p> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears S. 70° E., 23 lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p> <p>A fir, 32 ins. diam., bears S. 83° W., 64 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. $25^{\circ} 26' 00''$ W., 0.302 chs. dist.; monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the bearing trees.</p> <p>Continue along steep E. slope.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
77.50	Ravine, drains N. 50° W.								
80.500	<p>Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T23S</td> <td style="padding: 0 5px;">R6W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1994</td> </tr> </table> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 83° W., 137 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 67° W., 62 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 65° E., 104 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 33° E., 119 lks. dist., mkd. T23S R6W S27 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the cor. of secs. 21, 22, 27, and 28, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 70° 19' 30" W., 0.481 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted. The NE. and SE. bearing trees are not usable and marks cannot be removed.</p> <p>From this same point, United States Geological Survey triangulation station "YELLOW 1904," bears S. 50° 06' 30" E., 11.843 chs. dist. (mean bearing and sea level distance); monumented with a standard brass tablet, 3½ ins. diam., set in a boulder projecting 2 ins. above the ground, mkd. YELLOW 1904 1989 and a triangle. Station is located beneath the Yellow Butte Lookout tower.</p> <hr style="width: 80%; margin-left: 0;"/> <p>From the cor. of secs. 22, 23, 26, and 27.</p> <p style="padding-left: 40px;">N. 88° 39' 00" W., bet. secs. 22 and 27.</p> <p style="padding-left: 40px;">Ascend SE. slope along S. edge of logged area.</p>	T23S	R6W	S21	S22	S28	S27	1994	
T23S	R6W								
S21	S22								
S28	S27								
1994									
40.15	Abandoned graveled road, 20 lks. wide, bears NE. and SW.								
40.230	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate distance. There is no remaining evidence of the original corner.								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, the top flush with ground surface, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W S22 ¼ ————— S27 1994</p> <p>from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1975</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 60° W., 98 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 40¼° E., 72 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 22 and 27, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 70° 17' 30" W., 0.554 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NW. bearing tree is gone. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted. The SE. bearing tree is unusable and marks cannot be removed.</p> <p>Continue along N. edge of ridge, through heavy timber and dense undergrowth.</p>
60.345	<p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 W 1/16 ————— S27 1994</p> <p>from which a bearing tree mkd. by Winford Haines, Registered Land Surveyor No. 239, in 1961, recorded in County Survey No. M20-29</p> <p style="padding-left: 40px;">A fir, 60 ins. diam., bears N. 54° W., 85 lks. dist., with scribe marks W 1/16 S22 BT visible on the bark.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 2° E., 68 lks. dist., mkd. W 1/16 S27 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, a point established as the W 1/16 sec. cor. of secs. 22 and 27 by Winford Haines, Registered Land Surveyor No. 239, in 1961, recorded in County Survey No. M20-29, bears N. 87° 58' 30" W., 0.481 chs. dist.; monumented with an iron T-Bar, 1 in. diam., flattened under a fir log, from which the remains of a bearing tree mkd. by Haines:</p> <p style="padding-left: 40px;">A root hole, bears S. 6° W., 69 lks. dist.</p> <p>This corner was established using erroneous control and is not utilized in this survey.</p>
61.30	Ravine, drains N.; asc. NE. slope.
76.25	Ridge, bears N. 60° W. and S. 60° W.
80.460	The cor. of secs. 21, 22, 27, and 28.
	<hr/> <p>N. 21° 48' 00" E., bet. secs. 21 and 22.</p> <p>Ascend S. slope through heavy timber and dense undergrowth.</p>
1.25	Ridge, bears N. 60° W. and S. 60° E.; desc. N. slope.
42.150	<p>The ¼ sec. cor. of secs. 21 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p>¼</p> <p>S21 S22</p> <p>1957</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed, burned fir stump, 48 ins. diam., bears N. 40° E., 49 lks. dist., no marks. (Record and to face, 46 lks.)</p> <p>and the remains of bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A hemlock stump, 10 ins. diam., bears S. 11° E., 29 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A hemlock stump, 12 ins. diam., bears N. 36° W., 14 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 20 ins. diam., bears N. 14½° E., 116 lks. dist., mkd. ¼ S22 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 26½° W., 67 lks. dist., mkd. ¼ S21 BT.</p> <p>The corner is located at N. edge of ravine, drains E.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS											
	(Dependent Resurvey)										
	N. 0° 28' 30" W., beginning new measurement.										
	Descend gradually along steep E. slope through heavy timber and dense undergrowth.										
36.600	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 18 ins. above the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T23S</td> <td>R6W</td> </tr> <tr> <td style="border-right: 1px solid black;">S16</td> <td>S15</td> </tr> <tr> <td style="border-right: 1px solid black;">S21</td> <td>S22</td> </tr> <tr> <td colspan="2" style="text-align: center;">1957</td> </tr> </table>	T23S	R6W	S16	S15	S21	S22	1957			
T23S	R6W										
S16	S15										
S21	S22										
1957											
	from which an original bearing tree										
	A fir, 50 ins. diam., bears N. 53° W., 31 lks. dist., with fragmentary scribe marks visible on the bark. (Record, N. 56° E., 40 lks.)										
	and bearing trees mkd. by Gould, Gawron, and Eggen										
	A hemlock, 19 ins. diam., bears N. 37½° E., 25 lks. dist., with healed blaze. (Record, N. 41° E.)										
	A hemlock, 27 ins. diam., bears S. 32½° E., 72 lks. dist., with healed blaze. (Record, 75 lks.)										
	A hemlock, 16 ins. diam., bears S. 7½° W., 97 lks. dist., with healed blaze. (Record, S. 6° W., 99 lks.)										
	A hemlock, 22 ins. diam., bears N. 64½° W., 80 lks. dist., with healed blaze. (Record, 75 lks.)										
	(Corrective Dependent Resurvey)										
	From the cor. of secs. 14, 15, 22, and 23.										
	N. 88° 01' 00" W., bet. secs. 15 and 22.										
	Ascend NE. slope through logged area.										
1.80	Top of Prince Albert Mountain, bears NW. and SE.; desc. SW. slope.										
35.555	Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance. There is no remaining evidence of the original corner.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T23S</td> <td>R6W</td> </tr> <tr> <td></td> <td style="text-align: center;">S15</td> </tr> <tr> <td>¼</td> <td style="text-align: center;">-----</td> </tr> <tr> <td></td> <td style="text-align: center;">S22</td> </tr> <tr> <td></td> <td style="text-align: center;">1994</td> </tr> </table>	T23S	R6W		S15	¼	-----		S22		1994
T23S	R6W										
	S15										
¼	-----										
	S22										
	1994										
	from which a bearing tree mkd. by Gould, Gawron, and Eggen										

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A cedar, 16 ins. diam., bears S. 12° W., 38 lks. dist. I remark ¼ S22 BT.</p> <p>and a new bearing tree</p> <p>A fir, 6 ins. diam., bears N. 39½° W., 96 lks. dist., mkd. ¼ S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on steep N. slope at S. edge of logged area.</p> <p>From this point, the ¼ sec. cor. of secs. 15 and 22, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 13° 58' 00" E., 0.207 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the NE. bearing tree is a rotted stump, bears N. 48° E. (record, N. 44° E.). Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the stump.</p>
36.00	Creek, 8 lks. wide, course NE.; asc. steep E. slope.
71.110	The cor. of secs. 15, 16, 21, and 22.
	<hr/> (Dependent Resurvey)
	N. 3° 28' 00" W., bet. secs. 15 and 16.
	Descend NE. slope through heavy timber and dense undergrowth.
39.380	The ¼ sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.
	T23S R6W ¼ S16 S15 1957
	from which the remains of bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 9 ins. diam., bears S. 46° E., 35 lks. dist., with healed blaze.
	A fir stump, 12 ins. diam., bears S. 62½° W., 69 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, 71 lks.)
	and bearing trees not of record
	A fir, 50 ins. diam., bears N. 7° E., 11 lks. dist., with scribe marks ¼ S 239 BT visible on bark blaze.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	A fir, 32 ins. diam., bears S. 20° E., 48 lks. dist., with healed blaze.								

	N. 3° 33' 00" W., beginning new measurement.								
	Along W. slope.								
27.50	Descend NE. slope.								
35.00	Graveled road, 30 lks. wide, bears N. 30° W. and S. 30° E.								
39.400	The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.								
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>T23S</td> <td>R6W</td> </tr> <tr> <td>S9</td> <td>S10</td> </tr> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td colspan="2" style="text-align: center;">1955</td> </tr> </table>	T23S	R6W	S9	S10	S16	S15	1955	
T23S	R6W								
S9	S10								
S16	S15								
1955									
	from which an original bearing tree								
	A fir, 56 ins. diam., bears N. 33° E., 45 lks. dist., with healed blaze.								
	and the remains of bearing trees mkd. by Gould, Gawron, and Eggen								
	A sawed fir stump, 18 ins. diam., bears N. 65° E., 100 lks. dist., no marks visible.								
	A sawed fir stump, 24 ins. diam., bears S. 59½° E., 58 lks. dist., with healed blaze. (Record, S. 70° E.)								
	A maple, 38 ins. diam., bears S. 42° W., 87 lks. dist., no marks visible. (Record, S. 30° W.)								
	A sawed fir stump, 14 ins. diam., bears N. 85° W., 69 lks. dist., no marks visible.								
	No new accessories available.								
	From this point, the Bureau of Land Management Geodetic Control Station No. EC 41179, at latitude 43° 33' 31.936" N. and longitude 123° 23' 27.852" W. (NAD 1927), determined by NAVSTAR Global Position System, bears S. 24° 54' 58" E., 103.855 chs. dist. (mean bearing and sea level distance), hereinbefore described.								

	From the cor. of secs. 10, 11, 14, and 15.								
	N. 85° 18' 30" W., bet. secs. 10 and 15.								
	Ascend over SE. slope through heavy timber and dense undergrowth.								
19.75	Spur, slopes N. 10° E.; desc. over NW. slope; also, dirt road, 10 lks. wide, bears N. 10° E. and S. 10° W.								
30.55	End of dirt road, 30 lks. wide, extending S. 10° W.								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
35.700	<p>The ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W S10 ¼ ----- S15 1957</p> <p>from which the remains of a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A root hole, bears S. 65½° E., 41 lks. dist., alongside of which is lying a decayed hemlock, size indeterminate, with fragmentary scribe marks visible on decayed blaze.</p> <p>and bearing trees mkd. by Ken W. Hoffine, Registered Land Surveyor No. 2291, in 1992, and recorded in Douglas County Surveyor's Office Corner Renewal File No. 96</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 30° W., 42 lks. dist., with scribe marks ¼ S15 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 32 ¾° W., 34 lks. dist., with scribe marks ¼ S10 BT visible on open blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85° 08' 30" W., beginning new measurement.</p> <p>Descend over NW. slope.</p>
9.05	Graveled road, 30 lks. wide, bears N. 5° E. and S. 25° E., in a curve.
17.15	Andrews Creek, 8 lks. wide, course N. 20° E.; asc. over NE. slope.
35.640	<p>The cor. of secs. 9, 10, 15, and 16.</p> <hr style="width: 80%; margin: 10px auto;"/> <p style="text-align: center;">(Corrective Dependent Resurvey)</p> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp. N. 20° 18' 00"E., bet. secs. 32 and 33.</p> <p>Ascend steep SE. slope, changing to S. slope; over sandstone ledges.</p>
42.950	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W ¼ S32 S33 1994</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 18 ins. diam., bears N. 5° E., 77 lks. dist., with healed blaze.

A hemlock, 10 ins. diam., bears N. 44¼° E., 61 lks. dist., with healed blaze.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the ¼ sec. cor. of secs. 32 and 33, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 27° 37' 00" E., 0.826 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap marked and witnessed as described in the official record, except the SE. bearing tree is a hemlock, bears S. 8¼° E. (record, fir, S. 9 3/4° E.), and the NW. bearing tree bears N. 82 3/4° W., 32 lks. dist. (record, N. 83½° W., 33 lks.) Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.

Descend over broken NW. slope through heavy timber and dense undergrowth.

85.900

The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T23S	R6W
<u>S29</u>	<u>S28</u>
S32	S33
1957	

from which the remains of the original bearing trees remarked by Gould, Gawron, and Eggen

A fir, 55 ins. diam., bears N. 19¼° E., 23 lks. dist., with partially healed blaze.

A fir, 33 ins. diam., bears S. 38° E., 100 lks. dist., with healed double blaze.

A fir, 52 ins. diam., bears S. 48° W., 13 lks. dist., with scribe marks T23 R6W S32 visible on bark blaze.

A fir snag, 44 ins. diam., bears N. 11 3/4° W., 45 lks. dist., with healed blaze.

and a new bearing tree

A hemlock, 4 ins. diam., bears N. 38° W., 16½ lks. dist., mkd. X BT.

From the cor. of secs. 27, 28, 33, and 34.

N. 88° 05' 00" W., bet. secs. 28 and 33.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend steep NE. slope through heavy timber and moderate undergrowth.
35.610	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate distance. There is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T23S R6W S28 $\frac{1}{4}$ ——— S33 1994 </div>
	from which bearing trees mkd. by Gould, Gawron, and Eggen <div style="margin-left: 40px;"> A fir, 38 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ E., 126 lks. dist., with healed blaze. A fir, 40 ins. diam., bears N. $79\frac{1}{2}^{\circ}$ W., 93 lks. dist., with healed blaze. </div>
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. From this point, the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. $45^{\circ} 28' 30''$ W., 0.086 chs. dist.; monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the SE. bearing tree is 130 lks. dist. (record, 123 lks.), and the NW. bearing tree is 90 lks. dist. (record, 88 lks.) Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted. Descend W. slope.
36.60	Ravine, drains NW.
71.220	The cor. of secs. 28, 29, 32, and 33. <hr/>
	N. $20^{\circ} 37' 30''$ W., bet. secs. 28 and 29. Descend over NW. slope through heavy timber and moderate undergrowth. 4.50 Doe Creek, 10 lks. wide, course S. 50° W.; asc. over SE. slope. 12.15 Spur, slopes S. 80° E.; desc. over NE. slope. 20.570 Point for the S $\frac{1}{16}$ sec. cor. of secs. 28 and 29. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S $\frac{1}{16}$ S29 S28 1994 </div>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears S. 64° E., 68 lks. dist., mkd. S 1/16 S28 BT.</p> <p style="padding-left: 40px;">A maple, 19 ins. diam., bears S. 56° W., 37 lks. dist., mkd. S 1/16 S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the S 1/16 sec. cor. of secs. 28 and 29, erroneously established by Gould, Gawron, and Eggen in 1943-1957, bears S. 24° 41' 00" W., 3.014 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the bearing trees.</p> <p>Along westerly edge of creek, 15 lks. wide, course S. 20° E.</p>
22.65	Ravine, drains E.; asc. along E. slope.
41.140	<p>Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T23S R6W</p> <p style="margin-left: 100px;">¼</p> <p>S29 S28</p> <p style="margin-left: 100px;">1994</p> </div> <p>from which bearing trees mkd. in 1986 under this group</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears S. 68½° W., 50 lks. dist., mkd. ¼ S29 BT. (In 1994 this is a healed blaze.)</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 16½° W., 16 lks. dist., mkd. ¼ S28 BT. (In 1994 this is a healed blaze.)</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 28 and 29, erroneously reestablished by Gould, Gawron, and Eggen in 1943-1957, bears S. 34° 22' 30" W., 3.183 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the bearing trees.</p>
42.20	Creek, 5 lks. wide, course SE.; asc. steep SW. slope.
46.50	Spur, slopes S. 60° E.
82.280	Point for the cor. of secs. 20, 21, 28, and 29, at proportionate distance. There is no remaining evidence of the original corner.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S	R6W
S20	S21
S29	S28
1994	

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 42 ins. diam., bears N. 67° E., 28 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 58 3/4° W., 80 lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley, Rogers, and Bishop

A fir, 9 ins. diam., bears S. 81½° W., 180 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and a new bearing tree

A fir, 26 ins. diam., bears S. 35½° E., 78 lks. dist., mkd. T23S R6W S28 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 20, 21, 28, and 29, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 83° 37' 00" W., 0.585 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record, except the SW. bearing tree mkd. by Gould, Gawron, and Eggen is dead and down, and the SE. bearing tree mkd. by Jelley, Rogers, and Bishop is a snag. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the SW. dead and down tree and the SE. snag.

From the cor. of secs. 21, 22, 27, and 28.

N. 89° 14' 00" W., bet. secs. 21 and 28.

Descend SW. slope through heavy timber and dense undergrowth.

40.660

Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S	R6W
	S21
¼	-----
	S28
1994	

from which bearing trees mkd. by Gould, Gawron, and Eggen

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 36 ins. diam., bears S. 20½° E., 118 lks. dist., with healed blaze.</p> <p>A fir, 54 ins. diam., bears S. 88¼° W., 56 lks. dist., with healed blazes on S. and W. sides.</p> <p>and a new bearing tree</p> <p>A chinquapin, 6 ins. diam., bears N. 5½° W., 43 lks. dist., mkd. ¼ S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 21 and 28, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 83° 19' 00" W., 0.593 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p>
41.15	Ridge, bears NW. and SE.
41.85	Graveled road, 25 lks. wide, bears NW. and SE.; desc. SW. slope.
60.990	Point for the W 1/16 sec. cor. of secs. 21 and 28.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S21</p> <p>W 1/16 <u> </u></p> <p>S28</p> <p>1994</p> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p>A fir, 12 ins. diam., bears S. 67° W., 56 lks. dist., with healed blaze.</p> <p>A fir, 9 ins. diam., bears N. 28° W., 40 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the W 1/16 sec. cor. of secs. 21 and 28, erroneously established by Gould, Gawron, and Eggen in 1943-57, bears N. 85° 53' 30" W., 0.601 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p>
62.30	Head of ravine, drains SW.; asc. SE. slope.
81.320	The cor. of secs. 20, 21, 28, and 29.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 18° 29' 00" E., bet. secs. 20 and 21.
	Ascend over SE. slope.
4.00	Ridge, bears N. 75° E. and S. 75° W.; also, graveled road, 25 lks. wide, bears same; desc. over logged area.
40.605	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate distance. There is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T23S R6W ¼ S20 S21 1994
	from which bearing trees mkd. by Gould, Gawron, and Eggen
	A fir, 18 ins. diam., bears S. 85½° W., 89 lks. dist., with healed blaze.
	A fir, 26 ins. diam., bears N. 79° W., 26 lks. dist., with healed blaze. I remark X at breast height and BT at the base.
	and a new bearing tree
	A fir, 18 ins. diam., bears S. 87° E., 27 lks. dist., mkd. ¼ S21 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	The corner is located at the toe of a steep NW. slope and on the E. edge of a flat bench.
	From this point, the ¼ sec. cor. of secs. 20 and 21, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears S. 61° 03' 00" W., 0.667 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM1994 1957 and reset the monument inverted.
	Along E. edge of bench.
42.00	Leave bench; desc. steep NW. slope, through heavy timber and light undergrowth.
81.210	The cor. of secs. 16, 17, 20, and 21, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.
	From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp.
	N. 11° 22' 30" E., bet. secs. 31 and 32.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
40.260	<p>Descend N. slope through heavy timber and dense undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T23S</td><td>R6W</td></tr> <tr><td>S31</td><td> S32</td></tr> <tr><td></td><td>1994</td></tr> </table> </div> <p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 73° E., 78 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 36 ins. diam., bears N. 21° W., 25 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located at head of ravine, drains NE.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, erroneously corrected by Brooks in 1964, bears N. $76^{\circ} 05' 30''$ E., 0.429 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p> <p>Descend steep NE. slope.</p>	T23S	R6W	S31	S32		1994		
T23S	R6W								
S31	S32								
	1994								
80.00	Graveled road, 25 lks. wide, bears NW. and SE.								
80.520	<p>Point for the cor. of secs. 29, 30, 31, and 32 at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table> <tr><td>T23S</td><td>R6W</td></tr> <tr><td>S30</td><td> S29</td></tr> <tr><td>S31</td><td> S32</td></tr> <tr><td></td><td>1994</td></tr> </table> </div> <p>from which a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E., 108 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 122 lks. dist., with healed blaze.</p> <p>and new bearing trees</p>	T23S	R6W	S30	S29	S31	S32		1994
T23S	R6W								
S30	S29								
S31	S32								
	1994								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

A fir, 10 ins. diam., bears S. $85\frac{1}{2}^{\circ}$ E., 23 lks. dist., mkd.
T23S R6W S32 BT.

A fir, 11 ins. diam., bears S. 71° W., 13 lks. dist., mkd.
T23S R6W S31 BT.

Deposit a white "DEEP-1" magnetic marker at the base and steel fence post alongside the stainless steel post.

From this point, cor. of secs. 29, 30, 31, and 32, erroneously corrected by Brooks in 1964, bears N. $11^{\circ} 04' 30''$ W., 0.193 chs. dist.; monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record except the SE. bearing tree marked by Brooks is a stump. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the stump.

From the cor. of secs. 28, 29, 32, and 33.

S. $88^{\circ} 56' 30''$ W., bet. secs. 29 and 32.

47.605

Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate distance. There is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T23S R6W
S 29
 $\frac{1}{4}$ -----
S 32
1994

from which

A fir, 9 ins. diam., bears N. $4\frac{3}{4}^{\circ}$ E., 35 lks. dist., mkd.
 $\frac{1}{4}$ S29 BT.

A fir, 9 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ E., 11 lks. dist., mkd. $\frac{1}{4}$
S32 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

The corner is located on SW. slope.

From this point, the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, erroneously corrected by Brooks in 1964, bears N. $1^{\circ} 57' 00''$ E., 1.059 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record except the remaining tree marked by Gould, Gawron, and Eggen is dead and down, the NE. bearing tree marked by Brooks is gone, and the SE. bearing tree marked by Brooks is a snag. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on all bearing trees.

Descend steep SW. slope through dense young fir timber.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
88.70	Graveled road, 20 lks. wide, bears N. and S.
95.210	The cor. of secs. 29, 30, 31, and 32. <hr/>
	S. 89° 26' 30" W., bet. secs. 30 and 31. Descend SW. slope through heavy timber and dense undergrowth.
0.75	Graveled road, 25 lks. wide, bears NW. and SE.
47.410	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate distance. There is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;">T23S R6W S 30 ¼ ----- S 31 1994</div> from which bearing trees mkd. by Brooks <div style="margin-left: 40px;">A fir, 29 ins. diam., bears S. 53° W., 78 lks. dist., with healed blaze. A fir, 12 ins. diam., bears N. 44½° W., 82 lks. dist., with healed blaze.</div> Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. From this point, the ¼ sec. cor. of secs. 30 and 31, erroneously corrected by Brooks in 1964, bears N. 80° 09' 00" W., 0.561 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.
47.75	Ravine, drains S. 60° E.; asc. steep E. slope.
51.00	Ridge, bears N. and S.; desc. SW. slope.
92.885	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp. <hr/>
	From the cor. of secs. 29, 30, 31, and 32. N. 10° 46' 00" W., bet. secs. 29 and 30. Along broken W. slope through dense young fir timber.
40.180	Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate distance. There is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	T23S R6W $\frac{1}{4}$ S30 S29 1994
	<p>from which a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears N. 56° W., 51 lks. dist., with healed blaze. (Record, fir.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 21½° E., 26 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, erroneously corrected by Brooks in 1964, bears N. 25° 34' 30" W., 0.364 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap marked and witnessed as described in the official record except the bearing trees are hemlock (record, fir.) Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the NE. bearing tree.</p> <p>Descend steep NW. slope through heavy timber and dense undergrowth.</p>
42.70	Creek, 6 lks. wide, course W.; asc. steep S. slope.
51.00	Spur, slopes SW.; continue along W. slope on W. edge of logged area.
80.360	<p>Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p>
	T23S R6W <u>S19 S20</u> S30 S29 1994
	<p>from which bearing trees mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 68½° W., 79 lks. dist., with fragmentary scribe marks visible on pitched over blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 43° W., 34 lks. dist., with healed blaze.</p> <p>and a bearing object set by Gregory Quibell, Deputy County Surveyor, in 1982, as indicated in Government Corner Renewal No. 77</p> <p style="padding-left: 40px;">A nail set in sandstone bedrock, bears N. 11½° W., 25 lks. dist.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	<p>and new bearing trees</p> <p style="padding-left: 40px;">A double fir, 10 ins. diam., bears N. 26° E., 73 lks. dist., mkd. T23S R6W S20 BT.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 75° E., 34 lks. dist., mkd. T23S R6W S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on steep spur, slopes S. 20° W.</p> <p>From this point, the cor. of secs. 19, 20, 29, and 30, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 27° 32' 30" W., 0.236 chs. dist.; monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked and witnessed as described in the official record except the SE. bearing tree is a stump and has no marks and the county added the marks RESET 1982 to the brass cap. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the NE. bearing tree.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89° 53' 30" W., bet. secs. 20 and 29.</p> <p>Ascend SE. slope.</p>								
6.00	<p>Ridge, bears NE. and SW.; also, graveled road, 20 lks. wide, bears same; desc. NW. slope.</p>								
19.00	<p>Creek, 3 lks. wide, course N.</p>								
20.310	<p>Point for the E 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: 40px; border-collapse: collapse;"> <tr> <td style="padding-right: 40px;">FD. OK BY</td> <td style="text-align: right;">S20</td> </tr> <tr> <td>M. SMALLEY</td> <td style="text-align: right;">E 1/16 -----</td> </tr> <tr> <td>3/2006</td> <td style="text-align: right;">S29</td> </tr> <tr> <td>C.S. 65/58-6</td> <td style="text-align: right;">1994</td> </tr> </table> <p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 87 3/4° W., 60 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 5° W., 34 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a spur, slopes NE.</p>	FD. OK BY	S20	M. SMALLEY	E 1/16 -----	3/2006	S29	C.S. 65/58-6	1994
FD. OK BY	S20								
M. SMALLEY	E 1/16 -----								
3/2006	S29								
C.S. 65/58-6	1994								

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, the E 1/16 sec. cor. of secs. 20 and 29, erroneously corrected by Jelley, Rogers, and Bishop in 1982-83, bears N. 74° 28' 30" W., 0.374 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p>
21.20	Ravine, drains N. 70° E.; asc. steep E. slope.
29.00	Ridge, bears N. 20° W. and S. 20° E.; also, graveled road, 25 lks. wide, bears same; desc. SW. slope.
39.30	Leave timber, edge bears N. and S.
40.620	<p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p>S20</p> <p>¼ —————</p> <p>S29</p> <p>1994</p> </div> <p>from which a bearing tree mkd. by Gould, Gawron, and Eggen</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 7° E., 95 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 42° E., 180 lks. dist., mkd. ¼ S29 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 20 and 29, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 28° 06' 30" W., 0.299 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record except the SW. bearing tree is a stump. Amended the marks on the brass cap to read AM 1994 1957, reset the monument inverted, and obliterated the marks on the stump.</p> <p>Descend SW. slope along N. edge of logged area.</p>
81.240	<p>The cor. of secs. 19, 20, 29, and 30.</p> <hr style="width: 100%;"/> <p>S. 89° 00' 30" W., bet. secs. 19 and 30.</p> <p>Descend steep SW. slope.</p>
40.515	<p>Point for the ¼ sec. cor. of secs. 19 and 30 at proportionate distance. There is no remaining evidence of the original corner.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S R6W
S19
¼ ———
S30
1994

from which bearing trees mkd. by Gould, Gawron, and Eggen

A fir, 30 ins. diam., bears N. 36½° E., 55½ lks. dist., with healed blaze.

A fir, 30 ins. diam., bears S. 46° E., 30 lks. dist., with healed blaze.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the ¼ sec. cor. of secs. 19 and 30, erroneously reestablished by Gould, Gawron, and Eggen in 1943-57, bears N. 15° 12' 00" E., 0.286 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.

Descend NW. slope.

78.905

The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, in a collar of stone, with brass cap mkd.

T23S
R7W R6W
S24 | S19
S25 | S30
1957

from which the remains of an original bearing tree

A sawed fir stump, 48 ins. diam., bears N. 30° W., 119 lks. dist., with fragmentary scribe marks visible on opened blaze.

and the remains of bearing trees mkd. by Gould, Gawron, and Eggen

A broken fir stump, 20 ins. diam., bears N. 36° E., 43 lks. dist., no marks. (Record, N. 14° E.)

A fir, 28 ins. diam., bears S. 72° E., 50 lks. dist., with healed blaze. (Record, S. 64½° E.)

A fir, 40 ins. diam., bears S. 29° W., 79 lks. dist., with healed blaze. (Record, S. 9½° W.)

and new bearing trees

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 25 ins. diam., bears N. 45° E., 21 lks. dist., mkd. T23S R6W S19 BT.</p> <p>A hemlock, 10 ins. diam., bears N. 59° W., 95 lks. dist., mkd. T23S R7W S24 BT.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 25° 03' 00" E., bet. secs. 19 and 20.</p> <p>Ascend steep SE. slope over sandstone ledges.</p>
43.570	<p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W S19 S20 1994</p> <p>from which remains of the bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, as indicated in Government Corner Renewal No. 44</p> <p>A fir stump, 18 ins. diam., bears N. 22½° E., 103 lks. dist., with scribe marks ¼ S20 CS BT visible on open, double blaze.</p> <p>A hemlock, 19 ins. diam., bears N. 6° W., 136 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 60° E., 47 lks. dist., mkd. ¼ S20 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the ¼ sec. cor. of secs. 19 and 20, erroneously corrected by Brooks in 1964, bears N. 55° 00' 30" W., 0.097 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record except the NE. bearing tree marked by the County Surveyor's Office is a stump and Brooks' bearing tree is dead. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted, and obliterated the marks on Brooks' bearing tree.</p> <p>Ascend SE. slope through heavy timber and dense undergrowth.</p>
46.30	<p>Ridge, bears N. 80° E. and S. 80° W.; also, graveled road, 25 lks. wide, bears same; desc. NW. slope.</p>
65.355	<p>Point for the N 1/16 sec. cor. of secs. 19 and 20.</p>

**Dependent Resurvey and Corrective Dependent Resurvey
of a Portion of the Subdivisional Lines,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S19 S20 1994</p> <p>from which bearing trees mkd. by Brooks</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 79¼° E., 71 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 7¼° W., 109 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the N 1/16 sec. cor. of secs. 19 and 20, erroneously corrected by Brooks in 1964, bears N. 16° 53' 00" W., 0.058 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1957 and reset the monument inverted.</p>
66.75	Spur, slopes NW.; desc. steep broken NW. slope.
87.140	The cor. of secs. 17, 18, 19, and 20, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.
<hr/> <p>Corrective Survey of the Subdivision of Section 20, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>	
<p>(Correcting the survey by James E. Jelley, Wayne L. Rogers, and Lance J. Bishop in 1982-83)</p> <hr/>	
	<p>From the ¼ sec. cor. of secs. 20 and 29.</p> <p>N. 21° 54' 30" E., on the N. and S. centerline of sec. 20.</p> <p>Ascend SW. slope.</p>
18.50	Ridge, bears NW. and SE.; desc. NE. slope.
20.00	Graveled road, 20 lks. wide, bears NW. and SE.
42.020	<p>Point for the center ¼ sec. cor. of sec. 20, at intersection with the E. and W. centerline.</p> <p>From this point, the center ¼ sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 52° 19' 30" W., 0.227 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap marked and witnessed as described in the</p>

**Corrective Survey of the Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>official record except the NW. bearing tree is uprooted. Remove the aluminum post, destroy the marks on the uprooted bearing tree, and at the true corner point:</p> <p>Reset the aluminum post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, in a collar of stone, with aluminum cap mkd.</p> <p align="center">T23S R6W C¼ S20 1994</p> <p>from which a bearing tree mkd. by Jelley, Rogers, and Bishop</p> <p>A fir, 23 ins. diam., bears S. 76° W., 26 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 22 ins. diam., bears N. 18½° E., 15½ lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the aluminum post.</p> <p>The corner is located on a spur, slopes E.</p> <p>Descend NE. slope.</p>
62.25	Ravine, drains E.
63.050	<p>Point for the center N 1/16 sec. cor. of sec. 20.</p> <p>From this point, the center N 1/16 sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 51° 27' 00" W., 0.113 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Remove the iron post and at the true corner point:</p> <p>Reset the iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p align="center">C N 1/16 S20 C 1994</p> <p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p>A hemlock, 12 ins. diam., bears N. 74½° E., 32½ lks. dist., with scribe marks CN 1/16 S20 BT visible on partially healed blaze.</p> <p>A cedar, 12 ins. diam., bears S. 60 ¾° W., 58 lks. dist., with scribe marks CN 1/16 S20 BT visible on partially healed blaze.</p>

**Corrective Survey of the Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS									
	Deposit a white "DEEP-1" magnetic marker at the base of the iron post.								
64.00	Spur, slopes E.								
84.080	The ¼ sec. cor. of secs. 17 and 20, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.								
	<hr/> From the ¼ sec. cor. of secs. 20 and 21. N. 89° 09' 30" W., on the E. and W. centerline of sec. 20. Over flat bench; thence desc. steep NW. slope.								
13.75	Spur, slopes N.; also, graveled road, 25 lks. wide, bears N. and S.; desc. steep W. slope along S. edge of logged area.								
18.920	Point for the center E 1/16 sec. cor. of sec. 20. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.								
	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">FD. OK M. SMALLEY</td> <td style="width: 50%; text-align: center;">E 1/16</td> </tr> <tr> <td>3/2006</td> <td style="text-align: center;">C <u> </u> C</td> </tr> <tr> <td>C.S. 65/58-4</td> <td style="text-align: center;">S20</td> </tr> <tr> <td></td> <td style="text-align: center;">1994</td> </tr> </table>	FD. OK M. SMALLEY	E 1/16	3/2006	C <u> </u> C	C.S. 65/58-4	S20		1994
FD. OK M. SMALLEY	E 1/16								
3/2006	C <u> </u> C								
C.S. 65/58-4	S20								
	1994								
	from which bearing trees mkd. by Jelley, Rogers, and Bishop A fir, 22 ins. diam., bears S. 26½° W., 57 lks. dist., with healed blaze. A hemlock, 9 ins. diam., bears S. 83° W., 47 lks. dist., with healed blaze.								
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.								
	From this point, the center E 1/16 sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 58° 53' 30" W., 0.446 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with aluminum cap marked and witnessed as described in the official record. This point now serves as a reference monument to the center E 1/16. Aluminum cap now mkd. RM CE 1/16 S20 29.4 FT TO COR 1994 and an arrow pointing to the corner.								
	Descend steep W. slope.								
37.840	The center ¼ sec. cor. of sec. 20.								
	Ascend spur, sloping E.								
56.770	Point for the center W 1/16 sec. cor. of sec. 20.								

**Corrective Survey of the Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, the center W 1/16 sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 71° 35' 30" W., 0.136 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap marked and witnessed as described in the official record. Remove the iron post and at the true corner point:</p>
	<p>Reset the iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p align="center">W 1/16 C ————— C S20 1994</p>
	<p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p>
	<p>A fir, 10 ins. diam., bears S. 51½° E., 19 lks. dist., with healed blaze.</p>
	<p>A fir, 16 ins. diam., bears N. 66½° W., 31½ lks. dist., with healed blaze.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the iron post.</p>
57.25	<p>Ridge, slopes S. 30° E.; along S. slope.</p>
75.700	<p>The ¼ sec. cor. of secs. 19 and 20.</p> <hr/>
	<p>(The following N. and S. centerline of the NE¼ of sec. 20 is returned by calculation based on this corrective survey of sec. 20 and the Gould, Gawron, and Eggen 1943-57 resurvey of the E½ mile bet. secs. 17 and 20.)</p> <p>From the center E 1/16 sec. cor. of sec. 20.</p> <p>N. 20° 12' 00" E., on the N. and S. centerline of the NE¼ of sec. 20.</p>
41.320	<p>The E 1/16 sec. cor. of secs. 17 and 20, described in the field notes by Jelley, Rogers, and Bishop in 1982-83.</p> <hr/>
	<p>(The following N. and S. centerline of the SE¼ of sec. 20 is returned by calculation based on this corrective resurvey and survey.)</p> <p>From the E 1/16 sec. cor. of secs. 20 and 29.</p> <p>N. 20° 12' 00" E., on the N. and S. centerline of the SE¼ of sec. 20.</p>
41.285	<p>The center E 1/16 sec. cor. of sec. 20.</p> <hr/>
	<p>From the center W 1/16 sec. cor. of sec. 20.</p>

**Corrective Survey of the Subdivision of Section 20,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>N. 23° 32' 00" E., on the N. and S. centerline of the NW¼ of sec. 20.</p>
	<p>Along E. slope.</p>
21.410	<p>Point for the NW 1/16 sec. cor. of sec. 20, at intersection with the E. and W. centerline of the NW¼.</p>
	<p>From this point, the NW 1/16 sec. cor. of sec. 20, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears S. 82° 09' 00" W., 0.059 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record except both bearing trees are dead. Remove the iron post, obliterate the marks on the dead bearing trees, and at the true point:</p>
	<p>Reset the iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p align="center">NW 1/16 S20 1994</p>
	<p>from which</p>
	<p>A fir, 15 ins. diam., bears S. 34° E., 41 lks. dist., mkd. NW 1/16 S20 BT.</p>
	<p>A fir, 18 ins. diam., bears N. 34° W., 55 lks. dist., mkd. X BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the iron post.</p>
22.50	<p>Spur, slopes NE.; desc. N. slope.</p>
42.860	<p>The W 1/16 sec. cor. of secs. 17 and 20, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.</p> <hr/>
	<p>From the center N 1/16 sec. cor. of sec. 20.</p>
	<p>N. 88° 47' 00" W., on the E. and W. centerline of the NW¼ of sec. 20.</p>
	<p>Ascend SE. slope through heavy timber and light undergrowth.</p>
18.230	<p>The NW 1/16 sec. cor. of sec. 20.</p>
19.25	<p>Spur, slopes NE.</p>
23.00	<p>Dirt road, 25 lks. wide, bears N. 20° W. and S. 20° E.</p>
36.490	<p>The N 1/16 sec. cor. of secs. 19 and 20.</p> <hr/>
	<p align="center">Corrective Survey of the Subdivision of Section 26, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p align="center">(Correcting the survey by James E. Jelley, Wayne L. Rogers, and Lance J. Bishop in 1982-83)</p> <hr/> <p>From the ¼ sec. cor. of secs. 26 and 35, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.</p> <p>N. 0° 52' 00" W., on the N. and S. centerline of sec. 26.</p>
37.90	Ravine, drains NW.
38.195	<p>Point for the center ¼ sec. cor. of sec. 26, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">T23S R6W C¼ S26 1994</p> <p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p>A fir, 12 ins. diam., bears N. 43½° E., 6 lks. dist., with healed blaze.</p> <p>A fir, 25 ins. diam., bears S. 47° W., 37 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the center ¼ sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 69° 18' 00" W., 0.096 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1982 and reset the monument inverted.</p> <p>Descend NW. slope across logged area.</p>
57.230	<p>Point for the center N 1/16 sec. cor. of sec. 26.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">C N 1/16 S26 C 1994</p> <p>from which</p> <p>A fir, 3 ins. diam., bears N. 32 ¾° E., 14½ lks. dist., mkd. X at breast height and BT at the base.</p> <p>A maple, 6 ins. diam., bears N. 33½° E., 55 lks. dist., mkd. X at breast height and BT at the base.</p>

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the center N 1/16 sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 66° 41' 00" W., 0.146 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap marked and witnessed as described in the official record except the bearing trees mkd. by Haines are now stumps and the bearing tree mkd. by Jelley, Rogers, and Bishop is dead and down. Amended the marks on the aluminum cap to read AM 1994 1982, reset the monument inverted, and obliterated the marks on the dead and down bearing tree.</p> <p>Descend steep NE. slope.</p>
73.80	Spur, slopes S. 30° E.; along E. slope through heavy timber.
76.265	The ¼ sec. cor. of secs. 23 and 26.
	<hr/> <p>From the ¼ sec. cor. of secs. 25 and 26, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T23S R6W</p> <p> ¼</p> <p>S26 S25</p> <p> 1982</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A root hole, bears East, 77 lks. dist., alongside of which is lying a fir, size indeterminate, no marks visible.</p> <p>and the remains of bearing trees mkd. by Vernon R. Tracy, Deputy County Surveyor, in 1962, as indicated in Government Corner Renewal No. 42, reported by Jelley, Rogers, and Bishop</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 11° E., 76 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir snag, 14 ins. diam., bears S. 41° W., 131 lks. dist., with scribe marks ¼ S26 CS BT visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Jelley, Rogers, and Bishop</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 53½° W., 13½ lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>S. 89° 40' 00" W., on the E. and W. centerline of sec. 26.</p>
20.10	Dirt road, 25 lks. wide, bears N. 10° E. and S. 60° W., in a curve.
20.345	Point for the center E 1/16 sec. cor. of sec. 26.

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">E 1/16 C ————— C S26 1994</p> <p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p>A fir, 10 ins. diam., bears N. 7 3/4° E., 28 lks. dist., with scribe marks X BT visible on partially healed double blaze.</p> <p>A fir, 15 ins. diam., bears S. 15 3/4° W., 12½ lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the center E 1/16 sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 68° 45' 00" W., 0.048 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1982 and reset the monument inverted.</p>
20.45	Ravine, drains NW.; desc. NW. slope through medium timber and moderate undergrowth.
40.690	The center ¼ sec. cor. of sec. 26.
40.95	Ravine, drains NW.
57.00	Spur, slopes S.; desc. steep SW. slope.
59.045	Point for the center W 1/16 sec. cor. of sec. 26.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p align="center">W 1/16 C ————— C S26 1994</p> <p>from which bearing trees mkd. by Haines, reported by Jelley, Rogers, and Bishop</p> <p>A fir, 18 ins. diam., bears N. 72½° W., 30 lks. dist., with healed blaze.</p> <p>A fir, 32 ins. diam., bears N. 47° W., 21 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Jelley, Rogers, and Bishop</p> <p>A fir, 27 ins. diam., bears S. 72° W., 36 lks. dist., with healed blaze.</p>

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	From this point, the center W 1/16 sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 64° 09' 00" W., 0.117 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap marked and witnessed as described in the official record. Amended the marks on the aluminum cap to read AM 1994 1982 and reset the monument inverted.
	Descend steep W. slope.
61.00	Creek, 5 lks. wide, course SE.; asc. steep E. slope along N. edge of logged area.
68.30	Dirt road, 20 lks. wide, bears NW. and SE.
77.400	The ¼ sec. cor. of secs. 26 and 27.
	<hr/> <p>From the center E 1/16 sec. cor. of sec. 26.</p> <p>N. 0° 53' 00" W., on the N. and S. centerline of the NE¼ of sec. 26.</p> <p>Along broken W. slope through medium timber and moderate undergrowth.</p>
19.155	<p>Point for the NE 1/16 sec. cor. of sec. 26, at intersection with the E. and W. centerline of the NE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p align="center">NE 1/16 S26 1994</p>
	from which bearing trees mkd. by Jelley, Rogers, and Bishop
	A fir, 16 ins. diam., bears S. 36° E., 46 lks. dist., with healed blaze.
	A fir, 14 ins. diam., bears N. 25° W., 61 lks. dist., with scribe marks X BT visible on partially healed double blaze.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	From this point, the NE 1/16 sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 64° 10' 00" W., 0.069 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap marked and witnessed as described in the official record. Amended the marks on the brass cap to read AM 1994 1982 and reset the monument inverted.
38.350	The E 1/16 sec. cor. of secs. 23 and 26.
	<hr/>

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the N 1/16 sec. cor. of secs. 25 and 26, set, marked, and witnessed as described in the field notes by Jelley, Rogers, and Bishop in 1982-83.</p> <p>S. 89° 20' 00" W., on the E. and W. centerline of the NE¼ of sec. 26.</p> <p>Descend SW. slope.</p>
20.380	<p>The NE 1/16 sec. cor. of sec. 26.</p> <p>Descend SW. slope along creek, course irregularly W.</p>
28.80	<p>Spur, slopes SW.</p>
33.20	<p>Yellow Creek, 20 lks. wide, course S.</p>
40.715	<p>The center N 1/16 sec. cor. of sec. 26.</p> <hr/>
	<p>From the center W 1/16 sec. cor. of sec. 26.</p> <p>N. 3° 51' 30" W., on the N. and S. centerline of the NW¼ of sec. 26.</p> <p>Ascend steep SW. slope along W. edge of logged area.</p>
18.945	<p>Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E. and W. centerline of the NW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p align="center">NW 1/16 S26 1994</p>
	<p>from which bearing trees mkd. by Jelley, Rogers, and Bishop</p> <p>A fir, 12 ins. diam., bears S. 80° W., 27 lks. dist., with healed blaze.</p> <p>A fir, 22 ins. diam., bears N. 22¼° W., 26 lks. dist., with healed blaze.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, the NW 1/16 sec. cor. of sec. 26, erroneously established by Jelley, Rogers, and Bishop in 1982-83, bears N. 67° 04' 30" W., 0.190 chs. dist.; monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap marked and witnessed as described in the official record. Amended the marks on the aluminum cap to read AM 1994 1982 and reset the monument inverted.</p>
19.70	<p>Ridge, bears N. 30° W. and S. 30° E.; desc. steep NE. slope along W. edge of logged area.</p>

**Corrective Survey of the Subdivision of Section 26,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
37.905	<p>The W 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 26.</p> <p>S. 89° 14' 00" W., on the E. and W. centerline of the NW¼ of sec. 26.</p> <p>Ascend steep NE. slope over logged area.</p>
18.85	Spur, slopes SE.; desc. SW. slope, enter timber.
19.340	<p>The NW 1/16 sec. cor. of sec. 26.</p> <p>Descend steep SW. slope.</p>
36.70	Ravine, drains S. 30° E.
37.85	Dirt road, 25 lks. wide, bears N. 30° W. and S. 30° E.
38.690	<p>The N 1/16 sec. cor. of secs. 26 and 27.</p> <hr/> <p align="center">Subdivision of Section 1, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>From the ¼ sec. cor. of secs. 1 and 12.</p> <p>N. 2° 08' 00" E., on the N. and S. centerline of sec. 1.</p> <p>Descend marshy ground.</p>
0.40	Flagler Creek, 23 lks. wide, course N. 20° W.; asc. over rolling bottom land.
19.00	Flagler Creek, 15 lks. wide, course N. 60° E.; asc. marshy creek bottom.
21.370	<p>Point for the center S 1/16 sec. cor. of sec. 1.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} C \\ S\ 1/16 \quad \quad S1 \\ C \\ 1986 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">An alder, 16 ins. diam., bears S. 82° E., 137 lks. dist., mkd. CS 1/16 S1 BT.</p> <p style="margin-left: 40px;">A fir, 26 ins. diam., bears N. 50½° W., 136 lks. dist., mkd. CS 1/16 S1 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend rolling bottom land.
29.05	Andrews Creek, 12 lks. wide, course S. 55° E.; asc. SE. slope.
30.70	County Road No. 71, graveled surface, 35 lks. wide, bears N. 40° E. and S. 40° W.
39.60	Graveled road, 15 lks. wide, bears N. 50° E. and S. 50° W.
42.740	The center ¼ sec. cor. of sec. 1, established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1974, and recorded in County Survey No. M49-60, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Bentz: <p style="margin-left: 40px;">A fir, 10 ins. diam., bears S. 50 3/4° E., 4 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 59 3/4° W., 30½ lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W C¼ S1 1986</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 10' 00" E., beginning new measurement.</p> <p>Ascend SE. slope.</p>
12.00	Top of ascent; desc. NE. slope.
12.40	Creek, 4 lks. wide, course S. 65° E.; asc. SW. slope.
17.60	Slope changes to SE.
21.250	Point for the center N 1/16 sec. cor. of sec. 1. <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S1 C 1986</p> <p>from which</p> <p style="margin-left: 40px;">A fir, 4 ins. diam., bears N. 78½° E., 13 lks. dist., mkd. X BT.</p>

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 12 ins. diam., bears S. 22° W., 48 lks. dist., mkd. CN 1/16 S1 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend broken SE. slope.</p>
42.610	<p>The standard ¼ sec. cor. of sec. 1 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp. S. 86° 03' 00" W., on the E. and W. centerline of sec. 1.</p> <p>Descend broken NW. slope through heavy timber and dense undergrowth.</p>
16.10	<p>County Road No. 71A, asphalt surface, 25 lks. wide, bears N. 40° E. and S. 40° W.</p>
17.05	<p>South shoulder of County Road No. 71, asphalt surface, 35 lks. wide, bears N. 65° E. and S. 85° W.</p>
19.650	<p>The center E 1/16 sec. cor. of sec. 1, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, recorded in County Survey No. M35-11, and is accepted as the corner, monumented with an iron rod, ½ in. diam., firmly set, with top 4 ins. below the surface of the road.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with top 6 ins. below road surface, encased in a 5 in. diam. PVC pipe with an aluminum access cover, set flush with the road surface, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ————— C S1 1986</p> <p>from which</p> <p style="padding-left: 40px;">The mark X on the S. end of bridge abutment, bears S. 78° W., 192 lks. dist.</p> <p style="padding-left: 40px;">The mark X on the N. end of bridge abutment, bears N. 89° W., 182 lks. dist.</p> <p>Deposit the iron rod alongside the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 85° 49' 00" W., beginning new measurement.</p> <p>Along County Road No. 71.</p>
2.60	<p>Billy Creek, 23 lks. wide, course N. 5° E. from S. 35° W.; asc. gentle SE. slope.</p>

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
3.85	North shoulder of County Road No. 71, bears N. 85° E. and S. 65° W., leave road.
14.95	Graveled road, 15 lks. wide, bears N. 60° E. and S. 60° W.
19.690	The center ¼ sec. cor. of sec. 1. <hr style="width: 20%; margin: 0 auto;"/>
	S. 85° 58' 00" W., beginning new measurement. Ascend gentle SE. slope.
4.85	Top of ascent; desc. SW. slope.
6.05	Graveled road, 20 lks. wide, bears N. 55° W. and S. 55° E.
7.40	Ravine, drains S. 35° E.; asc. NE. slope.
8.60	Graveled road, 25 lks. wide, bears N. 20° E. and S. 20° W.
11.40	Top of ascent; also, graveled road, 25 lks. wide, bears N. 40° W. and S. 40° E.; desc. SW. slope.
17.85	Creek, 3 lks. wide, course S. 30° E.; asc. NE. slope.
18.70	Top of ascent; desc. broken SW. slope.
20.730	Point for the center W 1/16 sec. cor. of sec. 1. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ————— C S1 1986 </div> from which <div style="margin-left: 40px;"> A fir, 18 ins. diam., bears N. 31½° E., 52 lks. dist., mkd. CW 1/16 S1 BT. A cedar, 8 ins. diam., bears N. 69½° W., 38 lks. dist., mkd. CW 1/16 S1 BT. </div> Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend broken SW. slope.
33.20	Creek, 10 lks. wide, course S. 5° E.; asc. broken NE. slope.
36.80	Top of ascent; desc. SW. slope.
40.60	Creek, 4 lks. wide, course S. 20° E.; asc. E. slope.
41.460	The ¼ sec. cor. of secs. 1 and 2. <hr style="width: 80%; margin: 0 auto;"/>
	From the E 1/16 sec. cor. of secs. 1 and 12.

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	N. 1° 08' 00" E., on the N. and S. centerline of the SE¼ of sec. 1.
	Ascend SW. slope through heavy timber and dense undergrowth.
6.40	Ridge, bears N. 60° W. and S. 80° E.; desc. NE. slope.
17.45	Ravine, drains N. 80° W.; asc. SW. slope.
20.630	The SE 1/16 sec. cor. of sec. 1, established by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1973, recorded in County Survey No. M48-3, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, from which bearing trees mkd. by Hosford:
	A fir, 14 ins. diam., bears N. 9° E., 12 lks. dist., with healed blaze.
	A fir, 46 ins. diam., bears S. 73 3/4° W., 69 lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.
	SE 1/16 S1 1986
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

	N. 1° 12' 00" E., beginning new measurement.
	Ascend gentle SW. slope.
1.85	Spur, slopes N. 80° W.; desc. broken NW. slope.
17.50	County Road No. 71A, asphalt surface, 35 lks. wide, bears N. 65° W. and S. 65° E.
20.620	The center E 1/16 sec. cor. of sec. 1.

	From the S 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.
	S. 83° 58' 00" W., on the E. and W. centerline of the SE¼ of sec. 1.
	Descend broken NW. slope changing to SW. slope.
20.130	The SE 1/16 sec. cor. of sec. 1.

	S. 83° 47' 00" W., beginning new measurement.
	Descend broken SW. slope.

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
4.00	Ravine, drains N. 55° W.; asc. NE. slope.
6.45	Ridge, bears N. 55° W. and S. 55° E.; desc. W. slope.
10.40	County Road No. 71A, graveled surface, 20 lks. wide, bears N. 20° E. and S. 20° W.
11.10	Flagler Creek, 15 lks. wide, course N. 15° E.; asc. marshy ground.
20.120	The center S 1/16 sec. cor. of sec. 1.
	<hr/>
	From the W 1/16 sec. cor. of secs. 1 and 12.
	N. 1° 36' 00" E., on the N. and S. centerline of the SW¼ of sec. 1.
	Descend NW. slope.
2.00	Ravine, drains N. 80° E.; asc. SE. slope.
19.00	Ridge, bears N. 60° E. and S. 60° W.; desc. broken NW. slope, changing to NE. slope.
22.080	Point for the SW 1/16 sec. cor. of sec. 1, at intersection with the E. and W. centerline of the SW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	SW 1/16 S1 1986
	from which
	A cedar, 20 ins. diam., bears S. 40½° W., 17 lks. dist., mkd. SW 1/16 S1 BT.
	A fir, 12 ins. diam., bears N. 74½° W., 67 lks. dist., mkd. SW 1/16 S1 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Descend broken NE. slope.
37.50	Andrews Creek, 15 lks. wide, course S. 50° E.; asc. SW. slope.
38.60	County Road No. 71, graveled surface, 35 lks. wide, bears E. and W.
44.160	The center W 1/16 sec. cor. of sec. 1.
	<hr/>
	From the center S 1/16 sec. cor. of sec. 1.
	S. 83° 57' 00" W., on the E. and W. centerline of the SW¼ of sec. 1.

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend gentle E. slope through scattering timber and light undergrowth.
18.62	Slope changes to NE.
20.620	The SW 1/16 sec. cor. of sec. 1.
38.30	Spur, slopes N. 50° W.; desc. W. slope.
41.240	The S 1/16 sec. cor. of secs. 1 and 2.
	<hr/>
	From the center W 1/16 sec. cor. of sec. 1.
	N. 1° 36' 00" E., on the N. and S. centerline of the NW¼ of sec. 1.
	Ascend broken SW. slope through young timber and dense undergrowth.
20.05	Dirt road, 15 lks. wide, bears N. 85° W. and S. 85° E.
22.030	The NW 1/16 sec. cor. of sec. 1, established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1974, recorded in County Survey No. M49-60, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above the ground, from which bearing trees mkd. by Bentz:
	A fir, 16 ins. diam., bears N. 19° E., 156 lks. dist., with healed blaze.
	A fir, 16 ins. diam., bears N. 21¼° W., 64 lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron rod, with brass cap mkd.
	NW 1/16 S1 1986
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	<hr/>
	N. 1° 35' 00" E., beginning new measurement.
	Ascend broken SE. slope through young timber.
0.75	Barbed wire fence, bears N. 5° W. and S. 5° E.
1.15	Barbed wire fence, bears N. 50° W. and S. 50° E.
1.45	Spring box, 6 x 4 ft.
1.60	Barbed wire fence, bears N. 70° W. and S. 70° E.
21.95	Barbed wire fence, bears E. and W.

**Subdivision of Section 1,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
22.110	<p>The standard W 1/16 sec. cor. of sec. 1 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 1.</p> <p>S. 88° 05' 00" W., on the E. and W. centerline of the NW¼ of sec. 1.</p> <p>Ascend broken SE. slope through scattering timber and open pasture.</p>
20.880	<p>The NW 1/16 sec. cor. of sec. 1.</p> <hr/> <p>S. 87° 52' 00" W., beginning new measurement.</p> <p>Ascend SE. slope.</p>
4.60	Top of ascent; desc. SW. slope.
12.65	Graveled road, 15 lks. wide, bears N. 30° W. and S. 30° E.
17.65	Creek, 6 lks. wide, course S. 20° E.; asc. SE. slope.
20.880	The N 1/16 sec. cor. of secs. 1 and 2.
	<hr/> <p>Subdivision of Section 25, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/>
	<p>From the ¼ sec. cor. of secs. 25 and 36.</p> <p>N. 4° 52' 00" E., on the N. and S. centerline of sec. 25.</p> <p>Ascend SW. slope through heavy timber and dense undergrowth.</p>
1.10	Spur, slopes S. 75° E.; desc. NE. slope.
6.75	Churchill Canyon, drains S. 85° E.; asc. broken SE. slope.
19.780	<p>Point for the center S 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} C \\ S\ 1/16\ \left \right.\ S25 \\ C \\ 1986 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 28 ins. diam., bears S. 50° E., 61 lks. dist., mkd. CS 1/16 S25 BT.</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears S. 85° W., 4½ lks. dist., mkd. CS 1/16 S25 BT.</p>

**Subdivision of Section 25,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend broken SE. slope.</p>
28.55	Spur, slopes S. 70° E.; desc. NE. slope.
35.35	Ravine, drains SE.; asc. broken SW. slope.
39.560	<p>Point for the center ¼ sec. cor. of sec. 25, at intersection with the E. and W. centerline.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W C¼ S25 1986</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 61° W., 40 lks. dist., mkd. C¼ S25 BT.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 59° W., 45 lks. dist., mkd. C¼ S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the iron post.</p> <p>Ascend broken SW. slope.</p>
45.00	Spur, slopes SE.; desc. NE. slope.
59.295	<p>Point for the center N 1/16 sec. cor. of sec. 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S25 C 1986</p> <p>from which</p> <p style="padding-left: 40px;">A sawed fir stump, 27 ins. diam., bears S. 9½° W., 115 lks. dist., mkd. CN 1/16 S25 BT.</p> <p style="padding-left: 40px;">A sawed fir stump, 52 ins. diam., bears S. 35½° W., 68 lks. dist., mkd. CN 1/16 S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend NE. slope.</p>
61.75	Ravine, drains S. 40° E.; asc. broken SE. slope.

**Subdivision of Section 25,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
55.890	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 26.</p> <hr/> <p>From the center E $\frac{1}{16}$ sec. cor. of sec. 25.</p> <p>N. $2^{\circ} 26' 00''$ E., on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 25.</p> <p>Descend NE. slope through heavy timber and dense undergrowth.</p>
11.60	Creek, 1 lk. wide, course S. 25° E.; asc. broken SE. slope.
12.95	Creek, 1 lk. wide, course S. 60° W.; asc. SE. slope.
15.60	Creek, 1 lk. wide, course S. 25° E.; asc. broken SW. slope.
19.800	<p>The NE $\frac{1}{16}$ sec. cor. of sec. 25, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1961, recorded in County Survey No. M20-46, and is accepted as the corner; monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above ground, from which a bearing tree mkd. by Haines:</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 23° W., 60 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">NE $\frac{1}{16}$ S25 1986</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears S. 55° E., 22 lks. dist., mkd. NE $\frac{1}{16}$ S25 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr/> <p>N. $2^{\circ} 28' 00''$ E., beginning new measurement.</p> <p>Ascend broken SW. slope, changing to SE. slope.</p>
15.15	Dirt road, 20 lks. wide, bears N. 25° W. and S. 15° E.
19.820	<p>The E $\frac{1}{16}$ sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the N $\frac{1}{16}$ sec. cor. of secs. 25 and 30 on the E. bdy. of the Tp.</p> <p>S. $88^{\circ} 12' 00''$ W., on the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 25.</p>

**Subdivision of Section 25,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
20.235	<p>Descend SW. slope through heavy timber and dense undergrowth.</p> <p>The NE 1/16 sec. cor. of sec. 25.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 03' 00" W., beginning new measurement.</p> <p>Descend SW. slope.</p>
2.50	Creek, 2 lks. wide, course S. 30° E.; asc. NE. slope.
10.75	Spur, slopes S. 55° E.; desc. SW. slope.
17.25	Ravine, drains S. 50° E.; asc. NE. slope.
20.190	<p>The center N 1/16 sec. cor. of sec. 25.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 25 and 36.</p> <p>N. 2° 28' 00" E., on the N. and S. centerline of the SE¼ of sec. 25.</p> <p>Ascend broken SW. slope through open pasture.</p>
17.55	Spur, slopes S. 60° E.; desc. broken NE. slope.
19.900	<p>The SE 1/16 sec. cor. of sec. 25, established by Wilford N. Haines, Registered Land Surveyor No. 239, in 1961, recorded in County Survey No. M20-46, and is accepted as the corner; monumented with a 1 in. "T" shaped iron rod, firmly set, projecting 8 ins. above ground, from which bearing trees mkd. by Haines:</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 42° W., 8 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 21° W., 34 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S25 1986</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 25' 00" E., beginning new measurement.</p> <p>Descend broken NE. slope.</p>
4.30	Creek, 5 lks. wide, course N. 65° E.; asc. SE. slope.
13.35	Spur, slopes S. 65° E.; desc. broken NE. slope.

**Subdivision of Section 25,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
19.900	<p>The center E 1/16 sec. cor. of sec. 25.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 88° 59' 00" W., on the E. and W. centerline of the SE¼ of sec. 25.</p> <p>Ascend broken NE. slope through heavy timber and dense undergrowth.</p>
21.835	<p>The SE 1/16 sec. cor. of sec. 25.</p> <hr/> <p>S. 88° 57' 00" W., beginning new measurement.</p> <p>Ascend NE. slope.</p>
5.45	<p>Spur, slopes S. 70° E.; asc. SE. slope.</p>
21.845	<p>The center S 1/16 sec. cor. of sec. 25.</p> <hr/> <p style="text-align: center;">Subdivision of Section 28, T. 23 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p>Note: This section was subdivided by Boyd Peterson in 1987. Prior to approval, corrective work was done on the section lines. In 1994 Philip Griffin resubdivided the section. In many cases he used Peterson's bearing trees. The year the tree was scribed is noted.</p> <p>From the ¼ sec. cor. of secs. 28 and 33.</p> <p>N. 17° 06' 30" W., on the N. and S. centerline of sec. 28.</p> <p>Descend steep NW. slope through heavy timber and light undergrowth.</p>
11.25	<p>Creek, 9 lks. wide, course N. 60° W.; asc. along W. slope.</p>
14.15	<p>Top of ascent; desc. broken NW. slope.</p>
20.295	<p>Point for the center S 1/16 sec. cor. of sec. 28.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} C \\ S\ 1/16 \quad \quad S28 \\ C \\ 1994 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. 87° W., 45½ lks. dist., mkd. CS 1/16 S28 BT, in 1987.</p>

**Subdivision of Section 28,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 25 ins. diam., bears N. 35° W., 28 lks. dist., mkd. CS 1/16 S28 BT, in 1987.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, an iron pipe of which I have no record, 1 in. diam., firmly set, projecting 6 ins. above ground, bears S. 56° 40' 00" W., 0.228 chs. dist.</p>
20.80	Shallow ravine, drains SW.; continue along gradual W. slope.
34.55	Doe Creek, 6 lks. wide, course S.; asc. steep SE. slope.
40.590	<p>Point for the center ¼ sec. cor. of sec. 28, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T23S R6W C¼ S28 1994</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. 61° E., 20 lks. dist., mkd. C¼ S28 BT in 1994.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 53° W., 83 lks. dist., mkd. C¼ S28 BT in 1987.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, an iron pipe of which I have no record, 1 in. diam., firmly set, projecting 14 ins. above ground, bears S. 77° 12' 00" W., 0.307 chs. dist.</p> <p>Ascend steep SE. slope.</p>
49.35	Top of steep ascent, slope changes to W.; thence over gentle ascent.
80.00	Ridge, bears NW. and SE.
80.20	Graveled road, 25 lks. wide, bears N. 40° W. and S. 40° E.
81.230	The ¼ sec. cor. of secs. 21 and 28.
	<hr/> <p>From the ¼ sec. cor. of secs. 27 and 28.</p> <p>N. 88° 43' 00" W., on the E. and W. centerline of sec. 28.</p> <p>Ascend steep E. slope through heavy timber and light undergrowth.</p>
4.60	Ridge, bears N. and S., also dirt road, 10 lks. wide, bears same; desc. broken NW. slope.

**Subdivision of Section 28,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
32.90	Doe Creek, 15 lks. wide, course S. 20° W.; asc. SE. slope.
38.120	The center ¼ sec. cor. of sec. 28.
43.15	Spur, slopes SW.; desc. NW. slope.
57.200	Point for the center W 1/16 sec. cor. of sec. 28. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ————— C S28 1994 </div> from which <div style="margin-left: 40px;"> A fir, 24 ins. diam., bears S. 63° E., 33 lks. dist., mkd. X BT, in 1994. A fir, 33 ins. diam., bears N. 71° W., 41 lks. dist., mkd. CW 1/16 S28 BT, in 1987. </div> Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend broken SW. slope.
75.00	Creek, 18 lks. wide, course S. 80° E.; asc. NE. slope.
76.280	The ¼ sec. cor. of secs. 28 and 29. <hr/> From the center S 1/16 sec. cor. of sec. 28. N. 88° 22' 00" W., on the E. and W. centerline of the SW¼ of sec. 28. Descend broken SW. slope through heavy timber and moderate undergrowth.
0.60	Shallow ravine, drains SW.
11.85	Creek, 3 lks. wide, course S. 45° E. from N. 10° W.; asc. SE. slope.
12.45	Spur, slopes S. 30° W.; desc. W. slope.
13.15	Doe Creek, 3 lks. wide, course S. 10° W.; asc. SE. slope.
24.60	Slope changes to S., over nearly level land.
25.80	Slope changes to SW.; begin descent.
36.40	Creek, 8 lks. wide, course S. 30° E. from N. 45° E.; asc. NE. slope.
36.890	The S 1/16 sec. cor. of secs. 28 and 29. <hr/>

**Subdivision of Section 28,
T. 23 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>From the center W 1/16 sec. cor. of sec. 28.</p> <p>N. 18° 52' 00" W., on the N. and S. centerline of the NW¼ of sec. 28.</p> <p>Ascend broken SW. slope through heavy timber and dense undergrowth.</p>
40.865	<p>The W 1/16 sec. cor. of secs. 21 and 28.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands covered by this survey are located in Douglas County approximately seven miles southwesterly from Yoncalla, Oregon. Access is gained by way of graveled roads along Yellow Creek, County Road No. 71, and other graveled and dirt roads. The area varies from gentle to steep mountainous slopes. The elevation ranges from about 520 feet above sea level to about 2,500 feet above sea level.</p> <p>The area is drained to the southwest by Doe Creek and Yellow Creek and their tributaries, to the southeast by Marsh Creek and its tributaries, and to the northeast by Billy Creek and its tributaries, with numerous other seasonal drainage.</p> <p>The soil consists mainly of a rocky clay with clay loam in the creek bottoms. The timber consists of fir, hemlock, cedar, oak, madrone, maple, chinquapin, yew, ash, and alder. The undergrowth consists of salal, poison oak, arrowwood, hazel, vine maple, blackberry, ferns, huckleberry, salmonberry, thimbleberry, young timber, and Oregon grape.</p> <p>The land is used mainly for timber production. Section 1 has timber production and open pastures for grazing. It also has been subdivided with several residential homes.</p> <p>No mines or mineral deposits were noted.</p> <p>The mean magnetic declination is 19° East as shown on the United States Geological Survey 7½ minute quadrangle map "YONCALLA" and "YELLOW BUTTE, OREGON," provisional edition, published in 1987.</p> <hr/>