

CHAINS

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF PORTIONS OF THE
EAST BOUNDARY AND SUBDIVISIONAL LINES,
AND
THE SUBDIVISION OF SECTION 24,
TOWNSHIP 32 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Francis J. Simon, Cadastral Surveyor

Under Special Instructions dated July 27, 1992, approved July 30, 1992,
which provided for the surveys included under Group No. 1666,
and Assignment Instructions dated August 4, 1992.

Survey commenced August 4, 1992

Survey completed September 23, 1992

T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of portions of the east boundary and subdivisional lines, and the subdivision of section 24, township 32 south, range 6 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

The east boundary and a portion of the subdivisional lines were surveyed by Wells Lake and George Hyde, U.S. Deputy Surveyors, in 1855.

A portion of the subdivisional lines was surveyed by William H. Byars, U.S. Deputy Surveyor, in 1881.

A portion of the subdivisional lines was dependently resurveyed by Rollin D. Aanrud, Cadastral Surveyor, in 1980.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated July 27, 1992, for Group No. 1666, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the quarter section corner of sections 13 and 24, as determined by a tie to control station EC-41161, established by the Geodetic Control Unit of the Oregon State Office of the Bureau of Land Management, is as follows:

Latitude: 42° 47' 00.26" N. Longitude: 123° 21' 23.39" W.

The mean magnetic declination is 18° 30' East.

**Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Wells Lake and George Hyde)

**Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Beginning at the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., perpetuated and recorded by George J. Wenderoth, Registered Land Surveyor No. 5, in 1950, County Surveyor Remonumentation records No. 20 and 39, and County Survey record C.S. 53/58, from evidence no longer in existence, monumented with an iron pipe, 1 in. diam., firmly set 2 ins. below the surface of the ground, from which bearing trees mkd. by Wenderoth:</p> <p style="padding-left: 40px;">A white oak, 23 ins. diam., bears N. 12½° E., 293½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A white oak, 12 ins. diam., bears S. 78¼° W., 90 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., directly over the iron pipe, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32S R6W R5W 1/4 S 24 * S 19 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located 3 lks. N. of the corner of a barbed wire fence, 4 strands, extends E. and S.</p> <p>N. 0° 05' 00" W., bet. secs. 19 and 24, on the E. bdy. of the Tp. Ascend SE. slope, through moderate timber and light undergrowth.</p>
0.30	Dirt road, 15 lks. wide, bears generally E. and W.
20.020	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 24 * S 19 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 9 3/4° E., 70½ lks. dist., mkd. N1/16 S19 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 84 3/4° W., 6½ lks. dist., mkd. N1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend S. slope.</p>
36.20	Saddle in ridge, bears N. 70° E. and S. 70° W.; desc. N. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>no remaining evidence of the original corner; therefore this position is accepted as the best available evidence of the corner; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, from which bearing trees mkd. by Lawrence:</p> <p style="padding-left: 40px;">A black oak, 35 ins. diam., bears N. 50° E., 166 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A black oak, 38 ins. diam., bears S. 71° W., 352 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Wenderoth</p> <p style="padding-left: 40px;">A white oak, 31 ins. diam., bears N. 25¼° E., 189½ lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., directly over the iron pipe, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32S R6W S 24 1/4 ----- S 25 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>S. 89° 33' 00" W., bet. secs. 24 and 25.</p> <p>Ascend E. slope, through open meadow.</p> <p>5.00 Enter heavy timber and light undergrowth, edge bears generally N. and S.</p> <p>20.030 Point for the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 24 W 1/16 ---- S 25 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 54° E., 13 lks. dist., mkd. W1/16 S25 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 37 3/4° W., 68 lks. dist., mkd. W1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend SE. slope.</p>
--------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS 33.10	Top of ascent, slopes S.; desc. slightly along broken S. slope.
40.060	<p>The cor. of secs. 23, 24, 25, and 26, reestablished and recorded by H. W. Lawrence, Registered Engineer No. 1543, in 1951, County Survey record C.S. 40/397, utilized by George J. Wenderoth, Registered Land Surveyor No. 5, in 1963, County Survey record C.S. 53/21, utilized by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1978, County Survey record C.S. 58/125. There is no remaining evidence of the original corner; therefore, this position is accepted as the best available evidence of the original corner, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 6 ins. above the ground, from which the remains of the bearing trees mkd. by Lawrence:</p> <p style="padding-left: 40px;">A ponderosa pine stump, 36 ins. diam., bears N. 56° E., 23½ lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed pine stump, size indeterminate, bears S. 48° E., 6 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A black oak, 15 ins. diam., bears S. 42° W., 23½ lks. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Wenderoth</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 77 3/4° E., 57 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 81¼° W., 77 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., directly over the iron pipe, 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T32S R6W S 23 * S 24 ----- S 26 * S 25 1992</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 19 3/4° E., 15 lks. dist., mkd. T32S R6W S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr/> <p>N. 0° 34' 00" W., bet. secs. 23 and 24.</p> <p>Ascend S. slope, through heavy timber and light undergrowth.</p>
3.00	Cow Creek and Windy Creek divide, bears E. and W.; desc. steep N. slope.
20.355	Point for the S 1/16 sec. cor. of secs. 23 and 24.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 23 * S 24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 33° E., 48 lks. dist., mkd. S1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 81½° W., 29½ lks. dist., mkd. S1/16 S23 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend steep N. slope.</p>
22.30	Ravine, drains N. 20° E.; continue descending NE. slope.
40.710	<p>The 1/4 sec. cor. of secs. 23 and 24, reestablished and recorded by Ronald A. Brandt, Registered Land Surveyor No. 841, in 1978, County Survey record C.S. 58/125, by proportionate measurement. There is no remaining evidence of the original corner; therefore, this position is accepted as the best available evidence of the original corner, monumented with an iron rod, 1 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Brandt:</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 75° E., 53 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 22° W., 32 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T32S R6W 1/4 S 23 * S 24 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, the cor. of secs. 13, 14, 23, and 24, bears N. 0° 30' 30" W., 40.685 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T32S R6W S 14 * S 13 ----- S 23 * S 24 1980</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	<p>from which bearing trees mkd. by George J. Wenderoth, Registered Land Surveyor No. 5, in 1963</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears N. 30° E., 21 lks. dist., with illegible scribe marks visible on partially healed, double blaze.</p> <p style="padding-left: 40px;">An uprooted madrone, 11 ins. diam., bears S. 60° W., 30½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A chinquapin, 14 ins. diam., bears N. 53° W., 20 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>and a bearing tree mkd. by Aanrud</p> <p style="padding-left: 40px;">A madrone, 9 ins. diam., bears S. 29½° E., 43½ lks. dist., with scribe marks T32S R6W S24 BT visible on partially healed blaze. (Record, 45 lks.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A chinquapin, 9 ins. diam., bears S. 32½° W., 67½ lks. dist., mkd. T32S R6W S23 BT.</p> <p>The corner is located 6 lks. south of woven wire fence, extends generally E. and W.</p> <p>From this same point, a point erroneously established and recorded by George J. Wenderoth, Registered Land Surveyor No. 5, in 1963, County Survey record C.S. 53/21, as the ¼ sec. cor. of secs. 23 and 24, bears N. 2° 46' 30" W., 0.878 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 7 ins. above the ground.</p> <hr/> <p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp.</p> <p>N. 89° 32' 00" W., bet. secs. 13 and 24.</p> <p>Descend NW. slope, through heavy timber and dense undergrowth.</p>
19.900	<p>The E 1/16 sec. cor. of secs. 13 and 24, established by person(s) unknown, accepted and recorded by H. W. Lawrence, Registered Engineer No. 1543, in 1957, County Survey records C.S. 42/293 and C.S. 42/294, and is accepted as the corner, monumented with an iron pipe, ½ in. diam., firmly set, projecting 10 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., directly over the iron pipe, 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 13 E 1/16 ----- S 24 1992</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 S., R. 6 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 39¼° E., 26 lks. dist., mkd. E1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 45 3/4° W., 4½ lks. dist., mkd. E1/16 S13 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 43' 00" W., beginning new measurement.</p> <p>Descend NW. slope.</p>
1.20	Natural gas pipeline, extends N. 10°W. and S. 10° E.
19.950	<p>The 1/4 sec. cor. of secs. 13 and 24, perpetuated and recorded by the County Surveyor's Office in 1945 and 1959, County Surveyor Remonumentation records No. 5 and No. 61, from evidence no longer in existence, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S 13 1/4 ----- S 24 T32S R6W 1959</p> <p>from which a bearing tree mkd. by the County Surveyors Office in 1945</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears N. 64° E., 21 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by the County Surveyors Office in 1959</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 52¼° E., 59½ lks. dist., with ax marks visible.</p> <p style="padding-left: 40px;">A cedar, 32 ins. diam., bears S. 61° E., 83 lks. dist., with scribe marks BT visible on partially healed blaze.</p> <p>The corner is located 1.30 chs. East of Windy Creek, 25 lks. wide, course S. 20° W.</p> <p>From this point, Electronic Control Station 41161, at Latitude 42° 46' 57.222" N. and Longitude 123° 21' 32.582" W. (NAD 1927), determined by the Bureau of Land Management, Oregon State Office, Geodetic Control Unit, in 1992, and occupied in 1992, bears S. 65° 51' 05" W., 11.379 chs. dist. (mean bearing and sea level distance), monumented with an aluminum tablet, 2½ ins. diam., firmly set flush with the ground, mkd. EC-41161 1992 and a triangle.</p>

From this same point, the cor. of secs. 13, 14, 23, and 24, bears S. 89° 58' 00" W., 40.830 chs. dist., hereinbefore described.

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 24 and 25. N. 0° 00' 30" E., on the N. and S. centerline of sec. 24. Ascend SE. slope, through heavy timber and dense undergrowth.</p>
20.295	<p>Point for the center S 1/16 sec. cor. of sec. 24. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 * S 24 C 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 17¼° E., 7 lks. dist., mkd. CS1/16 S24 BT.</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 46 3/4° W., 68 lks. dist., mkd. CS1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend SE. slope.</p>
29.90	<p>Cow Creek and Windy Creek divide, bears NE. and SW., slopes NE.; desc. NW. slope.</p>
40.590	<p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T32S R6W C 1/4 S 24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 32½° E., 49 lks. dist., mkd. C1/4 S24 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 11½° E., 26 lks. dist., mkd. C1/4 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Descend NW. slope.</p>
60.30	<p>Ravine, drains N. 20° W.; continue descending NW. slope.</p>
60.845	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p>

Subdivision of Section 24,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 * S 24 C 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 21 ¾° E., 32 lks. dist., mkd. CN1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 18 ¾° W., 50½ lks. dist., mkd. CN1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend NW. slope.</p> <p>81.100 The 1/4 sec. cor. of secs. 13 and 24.</p>
19.965	<p>From the 1/4 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 89° 44' 00" W., on the E. and W. centerline of sec. 24.</p> <p>Ascend E. slope, through scattering timber and light undergrowth.</p> <p>Point for the center E 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ----- C S 24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 42° W., 2½ lks. dist., mkd. CE1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 40° W., 13 lks. dist., mkd. CE1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend E. slope, enter dense undergrowth.</p>
32.60	<p>Cow Creek and Windy Creek divide, bears N. 30° E. and S. 20° W.; desc. steep NW. slope, enter heavy timber.</p>
39.930	<p>The center 1/4 sec. cor. of sec. 24.</p> <p>Descend NW. slope, no topography taken on W½ mile.</p>

Subdivision of Section 24,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
60.165	<p>Point for the center W 1/16 sec. cor. of sec. 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ----- C S 24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 89¼° E., 160 lks. dist., mkd. CW1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 11° E., 112½ lks. dist., mkd. CW1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend NW. slope.</p>
80.400	<p>The 1/4 sec. cor. of secs. 23 and 24.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 24.</p> <p>N. 0° 01' 30" E., on the N. and S. centerline of the NE 1/4 of sec. 24.</p> <p>Ascend broken SE. slope, through scattering timber and dense undergrowth.</p>
20.135	<p>Point for the NE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. centerline of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 54 3/4° E., 99½ lks. dist., mkd NE1/16 S24 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 25¼° W., 57½ lks. dist., mkd. NE1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend broken SE. slope, enter medium timber.</p>
22.80	<p>Cow Creek and Windy Creek divide, bears N. 30° E. and S. 30° W.; also natural gas pipeline; desc. steep NW. slope.</p>
31.60	<p>Natural gas pipeline, bears N. 10° W. and S. 10° E.</p>

Subdivision of Section 24,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
40.315	<p>The E 1/16 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89° 57' 00" W., on the E. and W. centerline of the NE 1/4.</p> <p>Ascend broken SE slope, through heavy timber and dense undergrowth.</p>
19.935	<p>The NE 1/16 sec. cor. of sec. 24.</p> <p>Ascend SE. slope.</p>
21.50	<p>Cow Creek and Windy Creek divide, bears N. 30° E. and S. 30° W.; also natural gas pipeline; desc. steep NW. slope.</p>
39.895	<p>The center N 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 24 and 25.</p> <p>N. 0° 16' 00" W., on the N. and S. centerline of the SW 1/4 of sec. 24.</p> <p>Ascend steep broken SE. slope, through heavy timber and dense undergrowth.</p>
10.50	<p>Cow Creek and Windy Creek divide, bears N. 30° E. and S. 30° W.; desc. broken NW. slope.</p>
20.325	<p>Point for the SW 1/16 sec. cor. of sec. 24, at intersection with the E. and W. centerline of the SW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S24 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 51° W., 56½ lks. dist., mkd. SW1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 28½° W., 32½ lks. dist., mkd. SW1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend steep NW. slope.</p>
40.650	<p>The center W 1/16 sec. cor. of sec. 24.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 24.</p>

Subdivision of Section 24,
T. 32 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	<p>S. 89° 38' 00" W., on the E. and W. centerline of the SW 1/4 of sec. 24.</p> <p>Ascend steep SE. slope, through heavy timber and dense undergrowth.</p> <p>10.60 Cow Creek and Windy Creek divide, bears N. 70° E. and S. 70° W.; desc. NW. slope.</p> <p>20.130 The SW 1/16 sec. cor. of sec. 24.</p> <p>Descend broken NW. slope.</p> <p>40.260 The S 1/16 sec. cor. of secs. 23 and 24.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located approximately four miles northeast of the town of Glendale, Oregon. Access is gained by paved county roads and several dirt roads branching from them. Elevations range from approximately 1,600 feet above sea level where the line between sections 23 and 24 crosses Windy Creek, to approximately 2,600 feet above sea level near the corner of sections 23, 24, 25, and 26.</p> <p>The soil in the area is composed generally of rocky clay. There is a ridge running from the southwest to the northeast of the section, several small drainages to the west of the ridge drain into Windy Creek and several small drainages to the east drain into Cow Creek. The timber in the area consists chiefly of fir, pine, cedar, madrone, white oak, black oak, chinquapin, and alder. The undergrowth consists mainly of manzanita, Oregon grape, salal, poison oak, vine maple, and young timber.</p> <p>There were no mineral deposits or mining activity noted along the lines surveyed. There are several residences located in the northwest one-quarter of the section. There are several springs near the one-quarter corner of sections 24 and 19.</p> <p>The magnetic declination is 18½° East, as taken from the "QUINES CREEK, OREG." quadrangle, 7½ minute series topographic map, 1986 provisional edition.</p>
--------	---