

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH BOUNDARY,
SUBDIVISIONAL LINES, AND THE BOUNDARY OF TRACT 38,

AND

THE SUBDIVISION OF SECTIONS 11 AND 35,

TOWNSHIP 26 SOUTH, RANGE 2 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Dale T. Bedell, Cadastral Surveyor

Bryan S. Seibold, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated March 26, 1992,
approved April 3, 1992,
which provided for the surveys included under Group No. 1638,
and Assignment Instructions dated July 9, 1992.

Survey commenced July 14, 1992

Survey completed April 11, 1995

T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of portions of the south boundary, subdivisional lines, and the boundary of tract 38, and the subdivision of sections 11 and 35, township 26 south, range 2 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1882, Samuel C. Flint, U.S. Deputy Surveyor, surveyed the south boundary.

In 1883, John A. McQuinn, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1909-10, William N. Gibbs, U.S. Deputy Surveyor, made a revision survey of a portion of the subdivisional lines and surveyed a portion of the subdivisional lines. The revision survey was rejected and the field work was corrected by Fred Mensch in 1916.

In 1913, Charles M. Collier, U.S. Surveyor, resurveyed a portion of the south boundary.

In 1916, Fred Mensch, U.S. Surveyor, retraced portions of the south boundary and subdivisional lines and correctively resurveyed portions of the subdivisional lines.

In 1918, Fred Mensch, U.S. Surveyor, made a revision of his 1916 corrective resurvey and surveyed tract 38.

In 1959, Irving Zirpel Jr. and William W. Glenn, Cadastral Surveyors, resurveyed a portion of the subdivisional lines.

In 1968, Lynn M. Roseberry, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1979, Wayne L. Rogers, Cadastral Surveyor, resurveyed the line between sections 1 and 2, T. 27 S., R. 2 W.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 26, 1992, for Group No. 1638, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming a closure were measured twice.

T. 26 S., R. 2 W., Willamette Meridian, Oregon

CHAINS

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of Corner No. 4 of Tract 38, as determined by a tie to triangulation station "SHIVIGNY" established by the National Geological Survey in 1953, is as follows:

Latitude: 43° 15' 52.69" N. Longitude: 122° 54' 02.46" W.

The geographic position (NAD 1927) of the corner of sections 10, 11, 14, and 15, as determined by a tie to Geodetic Control Station EC 41166, established by the Bureau of Land Management in 1992, is as follows:

Latitude: 43° 18' 50.27" N. Longitude: 122° 54' 41.72" W.

The mean magnetic declination is 18° East.

**Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

(Restoring the 1882 survey by Samuel C. Flint and the 1916
retracement by Fred Mensch)

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyors Office corner renewal file No. 40; monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

```

      T26S
    S35 | S36 R
    ----- 2
    S 2 | S 1 W
      T27S
      1967
  
```

from which the remains of the original bearing trees

A fir, 25 ins. diam., bears S. 30° W., 24 lks. dist., with a healed blaze.

A fir stump, 22 ins. diam., bears N. 14° W., 14 lks. dist., with a healed blaze.

and a bearing tree mkd. by Collier in 1913, and reported by Mensch

A fir, 25 ins. diam., bears N. 39½° E., 18 lks. dist., with a decayed blaze.

**Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	and bearing trees mkd. by Tracy
	A fir, 17 ins. diam., bears N. 3½° E., 8 lks. dist., with a healed double blaze.
	A fir, 19 ins. diam., bears S. 84° E., 132 lks. dist., with a healed double blaze.
	A fir, 27 ins. diam., bears S. 13° W., 30 lks. dist., with a healed double blaze.
	No suitable bearing trees available NW. of the corner.
	S. 88° 04' 00" W., bet. secs. 2 and 35.
	Ascend over a gentle SE. slope, through heavy timber and dense undergrowth.
1.40	Spur, slopes S.; desc. over a broken SW. slope.
6.90	Ravine, drains S. 20° E.; asc. over a broken SE. slope.
19.910	The E 1/16 sec. cor. of secs. 2 and 35, established by Ronald G. Geisler, Registered Land Surveyor No. 1988, in 1984, recorded in Douglas County Surveyors Office map file No. M90-55, and is accepted as the corner; monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd.
	S 35 E 1/16 ——— S 2 1984 PLS 1988
	from which bearing trees mkd. by Geisler
	A fir, 8 ins. diam., bears N. 43½° E., 20 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.
	A fir, 5 ins. diam., bears S. 55 3/4° W., 5 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.
	—————
	S. 88° 02' 00" W., beginning new measurement.
	Ascend over a SE. slope.
1.70	Spur, slopes S. 15° E.; desc. over a broken SW. slope.
16.50	Creek, 10 lks. wide, course S. 35° E.; asc. over a broken NE. slope.
19.900	The 1/4 sec. cor. of secs. 2 and 35, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyors Office corner renewal file No. 57, and further perpetuated by Ronald G. Geisler, Registered Land Surveyor No.

**Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS

1988, in 1984, recorded in Douglas County Surveyors Office map file No. M90-55; monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone 4 ft. base, 1 ft. high, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T26S
S 35 R
1/4 ——— 2
S 2 W
T27S
1967

from which the remains of a bearing tree mkd. by Collier and reported by Mensch

A decayed fir snag, 36 ins. diam., bears N. 4° W., 45 lks. dist., with scribe marks 1/4 S35 BT visible on an opened blaze.

and a bearing tree mkd. by Tracy

A fir, 16 ins. diam., bears S. 18° W., 5 lks. dist., with a healed blaze.

and a bearing tree mkd. by Geisler

A fir, 9 ins. diam., bears N. 33 3/4° W., 62 lks. dist., with a healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

(Restoring the 1883 survey by John A. McQuinn, the 1916 corrective resurvey by Fred Mensch and the 1968 resurvey by Lynn M. Roseberry)

From the 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T26S R2W
1/4
S 11 | S 12
1968

from which bearing trees mkd. by Roseberry

A fir, 23 ins. diam., bears S. 64° E., 43 lks. dist., with a healed blaze.

A fir, 23 ins. diam., bears S. 64° W., 19 lks. dist., with a healed blaze.

N. 1° 15' 00" E., bet. secs. 11 and 12.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS																
	Descend over a NW. slope, through scattering timber and dense undergrowth.															
11.20	Creek, 2 lks. wide, course S. 65° W.; asc. over a SW. slope.															
19.45	Spur, slopes W.; desc. over a NW. slope.															
20.345	Point for the N 1/16 sec. cor. of secs. 11 and 12. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td></td><td>N 1/16</td><td></td></tr> <tr><td>S 11</td><td> </td><td>S 12</td></tr> <tr><td></td><td>1992</td><td></td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears N. 69° E., 22 lks. dist., mkd. N 1/16 S 12 BT.</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 44° W., 18 lks. dist., mkd. N 1/16 S 11 BT.</p>		N 1/16		S 11		S 12		1992							
	N 1/16															
S 11		S 12														
	1992															
	Descend over a broken NW slope.															
30.75	Creek, 3 lks. wide, course N. 65° W.; asc. over a SW. slope.															
37.40	Spur, slopes SW.; desc. over a NW. slope.															
40.690	The cor. of secs. 1, 2, 11, and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T26S</td><td></td><td>R2W</td></tr> <tr><td>S 2</td><td> </td><td>S 1</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S 11</td><td> </td><td>S 12</td></tr> <tr><td></td><td>1968</td><td></td></tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 52 ins. diam., bears N. 58° E., 83 lks. dist., with fragmentary bark scribe marks visible.</p> <p style="margin-left: 40px;">A fir snag, 48 ins. diam., bears S. 65½° E., 44 lks. dist., with fragmentary bark scribe marks visible.</p> <p>and the remains of bearing trees mkd. by G. R. Lecklider, Registered Engineer No. 4079, in 1959, recorded in Douglas County Surveyors Office map file No. M11-31, reported by Roseberry</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 47° E., 13½ lks. dist., with bark scribe marks S1 R 4079 visible and a healed blaze.</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears S. 18½° E., 9 lks. dist., with healed double blaze.</p>	T26S		R2W	S 2		S 1				S 11		S 12		1968	
T26S		R2W														
S 2		S 1														
S 11		S 12														
	1968															

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS									
	<p>A fir, 11 ins. diam., bears S. $56\frac{1}{2}^{\circ}$ W., 15$\frac{1}{2}$ lks. dist., with healed double blaze.</p> <p>A fir, 9 ins. diam., bears N. $30\frac{1}{4}^{\circ}$ W., 25 lks. dist., with healed double blaze.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36,, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 10px;">T26S</td> <td style="border-left: 1px solid black; padding: 0 10px;">R2W</td> </tr> <tr> <td style="padding: 0 10px;">S 26</td> <td style="border-left: 1px solid black; padding: 0 10px;">S 25</td> </tr> <tr> <td style="border-top: 1px solid black; padding: 0 10px;">S 35</td> <td style="border-left: 1px solid black; border-top: 1px solid black; padding: 0 10px;">S 36</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1916</td> </tr> </table> </div> <p>from which the remains of a bearing tree mkd. by Mensch in 1916</p> <p>A madrone stump, 22 ins. diam., bears N. 55° W., 38 lks. dist., with fragmentary reverse scribe marks visible through a hollow center.</p> <p>and bearing trees mkd. by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyors Office corner renewal file No. 50</p> <p>A maple, 10 ins. diam., bears N. 72° E., 41 lks. dist., with fragmentary scribe marks on a partially healed blaze.</p> <p>A fir, 19 ins. diam., bears S. 30° E., 25 lks. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 66° W., 38 lks. dist., with a healed blaze.</p> <p>No suitable bearing trees available in NW. quadrant.</p> <p>N. $89^{\circ} 50' 00''$ W., bet. secs. 26 and 35.</p> <p>Descend over a steep broken SW. slope, along the southerly edge of a clear-cut logging area.</p> <p>6.80 Creek, 10 lks. wide, course S. 10° E.; asc. over a steep broken SE. slope.</p> <p>14.80 Abandoned dirt road, 20 lks. wide, bears N. and S.; enter heavy timber and dense undergrowth.</p> <p>30.80 Begin descent over a broken SW. slope.</p> <p>33.280 Cor. No. 1 of Tract 38, hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 35' 30''$ W., beginning new measurement.</p> <p>Descend over a broken SW. slope.</p> <p>6.710 Point for the 1/4 sec. cor. of sec. 35 only.</p>	T26S	R2W	S 26	S 25	S 35	S 36	1916	
T26S	R2W								
S 26	S 25								
S 35	S 36								
1916									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26S R2W ----- 1/4 S 35 1992</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears S. 37 3/4° E., 53 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 49½° W., 51 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over a SW. slope.</p>
6.915	<p>The 1/4 sec. cor. of sec. 26 only, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyor's Office corner renewal file No. 51, and utilized by Thomas E. Shrum, Jr., Registered Land Surveyor No. 1706, in 1981, recorded in Douglas County Surveyor's Office map file M89-28; monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 26 ----- 1916</p> <p>from which the remains of bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A madrone root crown, size indeterminate, bears N. 56° E., 24 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A cedar, 56 ins. diam., bears N. 42° W., 23 lks. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 52° E., 65 lks. dist., with scribe marks 1/4 S26 CS BT visible on a partially healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears N. 55° W., 58 lks. dist., with a healed double blaze.</p> <p style="text-align: center;">-----</p> <p>N. 89° 57' 00" W., beginning new measurement.</p> <p>Descend over a broken SW. slope.</p>
20.10	<p>Spur, slopes S.; desc. over a broken SW. slope.</p>
29.70	<p>Ravine, drains S. 30° E.; asc. over a steep SE. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS

and a bearing tree mkd. by Tracy

The northerly trunk of a double hemlock, 14 ins. diam., bears
N. 70° E., 33 lks. dist., with a healed blaze.

The corner is located on a steep SW. slope.

From the 1/4 sec. cor. of secs. 10 and 11, reestablished at proportionate distance by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in Douglas County Surveyors Office map file No. M38-25, and is accepted as the best available evidence of the position of the original corner; monumented with an iron pipe, 1/2 in. diam., firmly set flush with the ground, from which bearing trees mkd. by Rogers:

A fir, 11 ins. diam., bears N. 87 3/4° E., 23 lks. dist.,
with healed double blaze.

A fir, 21 ins. diam., bears N. 41 3/4° W., 28 lks. dist.,
with healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T26S R2W
 1/4
S 10 | S 11
 1993

Deposit a white "DEEP-1" magnetic marker at base and iron pipe inside of stainless steel post.

From this point, a point reestablished as the 1/4 sec. cor. of secs. 10 and 11 by G. R. Lecklider, Registered Engineer No. 4079, in 1959, recorded in Douglas County Surveyors Office map file No. M16-68, bears S. 7° 37' 30" E., 0.299 chs. dist.; monumented with an iron post, 1/2 in. diam., firmly set, projecting 4 inches above ground, with aluminum cap mkd. Property Corner, from which the bearing trees mkd. by Lecklider:

A fir, 21 ins. diam., bears N. 47 1/4° E., 23 lks. dist., with
healed blaze.

A fir, 17 ins. diam., bears N. 59° W., 20 lks. dist., with
healed blaze.

This point is not properly positioned and is not utilized in this survey.

From this same point, the cor. of secs. 10, 11, 14, and 15, bears S. 0° 18' 00" W., 40.155 chs. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS

T26S		R2W
S 10		S 11
S 15		S 14
1959		

from which the remains of the original bearing trees

A roothole, bears N. $63\frac{1}{2}^{\circ}$ E., 53 lks. dist., with uprooted fir alongside, 30 ins. diam., no marks visible.

A sawed fir stump, 36 ins. diam., bears S. $22\frac{3}{4}^{\circ}$ E., 99 lks. dist., no marks visible.

A sawed fir stump, 30 ins. diam., bears S. $27\frac{1}{4}^{\circ}$ W., 56 lks. dist., with fragmentary bark scribing visible.

A fir, 36 ins. diam., bears N. $40\frac{3}{4}^{\circ}$ W., 16 lks. dist., with scribe marks T26S R2W C BT visible.

and the remains of bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file No. 29

A madrone stump, 8 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ E., 74 lks. dist., with reverse scribe marks BT visible. (Record, N. 73° E.)

A sawed maple stump, 5 ins. diam., bears S. $85\frac{3}{4}^{\circ}$ E., 45 lks. dist., with decayed maple alongside, with scribe marks BT visible on opened blaze. (Record, S. 86° E.)

A fir, 12 ins. diam., bears S. $79\frac{3}{4}^{\circ}$ W., 184 lks. dist., with healed double blaze. (Record, $184\frac{1}{2}$ lks.)

and new bearing trees

A fir, 7 ins. diam., bears N. 55° E., 36 lks. dist., mkd. T26S R2W S11 BT.

A fir, 10 ins. diam., bears S. 52° E., 47 lks. dist., mkd. T26S R2W S14 BT.

From the section corner, the Bureau of Land Management, Geodetic Control Station No. EC 41166, at latitude $43^{\circ} 18' 50.0488''$ N., longitude $122^{\circ} 54' 39.1635''$ W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. $83^{\circ} 07' 48''$ E., 2.883 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap, $3\frac{1}{4}$ ins. diam., set in concrete in bedrock, with cap mkd. EC41166 GPS 1992 and a triangle.

N. $0^{\circ} 08' 00''$ E., bet. secs. 10 and 11.

Ascend over a SW. slope, through second growth timber and dense undergrowth.

9.25

Spur, slopes S. 50° E.; asc. over a SE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
20.080	<p>The N 1/16 sec. cor. of secs. 10 and 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyors Office map file No. M38-25, and is accepted as the corner; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Rogers:</p> <p style="padding-left: 40px;">A roothole, bears N. 29° E., 44 lks. dist.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 34 3/4° W., 23 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S 10 S 11</p> <p>1993</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 55° E., 73 lks. dist., mkd. N 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base and iron rod inside of stainless steel post.</p> <p>From this point, a point established as the N 1/16 sec. cor. of secs. 10 and 11, by G. R. Lecklider, Registered Engineer No. 4079, in 1959, recorded in the Douglas County Surveyors Office Map File No. M16-68, bears S. 7° 36' 00" E., 0.149 chs. dist., monumented with an iron pipe, ½ in. diam., firmly set, projecting 8 ins. above ground, with an aluminum cap mkd. Property Corner, from which the remains of bearing trees mkd. by Lecklider:</p> <p style="padding-left: 40px;">A pine, 38 ins. diam., bears N. 45½° E., 44 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 17 ins. diam., bears S. 83½° W., 45 lks. dist., with fragmentary scribe marks visible on open upper blaze and healed lower blaze.</p> <p>This point is not properly positioned and is not utilized in this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 22' 30" E., beginning new measurement.</p> <p>Ascend over a SE. slope.</p>
20.075	<p>The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, and in a collar of stone, 3 feet diam., with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Fd ok by T26S R2W Ed Monrean S 3 S 2 4/2004 C.S. 65/49-35 S 10 S 11 1959</p>
	<p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, 63 ins. diam., bears N. 35½° E., 79 lks. dist., with fragmentary scribe marks visible on open blaze. (Record, N. 35° E.)</p> <p>and the remains of bearing trees mkd. by Ben B. Irving, Deputy County Surveyor, in 1927, recorded in the Douglas County Surveyors Office corner renewal No. 5</p> <p>A sawed fir stump, 40 ins. diam., bears N. 78½° E., 96 lks. dist., with partially healed blaze.</p> <p>A fir snag, 47 ins. diam., bears S. 66½° E., 100 lks. dist., with healed blaze.</p> <p>A decayed sawed fir stump, size undeterminate, bears S. 62½° W., 36 lks. dist., with healed blaze.</p> <p>A decayed snag, size undeterminate, bears N. 9½° W., 102 lks. dist., with no marks visible.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p>A fir, 22 ins. diam., bears N. 55¼° E., 44½ lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 7 ins. diam., bears S. 10½° E., 30 lks. dist., mkd. T26S R2W S11 BT.</p> <p>A fir, 12 ins. diam., bears S. 49½° W., 81½ lks. dist., mkd. T26S R2W S10 BT.</p> <p>A fir, 8 ins. diam., bears N. 59 3/4° W., 56½ lks. dist., mkd. T26S R2W S3 BT.</p>
	<hr/> <p>From the sec. cor. of secs. 1, 2, 11, and 12.</p> <p>S. 89° 34' 30" W., bet. secs. 2 and 11.</p> <p>Descend over a steep broken NW. slope, through heavy timber and dense undergrowth.</p>
10.40	Susan Creek, 15 lks. wide, course S. 20° W.; asc. over a SE. slope.
19.600	Point for the E 1/16 sec. cor. of secs. 2 and 11.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	S 2 E 1/16 <u> </u> S 11 1993
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 31° E., 25 lks. dist., mkd. E 1/16 S2 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 48° W., 4 lks. dist., mkd. E 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over a steep SE. slope.</p>
39.200	<p>The 1/4 sec. cor. of secs. 2 and 11, reestablished at proportionate distance by G. R. Lecklider, Registered Engineer No. 4079, in 1959, recorded in the Douglas County Surveyors Office map file No. M11-31, and is accepted as the best available evidence of the position of the original corner; monumented with a steering column, 3/4 in. diam., firmly set flush with the ground, from which bearing trees mkd. by Lecklider:</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 53½° E., 7 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears N. 45½° W., 29 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> T26S R2W S 2 1/4 <u> </u> S 11 1992 </p> <p>Deposit steering column inside of stainless steel post.</p> <p style="text-align: center;">_____</p> <p>S. 89° 38' 00" W., beginning new measurement.</p> <p>Ascend over a broken SE. slope.</p>
5.35	<p>Creek, 5 lks. wide, course S. 30° E.; continue to asc. over a broken SE. slope.</p>
19.600	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>The corner point is occupied by a fir, 24 ins. diam., which we mkd. W 1/16 S2 on the north face and W 1/16 S11 on the south face, from which</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS													
	<p>A cedar, 8 ins. diam., bears N. 27¼° E., 22½ lks. dist., mkd. W 1/16 S2 BT.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° E., 15 lks. dist., with brass cap mkd. RM W1/16 S11 15 LKS 1995 and an arrow pointing to the corner.</p> <p>The corner is located on a spur, slopes S. 25° E.</p> <p>Ascend over a broken SE. slope.</p>												
35.15	Dirt road, 20 lks. wide, bears S. 50° E. and N. 60° W.												
39.200	The cor. of secs. 2, 3, 10, and 11.												
<hr/> <p>Dependent Resurvey of the Boundary of Tract 38, T. 26 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>													
<p>(Restoring the 1918 survey by Fred Mensch)</p> <hr/>													
<p>From Cor. No. 1 of Tract 38, on line bet. secs. 26 and 35, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyor's Office corner renewal file No. 53; monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p>													
<table border="0"> <tr> <td colspan="2">T26S R2W</td> </tr> <tr> <td colspan="2">S 26</td> </tr> <tr> <td colspan="2"><hr/></td> </tr> <tr> <td style="text-align: center;">1</td> <td style="text-align: center;"> S 35</td> </tr> <tr> <td>TR 38</td> <td></td> </tr> <tr> <td>1918</td> <td></td> </tr> </table>		T26S R2W		S 26		<hr/>		1	S 35	TR 38		1918	
T26S R2W													
S 26													
<hr/>													
1	S 35												
TR 38													
1918													
<p>from which the original bearing tree</p> <p>A fir, 55 ins. diam., bears S. 60° W., 6 lks. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Tracy</p> <p>A fir, 20 ins. diam., bears S. 52° E., 67 lks. dist., with a healed double blaze.</p> <p>S. 89° 35' 30" W., on line 1-2 of Tract 38, identical with the line bet. secs. 26 and 35.</p> <p>Descend over a broken SW. slope, through heavy timber and dense undergrowth.</p>													
6.710	The 1/4 sec. cor. of sec. 35 only, hereinbefore described.												
6.915	The 1/4 sec. cor. of sec. 26 only, hereinbefore described.												
<hr/>													
<p>N. 89° 57' 00" W., beginning new measurement.</p>													

**Dependent Resurvey of the Boundary of Tract 38,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	Descend over a broken SW. slope.
20.10	Spur, slopes S.; desc. over a broken SW. slope.
29.70	Ravine, drains S. 30° E.; asc. over a steep SE. slope.
33.120	Corner No. 2 of Tract 38, identical with the cor. of secs. 34 and 35, hereinbefore described.
	<hr/>
	S. 0° 49' 30" W., on line 2-3 of Tract 38, identical with the line bet. secs. 34 and 35.
	Descend over a broken SE. slope, through heavy timber and dense undergrowth.
10.70	Creek, 2 lks. wide, course S. 80° E.; asc. over a broken NE. slope.
19.400	The 1/4 sec. cor. of secs. 34 and 35, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyor's Office corner renewal file No. 65, and utilized by Thomas E. Shrum, Jr., Registered Land Surveyor No. 1706, in 1979, recorded in Douglas County Surveyor's Office map file M76-56; monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \text{ S } 34 \quad \quad \text{S } 35 \\ \quad \quad \quad 1916 \end{array}$
	from which a bearing tree mkd. by Tracy
	A hemlock, 24 ins. diam., bears S. 26° E., 168 lks. dist., with scribe marks S35 CS BT visible on a partially healed blaze.
	and a new bearing tree
	A cedar, 4 ins. diam., bears N. 16¼° W., 38 lks. dist., mkd. X BT.
	<hr/>
	S. 0° 49' 30" W., beginning new measurement.
	Ascend over a broken NE. slope, through a partially logged area.
0.190	Corner No. 3 of Tract 38, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyor's Office corner renewal file No. 66; monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.
	$\begin{array}{c} \text{T26S} \quad 3 \\ \quad \quad \\ \quad \quad \text{TR } 38 \\ \quad \quad \\ \text{S } 34 \quad \\ \text{R2W} \quad \quad \text{S } 35 \\ \quad \quad 1918 \end{array}$
	from which a bearing tree mkd. by Tracy

**Dependent Resurvey of the Boundary of Tract 38,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS									
	<p style="text-align: center;">A cedar, 18 ins. diam., bears N. 74° E., 145 lks. dist., with a healed blaze.</p> <p>No suitable trees available within limits.</p> <hr/> <p>S. 89° 24' 30" E., on line 3-4 of Tract 38.</p> <p>Descend over a broken NE. slope, through scattering timber and dense undergrowth.</p>								
15.00	<p>Creek, 5 lks. wide, course SE.; asc. over a broken SW. slope, changing to a broken S. slope.</p>								
35.725	<p>Point for the crossing closing cor. on the N. and S. center line of sec. 35, hereinafter described.</p> <p>Cross a gentle S. slope.</p>								
40.200	<p>Corner No. 4 of Tract 38, perpetuated by Vernon Ray Tracy, Deputy County Surveyor, in 1967, recorded in Douglas County Surveyor's Office corner renewal file No. 54; monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">TR 38</td> <td style="padding: 0 5px;">T26S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">4</td> <td style="padding: 0 5px;">R2W</td> </tr> <tr> <td colspan="2" style="padding: 5px 0 0 20px;">S 35</td> </tr> <tr> <td colspan="2" style="padding: 0 0 0 20px;">1918</td> </tr> </table> </div> <p>from which the original bearing tree</p> <p style="text-align: center;">A cedar, 17 ins. diam., bears N. 8° W., 31 lks. dist., with scribe marks TR 38 visible on a partially healed blaze.</p> <p>and bearing tree mkd. by Tracy</p> <p style="text-align: center;">A cedar, 19 ins. diam., bears N. 26° W., 79 lks. dist., with scribe marks TR38 CS BT visible on a partially healed blaze.</p> <p>and a new bearing tree</p> <p style="text-align: center;">A fir, 9 ins. diam., bears S. 10° W., 20 lks. dist., mkd. S35 BT.</p> <p>The corner is located on a gentle S. slope 50 lks. W. of a graveled road 30 lks. wide, bears N. 20° E. and S. 20° W.</p> <p>From this corner, National Geological Survey triangulation station "SHIVIGNY", 1953, bears N. 66° 23' 30" W., 81.860 chs. (mean bearing and sea level dist.); monumented with a brass disk, 3 ins. diam., set in a concrete post, 10 ins. square, projecting 4 ins. above the ground, mkd. NATIONAL GEOLOGICAL SURVEY SHIVIGNY 1953 1977 and a triangle.</p> <hr/> <p>N. 0° 19' 00" E., on line 4-1 of Tract 38.</p>	TR 38	T26S	4	R2W	S 35		1918	
TR 38	T26S								
4	R2W								
S 35									
1918									

**Dependent Resurvey of the Boundary of Tract 38,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over a broken S. slope, through heavy timber and dense undergrowth.
10.90	Spur, slopes S. 60° W.; asc. over a broken SW. slope.
20.040	Cor. No. 1 of Tract 38.
<hr/> <p>Subdivision of Section 11, T. 26 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>	
	From the 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 2½ ins. diam., firmly set in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.
	T26S R2W S 11 1/4 ——— S 14 1968
	from which bearing trees mkd. by Roseberry
	A madrone, 11 ins. diam., bears N. 25° E., 80 lks. dist., with healed blaze.
	A fir, 36 ins. diam., bears S. 31½° W., 43 lks. dist., with healed blaze.
	N. 0° 37' 00" E., on the N. and S. centerline of sec. 11.
	Descend over a NW. slope, through second growth timber and dense undergrowth.
19.95	Dry creekbed, 5 lks. wide, drains SW.; continue descending over a NW. slope.
20.190	The center S 1/16 sec. cor. of sec. 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyors Office map file No. M38-25, and is accepted as the corner; monumented with an iron rod, 1 in. diam., firmly set, projecting 30 ins. above mound of stone, 3 ft. base, 1½ ft. high, from which bearing trees mkd. by Rogers:
	A fir, 28 ins. diam., bears N. 28½° E., 17 lks. dist., with healed blaze.
	A maple, 15 ins. diam., bears S. 9° W., 19½ lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

**Subdivision of Section 11,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	C S 1/16 S 11 C 1992
	Deposit iron rod alongside stainless steel post.

	N. 0° 51' 00" E., beginning new measurement.
	Descend over a broken NW. slope.
20.220	<p>The center 1/4 sec. cor. of sec. 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyors Office map file No. M38-25, and is accepted as the corner; monumented with an iron rod, 1 in. diam., firmly set, projecting 18 ins. above ground, from which bearing trees mkd. by Rogers:</p> <p style="padding-left: 40px;">An alder, 12 ins. diam., bears S. 31½° E., 25 lks. dist., with decayed blaze.</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears N. 5¼° W., 63½ lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26S R2W C 1/4 S 11 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base and iron rod inside of stainless steel post.</p> <p style="text-align: center;">_____</p> <p>N. 0° 41' 00" E., beginning new measurement.</p> <p>Descend over a NW. slope.</p>
0.50	Susan Creek, 20 lks. wide, course S. 20° W.; asc. over SE. slope.
6.70	Dirt road, 25 lks. wide, bears NE. and S. 50° W.
20.225	<p>The center N 1/16 sec. cor. of sec. 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyors Office Map File No. M38-25, and is accepted as the corner; monumented with an iron rod, 1 in. diam., firmly set, projecting 20 ins. above ground, from which bearing trees mkd. by Rogers:</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 74° E., 34 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears S. 23° E., 14½ lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p>

**Subdivision of Section 11,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N \ 1/16 \quad \quad S \ 11 \\ C \\ 1992 \end{array}$ </div> <p>Deposit a white "DEEP-1" magnetic marker at base and iron rod inside of stainless steel post.</p> <hr/> <p>N. 0° 51' 00" E., beginning new measurement.</p> <p>Ascend over a SE. slope.</p> <p>1.60 Spur, slopes N. 80° E.; desc. over a NE. slope.</p> <p>8.70 Ravine, drains SE.; asc. over a SE. slope.</p> <p>11.30 Dirt road, 25 lks. wide, bears S. 75° E. and S. 80° W.</p> <p>20.170 The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>S. 89° 56' 00" W., on the E. and W. centerline of sec. 11.</p> <p>Descend over a broken SW. slope, through second growth timber and dense undergrowth.</p> <p>19.380 The center E 1/16 sec. cor. of sec. 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyor's Office map file No. M38-25, and is accepted as the corner, determined at recorded distance from bearing trees mkd. by Rogers:</p> <div style="margin-left: 40px;"> <p>A fir, 19 ins. diam., bears N. 73 3/4° E., 49 lks. dist., with healed double blaze.</p> <p>A maple, 11 ins. diam., bears S. 15½° E., 17 lks. dist., with healed double blaze.</p> </div> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} E \ 1/16 \\ C \ \text{-----} \ C \\ S \ 11 \\ 1993 \end{array}$ </div> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>

**Subdivision of Section 11,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	

	N. 89° 54' 00" W., beginning new measurement.
	Descend over a broken SW. changing to a broken NW. slope.
19.480	The center 1/4 sec. cor. of sec. 11.

	S. 89° 58' 00" W., beginning new measurement.
	Descend over a broken NW. slope.
0.75	Susan Creek, 20 lks. wide, course S. 15° W.; asc. over a SE. slope.
4.50	Dirt road, 20 lks. wide, bears S. 20° E. and N. 20° E.
19.355	The center W 1/16 sec. cor. of sec. 11, established by Bruce R. Rogers, Registered Land Surveyor No. 660, in 1969, recorded in the Douglas County Surveyor's Office map file No. M38-25, and is accepted as the corner; monumented with an iron rod, ½ in. diam., firmly set, projecting 14 ins. above ground, from which bearing trees mkd. by Rogers:
	A fir, 19 ins. diam., bears S. 45° W., 39 lks. dist., with healed blaze. The blaze is facing east.
	A fir, 30 ins. diam., bears N. 1° W., 59 lks. dist., with healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	W 1/16 C ————— C S 11 1993
	Deposit a white "DEEP-1" magnetic marker at base and iron rod inside of stainless steel post.

	S. 89° 59' 00" W., beginning new measurement.
	Ascend over a broken SE. slope.
16.10	Spur, slopes S. 10° E.; desc. over a SW. slope.
19.460	The 1/4 sec. cor. of secs. 10 and 11.

	From the center E 1/16 sec. cor. of sec. 11 and 12.
	N. 0° 55' 30" E., on the N. and S. centerline of the NE. 1/4 of sec. 11.

**Subdivision of Section 11,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over a SW. slope, through second growth timber and dense undergrowth.
9.55	Spur, slopes N. 60° W.; desc. over a broken NW. slope.
20.320	Point for the NE. 1/16 sec. cor. of sec. 11, at intersection with the E. and W. centerline of the NE¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	NE 1/16 S11 1993
	from which
	A fir, 22 ins. diam., bears N. 67° E., 29 lks. dist., mkd. NE 1/16 S11 BT.
	A fir, 11 ins. diam., bears S. 63° E., 31½ lks. dist., mkd. NE 1/16 S11 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over a NW. slope.
21.30	Susan Creek, 25 lks. wide, course S. 40° W.; asc. over a SE. slope.
40.570	The E 1/16 sec. cor. of secs. 2 and 11.

	From the N 1/16 sec. cor. of secs. 11 and 12.
	S. 89° 50' 00" W., on the E. and W. centerline of the NE 1/4 sec. 11.
	Descend over a broken NW. slope, through scattering timber and dense undergrowth.
19.490	The NE 1/16 sec. cor. of sec. 11.
	Descend over a broken NW. slope.
20.00	Susan Creek, 25 lks. wide, course S. 10° W.; asc. over a SE. slope.
29.00	Dirt road, 20 lks. wide, bears N. and S.
39.060	The center N 1/16 sec. cor. of sec. 11.

	S. 89° 46' 30" W., on the E. and W. centerline of the NW 1/4 of sec. 11.

**Subdivision of Section 11,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
	Ascend over a broken SE. slope, through second growth timber and dense undergrowth.
3.05	Dirt road, 20 lks. wide, bears N. 80° E. and N. 65° W.
4.45	Spur, slopes S. 30° E.; desc. over a SW. slope.
5.10	Dirt road, 20 lks. wide, bears S. 75° E. and N. 45° W.
18.25	Creek, 2 lks. wide, course S. 25° E.; asc. over a SE. slope.
39.020	The N. 1/16 sec. cor. of secs. 10 and 11.
<hr/> <p style="text-align: center;">Subdivision of Section 35, T. 26 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>	
	From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.
	N. 6° 05' 00" W., on the N. and S. centerline of sec. 35.
	Descend over a steep broken NE. slope, through heavy timber and dense undergrowth.
8.50	Creek, 10 lks. wide, course S. 40° E.; asc. over a broken SW. slope.
38.890	Point for a crossing closing cor. at the intersection with line 3-4 of Tract 38.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<pre> CCC C TR 38 --- --- S 35 C 1992 </pre>
	from which
	A fir, 15 ins. diam., bears S. 23° E., 34½ lks. dist., mkd. S35 CCC BT.
	A fir, 9 ins. diam., bears S. 47° W., 26 lks. dist., mkd. S35 CCC BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	From this corner, Cor. No. 4 of Tract 38 bears S. 89° 24' 30" E., 4.475 chs. distance.
	Ascend over a broken SW. slope.

**Subdivision of Section 35,
T. 26 S., R. 2 W., Willamette Meridian, Oregon**

CHAINS	
58.950	<p>The 1/4 sec. cor. of sec. 35 only.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in Douglas County approximately 12 miles easterly of the town of Glide, Oregon.</p> <p>The terrain is mountainous, the elevations range from about 1600 feet above sea level at the corner of sections 10, 11, 14, and 15, to approximately 2800 feet above sea level at the 1/4 section corner of section 35 only. Section 11 is drained by Susan Creek flowing southerly with numerous small and seasonal creeks flowing into it. Section 35 is drained by Emile Creek flowing southerly with numerous small and seasonal creeks flowing into it.</p> <p>The soil is made up of a rocky clay. The lands are forested with fir, cedar, hemlock, pine, yew, alder, cherry, maple, oak, madrone, willow, ash and chinquapin; with undergrowth of ferns, poison oak, arrowwood, hazel, Oregon grape, salal, huckleberry, blackberry, thimbleberry, salmonberry, gooseberry, currant, wild rose, rhododendron, manzanita and young timber.</p> <p>Access is via State Highway No. 138 and County Road No. 17, with several graveled and dirt roads branching from them into the area surveyed.</p> <p>No evidence of mineral deposits were noted along the lines surveyed. The principle uses are timber production and recreation.</p> <p>The mean magnetic declination is 18° East, with a range of 1° due to local attraction.</p> <hr/>