

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

CORRECTIVE DEPENDENT RESURVEY OF THE EAST HALF OF THE LINE
BETWEEN SECTIONS 7 AND 18, DEPENDENT RESURVEY OF PORTIONS OF
THE SOUTH AND WEST BOUNDARIES AND SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 6, 7, 11 AND 31,

TOWNSHIP 29 SOUTH, RANGE 4 WEST,

OF THE

WILLAMETTE MERIDIAN

IN THE STATE OF OREGON.

EXECUTED BY

Wayne L. Rogers, Cadastral Surveyor

Dale T. Bedell, Cadastral Surveyor

Bryan S. Seibold, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated August 7, 1991,
and approved August 7, 1991,
and Supplemental Special Instructions dated March 16, 1992,
and approved March 18, 1992,
which provided for the surveys included under Group No. 1625,
and Assignment Instructions dated August 22, 1991,
December 16, 1991, and March 25, 1992.

Survey commenced September 24, 1991

Survey completed April 13, 1993

T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the corrective dependent resurvey of the east half of the line between sections 7 and 18, the dependent resurvey of portions of the south and west boundaries and subdivisional lines, and the subdivision of sections 6, 7, 11 and 31, township 29 south, range 4 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

In 1851, James E. Freeman, U. S. Deputy Surveyor, surveyed the west boundary of the township.

In 1854, Nathaniel Ford, U. S. Deputy Surveyor, surveyed the remaining boundaries and a portion of the subdivisional lines.

In 1857, Dennis Hathorn, U. S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1857, Dennis Hathorn, U. S. Deputy Surveyor, surveyed Donation Land Claim No. 41.

In 1881, William H. Byars, U. S. Deputy Surveyor, resurveyed the north boundary and surveyed or resurveyed portions of the subdivisional lines.

In 1889, William Theil, U. S. Deputy Surveyor, resurveyed the north boundary of T. 30 S., R. 4 W.

In 1899, William F. Briggs, U. S. Deputy Surveyor, surveyed or resurveyed portions of the west boundary, subdivisional lines, and Donation Land Claim No. 41.

In 1957, Irving Zirpel, Jr., Cadastral Surveyor, resurveyed portions of the west boundary and subdivisional lines, and subdivided section 25, T. 29 S., R. 5 W.

In 1964, Donald R. Beck, Cadastral Surveyor, resurveyed a portion of the subdivisional lines.

In 1987-88, Boyd W. Peterson, Cadastral Surveyor, resurveyed portions of the subdivisional lines, Donation Land Claim boundaries, and subdivided sections 17 and 19.

While performing the work authorized under this group, an apparent error in the location of the E 1/16 section corner of sections 7 and 18 was found, necessitating the corrective dependent resurvey of the east one-half mile of the line between sections 7 and 18.

T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated August 7, 1991, and Supplemental Special Instructions dated March 16, 1992, for Group No. 1625, Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the E 1/16 section corner of sections 7 and 18, as determined from a direct tie to Geodetic Control Station No. EC 1G1394, established by the Bureau of Land Management in 1987, is as follows:

Latitude: 43° 03' 20.80" N. Longitude: 123° 12' 38.01" W.

The geographic position (NAD 1927) of the corner of sections 2, 3, 10, and 11, as determined from a tie to Geodetic Control Station No. EC 41119, established by the Bureau of Land Management in 1991, is as follows:

Latitude: 43° 04' 06.25" N. Longitude: 123° 09' 05.79" W.

The geographic position (NAD 1927) of the corner of sections 31 and 32, as determined from a tie to Geodetic Control Station No. EC 41168, established by the Bureau of Land Management in 1991, is as follows:

Latitude: 43° 00' 02.52" N. Longitude: 123° 12' 49.06" W.

The mean magnetic declination is 18½° East.

**Corrective Dependent Resurvey of the East Half
of the Line Between Sections 7 and 18,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>(Restoring the survey by Dennis Hathorn in 1857, the resurvey by William F. Briggs in 1899, and correcting the resurvey by Boyd W. Peterson in 1987-88)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the true point for the cor. of secs. 7, 8, 17, and 18, determined at record bearing and distance from the witness corner, the corner point falls on the right bank of the North Fork Myrtle Creek, where it is impractical to establish a permanent monument.</p> <p>West, bet. secs. 7 and 18.</p> <p>Ascend over creek bottom.</p>
0.182	<p>The witness cor. for secs. 7, 8, 17, and 18, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">W COR 7 * 8 12 FT ----- 18 * 17 EAST T29S R4W 1954</p> <p>from which the bearing trees mkd. by Ben B. Irving, Douglas County Surveyor, in 1954, recorded in the Douglas County Surveyor's Office corner renewal No. 84 and 185, and C. S. file No. 45/234.</p> <p style="padding-left: 40px;">A cedar, 31 ins. diam., bears N. 2¼° E., 141 lks. dist., with a healed double blaze. (Record, N. 3° W.)</p> <p style="padding-left: 40px;">A cedar, 34 ins. diam., bears N. 38 3/4° E., 50 lks. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears S. 58 3/4° W., 56 lks. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears N. 88 3/4° W., 5 lks. dist., with a healed blaze.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 55' 30" W., beginning a new measurement.</p> <p>Ascend over broken E. slope, through scattering timber and dense undergrowth.</p>
8.20	<p>North Myrtle Creek Road, asphalt surface, 30 lks. wide, bears N. and S. 15° W.</p>
14.85	<p>Spur, slopes S. 20° E.; desc. over SW. slope.</p>

**Corrective Dependent Resurvey of the East Half
of the Line Between Sections 7 and 18,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
16.70	Ravine, drains S. 35° E.; asc. over NE. slope.
19.895	<p>The E 1/16 sec. cor. of secs. 7 and 18, established by person(s) unknown, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, this position is accepted as the corner.</p> <p>From this point, the E 1/16 sec. cor. of secs. 7 and 18, erroneously established by Boyd W. Peterson, Cadastral Surveyor, in 1988, bears S. 89° 25' 09" W., 0.178 chs. dist.; monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. and witnessed as described in the official record. Destroy the marks on the bearing trees.</p> <p>Remove the stainless steel post and at the true corner point, reset the stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 7 E 1/16 ----- S 18 1992</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 47½° W., 71 lks. dist., mkd. E 1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 44 ¾° W., 86 lks. dist., mkd. E 1/16 S7 BT.</p> <p>From this same point, the Bureau of Land Management, Geodetic Control Station EC 1G1394 at latitude 43° 03' 13.747" N., longitude 123° 11' 28.975" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 82° 04' 20" E., 78.415 chs. dist. (mean bearing and sea level distance); monumented with a ¾ in. diam. aluminum cap, firmly set in concrete flush with the ground, with aluminum cap mkd. EC1G1394 1987 BLM.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 57' 30" W., beginning a new measurement.</p> <p>Ascend over a NE. slope, through second growth timber and dense undergrowth.</p>
5.70	Ridge, bears N. 20° W. and S. 20° E.; desc. over a SW. slope.
11.30	Ravine, drains S.; asc. over SE. slope.

**Corrective Dependent Resurvey of the East Half
of the Line Between Sections 7 and 18,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
16.50	Spur, slopes S.; desc. over SW. slope.
20.085	The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE 1/4 S 7 ----- 18 1954 T29S R4W
	from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963 (as recorded in the Douglas County Surveyor's Office corner renewal No. 181)
	A fir, 19 ins. diam., bears N. 43° E., 43 lks. dist., with a healed double blaze.
	A madrone, 12 ins. diam., bears S. 54 1/2° E., 140 lks. dist., with a healed blaze.
	The corner is located in a ravine that drains S.
	<hr/> Dependent Resurvey of a Portion of the South Boundary, T. 29 S., R. 4 W., Willamette Meridian, Oregon <hr/>
	(Restoring the 1854 survey by Nathaniel Ford and the 1889 resurvey by William Thiel) <hr/>
	From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., perpetuated by John H. Markham Jr., Registered Engineer No. 2880, in 1951, recorded in Douglas County Surveyor's Office corner renewal No. 30 and C. S. file No. 40/304; monumented with rust lined hole, 1 1/4 ins. diam., with an iron pipe, 1 1/4 ins. diam., 24 ins. long, lying alongside, from which the remaining original bearing tree:
	A fir, 56 ins. diam., bears N. 32° W., 19 lks. dist., no marks visible.
	and a bearing tree mkd. by Markham
	A maple, 17 ins. diam., bears N. 80 1/4° W., 89 lks. dist., with fragmentary scribe marks visible on opened blaze.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W 1/4 S 31 ----- 1992</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 3½° E., 77½ lks. dist., mkd 1/4 S31 BT.</p> <p>S. 74° 00' 30" W., bet. secs. 6 and 31.</p> <p>Descend over broken W. slope, through heavy timber and dense undergrowth.</p>
3.00	Creek, 5 lks. wide, course S. 20° W.; asc. over SE. slope.
5.40	Spur, slopes S. 10° E.; desc. over SW. slope.
5.500	Point for the W 1/16 sec. cor. of sec. 31 only.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 S 31 ----- 1992</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 60 3/4° E., 20 lks. dist., mkd. W 1/16 S31 BT.</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears N. 43° W., 47 lks. dist., mkd. W 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend a broken SW. slope.</p>
10.615	The cor. of Tps. 29 and 30 S., Rs. 4 and 5 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>L T29S R5W R4W S 36 * S 31 B ----- M S 1 * S 6 T30S 1957</p>
	<p>from which the remains of the original bearing trees</p> <p>A cedar, 15 ins. diam., bears N. 75° E., 3 lks. dist., with a partially healed blaze. (Record, N. 60° E.)</p> <p>A cedar, 34 ins. diam., bears S. 65° E., 67 lks. dist., with a healed double blaze. (Record, S. 65½° E.)</p> <p>A cedar, 28 ins. diam., bears S. 75° W., 35 lks. dist., with a healed double blaze. (Record, S. 76 3/4° W.)</p> <p>A root hole, bears N. 16½° W., 20 lks. dist., with down cedar alongside, 21 ins. diam., with a healed blaze.</p> <p>and a bearing tree mkd. by John H. Markham Jr., Registered Engineer No. 2880, in 1951, recorded in Douglas County Surveyor's Office corner renewal No. 234</p> <p>A fir, 46 ins. diam., bears S. 79½° E., 17 lks. dist., with fragmentary scribe marks T30 R4W S visible on bark blaze. (Record, S. 78° E., 19 lks.)</p>
	<hr/> <p>Dependent Resurvey of a Portion of the West Boundary, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>(Restoring the 1851 survey by James Freeman)</p> <hr/>
	<p>From the cor. of Tps. 29 and 30 S., Rs. 4 and 5 W.</p> <p>N. 1° 24' 00" E., bet. secs. 31 and 36.</p> <p>Ascend over SW. slope, through heavy timber and dense undergrowth.</p>
12.65	Spur, slopes S. 75° E.; desc. over NE. slope.
19.940	Point for the S 1/16 sec. cor. of secs. 31 and 36.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 36 * S 31 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 4½° E., 66½ lks. dist., mkd. S 1/16 S31 BT.</p> <p style="padding-left: 40px;">A maple, 9 ins. diam., bears S. 55° W., 25 lks. dist., mkd. S 1/16 S36 BT.</p> <p>Descend over NE. slope.</p>
20.40	Ravine, drains S. 30° E.; asc. over SW. slope.
26.05	Spur, slopes S. 50° E.; continue ascent over SE. slope.
33.50	Ridge, bears N. 30° E. and S. 30° W.; desc. over NW. slope, also dirt road, 15 lks. wide, bears same.
39.880	<p>The 1/4 sec. cor. of secs. 31 and 36, perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1958, from original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 139 and C.S. file No. 42/345; monumented with an axle, 2 ins. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by person(s) unknown, reported and remarked by Markham:</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 32° W., 24 lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">A root hole, bears N. 11° E., 104 lks. dist., with down and decayed fir alongside, size indeterminate, with fragmentary scribe marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, 52 ins. diam., bears S. 66° E., 9 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A maple, 10 ins. diam., bears S. 33° E., 62 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R5W R4W 1/4 S 36 * S 31 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base and axle inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' 00" W., beginning a new measurement.</p> <p>Descend over NW. slope.</p>
19.785	<p>The N 1/16 sec. cor. of secs. 31 and 36, established by Ronald A. Brandt, Registered Professional Engineer No. 6803, in 1975, recorded in Douglas County Surveyor's Office C.S. file No. 58/55, and is accepted as the corner; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 3 ins. above ground, from which bearing trees mkd. by Brandt:</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 65 3/4° E., 34 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 3¼° W., 50 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 36 * S 31 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base and iron rod inside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 00" W., beginning a new measurement.</p> <p>Descend over NW. slope, through scattering timber and dense undergrowth.</p>
4.00	Ravine, drains S. 80° W.; asc. over SW. slope.
8.75	Spur, slopes S. 50° W.; desc. over a NW. slope.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
12.55	Ravine, drains S. 25° W.; asc. over SE. slope.
13.50	Days Creek Cutoff Road, graveled, 25 lks. wide, bears S. 25° E. and S. 55° W.
18.40	Spur, slopes S. 40° W.; continue along westerly slope.
19.785	The cor. of secs. 25, 30, 31, and 36, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.
	T29S R5W R4W S 25 * S 30 ----- S 36 * S 31 1957
	from which the remains of the original bearing trees
	An oak, 17 ins. diam., bears S. 70° E., 32 lks. dist., with a healed blaze.
	A root hole, bears N. 17° W., 15 lks. dist., with a down and decayed madrone alongside, size indeterminate, no marks visible.
	and the remains of the bearing trees mkd. by Zirpel
	A fir, 15 ins. diam., bears N. 58° E., 64 lks. dist., with a healed blaze.
	A fir, 15 ins. diam., bears S. 31½° E., 46 lks. dist., with a healed blaze.
	A fir, 18 ins. diam., bears S. 89½° W., 47 lks. dist., with a healed blaze.
	A sawed fir stump, 20 ins. diam., bears N. 46¼° W., 49 lks. dist., no marks visible.
	There was no suitable tree available in the NW. quadrant.
	From this point, a point established as the cor. for secs. 25, 30, 31, and 36 by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, reported by Zirpel and recorded in Douglas County Surveyor's Office corner renewal No. 32 and C.S. file No. 40/375, bears N. 60° 51' 00" E., 0.038 chs. dist.; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of bearing trees mkd. by Markham:

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p>An oak, 12 ins. diam., bears N. $87\frac{1}{4}^{\circ}$ E., 41 lks. dist., with a healed blaze.</p> <p>A fir root crown, bears S. 24° E., 17 lks. dist., with a down and decayed fir alongside, 6 ins. diam., no marks visible.</p> <p>A sawed fir stump, 12 ins. diam., bears S. $20\frac{3}{4}^{\circ}$ W., $37\frac{1}{2}$ lks. dist., no marks visible.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1951, from the remains of original bearing trees no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 31, and C.S. file No. 40/375, further perpetuated by Arthur R. Evans, Professional Engineer No. 2741, in 1953, recorded in Douglas County Surveyor's Office corner renewal No. 80, further perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in Douglas County Surveyor's Office corner renewal No. 155 and C.S. file No. 49/64; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which the remains of the bearing trees mkd. by Evans:</p> <p style="padding-left: 40px;">A sawed fir stump, 30 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ E., 17 lks. dist., burned, no marks visible.</p> <p style="padding-left: 40px;">A madrone, 36 ins. diam., bears N. $86\frac{3}{4}^{\circ}$ W., 42 lks. dist., burned, no marks visible.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A burned fir, 17 ins. diam., bears S. $37\frac{1}{2}^{\circ}$ E., 38 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R5W R4W S 12 * S 7 ----- S 13 * S 18 1992</p> <p>There are no suitable trees available, this area was burned in 1987.</p> <p>Deposit a white "DEEP-1" magnetic marker at base and iron pipe</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>inside the stainless steel post.</p> <p>N. 0° 38' 30" E., bet. secs. 7 and 12.</p> <p>Ascend across broken E. slope, changing to a SE. slope, through a burned area.</p>
40.270	<p>Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R5W R4W 1/4 S 12 * S 7 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 57° E., 32 lks. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 2° W., 36 lks. dist., mkd. 1/4 S12 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend broken SE. slope,</p>
41.70	<p>Spur, slopes N. 15° E.; desc. over NE. slope.</p>
49.45	<p>Little Lick Creek, 5 lks. wide, course S. 40° E.; asc. over SE. slope.</p>
50.35	<p>Dirt road, 20 lks. wide, bears N. 20° W. and S. 35° E.</p>
53.90	<p>Spur, slopes S. 65° W.; desc. over NW. slope.</p>
58.25	<p>Ravine, drains S. 60° W.; asc. over SW. slope.</p>
60.405	<p>Point for the N 1/16 sec. cor. of secs. 7 and 12.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	N 1/16 S 12 * S 7 1992
	from which
	A fir, 11 ins. diam., bears N. 10½° E., 42½ lks. dist., mkd. N 1/16 S7 BT.
	A fir, 15 ins. diam., bears S. 35° W., 22 lks. dist., mkd. N 1/16 S12 BT.
	Ascend broken SE. slope,
62.05	Spur, slopes S. 50° W.; desc. over NW. slope.
71.65	Ravine, drains E.; asc. over SE. slope.
74.15	Spur, slopes SW.; desc. over NW. slope.
77.30	Little Lick Creek, 5 lks. wide, course S. 15° W.; continue over level creek bottom.
79.10	Little Lick Creek, 5 lks. wide, course S. 15° E.; asc. over SW. slope.
80.540	The cor. of secs. 1, 6, 7, and 12, perpetuated by Robert M. Thompson, Registered Engineer No. 3683, in 1958, determined from the remains of the original bearing trees no longer in existence, recorded in Douglas County renewal No. 140 and C.S. file No. 41/62, further perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in Douglas County renewal No. 156 and C.S. file No. 49/64; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T29S R S 1 * S 6 R 5 ----- 4 W S 12 * S 7 W 1962
	from which the remains of bearing trees mkd. by Thompson
	A burnt and sawed fir stump, size indeterminate, bears N. 87 ¾° E., 90 lks. dist., no marks visible.
	A cedar, 29 ins. diam., bears S. 32° E., 32 lks. dist., with healed double blaze.

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A sawed fir stump, 40 ins. diam., bears S. 76° W., 72 lks. dist., with scribe marks 29S R5W visible on bark blaze.</p> <p>A cedar, 29 ins. diam., bears N. 24½° W., 56 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by James W. Byron</p> <p>A fir, 16 ins. diam., bears N. 41½° E., 12 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>A fir, 5 ins. diam., bears S. 40¼° W., 68½ lks. dist., mkd. T29S R5W S12 BT.</p> <hr/> <p>N. 0° 08' 30" E., bet. secs. 1 and 6.</p> <p>Ascend broken SW. slope, through heavy timber and dense undergrowth.</p>
14.35	Ravine, drains SW.; continue ascent over SW. slope.
36.85	Ridge, bears S. 65° E. and N. 65° W.; desc. over NE. slope.
39.120	<p>The 1/4 sec. cor. of secs. 1 and 6, reestablished at proportionate distance by Robert M. Thompson, Registered Engineer No. 3683, in 1958, recorded in Douglas County Surveyor's Office corner renewal No. 142 and C.S. file No. 41/62, there is no remaining evidence of the original corner, therefore, this position is accepted as the corner; monumented with an iron pipe, 1 in. diam., loosely set, projecting 12 ins. above ground, from which bearing trees mkd. by Thompson:</p> <p>A fir, 26 ins. diam., bears S. 52½° E., 47 lks. dist., with healed double blaze.</p> <p>A fir, 21 ins. diam., bears S. 76½° W., 66 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

T29S
R5W R4W
1/4
S 1 * S 6
1992

Deposit a white "DEEP-1" magnetic marker at base and iron pipe inside the stainless steel post.

From this point, the cor. of Tps. 28 and 29 S., Rs. 4 and 5 W., perpetuated by James W. Byron, Deputy County Surveyor, in 1957, recorded in Douglas County Surveyor's Office corner renewal No.

131, bears N. 0° 18' 30" E., 39.280 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T28S
R 36 * 31 R
5 ----- 4
W 1 * 6 W
T29S
1957

from which the remaining original bearing tree

An oak, 30 ins. diam., bears N. 31° E., 38 lks. dist., with a healed double blaze.

and the remains of the bearing trees mkd. by Byron

A fir, 18 ins. diam., bears S. 55° E., 76 lks. dist., with a healed double blaze.

A fir, 22 ins. diam., bears S. 46½° W., 82 lks. dist., with a healed double blaze.

A fir stump, 30 ins. diam., bears N. 82° W., 16 lks. dist., with a healed double blaze.

and a new bearing tree

A fir, 7 ins. diam., bears N. 15½° W., 51 lks. dist., mkd.
T28S R5W S36 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

(Restoring the survey by Nathaniel Ford in 1854,
the survey by Dennis Hathorn in 1857, the
survey and resurvey by William H. Byars in 1881, and
the survey and resurvey by William F. Briggs in 1899)

From the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T29S R4W
S 11 * S 12

S 14 * S 13
1964

from which the remains of an original bearing tree

A decayed fir stump, 26 ins. diam., bears S. 13½° W., 15 lks. dist., badly decayed and no marks visible.

and the remains of the bearing trees mkd. by William H. Wood, Deputy County Surveyor, in 1925, recorded in Douglas County Surveyor's Office corner renewal No. 43

A sawed fir stump, 42 ins. diam., bears N. 72° E., 23 lks. dist., no marks visible on decayed and open blaze. (Record, N. 69¼° E., 25 lks.)

A cedar, 45 ins. diam., bears S. 42¼° E., 57 lks. dist., with a healed blaze.

A fir snag, 20 ins. diam., bears N. 8½° W., 34 lks. dist., with a healed blaze.

and the remains of bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 166 and C. S. file No. 52/126

A fir, 15 ins. diam., bears N. 0½° E., 65 lks. dist., with a healed double blaze.

A cedar, 17 ins. diam., bears N. 34½° W., 55 lks. dist., with a healed double blaze.

and a bearing tree mkd. by Beck

A fir, 12 ins. diam., bears S. 53° E., 86 lks. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	N. 1° 00' 00" E., bet. secs. 11 and 12.
	Descend broken NW. slope.
12.25	Creek, 5 lks. wide, course S. 75° W.; asc. over SW. slope.
16.35	Graveled road, 25 lks. wide, bears S. 75° E. and West.
19.530	Point for the S 1/16 sec. cor. of secs. 11 and 12.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 1/16 S 11 * S 12 1991
	from which
	A cedar, 4 ins. diam., bears N. 85° E., 31 lks. dist., mkd. S 1/16 S12 BT.
	A cedar, 5 ins. diam., bears N. 4° W., 19 lks. dist., mkd. X BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over broken SW. slope.
21.80	Spur, slopes N. 70° W.; desc. over broken NW. slope.
25.00	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
37.90	Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.
39.060	The 1/4 sec. cor. of secs. 11 and 12, perpetuated by Claude Kerr, Registered Professional Engineer No. 2125, in 1950, from original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 27, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 164 and C.S. file No. 52/126; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE 1/4* S 11 * S 12 1963

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>from which the remains of the bearing trees mkd. by Kerr</p> <p style="padding-left: 40px;">A sawed fir stump, 23 ins. diam., bears N. 70° E., 43 lks. dist., with scribe marks BT visible on open blaze.</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears S. 71½° W., 39 lks. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears S. 35¼° E., 34 lks. dist., with a healed double blaze.</p> <hr/> <p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>N. 87° 39' 00" W., bet. secs. 11 and 14.</p> <p>Descend broken NW. slope, through heavy timber and dense undergrowth.</p>
19.865	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 11 E 1/16 ----- S 14 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 42° W., 23 lks. dist., mkd. E 1/16 S14 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 23½° W., 7 lks. dist., mkd. E 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend broken NW. slope, through heavy timber and dense undergrowth.</p>
36.80	<p>Louis Creek Road, asphalt surface, 30 lks. wide, bears N. 15° E. and S. 15° W.</p>
38.15	<p>Louis Creek, 15 lks. wide, course S. 30° E.; asc. over nearly level ground.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS 39.730	<p>The 1/4 sec. cor. of secs. 11 and 14, reestablished at proportionate position by William H. Wood, Deputy County Surveyor, in 1925, recorded in Douglas County Surveyor's Office corner renewal No. 44, perpetuated by Arthur R. Evans, Registered Engineer No. 2741, in 1952, recorded in Douglas County Surveyor's Office corner renewal Nos. 75 and 81-A, further perpetuated by James W. Byron, Deputy County Surveyor, in 1962, recorded in Douglas County Surveyor's Office corner renewal No. 167, further perpetuated by Donald R. Martin, Registered Engineer No. 3900, in 1968, recorded in Douglas County Surveyor's Office, map file No. M39-21, and further recovered by Burt W. Holt, Registered Land Surveyor No. 418, in 1973, recorded in Douglas County Surveyor's Office, map file No. M49-39. There is no remaining evidence of the original corner, therefore, this position is accepted as the corner; monumented with an iron pipe, 2½ ins. diam., firmly set 6 ins. below ground, with an iron rod, 3/4 in. diam., driven inside, from which bearing trees mkd. by Evans:</p> <p style="margin-left: 40px;">A fir, 30 ins. diam., bears N. 14° E., 259 lks. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A cedar, 35 ins. diam., bears S. 80½° E., 149 lks. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W S 11 1/4 ----- S 14 1992</p> <p>Deposit a white "DEEP-1" magnetic marker at base with iron pipe and iron rod alongside the stainless steel post.</p> <p>From this point, a point unofficially established as the 1/4 cor. of secs. 11 and 14 by the Bureau of Land Management, in 1978, recorded in the Roseburg Bureau of Land Management Office, perpetuated by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in Douglas County Surveyor's Office map file No. M94-61 and C.S. file No. 58/270, bears N. 86° 32' 00" W., 0.225 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. T29S R4W 1/4 S11 S14 LS866 1983. Since Wood's 1/4 cor. had been properly reestablished prior to the 1978 survey, this point is not utilized in this survey.</p>
----------------------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

From this same point, a point established as the W 1/16 sec. cor. of secs. 11 and 14 by Burton W. Holt, Registered Land Surveyor No. 418, in 1973, recorded in Douglas County Surveyor's Office, map file No. M49-39, bears N. 87° 39' 30" W., 20.115 chs. dist.; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of bearing trees mkd. by Holt:

A cedar, 15 ins. diam., bears N. 29° E., 25½ lks. dist., with healed double blaze.

A sawed fir stump, 25 ins. diam., bears S. 26 3/4° E., 6½ lks. dist., bark scribed W 1/16 S14 on open upper face and BT on open lower face.

From this same point, the cor. of secs. 10, 11, 14, and 15, perpetuated by William H. Wood, Deputy County Surveyor, in 1925, recorded in Douglas County Surveyor's Office corner renewal No. 45, from original evidence no longer in existence, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 189, bears N. 87° 38' 00" W., 40.210 chs. dist.; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S

S 10 * S 11 R

----- 4

S 15 * S 14 W

1963

from which the remains of a bearing tree mkd. by Wood

A sawed fir stump, 21 ins. diam., bears S. 10° E., 22 lks. dist., with fragmentary scribe marks visible on open blaze.

and the remains of bearing trees mkd. by Byron

A cedar, 21 ins. diam., bears N. 74° E., 63 lks. dist., with healed double blaze.

A fir stump, 21 ins. diam., bears S. 70° W., 50 lks. dist., with down log alongside with a healed double blaze.

A cedar, 26 ins. diam., bears N. 48° W., 68 lks. dist., with a healed double blaze.

and new bearing trees

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 6 ins. diam., bears S. 59½° E., 11 lks. dist., mkd. T29S R4W S14 BT.</p> <p>A fir, 4 ins. diam., bears S. 87¼° W., 17½ lks. dist., mkd. X BT.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11, reestablished at proportionate position by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in the Douglas County Surveyor's Office, C.S. file No. 58/270 and map file No. M94-61. There is no remaining evidence of the original corner, and because of the close agreement of this survey with Ruppert's record and error closures, this position is accepted as the corner; monumented with a galvanized iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W 1/4 S 10 * S 11 LS 866 1983</p> <p>from which new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 50° E., 19 lks. dist., mkd. 1/4 S11 BT.</p> <p>A fir, 5 ins. diam., bears N. 40° W., 26 lks. dist., mkd. 1/4 S10 BT.</p> <hr/> <p>N. 0° 18' 00" W., beginning new measurement.</p> <p>Descend broken NE. slope, through second growth timber and dense undergrowth.</p> <p>3.85 Ravine, drains E.; asc. over SE. slope.</p> <p>7.15 Spur, slopes N. 65° E.; desc. over NE. slope.</p> <p>14.270 The witness cor. to the N 1/16 sec. cor. of secs. 10 and 11, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in Douglas County Surveyor's Office, map file No. M94-61 and C.S. file No. 58-270; monumented with a galvanized iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	WC N 1/16 S 10 * S 11 *3 LS 866 *0 1983 . 0
	from which a bearing tree mkd. by Ruppert A fir, 20 ins. diam., bears N. 67¼° W., 23 lks. dist., with a healed double blaze. This position no longer functions as a witness cor. and now becomes an angle point on the line. <hr style="width: 20%; margin: auto;"/> N. 0° 18' 00" W., beginning new measurement. Descend over broken NE. slope.
2.20	Dirt road, 20 lks. wide, bears N. 60° W. and S. 75° E.
2.70	Ravine, drains N. 70° E.; asc. over broken SE. slope.
3.70	Dirt road, 20 lks. wide, bears N. 80° E. and S. 40° W.
5.005	Point for the N 1/16 sec. cor. of secs. 10 and 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	N 1/16 S 10 * S 11 1992
	from which A cedar, 11 ins. diam., bears N. 28° E., 52 lks. dist., mkd. N 1/16 S11 BT. A madrone, 11 ins. diam., bears N. 82½° W., 3 lks. dist., mkd. N 1/16 S10 BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over broken SE. slope
20.10	Spur, slopes N. 55° E.; desc. over NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

<p>CHAINS 24.280</p>	<p>The cor. of secs. 2, 3, 10, and 11, perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 188, recovered by William J. Ruppert, Registered Land Surveyor No. 866, recorded in Douglas County Surveyor's Office, map file No. M94-61 and C.S. file No. 58/270; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S S 3 * S 2 R ----- 4 S 10 * S 11 W 1963</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A madrone clump, 24 ins. diam., bears N. 88° E., 43 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 83° E., 53 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 28½° E., 46 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 24¼° W., 31 lks. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears N. 24° W., 24 lks. dist., with a healed blaze.</p> <p>From this point, the Bureau of Land Management, Geodetic Control Station No. EC 41119, at latitude 43° 03' 04.391' N., longitude 123° 07' 52.304" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 41° 04' 00" E., 125.851 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap, 3¼ ins. diam., firmly set flush with the ground, with aluminum cap mkd. EC41119 GPS 1991.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1932, recorded in Douglas County Surveyor's Office corner renewal No. 46, further perpetuated by Arthur R. Evans, Professional Engineer No. 2741, in 1952, recorded in Douglas County Surveyor's Office corner renewal No. 76, further perpetuated by James W. Byron, Deputy County</p>
--------------------------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Surveyor, in 1963, recorded in Douglas County Surveyor's Office, corner renewal No. 163, further perpetuated by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1981-82, recorded in the Douglas County Surveyor's Office, corner renewal No. 254 and RM No. 3-54, further recovered by William J. Ruppert, Registered Land Surveyor No. 866, in 1982, recorded in Douglas County Surveyor's Office, map file No. M94-61 and C.S. file 58/270; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S S 2 R 1/4 ----- 4 S 11 W 1963</p> <p>from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 35 ins. diam., bears S. 14° W., 61 lks. dist., with a healed double blaze.</p> <p>and the remains of a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A sawed fir stump, 41 ins. diam., bears N. 25½° E., 30 lks. dist., with scribe marks 1/4 S2 visible on bark blaze and a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Evans, remarked by Byron</p> <p style="padding-left: 40px;">A fir snag, 34 ins. diam., bears S. 48 3/4° W., 38 lks. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Shaner</p> <p style="padding-left: 40px;">A cedar, 20 ins. diam., bears N. 32° W., 74 lks. dist., with a healed double blaze.</p> <p>N. 89° 22' 00" W. bet. secs. 2 and 11.</p> <p>Descend broken NW. slope, through heavy timber and dense undergrowth.</p>
11.90	Louis Creek Road, asphalt surface, 30 lks. wide, bears N. 10° E. and S. 5° W.
13.70	Louis Creek, 15 lks. wide, course S. 35° E.; asc. over broken SE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
20.30	Dirt road, 15 lks. wide, bears N. 5° W. and S. 5° E.
20.665	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 W 1/16 ----- S 11 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 3 3/4° W., 16½ lks. dist., mkd. W 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 11 3/4° W., 14 lks. dist., mkd. W 1/16 S2 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend a broken SE. slope changing to NE. slope.</p>
41.330	<p>The cor. of secs. 2, 3, 10, and 11.</p> <hr/> <p>From the cor. of secs. 31 and 32, on the S. bdy. of the Tp., perpetuated by George A. Barnhart, Registered Land Surveyor No. 120, in 1947, from original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 64, further perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in Douglas County Surveyor's Office corner renewal No. 153 and C.S. file No. 49/67; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S R4W S 31 * S 32 ----- S 6 1961</p> <p>from which the remains of the bearing trees mkd. by Barnhart</p> <p style="padding-left: 40px;">A fir snag, 10 ins. diam., bears S. 52½° E., 50½ lks. dist., no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A decayed fir stump, size indeterminate, bears N. 22° W., 50 lks. dist., with scribe marks T29S R W visible on open blaze.</p> <p>and the remains of a bearing tree mkd. by Byron</p> <p>A madrone snag, 23 ins. diam., bears S. 59° W., 196 lks. dist., with healed upper blaze and scribe marks BT visible on partially healed lower blaze.</p> <p>and new bearing trees</p> <p>A fir, 4 ins. diam., bears S. 51° E., 44 lks. dist., mkd. T30S R4W S6 BT.</p> <p>A fir, 5 ins. diam., bears S. 15½° W., 25½ lks. dist., mkd. X BT.</p> <p>A fir, 10 ins. diam., bears N. 44½° W., 40 lks. dist., mkd. T29S R4W S31 BT.</p> <p>From this point, the 1/4 sec. cor. of sec. 31 only bears S. 76° 24' 30" W., 42.145 chs. dist., hereinbefore described.</p> <p>From this same point, the Bureau of Land Management, Geodetic Control Station No. EC 41168, at latitude 42° 59' 59.965" N., longitude 123° 13' 05.969" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 78° 22' 07" W., 19.438 chs. dist.; monumented with an aluminum cap, 3¼ ins. diam., firmly set, projecting 1 in. above ground, with cap mkd. EC41168 GPS 1991.</p> <p>N. 22° 57' 30" E., bet. secs. 31 and 32.</p> <p>Descend a broken NW. slope through a clearing.</p>
0.95	Ravine, drains S. 50° E.; asc. over SE. slope.
2.35	Dirt road, 20 lks. wide, bears N. 85° E. and N. 80° W.
4.25	Spur, slopes S. 30° E.; desc. over NE. slope.
10.00	Ravine, drains S. 20° E.; asc. over SE. slope.
19.00	Ridge, bears N. 80° E. and S. 80° W.; desc. over NE. slope changing to NW. slope.
32.890	Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W 1/4 S 31 * S 32 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 66½° E., 51½ lks. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 27° W., 10 lks. dist., mkd. 1/4 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the 1/4 sec. cor. of secs. 31 and 32 by George A. Barnhart, Registered Land Surveyor No. 120, in 1947, recorded in Douglas County Surveyor's Office, corner renewal No. 65 and map file No. M28-78, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in Douglas County Surveyor's Office, corner renewal No. 154, bears N. 1° 39' 30" E., 1.902 chs. dist.; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 5 ins. above ground, from which the remains of bearing trees mkd. by Barnhart:</p> <p style="padding-left: 40px;">A sawed fir stump, 48 ins. diam., bears N. 43° E., 43 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 81¼° W., 14 lks. dist., with healed double blaze.</p> <p>and a bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 70½° E., 29½ lks. dist., with healed double blaze.</p> <p>Barnhart established this point at proportionate distance, but it is not properly positioned and is not utilized in this survey.</p> <p>Descend over a broken NW. slope,</p>
36.20	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 65° E. and S. 65° W.
65.780	The cor. of secs. 29, 30, 31, and 32, perpetuated by George A. Barnhart, Registered Land Surveyor No. 120, in 1946, from the

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

remains of original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 62, further perpetuated by Jack L. Sheppard, Registered Land Surveyor No. 180, in 1955, recorded in Douglas County Surveyor's Office corner renewal No. 93 and C. S. file 41/337, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 172 and C. S. file No. 52/126; monumented with an iron rod, 3/4 in. diam., firmly set, projecting 8 ins. above ground, from which the remains of bearing trees mkd. by Barnhart:

A cedar, 40 ins. diam., bears S. 51 3/4° W., 32 lks. dist., with healed blaze.

A root hole, bears N. 3° W., 6 1/2 lks. dist., with decayed and down fir alongside, 10 ins. diam., no marks visible.

and bearing trees mkd. by Sheppard

A cedar, 30 ins. diam., bears N. 46 1/4° E., 68 lks. dist., with a healed double blaze.

A maple, 15 ins. diam., bears S. 39 1/2° E., 79 lks. dist., with a healed blaze.

and a bearing tree mkd. by Byron

A fir, 19 ins. diam., bears N. 66 1/4° W., 35 lks. dist., with a healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.

T29S R4W
S 30 * S 29

S 31 * S 32
1993

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

N. 85° 27' 30" W. bet. secs. 30 and 31.

Descend NW. slope, through scattering timber and dense undergrowth.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
3.55	Creek, 5 lks. wide, course N. 25° E.; asc. over broken SE. slope.
21.35	Spur, slopes SE.; desc. over SW. slope.
24.10	Ravine, drains S. 60° E.; asc. over SE. slope.
38.750	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T29S R4W S 30 1/4 ----- S 31 1992 </div> from which <div style="text-align: center;"> A fir, 17 ins. diam., bears N. 45½° E., 4 lks. dist., mkd. 1/4 S30 BT. A fir, 11 ins. diam., bears S. 7½° E., 17½ lks. dist., mkd. 1/4 S31 BT. </div> Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend a broken SE. slope, through second growth timber and dense undergrowth.
45.15	Ridge, bears NE. and S. 70° W.; desc. over a broken NW. slope.
57.65	Ravine, drains N. 30° W.; asc. over NE. slope.
58.125	Point for the W 1/16 sec. cor. of secs. 30 and 31. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 30 W 1/16 ----- S 31 1992 </div> from which <div style="text-align: center;"> A fir, 9 ins. diam., bears N. 2½° E., 24 lks. dist., mkd. W 1/16 S30 BT. </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 5 ins. diam., bears S. 21° E., 22 lks. dist., mkd. W 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend NE. slope, through second growth timber and dense undergrowth.</p>
62.85	Spur, slopes N.; desc. over NW. slope.
66.40	Ravine, drains N. 10° W.; asc. over NE. slope.
67.815	Point for the WW 1/64 sec. cor. of secs. 30 and 31.
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 30 WW 1/64 ----- S 31 1992</p> <p>from which</p> <p style="text-align: center;">A fir, 9 ins. diam., bears N. 39° E., 30 lks. dist., mkd. WW 1/64 S30 BT.</p> <p style="text-align: center;">A fir, 20 ins. diam., bears S. 6° W., 16 lks. dist., mkd. WW 1/64 S31 BT.</p> <p>Ascend over a NE. slope, through heavy timber and dense undergrowth.</p>
74.20	Ridge, bears N. 15° W. and S. 65° E.; desc. over W. slope.
76.145	The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>S. 89° 57' 00" W., bet. secs. 7 and 18.</p> <p>Ascend over a broken NE. slope, through heavy timber and dense undergrowth.</p>
7.25	Ridge, bears N. 50° E. and S. 50° W.; desc. over a NW. slope.
19.875	Point for the W 1/16 sec. cor. of secs. 7 and 18.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 7 W 1/16 ----- S 18 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 55½° E., 30 lks. dist., mkd. W 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 2° E., 105 lks. dist., mkd. W 1/16 S18 BT.</p> <p>Descend over broken NW. slope.</p>
29.10	Dirt road, 20 lks. wide, bears N. and S.
30.10	Little Lick Creek, 10 lks. wide, course S.; asc. over E. slope.
39.750	The cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE 1/4 COR SEC 7 ----- SEC 8</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, size undeterminable, bears N. 8½° W., 60 lks. dist., no marks visible. (Record, N. 15° W.)</p> <p>and a bearing tree mkd. by Ben B. Irving, Douglas County Surveyor, in 1953, recorded in the Douglas County Surveyor's Office corner renewal No. 78 and C.S. file 45/234</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 14° E., 64 lks. dist., with a healed double blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyor's Office corner</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	renewal No. 184 and C.S. file No. 52/126
	A cedar, 30 ins. diam., bears N. 18° W., 72 lks. dist., with a healed double blaze.
	N. 0° 03' 30" E., bet. secs. 7 and 8.
	Descend broken NE. slope, through second growth timber and moderate undergrowth.
8.00	Dirt road, 20 lks. wide, bears N. 75° W. and S. 75° E.
9.35	Big Lick Creek, 10 lks. wide, course S. 5° E.; asc. over SW. slope.
11.30	Big Lick Creek Road, graveled, 20 lks. wide, bears N. 25° W. and S. 25° E.
14.40	Big Lick Creek Road, graveled, 20 lks. wide, bears N. 10° W. and S. 10° W.
19.960	Point for the N 1/16 sec. cor. of secs. 7 and 8.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	N 1/16 S 7 * S 8 1992
	from which
	A cedar, 7 ins. diam., bears N. 63° E., 90 lks. dist., mkd. N 1/16 S8 BT.
	A cedar, 5 ins. diam., bears S. 72½° W., 343 lks. dist., mkd. N 1/16 S7 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend SW. slope changing to a SE. slope.
39.920	The cor. of secs. 5, 6, 7, and 8, perpetuated by Frank Cain, Douglas County Surveyor, in 1915, from the remains of original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 6, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 182, further perpetuated by Gregory Quibell, Deputy County Surveyor, in 1982,

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

recorded in Douglas County Surveyor's Office corner renewal No. 256 and C.S. file No. 61/30; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T29S

S 6 * S 5 R

----- 4

S 7 * S 8 W

1963

from which the remains of bearing trees mkd. by Cain

A fir stump, 24 ins. diam., bears N. 39° E., 36 lks. dist., with a healed blaze.

A fir stump, 20 ins. diam., bears S. 73° E., 39 lks. dist., with a single blaze.

A fir stump, 41 ins. diam., bears S. 34 3/4° W., 151 lks. dist., with a healed blaze.

A fir stump, 48 ins. diam., bears N. 35½° W., 149 lks. dist., with a healed blaze.

and the remains of bearing trees mkd. by Byron

A fir stump, 12 ins. diam., bears N. 8° E., 20 lks. dist., with fragmentary scribe marks visible.

A fir stump, 18 ins. diam., bears S. 33° W., 25 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir snag, 12 ins. diam., bears N. 21° W., 33 lks. dist., with scribe marks R4W BT visible on open double blaze.

and bearing trees mkd. by Quibell

A double madrone, 5 ins. diam., bears N. 26° E., 19 lks. dist., with scribe marks CS BT visible on bark blaze.

A madrone, 5 ins. diam., bears S. 53° E., 10 lks. dist., with scribe marks S8 CS BT visible on bark blaze.

A madrone, 6 ins. diam., bears S. 35½° W., 39 lks. dist., with scribe marks S7 CS BT visible on bark blaze.

A madrone, 5 ins. diam., bears N. 83° W., 21 lks. dist., with scribe marks S6 CS BT visible on bark blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<hr/> <p>S. 89° 49' 00" W., bet. secs. 6 and 7.</p> <p>Ascend broken SE. slope through second growth timber and dense undergrowth.</p>
2.05	Spur, slopes S. 15° W.; desc. over SW. slope.
19.705	<p>The E 1/16 sec. cor. of secs. 6 and 7, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1985, recorded in Douglas County Surveyor's Office C. S. file No. 63/13a, and is accepted as the corner; monumented with an iron post, 2 ins. diam., firmly set in concrete, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W S 6 E 1/16 ----- S 7 LS 866 1985</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 57° E., 24 lks. dist., mkd. E 1/16 S6 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 19¼° E., 65 lks. dist., mkd. E 1/16 S7 BT.</p> <hr style="width: 20%; margin: 20px auto;"/>
	<p>S. 89° 49' 00" W., beginning a new measurement.</p> <p>Descend over broken SW. slope.</p>
0.55	Big Lick Creek Road, gravel, 20 lks. wide, bears N. 15° W. and S. 15° E.
0.80	Big Lick Creek, 5 lks. wide, course S. 15° E.; asc. over NE. slope.
14.75	Dirt road, 20 lks. wide, bears N. 25° W. and S. 75° E.
19.700	The 1/4 sec. cor. of secs. 6 and 7, perpetuated by Robert M. Thompson, Registered Engineer No. 3683, in 1958, recorded in Douglas County Surveyor's Office corner renewal No. 141, further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, recorded in Douglas County Surveyor's Office corner renewal No. 183 and C. S. file No. 52/126, further perpetuated by Gregory

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
	<p>Quibell, Deputy County Surveyor, in 1982, recorded in Douglas County Surveyor's Office corner renewal No. 257 and C. S. file No. 61/30; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T29S S 6 R ----- 4 S 7 W 1963</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears S. 60° W., 25 lks. dist., no marks visible.</p> <p>and a bearing tree mkd. by Thompson</p> <p style="padding-left: 40px;">A madrone, 25 ins. diam., bears S. 40° E., 28 lks. dist., with scribe marks 1/4 S BT visible on partially healed blaze.</p> <p>and bearing trees mkd. by Quibell</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 3½° E., 13 lks. dist., with partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 82½° E., 33 lks. dist., with partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 5 3/4° W., 59 lks. dist., with partially healed double blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 48' 30" W., beginning a new measurement.</p> <p>Ascend broken SE. slope, through heavy timber and dense undergrowth.</p>
10.40	Spur, slopes N. 30° W.; desc. over NW. slope.
19.935	Point for the W 1/16 sec. cor. of secs. 6 and 7.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">S 6 W 1/16 ----- S 7 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 32¼° W., 48 lks. dist., mkd. W 1/16 S7 BT.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 66 3/4° W., 96 lks. dist., mkd. W 1/16 S6 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by person(s) unknown, bears N. 25° 52' 00" W., 0.775 chs. dist., monumented with an iron rod, ½ in. diam., firmly set, projecting 10 ins. above ground.</p> <p>Descend over a broken SW. slope.</p> <p>20.48 Ravine, drains S. 10° W.; asc. over SE. slope.</p> <p>25.05 Spur, slopes S. 30° W.; desc. over NW. slope changing to SW.</p> <p>39.370 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 6, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 6 and 7.</p> <p>N. 0° 24' 30" E., on the N. and S. centerline of sec. 6.</p> <p>Descend broken NE. slope, through heavy timber and dense undergrowth.</p> <p>31.15 Big Lick Creek, 5 lks. wide, course S. 35° E.; asc. over SW. slope.</p> <p>36.00 Big Lick Creek Road, graveled, 20 lks. wide, bears N. 65° W. and S. 75° E.</p> <p>39.630 Point for the center 1/4 sec. cor. of sec. 6, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.</p>
--------	---

Subdivision of Section 6,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W C 1/4 S 6 1992</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears S. 59° W., 105 lks. dist., mkd. C 1/4 S6 BT.</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 9° W., 68 lks. dist., mkd. C 1/4 S6 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 13 ins. above ground, established by person(s) unknown, bears S. 12° 24' 30" W., 0.205 chs. dist.</p> <p>Ascend over SW. slope.</p>
51.15	Spur, slopes S. 60° W.; desc. over NW. slope.
74.00	Creek, 5 lks. wide, course W.; asc. over SW. slope.
74.45	Power transmission line, bears N. 85° E. and S. 85° W., also a ravine, drains S. 85° W.; asc. over SE. slope.
78.575	<p>The 1/4 sec. cor. of secs. 6 and 31, perpetuated by James W. Byron, Deputy County Surveyor, in 1957, from the remains of original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 130 and C. S. file No. 47/180; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T28S R4W 31 1/4 S ----- 6 T29S R4W 1957 OFFICE</p> <p>from which bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 26 ins. diam., bears S. 86° E., 76 lks. dist., with a healed double blaze.</p>

Subdivision of Section 6,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A cedar, 26 ins. diam., bears N. 9° W., 43 lks. dist., with a healed double blaze.</p> <p>From this point, the corner of townships 28 and 29 south, ranges 4 and 5 west, bears S. 89° 31' 00" W., 39.610 chs. dist.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 6, perpetuated by Frank Cain, Deputy County Surveyor, in 1915, from the remains of original evidence no longer in existence, recorded in Douglas County Surveyor's Office corner renewal No. 10, further perpetuated by James W. Byron, Deputy County Surveyor, in 1957, recorded in Douglas County Surveyor's Office corner renewal No. 129 and C. S. file No. 47/180; monumented with an iron post, 1¼ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T29S R4W 1/4 6 * 5 1957 OFFICE</p> <p>from which the remains of bearing trees mkd. by Cain</p> <p style="text-align: center;">A fir stump, 48 ins. diam., bears S. 76½° E., 77 lks. dist., no marks visible.</p> <p style="text-align: center;">A fir stump, 44 ins. diam., bears N. 65° W., 70 lks. dist., no scribe marks visible on opened blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="text-align: center;">A madrone, 23 ins. diam., bears S. 27 3/4° E., 63 lks. dist., with scribe marks BT visible on partially healed double blaze.</p> <p style="text-align: center;">A fir, 19 ins. diam., bears N. 14½° W., 142 lks. dist., with healed double blaze.</p> <p>S. 89° 04' 00" W., on the E. and W. centerline of sec. 6.</p> <p>Ascend a broken SE. slope, through second growth timber and dense undergrowth.</p>
6.50	Spur, slopes S.; desc. over SW. slope.
22.45	Dirt road, 20 lks. wide, bears N. 50° E. and S. 60° W.
39.320	The center 1/4 sec. cor. of sec. 6.

Subdivision of Section 6,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	Descend over SW. slope.
44.25	Big Lick Creek Road, graveled, 20 lks. wide, bears N. 50° W. and S. 50° E.
46.55	Big Lick Creek, 5 lks. wide, course S. 35° E.; asc. over NE. slope.
59.225	Point for the center W 1/16 sec. cor. of sec. 6. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ----- C S 6 1992 </div> from which <div style="text-align: center;"> A fir, 8 ins. diam., bears N. 71° E., 7 lks. dist., mkd. CW 1/16 S6 BT. A cedar, 15 ins. diam., bears S. 3° E., 31 lks. dist., mkd. CW 1/16 S6 BT. </div> Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over NE. slope.
66.75	Spur, slopes N. 10° E.; desc. over NW. slope.
69.40	Ravine, drains N. 20° W.; asc. over NE. slope.
78.880	The 1/4 sec. cor. of secs. 1 and 6. <hr/>
	From the W 1/16 sec. cor. of secs. 6 and 7. N. 0° 27' 30" E., on the N. and S. centerline of the SW¼ of sec. 6. Ascend a broken SW. slope, through heavy timber and dense undergrowth.
9.60	Spur, slopes S. 50° W.; continue ascending a SW. slope.
18.15	Spur, slopes S. 15° E.; desc. over NE. slope.

Subdivision of Section 6,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
39.380	<p>The center W 1/16 sec. cor. of sec. 6.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0° 22' 30" E., on the N. and S. centerline of sec. 7.</p> <p>Ascend a broken SW. slope, through heavy timber and dense undergrowth.</p>
5.60	Spur, slopes S. 65° W.; desc. over NW. slope.
17.60	Ravine, drains S. 35° W.; asc. over SW. slope.
40.560	<p>Point for the center 1/4 sec. cor. of sec. 7, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W C 1/4 S 7 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 13½° E., 18 lks. dist., mkd. C 1/4 S7 BT.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 80¼° E., 32 lks. dist., mkd. C 1/4 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SW. slope.</p>
60.610	<p>Point for the center N 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 * S 7 C 1992</p>

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 74¼° E., 17½ lks. dist., mkd. CN 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 15 ¾° W., 31½ lks. dist., mkd. CN 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SW. slope.</p>
61.65	Ridge, bears N. 20° W. and S. 20° E.; desc. over NE. slope.
70.10	Ravine, drains N. 85° E.; asc. over SE. slope.
77.60	Spur, slopes SE.; desc. over NE. slope.
80.660	The 1/4 sec. cor. of secs. 6 and 7.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>S. 89° 34' 00" W., on the E. and W. centerline of sec. 7.</p> <p>Ascend a broken NE. slope changing to a SE. slope, through second growth timber and dense undergrowth.</p>
19.820	<p>Point for the center E 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ----- C S 7 1992</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 73° E., 8 lks. dist., mkd. CE 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 30½° W., 26½ lks. dist., mkd. CE 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, a point established by person(s) unknown, bears S. 48° 21' 00" E., 0.240 chs. dist., monumented with an iron pipe, ½ in. diam., firmly set, projecting 8 ins. above ground.</p> <p>Ascend over broken SE. slope.</p>
33.30	Spur, slopes S. 50° W.; desc. over SW. slope.
39.640	The center 1/4 sec. cor. of sec. 7.
	Descend over SW. slope.
49.85	Ravine, drains N. 35° W.; continue descending over NW. slope.
59.545	Point for the CW 1/16 sec. cor. of sec. 7.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W 1/16 C ----- C S 7 1992
	from which
	A fir, 18 ins. diam., bears S. 34° W., 68½ lks. dist., mkd. CW 1/16 S7 BT.
	A fir, 18 ins. diam., bears N. 34° W., 30½ lks. dist., mkd. CW 1/16 S7 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over NW. slope.
64.75	Ravine, drains S. 65° W.; continue descending over NW. slope.
72.10	Dirt road, 20 lks. wide, bears N. and S.
76.10	Little Lick Creek, 10 lks. wide, course S. 10° E.; asc. over SE. slope.
79.205	The 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.
	<p>From the center E 1/16 sec. cor. of sec. 7.</p> <p>N. 0° 11' 00" E., on the N. and S. centerline of the NE 1/4 of</p>

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	sec. 7.
	Ascend a broken SE. slope, through heavy timber and dense undergrowth.
1.95	Spur, slopes S. 80° E.; desc. over NE. slope.
10.85	Ravine, drains E.; asc. over SE. slope.
11.970	A point established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1989, recorded in the Douglas County Surveyor's Office, map file No. M108-31; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with a yellow plastic cap mkd. BENTZ SURV. INC.
16.15	Spur, slopes S. 50° E.; continue ascending over SE. slope.
16.980	A point established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1987, recorded in the Douglas County Surveyor's Office, map file No. M105-19; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with yellow plastic cap mkd. BENTZ SURV. INC.
20.005	<p>The NE 1/16 sec. cor. of sec. 7, established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1987, recorded in Douglas County Surveyor's Office map file No. M103-75, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 5 ins. above ground, with a yellow plastic cap mkd. BENTZ SURV. INC., from which bearing trees mkd. by Bentz:</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 70° E., 40 lks. dist., with a healed single blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 22¼° W., 29 lks. dist., with a healed single blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S7 1992</p> <p>From this point, a point established by person(s) unknown, bears N. 1° 08' 00" W., 0.320 chs. dist., monumented with an iron pipe, ½ in. diam., firmly set.</p> <p>Deposit 5/8 in. iron rod inside the stainless steel post.</p>

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	

	N. 0° 14' 00" E., beginning a new measurement.
	Ascend over a SE. slope.
1.50	Spur, slopes N. 80° E.; desc. over NE. slope.
16.67	A point established by Donald A. Bentz, Registered Land Surveyor No. 839, in 1987, recorded in the Douglas County Surveyor's Office map file No. M103-75; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with a yellow plastic cap mkd. BENTZ SURV. INC.
18.75	Big Lick Creek Road, gravel, 20 lks. wide, bears N. 10° W. and S. 60° E.
19.30	Big Lick Creek, 5 lks. wide, course SE.; asc. over SW. slope.
20.000	The E 1/16 sec. cor. of secs. 6 and 7.

	From the N 1/16 sec. cor. of secs. 7 and 8.
	S. 89° 42' 00" W., on the E. and W. centerline of the NE¼ of sec. 7.
	Descend a gentle SW. slope, through a tree farm.
3.10	Big Lick Creek Road, gravel, 20 lks. wide, bears N. 10° W. and S. 10° E.
4.25	Big Lick Creek, 5 lks. wide, course S. 20° E.; asc. over SE. slope.
19.770	The NE 1/16 sec. cor. of sec. 7.

	S. 89° 40' 00" W., beginning a new measurement.
	Ascend over a SE. slope.
19.35	Ridge, bears N. 20° W. and S. 20° E.; desc. over SW. slope.
19.750	The center N 1/16 sec. cor. of sec. 7.

	From the E 1/16 sec. cor. of secs. 7 and 18.
	North, on the N. and S. centerline of the SE¼ of sec. 7.

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	Descend a broken NE. slope.
3.50	Ravine, drains S. 40° E.; asc. over SE. slope.
10.40	Spur, slopes S. 20° E.; desc. over NE. slope.
24.30	Ravine, drains S. 85° E.; asc. over SE. slope.
40.735	The center E 1/16 sec. cor. of sec. 7.
<hr/>	
	From the W 1/16 sec. cor. of secs. 7 and 18.
	N. 0° 20' 00" E., on the N. and S. centerline of the SW ¹ / ₄ of sec. 7.
	Descend over a gentle NW. slope.
1.65	Ravine, drains S. 70° W.; asc. over SW. slope.
7.45	Spur, slopes S. 60° W.; desc. over NW. slope.
12.95	Ravine, drains S. 60° W.; asc. over SW. slope.
15.40	Spur, slopes SW.; desc. over broken NW. slope.
20.75	Ravine, drains N. 80° W.; asc. over SW. slope.
23.05	Spur, slopes S. 80° W.; desc. over NW. slope.
27.35	Ravine, drains N. 80° W.; asc. over SW. slope.
34.55	Spur, slopes West; desc. over NW. slope.
38.65	Ravine, drains N. 60° W.; asc. over SW. slope.
39.15	Spur, slopes N. 80° W.; desc. over NW. slope.
40.410	The center W 1/16 sec. cor. of sec. 7.
<hr/>	
	N. 0° 18' 00" E., on the N. and S. centerline of the NW ¹ / ₄ of sec. 7.
	Descend over a NW. slope, through scattering timber and dense undergrowth.
1.10	Creek, 2 lks. wide, course S. 80° W.; asc. over SW. slope.

Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
6.15	Spur, slopes S. 55° W.; desc. over NW. slope.
10.60	Ravine, drains S. 75° W.; asc. over SE. slope.
13.35	Dirt road, 15 lks. wide, bears N. 50° E. and S. 70° W.
20.095	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. centerline of the NW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	NW 1/16 S7 1992
	from which
	A fir, 15 ins. diam., bears N. 17¼° E., 141 lks. dist., mkd. NW 1/16 S7 BT.
	A fir, 12 ins. diam., bears S. 82½° E., 86 lks. dist., mkd. NW 1/16 S7 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over SE. slope.
33.80	Spur, slopes S. 60° W.; desc. over NW. slope.
32.50	Bottom of descent, slopes N. 80° W.; asc. over SW. slope.
40.185	The W 1/16 sec. cor. of secs. 6 and 7.
	<hr/>
	From the center N 1/16 sec. cor. of sec. 7.
	S. 89° 40' 00" W., on the E. and W. centerline of the NW¼ of sec. 7.
	Descend over a broken SW slope, through heavy timber and dense undergrowth.
13.80	Ravine, drains S. 40° W.; asc. over SE. slope.
19.925	The NW 1/16 sec. cor. of sec. 7.
	Ascend over a broken SE. slope.
23.25	Spur, slopes S.; desc. over a SW. slope.

**Subdivision of Section 7,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
26.80	Ravine, drains S. 20° W.; asc. over SE. slope.
32.35	Spur, slopes S. 40° W.; desc. over a SW. slope.
39.465	The N 1/16 sec. cor. of secs. 7 and 12.
<hr/> <p style="text-align: center;">Subdivision of Section 11, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/>	
	From the 1/4 sec. cor. of secs. 11 and 14.
	N. 0° 34' 00" E., on the N. and S. centerline of sec. 11.
	Along creek bottom, through open pastureland.
10.30	Wire fence, bears NE. and S.
19.405	Point for the center S 1/16 sec. cor. of sec. 11.
	Set an iron rod, 24 ins. long, 3/8 in. diam., 23 ins. in the ground, on right bank of Louis Creek.
	from which
	A fir, 12 ins. diam., bears S. 67° W., 517 lks. dist., mkd. CS 1/16 S11 BT.
	A stainless steel post, 28 ins. long, 2½ ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 70° W., 60 lks. dist., with brass cap mkd. RM CS 1/16 S11 39.6 FT. and an arrow pointing to the corner.
	A cedar, 15 ins. diam., bears N. 68½° W., 447 lks. dist., mkd. CS 1/16 S11 BT.
	Continue along creek bottom, through open pasture.
19.50	Louis Creek, 15 lks. wide, course SE.; asc. over gentle SW. slope.
32.35	Graveled road, 20 lks. wide, bears N. 80° E. and S. 80° W.
38.30	Louis Creek Road, asphalt surface, 30 lks. wide, bears N. 30° W. and S. 10° E.
38.810	Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. centerline.

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. below the ground on the shoulder of Louis Creek Road, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W C 1/4 S 11 1992</p> <p>from which</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 45½° E., 20 lks. dist., with brass cap mkd. RM C 1/4 S11 13.20 FT and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears S. 81½° E., 77 lks. dist., mkd. C 1/4 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post, at the corner point.</p> <p>From this point, a point established as the center 1/4 sec. cor. of sec. 11 by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in Douglas County Surveyor's Office map file No. M94-61 and C.S. file 58/270, bears N. 87° 00' 00" E., 0.110 chs. dist., determined from reference monuments:</p> <p style="padding-left: 40px;">An iron pipe, 1½ ins. diam., firmly set, projecting 15 ins. above ground, bears N. 1° E., 53 lks. dist., with brass cap mkd. T29S R4W C1/4 S11 WC LS866 1983 35.0 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above ground, bears S. 88¼° E., 38 lks. dist., with brass cap mkd. T29S R4W C1/4 S11 WC LS866 1983 25.0 and an arrow pointing to the corner.</p> <p>This point was established using erroneous control and is not utilized in this survey.</p> <p>Ascend over SW. slope.</p>
53.550	<p>From this point, a point established as the witness corner for the center N 1/16 sec. cor. of sec. 11 by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in Douglas County Surveyor's Office map file No. M94-61 and C.S. file No. 58/270, bears West, 0.068 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. WC CN 1/16 S11 LS 866 1983, from which bearing trees mkd. by Ruppert:</p>

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 8 ins. diam., bears N. 74° E., 36½ lks. dist., with a healed double blaze.</p> <p>A cedar, 14 ins. diam., bears N. 51° W., 53 lks. dist., with a healed double blaze.</p> <p>This point was established using erroneous control and is not utilized in this survey.</p>
53.60	Spur, slopes S. 70° W.; desc. over NW. slope.
58.560	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 * S 11 C 1992</p> <p>from which</p> <p>A fir, 14 ins. diam., bears N. 55¼° E., 38 lks. dist., mkd. CN 1/16 S11 BT.</p> <p>A fir, 15 ins. diam., bears S. 82° W., 26 lks. dist., mkd. CN 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the center N 1/16 sec. cor. of sec. 11 by William J. Ruppert, Registered Land Surveyor No. 866, in 1983, recorded in Douglas County Surveyor's Office map file No. M94-61 and C.S. file No. 58/270, bears N. 85° 00' 00" W., 0.057 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd. CN 1/16 S11 LS 866 1983, from which bearing trees mkd. by Ruppert:</p> <p>A fir, 9 ins. diam., bears N. 85° E., 28 lks. dist., with a healed double blaze.</p> <p>A fir, 12 ins. diam., bears S. 85½° W., 36 lks. dist., with a healed double blaze.</p> <p>This point was established using erroneous control and is not utilized in this survey.</p> <p>Descend over NW. slope.</p>

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
61.85	Creek, 5 lks. wide, course S. 60° W.; asc. over SW. slope.
74.90	Spur, slopes W.; desc. over NW. slope.
78.310	The 1/4 sec. cor. of secs. 2 and 11.
	<hr/>
	From the 1/4 sec. cor. of secs. 11 and 12.
	N. 88° 02' 00" W., on the E. and W. centerline of sec. 11.
	Descend a broken NW. slope, through scattering timber and dense undergrowth.
2.35	Dirt road, 10 lks. wide, bears N. 5° E. and S. 5° W.
5.65	Creek, 5 lks. wide, course S. 10° W.; asc. over SE. slope.
10.85	Dirt road, 15 lks. wide, bears NE. and SW.
18.45	Spur, slopes S. 10° W.; desc. over SW. slope.
20.005	Point for the center E 1/16 sec. cor. of sec. 11.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	E 1/16 C ----- C S 11 1991
	from which
	A cedar, 9 ins. diam., bears S. 48° E., 30½ lks. dist., mkd. CE 1/16 S11 BT.
	A fir, 7 ins. diam., bears N. 24° W., 24½ lks. dist., mkd. CE 1/16 S11 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over SW. slope.
21.15	Ravine, drains S. 10° E.; asc. over SE. slope.
26.55	Spur, slopes S. 10° W.; desc. over SW. slope.

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
34.50	Graveled road, 20 lks. wide, bears N. and S.
40.010	The center 1/4 sec. cor. of sec. 11. Descend over a broken SW. slope.
40.20	Louis Creek Road, asphalt surface, 30 lks. wide, bears N. 30° W. and S. 10° E.
44.60	Louis Creek, 10 lks. wide, course S. 60° E.; asc. over SE. slope.
60.395	Point for the center W 1/16 sec. cor. of sec. 11. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W 1/16 C ----- C S 11 1992 </div> from which <div style="margin-left: 40px;"> A fir, 6 ins. diam., bears S. 50½° W., 15 lks. dist., mkd. CW 1/16 S11 BT. A fir, 6 ins. diam., bears N. 36½° W., 43 lks. dist., mkd. CW 1/16 S11 BT. </div> Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Ascend over SE. slope, changing to NE. slope.
80.780	The 1/4 sec. cor. of secs. 10 and 11. <hr/> From the E 1/16 sec. cor. of secs. 11 and 14. N. 0° 47' 30" E., on the N. and S. centerline of the SE¼ of sec. 11. Descend a broken NW. slope, through heavy timber and dense undergrowth.
7.35	Dirt road, 20 lks. wide, bears N. 85° E. and S. 85° W.
12.80	Creek, 5 lks. wide, course S. 55° W.; asc. over SW. slope.
18.70	Spur, slopes S. 60° W.; desc. over NW. slope.

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
19.465	<p>Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. centerline of the SE¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S11 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 17 3/4° E., 27 lks. dist., mkd. SE 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 82° W., 41½ lks. dist., mkd. SE 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NW. slope.</p>
29.95	Creek, 5 lks. wide, course S. 60° W.; asc. over SW. slope.
31.60	Graveled road, 25 lks. wide, bears N. 40° E. and S. 60° W.
32.95	Graveled road, 25 lks. wide, bears S. 70° E. and S. 55° W.
38.935	The center E 1/16 sec. cor. of sec. 11.
	<hr/> <p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 87° 50' 30" W., on the E. and W. centerline of the SE¼ of sec. 11.</p> <p>Descend a broken SW. slope changing to NW. slope, through second growth timber and dense undergrowth.</p>
19.35	Graveled road, 25 lks. wide, bears N. 30° E. and S.
19.940	The SE 1/16 sec. cor. of sec. 11.
	Descend over NW. slope.
36.45	Louis Creek Road, asphalt surface, 35 lks. wide, bears N. 20° E. and S. 25° W.
39.80	Louis Creek, 15 lks. wide, course S. 15° E.; cont. over creek bottom.

Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
39.870	<p>The center S 1/16 sec. cor. of sec. 11.</p> <hr/> <p>From the CW 1/16 sec. cor. of sec. 11.</p> <p>N. 0° 08' 30" E., on the N. and S. centerline of the NW¼ of sec. 11.</p> <p>Ascend a broken SE. slope, through scattering timber and dense undergrowth.</p>
7.35	<p>Spur, slopes N. 70° E.; desc. over NE. slope.</p>
19.505	<p>Point for the NW 1/16 sec. cor. of sec. 11, at intersection with the E. and W. centerline of the NW¼.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. below surface of dirt road, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S11 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 31° E., 39 lks. dist., mkd. NW 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 88° W., 29 lks. dist., mkd. NW 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located in the center of a dirt road, 20 lks. wide, bears N. 70° E. and S. 55° W.</p> <p>Descend over NE. slope.</p>
21.65	<p>Creek, 2 lks. wide, course N. 55° E.; asc. over SE. slope.</p>
39.020	<p>The W 1/16 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 11.</p> <p>N. 88° 42' 00" W., on the E. and W. centerline of the NW¼ of sec. 11.</p> <p>Descend a broken NW. slope, through heavy timber and dense undergrowth.</p>

**Subdivision of Section 11,
T. 29 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	
7.05	Louis Creek Road, asphalt surface, 35 lks. wide, bears N. 10° W. and S. 10° E.
10.35	Louis Creek, 10 lks. wide, course S. 25° W.; asc. over NE. slope.
17.25	Dirt road, 20 lks. wide, bears N. 50° W. and S. 60° E.
20.525	The NW 1/16 sec. cor. of sec. 11. Ascend over NE. slope, changing to SE. slope.
41.045	The N 1/16 sec. cor. of secs. 10 and 11.
<hr/> <p>Subdivision of Section 31, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p> <hr/>	
	From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp. N. 20° 49' 00" E., on the N. and S. centerline of sec. 31. Descend along a nearly level broken West slope.
10.70	Creek, 2 lks. wide, course SW.; asc. over SE. slope.
20.420	Point for the center S 1/16 sec. cor. of sec. 31. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	C S 1/16 * S 31 C 1992
	from which
	A maple, 19 ins. diam., bears S. 52¼° E., 71 lks. dist., mkd. CS 1/16 S31 BT.
	A cedar, 18 ins. diam., bears S. 51° W., 10½ lks. dist., mkd. CS 1/16 S31 BT.
	Ascend over SE. slope.
40.35	Ridge, bears N. 85° E. and N. 70° W.; desc. over NE. slope, also dirt road, 15 lks. wide, bears same.
40.840	Point for the center 1/4 sec. cor. of sec. 31, at intersection

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T29S R4W C 1/4 S 31 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 45° E., 9 lks. dist., mkd. C 1/4 S31 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 85½° W., 43 lks. dist., mkd. C 1/4 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NE. slope.</p>
51.25	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 60° W. and East.
57.80	Creek, 5 lks. wide, course S. 55° E.; asc. over SE. slope.
59.775	Point for the center N 1/16 sec. cor. of sec. 31.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 * S 31 C 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 66¼° E., 37 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 27 3/4° W., 24 lks. dist., mkd. CN 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p>

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
70.25	Dirt road, 20 lks. wide, bears S. 60° W. and East.
78.710	The 1/4 sec. cor. of secs. 30 and 31.

	From the 1/4 sec. cor. of secs. 31 and 32.
	S. 87° 04' 00" W., on the E. and W. centerline of sec. 31.
	Descend a broken NW. slope.
1.55	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 30° E. and S. 40° W.
4.50	Ravine, drains N.; asc. over NE. slope.
7.65	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 50° W. and S. 50° E.
16.80	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 65° E. and N. 65° W.
22.40	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 70° E. and N. 70° W.
39.320	The center 1/4 sec. cor. of sec. 31.
	Ascend over NE. slope
40.55	Ridge, bears N. 65° W. and S. 65° E.; continue to ascend along ridgetop.
48.75	Ridge, bears N. 70° W. and S. 70° E.; desc. over a SW. slope.
51.640	Point for the center W 1/16 sec. cor. of sec. 31.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.
	W 1/16 C ----- C S 31 1992
	from which
	A fir, 14 ins. diam., bears N. 75½° E., 117 lks. dist., mkd. CW 1/16 S31 BT.
	A fir, 8 ins. diam., bears N. 63¼° W., 93 lks. dist., mkd.

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	CW 1/16 S31 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Descend over SW. slope.
56.31	Ravine, drains S. 30° E.; asc. over NE. slope.
58.55	Dirt road, 20 lks. wide, bears N. and S.
59.55	Ridge, bears N. and S.; desc. over a NW. slope.
63.095	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<hr/>
	From the W 1/16 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.
	N. 10° 52' 00" E., on the N. and S. centerline of the SW¼ of sec. 31.
	Ascend a broken SW. slope changing to SE. slope.
10.75	Ravine, drains S. 60° E.; continue ascending over a SW. slope.
16.15	Spur, slopes S. 10° E.; continue ascending over a SE. slope.
18.50	Spur, slopes S. 60° E.; desc. over NE. slope.
19.885	Point for the SW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. centerline of the SW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	SW 1/16 S31 1992
	from which
	A fir, 8 ins. diam., bears N. 81½° E., 30 lks. dist., mkd. SW 1/16 S31 BT.
	A fir, 14 ins. diam., bears S. 8½° W., 8½ lks. dist., mkd. SW 1/16 S31 BT.
	Descend over NE. slope.
29.60	Ravine, drains S. 40° E.; asc. over SW. slope.

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
36.10	Dirt road, 20 lks. wide, bears N. 70° W. and E.
39.770	The center W 1/16 sec. cor. of sec. 31.
	<hr/>
	From the center S 1/16 sec. cor. of sec. 31.
	S. 83° 02' 00" W., on the E. and W. centerline of the SW¼ of sec. 31.
	Ascend over a gentle SE. slope.
1.45	Spur, slopes S. 25° E.; desc. over SW. slope.
3.05	Ravine, drains S. 40° E.; asc. over NE. slope.
8.860	The SW 1/16 sec. cor. of sec. 31.
	Ascend over NE. slope.
10.55	Spur, slopes S. 35° E.; desc. over SW. slope.
16.85	Ravine, drains S. 40° E.; asc. over NE. slope.
17.100	The S 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.
	<hr/>
	From the center W 1/16 sec. cor. of sec. 31.
	N. 9° 45' 30" E., on the N. and S. centerline of the NW¼ of sec. 31.
	Ascend over a SW. slope, through heavy timber and dense undergrowth.
1.00	Ridge, bears N. 70° W. and S. 70° E.; desc. over a NE. slope, also a dirt road, 20 lks. wide, bears the same.
17.30	Ravine, drains N. 75° E.; asc. over SE. slope.
19.055	Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. centerline of the NW¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	NW 1/16 S31 1992
	from which

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 13 ins. diam., bears S. 76½° E., 19 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>A fir, 17 ins. diam., bears S. 14½° W., 48 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over SE. slope.</p>
20.30	Spur, slopes S. 85° E.; desc. over NE. slope.
23.20	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 60° W. and S. 25° E.; also bottom of descent, drains S. 25° E.; asc. over a SE. slope.
31.85	Ridge, bears N. 85° E. and S. 85° W.; desc. over a NE. slope.
38.110	The W 1/16 sec. cor. of secs. 30 and 31.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 31.</p> <p>N. 88° 22' 00" W., on the E. and W. centerline of the NW¼ of sec. 31.</p> <p>Ascend over a SE. slope, through scattering timber and dense undergrowth.</p>
14.50	Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 20° E. and S. 35° W.
15.815	The NW 1/16 sec. cor. of sec. 31.
	Ascend over a broken SE. slope.
17.65	Ridge, bears N. 35° E. and S. 35° W.; desc. over a NW. slope, also dirt road, 20 lks. wide, bears same.
23.720	Point for the C-W-NW 1/64 sec. cor. of sec. 31.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 31 C-W-NW 1/64 1992</p>

Subdivision of Section 31,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 68° E., 37 lks. dist., mkd. C-W-NW 1/64 S31 BT.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 33° W., 39 lks. dist., mkd. C-W-NW 1/64 S31 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NW. slope.</p>
30.520	<p>The N 1/16 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp.</p> <hr/> <p>From the C-W-NW 1/64 sec. cor. of sec. 31.</p> <p>N. 4° 22' 30" E., on the N. and S. centerline of the NW¼ of the NW¼ of sec. 31.</p> <p>Descend over a NW. slope, through heavy timber and dense undergrowth.</p>
4.70	<p>Ravine, drains S. 60° W.; asc. over SW. slope.</p>
8.25	<p>Days Creek Cutoff Road, graveled, 30 lks. wide, bears N. 70° W. and S. 70° E.</p>
15.35	<p>Ridge, bears N. 65° W. and S. 65° E.; desc. over a NE. slope.</p>
19.375	<p>The WW 1/64 sec. cor. of secs. 30 and 31.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in Douglas County northeast of Myrtle Creek, Oregon. The elevations range from about 600 feet above sea level, to about 2,500 feet above sea level.</p> <p>The area is drained by North Myrtle Creek, Big Lick Creek, and Little Lick Creek, near sections 6 and 7, with numerous small and seasonal drainages flowing into them. Section 11 is drained by Louis Creek, with numerous small and seasonal drainages flowing into it. Section 31 has numerous small and seasonal drainages flowing from it. The soil consists of a clay loam. Portions of sections 6 and 7 were burned in forest fires in 1987. The lands are forested with fir, cedar, spruce, yew, pine, alder, cherry, maple, oak, madrone, willow, ash, and chinquapin. Undergrowth</p>

T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

consists of ferns, poison oak, arrowwood, hazel, Oregon grape, salal, huckleberry, blackberry, thimbleberry, salmonberry, gooseberry, currant, wild rose, rhododendron, manzanita, and young timber.

Access is gained to sections 6 and 7 via County Highway No. 15, with numerous paved, graveled, and dirt roads branching from it into the area. Access is gained to section 11 via County Highway 18, with numerous paved, graveled, and dirt roads from it into the area. Access is gained to section 31 via County Highway No. 42, and is also locally known as the Days Creek Cutoff Road, with numerous paved, graveled, and dirt roads branching from it into the area.

There were no mineral deposits noted along the lines resurveyed. The land is used mainly for timber production, farming, and recreation.

The mean magnetic declination is $18^{\circ} 30'$ E., with a range of 1° in local attraction.
