

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
TOWNSHIP 21 SOUTH, RANGE 9 WEST,
AND A PORTION OF THE SUBDIVISIONAL LINES,
AND CERTAIN DONATION LAND CLAIM BOUNDARIES
AND
THE SUBDIVISION OF SECTIONS 3, 4, 9, AND 10,
TOWNSHIP 22 SOUTH, RANGE 9 WEST,
OF THE
WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Boyd W. Peterson, Cadastral Surveyor

John A. Farmer, Cadastral Surveyor

Under Special Instructions dated September 19, 1995,
and approved September 19, 1995,
which provided for the surveys included under Group No. 1791,
and Assignment Instructions dated October 23, 1995.

Survey commenced October 23, 1995

Survey completed February 3, 1998

T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary, township 21 south, range 9 west, and a portion of the subdivisional lines, and certain Donation Land Claim boundaries and the subdivision of sections 3, 4, 9, and 10, township 22 south, range 9 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey, is as follows:

The meanders of the North Bank of the Umpqua River and a portion of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, in 1855.

Donation Land Claims Nos. 37 through 45, were surveyed by Dennis Hathorn, U.S. Deputy Surveyor, in 1856.

A portion of the subdivisional lines were surveyed by William H. Byars, U.S. Deputy Surveyor, in 1874.

The south boundary of T. 21 S., R. 9 W., was surveyed by Alonzo Gesner, U.S. Deputy Surveyor, in 1893.

A portion of the subdivisional lines were resurveyed and surveyed by Alonzo Gesner and Elmer O. Worrick, U.S. Deputy Surveyors, in 1894.

A portion of the subdivisional lines and Donation Land Claim boundaries were retraced by George S. Pershin, U.S. Deputy Surveyor, in 1896.

A portion of the subdivisional lines and Donation Land Claim boundaries were resurveyed by James E. Jelley, Cadastral Surveyor, in 1970.

A portion of the south boundary, T. 21 S., R. 9 W., and a portion of the subdivisional lines and Donation Land Claim boundaries were resurveyed and section 5 subdivided, T. 22 S., R. 9 W., by Joel E. Robb, Cadastral Surveyor, in 1985.

A portion of the subdivisional lines were resurveyed by Joel E. Robb, Cadastral Surveyor, in 1987.

A portion of the subdivisional lines, T. 21 S., R. 9 W., were resurveyed by Boyd W. Peterson, Cadastral Surveyor, in 1994-95.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated September 19, 1995, for Group No. 1791, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not to exceed 1:4000 in error. Measured distance and direction have been adjusted by the Cadastral Measurement Management (CMM), a computer

T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

program that incorporates least squares analysis. The adjusted bearings and distances are reported to the nearest second and 0.001 of a chain.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position (NAD 1927) of the true closing corner of sections 4 and 5, on the north boundary of the township, as reported in the 1985 dependent resurvey by Joel E. Robb, is as follows:

Latitude: 43° 41' 35.84" N. Longitude: 123° 47' 07.31" W.

The mean magnetic declination is 19° East.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

(Restoring the survey by Alonzo Gesner, in 1894,
and the resurvey by Joel E. Robb, in 1985)

Beginning at the point for the cor. of secs. 2, 3, 34, and 35 at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2 ½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S R9W
S34 * S35
-----3-----
S3 * S2
T22S
1996

from which

A fir, 10 ins. diam., bears N. 48 3/4° E., 85 lks. dist., mkd.
T21S R9W S35 BT.

A fir, 12 ins. diam., bears S. 32½° E., 61 lks. dist., mkd.
T22S R9W S2 BT.

A fir, 18 ins. diam., bears S. 71° W., 47 lks. dist., mkd.
T22S R9W S3 BT.

A fir, 21 ins. diam., bears N. 29½° W., 18 lks. dist., mkd.
T21S R9W S34 BT.

Deposit a magnet in a white plastic case at base of stainless steel post.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, a point established as the cor. of secs. 2, 3, 34, and 35, by International Paper Co., now Roseburg Lumber Co., recorded in their office at Reedsport, Oregon, not accepted in this survey due to improper procedures, bears N. 4° 10' 46" E., 0.245 chs. dist., determined at record distance from the remains of bearing trees mkd. by International Paper Co.:</p> <p style="padding-left: 40px;">A fir stump, 61 ins. diam., bears S. 16½° E., 251 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A cedar stump, 36 ins. diam., bears N. 44½° W., 150½ lks. dist., no marks visible.</p> <p>Also from this point, the cor. of secs. 35 and 36 only, bears S. 89° 23' 04" E., 78.570 chs. dist.; monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R9W S 35*S 36 ---2--- S1 T22S R9W 1994</p> <p>from which the remains of an original bearing tree mkd. by Gesner, reported obliterated by Worrick in 1895</p> <p style="padding-left: 40px;">A decayed fir stub, size indeterminate, bears S. 44° E., 47 lks. dist., with scribe marks S/ 9W S1 visible on open blaze.</p> <p>and bearing trees mkd. by Peterson</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 16° E., 26½ lks. dist., with scribe marks T21S R9W S36 BT visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 56¼ W., 22½ lks. dist., with scribe marks T21S R9W S35 BT visible on a partially healed blaze.</p> <p>From this point, a point established as the closing corner of sections 1 and 2 by person(s) unknown, bears N. 88° 03' 45" W, 1.205 chs. dist., monumented with an iron pipe, ½ in. diam., firmly set, projecting 8 ins. above ground.</p> <p>This control line was retraced and careful search was made for the 1/4 sec. cor. of sec. 35 only, which was not recovered.</p> <p>N. 89° 23' 04" W., on the S. bdy. of sec. 34.</p> <p>Descend over W. slope through moderate timber and dense undergrowth.</p>
4.15	Creek, 1 lk. wide, course S. 10° W.; asc. over E. slope.
13.00	Top of spur, slopes S.; desc. over SW slope.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
24.75	Creek, 1 lk. wide, course S. 40° E.; asc. over E. slope.
38.40	Spur, slopes S. 10° E., desc. over SW. slope.
39.286	<p>Point for the 1/4 sec. cor. of secs. 34 only, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R9W 1/4 S 34 ----- T22S 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 14° E., 5½ lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 6½° W., 26½ lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit a magnet in a white plastic case at base of stainless steel post.</p> <p>Continue descent over SW. slope.</p>
39.310	<p>Point for the 1/4 sec. cor. of sec. 3 only, T. 22 S., R. 9 W.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S ----- 1/4 S 3 T22S R9W 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 59° E., 51 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 75° W., 37 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at base of stainless steel post.</p> <p>Continue descent over SW. slope.</p>
43.30	Dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
44.80	Creek, 2 lks. wide, course S. 50° E.; asc. over NE. slope.
59.90	Top of ascent, slopes S. 60° W.; desc. over NW. slope.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
62.30	Creek, 1 lk. wide, course N. 70° E.; asc. over SE. slope.
78.572	The cor. of secs. 33 and 34 only, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T21S * R9W S 33 * S 34 -----2----- S 3 1971
	from which the remains of an original bearing tree
	A sawed fir stump, 26 ins. diam., bears N. 88° W., 59 lks. dist., with scribe marks T21 visible on an opened blaze.
	and bearing trees mkd. by Powell, reported by Robb
	A fir, 6 ins. diam., bears S. 80° E., 10½ lks. dist., with healed blaze.
	A fir, 13 ins. diam., bears N. 53° W., 6 lks. dist., with healed blaze.
	and a bearing tree mkd. by Robb
	A fir, 10 ins. diam., bears N. 18¼° E., 42 lks. dist., with scribe marks T21S R9W S34 BT visible on a partially healed blaze.
	An iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, is alongside the iron post.
	S. 89° 57' 23" W., on the S. bdy. of sec. 33.
	Ascend over E. slope.
1.00	Top of ascent, slopes S.; desc. over a gentle NW. slope.
3.537	True point for the closing corner of secs. 3 and 4, T. 22 S., R. 9 W., hereinafter described.
23.516	Point for the E 1/16 sec. cor. of secs. 4 only, T. 22 S., R. 9 W.
	Set a stainless steel post, 28 ins. long, 2 ½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	----- E 1/16 S 4 1996
	from which
	A fir, 14 ins. diam., bears S. 80 ¾° E., 57 lks. dist., mkd. E 1/16 S4 BT.

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 21 ins. diam., bears S. 10 3/4° W., 86½ lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue descent over SW. slope.</p>
32.25	Ravine, drains S.; asc. over SE. slope.
39.698	<p>The 1/4 sec. cor. of secs. 33 only, perpetuated by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, recorded in the Douglas County Courthouse file No. 41/292 and plat No. M 10-80; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above the ground, from which the remains of an original bearing tree:</p> <p style="text-align: center;">A fir stump, 47 ins. diam., bears N. 8½° E., 16 lks. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 ½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21S R9W 1/4 S 33 ----- T22S 1996</p> </div> <p>from which new bearing trees</p> <p style="text-align: center;">A fir, 5 ins. diam., bears N. 28½° E., 31½ lks. dist., mkd. X BT.</p> <p style="text-align: center;">A fir, 10 ins. diam., bears N. 60° W., 17 lks. dist., mkd. 1/4 S33 BT.</p> <p>Deposit the iron pipe and a magnet in a white plastic case at base of stainless steel post.</p> <div style="text-align: center;"> <p>-----</p> </div> <p>S. 89° 08' 44" W., beginning new measurement.</p> <p>Continue ascent over SE. slope.</p>
3.797	<p>Point for the 1/4 sec. cor. of sec. 4 only, T. 22 S., R. 9 W.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21S ----- 1/4 S 4 T22SR9W 1996</p> </div> <p>from which</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 9 ins. diam., bears S. 80¼° E., 10½ lks. dist., mkd. 1/4 S4 BT.</p> <p>A fir, 6 ins. diam., bears S. 65¼° W., 18½ lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at base of stainless steel post.</p> <p>Continue ascent over SE. slope.</p>
10.65	Top of ascent, slopes S. 20° W.; desc. over a W. slope.
15.05	Bottom of descent, slopes S.; asc. over SE. slope.
21.15	Top of ascent, slopes S. 10° W.; desc. over a W. slope.
23.776	<p>Point for the W 1/16 sec. cor. of sec. 4 only, T. 22 S., R. 9 W.</p> <p>Set a stainless steel post, 28 ins. long, 2 ½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">----- W 1/16 S 4 1996</p> <p>from which</p> <p>A fir, 8 ins. diam., bears S. 2° E., 75½ lks. dist., mkd. W 1/16 S4 BT.</p> <p>A fir, 53 ins. diam., bears S. 76¼° W., 45 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at base of stainless steel post.</p> <p>Continue descent over W. slope.</p>
40.150	<p>The cor. of secs. 32 and 33 only, monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T21S R9W S 32 * S 33 -----2----- 1985</p> <p>from which the remains of original bearing trees</p> <p>A fir snag, 19 ins. diam., bears S. 36° E., 104 lks. dist., no marks visible.</p> <p>A fir stump, 22 ins. diam., bears S. 34¼° W., 99 lks. dist., with axe marks on open face.</p> <p>A fir stump, 47 ins. diam., bears N. 71° W., 105 lks. dist., no marks visible on an open face.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	<p>and bearing trees mkd. by Robb</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 72° E., 11 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 38¼° W., 71 lks. dist., with healed blaze.</p> <hr/> <p>S. 89° 52' 58" W., on the S. bdy. of sec. 32.</p> <p>Continue descent over SW. slope.</p> <p>9.078 The true closing corner of secs. 4 and 5, T. 22 S., R. 9 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T21S R9W S32 -----O----- S5 * S4 T22S R9W CC 1985 </div> <p>from which bearing trees mkd. by Robb</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 72° E., 56 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 75° W., 66 lks. dist., with healed blaze.</p> <p>From this point, the original closing corner of secs. 4 and 5 bears N. 0° 01' E., 0.139 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> COUNTY SURVEYORS OFFICE T21S R9W S32 ----- S5 * S4 T22S R9W AM 1975 </div> <p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A fir, 46 ins. diam., bears N. 20½° E., 42 lks. dist., with illegible scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 39 ins. diam., bears S. 71½° E., 101 lks. dist., with scribe marks S B visible on an open face.</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears S. 52° W., 175 lks. dist., no marks visible.</p>
--------	--

**Dependent Resurvey of a Portion of the South Boundary,
T. 21 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS

The original corner stone is buried alongside the iron post.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Harvey Gordon and Charles T. Gardner, the 1874 survey by William H. Byars, the 1894 resurvey and survey by Alonzo Gesner and E. O. Worrick, the 1896 retracement by George S. Pershin, the 1970 resurvey by James E. Jelley, and the 1987 resurvey by Joel E. Robb)

From the cor. of secs. 10, 11, 14 and 15, perpetuated by Wilford N. Haines, Registered Land Surveyor No. 239, in 1967, recorded in the Douglas County Courthouse File No. 55/47 and M 34-31, and further perpetuated by Bruce A. Shaner, Registered land Surveyor No. 430, in 1977; monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

$$\begin{array}{r} T\ 22\ S\ R\ 9\ W \\ 10\ * \ 11 \\ \hline 3 \\ 15\ * \ 14 \\ 1977 \end{array}$$

from which the remains of the original bearing trees

A fir stub, size indeterminate, bears S. 76° E., 39 lks. dist., no marks visible.

A fir, 65 ins. diam., bears S. 59° W., 230 lks. dist., with illegible scribe marks visible on an open face. (Record, S. 48½° W., 221 lks.)

and bearing trees mkd. by Shaner

A fir stump, 31 ins. diam., bears S. 75° E., 101 lks. dist., no marks visible on a decayed face.

A fir, 34 ins. diam., bears N. 24° E., 39½ lks. dist., with healed face.

A fir, 40 ins. diam., bears N. 47° W., 94½ lks. dist., with healed blaze.

and a new bearing tree

A fir, 5 ins. diam., bears S. 29½° E., 57½ lks. dist., mkd. X BT.

N. 0° 39' 51" W., bet. secs. 10 and 11.

Ascend over S. slope through moderate timber and dense undergrowth.

5.95 Spur, slopes S. 70° E.; desc. over N. slope.

20.70 Creek, 5 lks. wide, course N. 55° W.; asc. over SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
27.25	Spur, slopes W.; desc. over N. slope.
43.522	Point for the 1/4 sec. cor. of secs. 10 and 11 at proportionate distance using the irregular boundary method; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W 1/4 S 10 * S 11 1996 </div> from which <div style="margin-left: 40px;"> A fir, 12 ins. diam., bears S. 24° E., 20 lks. dist., mkd. 1/4 S11 BT. A fir, 10 ins. diam., bears S. 43½° W., 55 lks. dist., mkd. 1/4 S10 BT. </div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Top of ascent, slopes W.; desc. over NE. slope. <div style="text-align: center;"> <hr style="width: 20%; margin: 0 auto;"/> </div> N. 0° 51' 34" W., beginning new measurement. Continue descent over NE. slope.
8.00	Creek, 2 lks. wide, course N. 70° W.; asc. over S. slope.
15.85	Spur, slopes W.; desc. over NW. slope.
20.45	Creek, 6 lks. wide, course S. 35° W.; asc. over S. slope.
34.45	Spur, slopes S. 70° E.; desc. over NE. slope.
40.921	The cor. of secs. 2, 3, 10 and 11, determined at record bearing and distance from the remains of a bearing tree mkd. by Worrick: <div style="margin-left: 40px;"> A fir stump, 40 ins. diam., bears S. 38° W., 34 lks. dist., with scribe marks 22S visible on an opened blaze. </div> At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W S 3 * S 2 -----3----- S 10 * S 11 1995 </div> and new bearing trees

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>A fir, 12 ins. diam., bears N. 68° E., 35½ lks. dist., mkd. T22S R9W S2 BT.</p> <p>A fir, 13 ins. diam., bears S. 52° E., 31½ lks. dist., mkd. T22S R9W S11 BT.</p> <p>A fir, 12 ins. diam., bears S. 60° W., 28 lks. dist., mkd. T22S R9W S10 BT.</p> <p>A fir, 12 ins. diam., bears N. 48 3/4° W., 28 lks. dist., mkd. T22S R9W S3 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
	<p>S. 89° 14' 57" W., bet. secs. 3 and 10.</p> <p>Ascend over E. slope through moderate timber and dense undergrowth.</p>
5.50	Spur, slopes S. 40° W.; desc. over NW. slope.
19.85	Ravine, drains S. 50° W.; asc. over SE. slope.
28.55	Spur, slopes S.; desc. over SW. slope.
37.65	Creek, 4 lks. wide, course S. 40° W.; asc. over SE. slope.
39.430	<p>The 1/4 sec. cor. of secs. 3 and 10, perpetuated from original evidence no longer in existence by International Paper Co., now Roseburg Lumber Co., recorded in their office at Reedsport, Oregon; monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W S 3 1/4 ----- S 10 1996</p> <p>from which new bearing trees</p> <p>A fir, 20 ins. diam., bears S. 3 3/4° W., 38½ lks. dist., mkd. 1/4 S10 BT.</p> <p>A fir, 14 ins. diam., bears N. 75½° W., 21 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit iron pipe and a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the N 1/16 sec. cor. of sec. 4 only, on the E. bdy. of the section, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 * S 4 * 1987</p> <p>from which the remains of bearing trees mkd. by Robb</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 42½° W., 40½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 2° W., 32½ lks. dist., with healed blaze.</p> <p>N. 0° 44' 13" E., bet. secs. 3 and 4.</p> <p>Descend over broken W. slope through moderate timber and dense undergrowth.</p>
11.60	Dirt road, 20 lks. wide, bears N. 70° W. and S. 70° E.
14.75	Dirt road, 20 lks. wide, bears E. and W.
18.360	<p>Intersect N. bdy. of township, true point for the closing corner of secs. 3 and 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 9 W S 33 ----- S 4 * S 3 CC T 22 S 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 65¼° E., 162½ lks. dist., mkd. T22S R9W S3 CC BT.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 7 3/4° W., 37 lks. dist., mkd. T22S R9W S4 CC BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, the original closing corner for secs. 3 and 4, bears N. 0° 44' 13" E., 0.148 chs. dist.; monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS

T 21 S R 9 W
S 33

S 4 * S 3
T 22 S
CC
1987

from which bearing trees mkd. by Robb

A fir, 13 ins. diam., bears S. $10\ 3/4^\circ$ E., $84\ 1/2$ lks. dist., with healed blaze.

A fir, 20 ins. diam., bears S. $61\ 1/2^\circ$ W., 55 lks. dist., with healed blaze.

I add the marks AM and bury the iron post 6 ins. below the surface of the ground.

From the cor. of secs. 8, 9, 16, and 17, monumented with an iron post, $1\ 1/4$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 22 S
S 8 * S 9
-----3-----
S 17 * S 16
R 9 W
1962

from which bearing trees mkd. by Godfrey and Tracy, Deputy County Surveyors, in 1962, reported by Jelley

A fir, 29 ins. diam., bears N. 67° E., $37\ 1/2$ lks. dist., with healed blaze.

A fir, 28 ins. diam., bears N. 86° W., 53 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. $35\ 1/2^\circ$ W., $160\ 1/2$ lks. dist., with healed blaze.

and bearing trees mkd. by Jelley

A fir, 25 ins. diam., bears S. $50\ 1/4^\circ$ E., $19\ 1/2$ lks. dist., with healed blaze. (This tree was remarked by Robb in 1987.)

A fir, 17 ins. diam., bears S. $5\ 3/4^\circ$ W., 25 lks. dist., with healed blaze.

From this point, a point established by person(s) unknown, reported by Robb, bears N. $73^\circ\ 00'$ E., 0.038 chs. dist.; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground.

N. $0^\circ\ 36'\ 06''$ W., bet. secs. 8 and 9.

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
27.457	<p>Descend over broken NW. slope through moderate timber and dense undergrowth.</p> <p>The angle point between secs. 8 and 9, determined at record bearing and distance from the remains of the bearing tree mkd. by Worrick:</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 8° E., 35 lks. dist., with scribe marks S9 T22S R9W visible on an opened face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">AP T 22 S R 9 W S 8 * S 9 1998</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 18½° E., 18 lks. dist., mkd. AP S9 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 32° W., 37½ lks. dist., mkd. AP S8 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 07' 54" W., beginning new measurement.</p> <p>Continue descent over NW. slope.</p>
1.295	<p>Intersect the N. bdy. of Donation Land Claim No. 40, point for the crossing closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T22S R9W CCC S 8 * S 9 -2- C 40 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 69° E., 95½ lks. dist., mkd. T22S R9W C40 CCC BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 8½° W., 50 lks. dist., mkd. T22S R9W C40 CCC BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From this point, the SE. cor. of Donation Land Claim No. 39, located on the N. bdy. of Donation Land Claim No. 40, bears S. 62° 45' 46" W., 1.280 chs. dist., hereinafter described.</p> <p>Continue descent over N. slope.</p>
4.15	Creek, 20 lks. wide, course S. 65° W.; asc. over SE. slope.
6.30	Graveled road, 25 lks. wide, bears N. 70° E. and S. 70° W.
12.946	<p>The ¼ sec. cor. of secs. 8 and 9, perpetuated by Douglas County Surveyor's Office in 1977 in an unrecorded survey, further perpetuated by Douglas County Surveyor's Office in 1996, recorded in the Douglas County Courthouse File No. 64/69-5; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W 1/4 S 8 * S 9 1977</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears S. 68½° E., 54 lks. dist., with scribe marks 1/4 S R visible on an open face.</p> <p>and bearing trees mkd. by Douglas County Surveyor's Office in 1977</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 88½° E., 7½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 75° W., 38 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Douglas County Surveyor's Office in 1996</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 16½° E., 15½ lks. dist., with scribe marks 1/4 S9 BT visible on an open face.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 21° W., 51 lks. dist., with scribe marks 1/4 S8 BT visible on an open face.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 07' 18" W., beginning new measurement, on the E. bdy. of sec. 8.</p> <p>Ascend over SW. slope.</p>
26.90	Top of ascent, slopes W.; desc. over NW. slope.
32.00	Ravine, drains SW.; asc. over SE. slope.
35.644	<p>From this point, the original closing cor. of secs. 4 and 9, bears East, 0.065 chs. dist., perpetuated by Vernon T. Hosford, Registered Land Surveyor No. 253, in 1954, and recorded in the Douglas County Courthouse file Nos. 41/292 and M 10-80, further perpetuated by John M. Powell, Deputy County Surveyor, in 1971,</p>

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>recorded in the Douglas County Courthouse File No. 53/66; monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S * S 4 S 8 *----- CC * S 9 1971</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, 33 ins. diam., bears S. 52° E., 23 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Powell</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 74° E., 19 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 58° E., 62 lks. dist., with healed blaze.</p> <p>Ascend over SW. slope.</p>
38.629	<p>Intersect the E. bdy. of Donation Land Claim No. 39. No permanent monument established.</p> <p>From this point, the NE. cor. of Donation Land Claim No. 39 bears N. 0° 10' 14" E., 4.555 chs. dist., hereinafter described.</p>
39.406	<p>The cor. of secs. 5 and 8 only, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S S 5 * -----3 S 4 S 8 * R 9 W 1971</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole, bears S. 26½° E., 13 lks. dist., with a downed fir alongside, size indeterminate, with illegible scribe marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 29° W., 33 lks. dist., with scribe marks T22S R9W S8 visible on open face.</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 88½° W., 29 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Powell in 1971, reported by Robb in 1985</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 61° E., 9½ lks. dist., with healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional lines,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS

A fir, 10 ins. diam., bears S. 69° E., 19½ lks. dist., with healed blaze.

A fir, 12 ins. diam., bears S. 86° W., 13 lks. dist., with healed blaze.

and a bearing tree mkd. by Robb in 1985

A fir, 12 ins. diam., bears N. 31° W., 35½ lks. dist., with healed blaze.

**Dependent Resurvey of the East Boundary
of Donation Land Claim No. 39,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

(Restoring the survey by Dennis Hathorn, in 1856,
and the resurvey by George S. Pershin, in 1896)

From the SE. cor. of Donation Land Claim No. 39, located on the N. bdy. of Donation Land Claim No. 40, perpetuated by person(s) unknown, utilized by Richard J. Hintz, Registered Land Surveyor No. 497, in 1971, recorded in the Douglas County Courthouse file No. M 42-40, and further perpetuated by Douglas County Surveyor's Office in 1996, recorded in the Douglas County Courthouse file No. 64/66-6. This point is harmoniously related to other original corners and is accepted as the best available evidence of the original corner position; monumented with an iron post, 1½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYOR

T 22 S

SE * R

COR * 9

* W

DLC 39

1996

from which bearing trees mkd. by the Douglas County Surveyor's Office

A fir, 21 ins. diam., bears N. 6½° E., 5 lks. dist., with scribe marks SE DLC39 CS BT visible on an open face.

A fir, 14 ins. diam., bears N. 89° W., 17½ lks. dist., with scribe marks SE DLC39 CS BT visible on an open face.

A maple, 10 ins. diam., bears N. 21° W., 16½ lks. dist., with scribe marks SE DLC39 CS BT visible on an open face.

N. 0° 10' 14" E., on the E. bdy. of Donation Land Claim No. 39.

Descend over N. slope through moderate timber and dense undergrowth.

Dependent Resurvey of the East Boundary
of Donation Land Claim No. 39,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
3.60	Creek, 20 lks. wide, course S. 65° W.; asc. over SE. slope.
5.20	Graveled road, 25 lks. wide, bears N. 70° E. and S. 70° W.
40.15	Top of ascent, slopes W.; desc. over NW. slope.
45.25	Ravine, drains W.; asc. over S. slope.
50.856	Intersect the line bet. secs. 4 and 8. No permanent monument established.
	From this point, the cor. of secs. 5 and 8 only bears N. 1° 07' 18" W., 0.777 chs. dist.
55.411	The NE. cor. of Donation Land Claim No. 39, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T 22 S NE COR <hr/> DLC 39* R 9 W 1971
	from which the remains of original bearing trees
	A fir stump, 62 ins. diam., bears N. 5° E., 115 lks. dist., with healed blaze.
	A fir snag, size indeterminate, bears S. 85° W., 35 lks. dist., no marks visible.
	and the remains of a bearing tree of no record, utilized by Powell, reported by Robb in 1985
	A fir snag, size indeterminate, bears N. 19° E., 32½ lks. dist., with illegible scribe marks visible on a partially decayed blaze.
	and the remains of bearing trees mkd. by Powell, reported by Robb in 1985
	A fir, 19 ins. diam., bears N. 61¼° E., 52 lks. dist., with healed blaze.
	A fir, 14 ins. diam., bears N. 74° W., 50 lks. dist., with healed blaze.
	and a bearing tree mkd. by Robb in 1985
	A fir, 10 ins. diam., bears S. 74° W., 60 lks. dist., with healed blaze.
	From this point, a point established by person(s) unknown, reported by Robb in 1985, bears S. 6° E., 0.031 chs. dist.; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 2 ins. above ground.

**Dependent Resurvey of the East Boundary
of Donation Land Claim No. 39,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS

From this same point, the crossing closing corner of secs. 4 and 5, bears N. 89° 16' W., 0.040 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 22 S R 9 W
CCC
S 5 * S 4

C 39
1985

from which bearing trees mkd. by Robb in 1985

A fir, 14 ins. diam., bears S. 83° E., 26 lks. dist., with healed blaze.

A fir, 11 ins. diam., bears N. 7° W., 19 lks. dist., with healed blaze.

**Dependent Resurvey of a Portion of the North Boundary
of Donation Land Claim No. 40,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

From the NE. cor. of Donation Land Claim No. 40, perpetuated by person(s) unknown, utilized by Richard J. Hintz, Registered Land Surveyor No. 497, in 1971, recorded in the Douglas County Courthouse file No. M 42-40, this point is harmoniously related to other original corners and is accepted as the best available evidence of the original corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground. No accessories found.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T22S R9W
S 9
C 40 *
1996

from which

A fir, 29 ins. diam., bears S. 58 3/4° W., 32 lks. dist., mkd.
T22S R9W C40 BT.

No other suitable accessories available.

From this point, the SE. cor. of Donation Land Claim No. 40, bears S. 0° 03' 19" W., 39.332 chs. dist., perpetuated by person(s) unknown, and recorded by Richard J. Hintz, Registered Land Surveyor No. 1305, in 1971, recorded in the Douglas County Courthouse file No. M 42-40, and utilized by Philip R. Ekelund, Registered Land Surveyor No. 1077, in 1989, recorded in the Douglas County Courthouse file No. M 109-59; monumented with an iron pipe, 1 in.

**Dependent Resurvey of a Portion of the North Boundary
of Donation Land Claim No. 40,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>diam., firmly set, projecting 8 ins. above ground. Alongside this iron pipe is an iron bolt, ½ in. diam., firmly set, projecting 6 ins. above ground, with a metal cap mkd. LOT CORNER.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W C 40 * S 16 ----- 1996</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears S. 40° W., 73 lks. dist., no marks visible. (Record, 67 lks.)</p> <p style="padding-left: 40px;">A fir snag, size indeterminate, bears S. 56° W., 122½ lks. dist., no marks visible. (Record, 120 lks.)</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears North, 50 lks. dist., mkd. T22S R9W C40 BT.</p> <p>Deposit a ½ in. iron bolt alongside and a 1 in. iron pipe and a magnet in a white plastic case at the base of the stainless steel post.</p> <p>S. 62° 45' 46" W., on the N. bdy. of Donation Land Claim No. 40.</p> <p>Descend over broken NW. slope through light timber and dense undergrowth.</p>
18.516	<p>Intersect the line between secs, 8 and 9, point for the crossing closing corner, hereinbefore described.</p> <p>From this point, the angle point between secs. 8 and 9 bears S. 1° 07' 54" E., 1.295 chs. dist.</p>
19.796	<p>The SE. cor. of Donation Land Claim No. 39, located on the N. bdy. of Donation Land Claim No. 40, hereinbefore described.</p> <hr/> <p style="text-align: center;">Subdivision of Section 3, T. 22 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p> <p>N. 0° 33' 55" E., on the N. and S. centerline of sec. 3.</p> <p>Ascend over E. slope through moderate timber and dense undergrowth.</p>
16.30	<p>Spur, slopes S. 60° E.; desc. over NE. slope.</p>
19.95	<p>Ravine, drains S. 40° E.; asc. over SW. slope.</p>

**Subdivision of Section 3,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
26.75	Spur, slopes S. 80° E.; desc. over N. slope.
30.000	Point selected for a witness point on the N. and S. centerline of sec. 3. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;">WP C * S 3 C 1996</div> from which <div style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 29° E., 33½ lks. dist., mkd. X BT.</div> <div style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 27¼° W., 24½ lks. dist., mkd. WP S3 BT.</div> This corner falls in a ravine, drains N. 50° E.; asc. over broken SE. slope.
37.30	Spur, slopes N. 40° E.; desc. over NW. slope.
47.50	Creek, 2 lks. wide, course N. 40° E.; asc. over SE. slope.
49.70	Top of ascent, slopes E.; desc. over N. slope.
50.50	Creek, 5 lks. wide, course S. 80° E.; asc. over S. slope.
50.85	Dirt road, 20 lks. wide, bears S. 80° E. and N. 70° W.
58.20	Spur, slopes E.; desc. over N. slope.
67.45	Creek, 5 lks. wide, course S. 20° E.; asc. over SW. slope.
69.75	Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
74.519	The 1/4 sec. cor. of sec. 3 only, on the N. bdy. of the Tp.
<p>Subdivision of Section 4, T. 22 S., R. 9 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 4 and 9, perpetuated by person(s) unknown and recorded by Verson W. Hosford, Registered Land Surveyor No. 253, in 1954, recorded in the Douglas County Courthouse file Nos. 41-292 and M 10-80, and further perpetuated by James Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Courthouse file No. 49/103, from original evidence no longer in existence; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>	

Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	COUNTY SURVEYORS OFFICE S 4 1/4 ----- S 9 T22S R9W 1958
	from which the remains of bearing trees mkd. by Byron A cedar stump, 59 ins. diam., bears S. 32½° W., 139 lks. dist., with scribe marks S9 CS BT visible on an open face. A cedar stump, 58 ins. diam., bears N. 35° E., 132½ lks. dist., with scribe marks 1/4 S4 BT visible on an open face. and new bearing trees A fir, 11 ins. diam., bears N. 35 3/4° E., 55 lks. dist., mkd. 1/4 S4 BT. A fir, 10 ins. diam., bears S. 43¼° E., 34½ lks. dist., mkd. 1/4 S9 BT. N. 0° 16' 28" E., on the N. and S. centerline of sec. 4. Ascend over SE. slope through moderate timber and light undergrowth.
11.85	Spur, slopes E.; desc. over NE. slope.
16.00	Creek, 1 lk. wide, course S. 75° E.; asc. over SW. slope.
38.485	The center 1/4 cor. of sec. 4, established by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, recorded in the Douglas County Courthouse file Nos. 41-292 and M 10-80, and is accepted as the corner; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 18 ins. above ground, from which the remains of a bearing tree mkd. by Hosford: A fir stump, 48 ins. diam., bears S. 29½° W., 42½ lks. dist., with scribe marks 4 S PS253 BT visible on an open face. At the corner point Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 22 S R 9 W C 1/4 S 4 1996
	A fir, 14 ins. diam., bears S. 51° E., 13 lks. dist., mkd. C 1/4 S4 BT. A fir, 10 ins. diam., bears S. 20° W., 44½ lks. dist., mkd. X BT. Deposit iron pipe and a magnet in a white plastic case at the base of the stainless steel post.

Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 17' 17" E., beginning new measurement.
	Continue ascent over SE. slope.
12.60	Dirt road, 20 lks. wide, bears N. 35° W. and S. 35° E.
20.574	The center N 1/16 sec. cor. of sec. 4 established by Vernon W. Hosford, Registered Land Surveyor No. 253, in 1954, and is accepted as the corner; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 24 ins. above ground, from which the remains of bearing trees mkd. by Hosford:
	A fir, 16 ins. diam., bears N. 68° E., 16 lks. dist., with healed blaze.
	A decayed hemlock stump, 37 ins. diam., bears N. 50½° W., 37 lks. dist., no marks visible, tag on stump.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C N 1/16 * S 4 C 1996
	and a new bearing tree
	A fir, 15 ins. diam., bears N. 27½° E., 26½ lks. dist., mkd. CN 1/16 S4 BT.
	Deposit iron pipe and a magnet in a white plastic case at the base of the stainless steel post.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 12' 11" E., beginning new measurement.
	Continue ascent over S. slope.
2.55	Dirt road, 20 lks. wide, bears N. 14° E. and S. 14° W.
17.75	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
18.317	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	T 22 S R 9 W 1/4 S 4 * 1987
	and bearing trees mkd. by Robb in 1987

Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 12 ins. diam., bears S. $25\frac{1}{4}^{\circ}$ W., 26 lks. dist., with healed blaze.</p> <p>A fir, 14 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ W., $31\frac{1}{2}$ lks. dist., with healed blaze.</p> <p>N. $89^{\circ} 26' 45''$ W., on the E. and W. centerline of sec. 4.</p> <p>Descend over W. slope through moderate timber and dense undergrowth, across creek; asc. over SE. slope.</p>
19.817	<p>Point for the center E 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C ----- C S 4 1996</p> <p>from which</p> <p>A fir, 13 ins. diam., bears N. $86\frac{1}{2}^{\circ}$ E., 44 lks. dist., mkd. CE 1/16 S4 BT.</p> <p>A fir, 13 ins. diam., bears S. $33\frac{3}{4}^{\circ}$ E., $18\frac{1}{2}$ lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue ascent over SE. slope.</p>
36.85	Dirt road, 20 lks. wide, bears N. 15° E. and S. 15° W.
39.634	The center 1/4 sec. cor. of sec. 4.
	<p style="text-align: center;">_____</p> <p>N. $89^{\circ} 27' 27''$ W., beginning new measurement.</p> <p>Continue ascent over SE. slope through moderate timber and moderate undergrowth.</p>
10.85	Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.
11.40	Dirt road, 20 lks. wide, bears N. and S.
13.80	Spur, slopes S. 30° W.; desc. over SW. slope.
19.960	<p>Point for the center W 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 C ----- C S 4 1996</p>

Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 5 3/4° E., 101½ lks. dist., mkd. CW 1/16 S4 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 54½° W., 60 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue descent over SW. slope.</p>
20.20	Golden Creek, 2 lks. wide, course S. 40° E.; asc. over NE. slope.
35.15	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
39.75	Ridge, bears N. 35° E. and S. 35° W.; desc. over NW. slope.
45.272	<p>The 1/4 sec. cor. of sec. 4 only, on the W. bdy. of sec. 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, in a mound of stone, 1 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 9 W 1/4 * S 4 1985</p> <p>from which the remains of bearing trees mkd. by Hosford, reported by Robb in 1985</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears N. 47¼° E.2, 87 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by Robb in 1985</p> <p style="padding-left: 40px;">An alder, 8 ins. diam., bears S. 79° E., 53 lks. dist., with scribe marks 1/4 S4 BT visible in the bark.</p> <p>The corner is located on a rock ledge, sloping NW.</p>
20.787	<p>From the center E 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 29' 16" E., on the N. and S. centerline of the NE 1/4 of sec. 4.</p> <p>Ascend over SE. slope.</p> <p>Point for the NE 1/16 sec. cor. of sec. 4, at intersection with the E. and W. centerline of the NE 1/16.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 4 1996</p>

Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 17½° E., 15½ lks. dist., mkd. NE 1/16 S4 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 54½° W., 23 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue ascent over SE. slope.</p>
39.153	<p>The E 1/16 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.</p> <hr/> <p>From the N 1/16 sec. cor. of sec. 4 only, on the E. bdy. of sec. 4. S. 89° 56' 20" W., on the E. and W. center line of the NE 1/4 of sec. 4.</p> <p>Descend over SW. slope through moderate timber and dense undergrowth.</p>
7.90	<p>Ravine, drains S. 40° W.; asc. over E. slope, across spur; desc. over W. slope.</p>
19.901	<p>The NE 1/16 sec. cor. of sec 4.</p> <p>Continue descent over W. slope.</p>
35.30	<p>Creek, 5 lks. wide, course S.; asc. over SW. slope.</p>
39.789	<p>The center N 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 4.</p> <p>N. 0° 13' 27" E., on the N. and S. center line of the NW 1/4 of sec. 4.</p> <p>Ascend over broken SE. slope through moderate timber and dense undergrowth.</p>
20.299	<p>Point for the NW 1/16 sec. cor. of sec. 4, at intersection with the E. and W. centerline of the NW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 4 1996</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 20 3/4° E., 29 lks. dist., mkd. NW 1/16 S4 BT.</p>

**Subdivision of Section 4,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p style="text-align: center;">A fir, 14 ins. diam., bears S. 35 3/4° E., 30 lks. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Continue descent over broken W. slope.</p>
38.404	<p>The W 1/16 sec. cor. of sec. 4 only, on the W. bdy. of sec. 4.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 4.</p> <p>S. 89° 45' 15" W., on the E. and W. centerline of the NW 1/4 of sec. 4.</p> <p>Ascend over SE. slope through moderate timber and dense undergrowth.</p>
0.80	Dirt road, 20 lks. wide, bears N. 20° E. and S. 20° W.
9.45	Spur, slopes S. 30° W.; desc. over SW. slope.
17.20	Ravine, drains S. 15° E.; asc. over SW. slope.
19.80	Spur, slopes S. 20° E.; desc. over broken SW. slope.
19.982	The NW 1/16 sec. cor. of sec. 4.
	Continue descent over broken W. slope.
45.381	<p>The N 1/16 sec. cor. of sec. 4 only, on the W. bdy. of sec. 4, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 * S 4 1985</p> <p>from which bearing trees mkd. by Robb in 1985</p> <p style="text-align: center;">A fir, 28 ins. diam., bears N. 16° E., 35 lks. dist., with healed blaze.</p> <p style="text-align: center;">A fir, 24 ins. diam., bears S. 51° E., 33 lks. dist., with healed blaze.</p>
	<p>Subdivision of Section 9, T. 22 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>

Subdivision of Section 9,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	T 22 S R 9 W S 9 1/4 ————— S 16 1987
	from which the remains of original bearing trees A fir stump, 40 ins. diam., bears N. 20½° E., 55 lks. dist., with scribe marks BT visible on an open blaze. A fir stump, 60 ins. diam., bears S. 20½° W., 10 lks. dist., with scribe marks S BT visible on an open blaze. and bearing trees mkd. by Robb in 1987 A fir, 12 ins. diam., bears N. 26¼° E., 22 lks. dist., with healed blaze. A fir, 14 ins. diam., bears S. 49 3/4° E., 28½ lks. dist., with healed blaze. N. 3° 17' 20" E., on the N. and S. centerline on sec. 9. Ascend over broken E. slope through moderate timber and dense undergrowth.
40.075	Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 22 S R 9 W C 1/4 S 9 1996 </div> from which A fir, 12 ins. diam., bears N. 8½° E., 21 lks. dist., mkd. X BT. A fir, 10 ins. diam., bears S. 43° E., 11½ lks. dist., mkd. C 1/4 S9 BT. Deposit a magnet in a white plastic case at the base of the stainless steel post. Continue ascent over gentle E. slope.
77.100	The 1/4 sec. cor. of secs. 4 and 9. <hr/> From the 1/4 sec. cor. of sec. 9 only, on the E. bdy. of sec. 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

Subdivision of Section 9,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	T 22 S R 9 W 1/4 S 9 * 1987
	from which bearing trees mkd. by Robb in 1987
	A fir, 18 ins. diam., bears S. 5¼° W., 46½ lks. dist., with healed blaze.
	A fir, 19 ins. diam., bears N. 35° W., 124 lks. dist., with healed blaze.
	N. 89° 28' 25" W., on the E. and W. centerline of sec. 9.
	Descend over W. slope through moderate timber and dense undergrowth.
0.65	Purdy Creek, 12 lks. wide, course S. 20° W.; asc. over steep E. slope, across small spur; desc. over SW. slope.
11.85	Creek, 3 lks. wide, course S. 30° E.; asc. over NE. slope.
42.220	The center 1/4 sec. cor. of sec. 9, at top of ascent, slopes N.; desc. over broken NW. slope.
52.95	Spur, slopes S. 75° W.; desc. over NW. slope.
65.584	Point for the center W 1/16 sec. cor. of sec. 9, to the S. only.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	C ----- C W 1/16 S 9 1996
	from which
	A fir, 11 ins. diam., bears S. 43° E., 56½ lks. dist., mkd. CW 1/16 S9 BT.
	A fir, 14 ins. diam., bears S. 26° W., 60 lks. dist., mkd. X BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Continue descent over NW. slope.
72.55	Golden Creek, 15 lks. wide, course S. 45° W.; asc. over SE. slope.
75.70	Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.
84.305	The 1/4 sec. cor. of secs. 8 and 9.

**Subdivision of Section 9,
T. 22 S., R. 9 W., Willamette Meridian, Oregon**

CHAINS	
	<p>From the W 1/16 sec. cor. of secs. 9 and 16, monumented with a stainless steel post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> S 9 W 1/16 ----- S 16 1987 </p> <p>from which bearing trees mkd. by Robb in 1987</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 7 3/4° E., 32½ lks. dist., no marks visible on a partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 33 ins. diam., bears N. 85° W., 54½ lks. dist., no marks visible on a partially healed blaze.</p> <p>N. 0° 52' 18" E., on the N. and S. centerline of the SW 1/4 of sec. 9.</p> <p>Descend over N. slope through moderate timber and dense undergrowth.</p>
1.95	Creek, 5 lks. wide, course S. 75° W.; asc. over SW. slope.
10.90	Top of ascent, slopes W.; desc. over N. slope.
15.55	Ravine, drains S. 75° W.; asc. over S. slope.
24.65	Top of ascent, slopes W.; desc. over NW. slope.
31.25	Ravine, drains S. 80° W.; asc. over S. slope.
37.00	Spur, slopes W.; desc. over N. slope.
40.222	The center W 1/16 sec. cor. of sec. 9, to the S. only.
<hr/> <p>Subdivision of Section 10, T. 22 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>S. 88° 20' 03" W., on the E. and W centerline of sec. 10.</p> <p>Ascend over NE. slope through moderate timber and dense undergrowth.</p>
2.45	Spur, slopes N. 30° E.; desc. over NW. slope.
9.40	Creek, 8 lks. wide, course S. 45° W.; asc. over SE. slope.
14.20	Spur, slopes N.; desc. over W. slope.
16.30	Burchard Creek, 12 lks. wide, course S. 10° E.; asc. over NE. slope.
39.000	Point selected for a witness point on the E. and W. centerline of sec. 10.

Subdivision of Section 10,
T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">WP C ----- C S 10 1996</p> <p>A fir, 14 ins. diam., bears S. 23° W., 13½ lks. dist., mkd. X BT.</p> <p>A fir, 12 ins. diam., bears N. 68 3/4° W., 36½ lks. dist., mkd. WP S10 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
39.80	Spur, slopes S.; desc. over SW. slope.
51.90	Creek, 1 lk. wide, course W.; asc. over SE. slope.
72.60	Ridge, bears N. and S.; desc. over W. slope.
82.408	<p>The 1/4 sec. cor. of sec. 10 only, on the W. bdy. of sec. 10, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 21 S R 9 W 1/4 * S 10 1987</p> <p>from which bearing trees mkd. by Robb in 1987</p> <p>A fir, 22 ins. diam., bears N. 53° E., 52 lks. dist., with healed blaze.</p> <p>A fir, 20 ins. diam., bears S. 79° E., 16 lks. dist., with healed blaze.</p>
	<p>GENERAL DESCRIPTION</p> <p>The lands involved in the foregoing survey are located in Douglas County, Oregon, approximately three miles northeasterly of the town of Scottsburg, Oregon. Access into the area is by way of State Highway No. 38, Wells Creek Road, and Weatherly Creek Road, with a few private dirt and graveled roads extending from them.</p> <p>The area is drained to the southwest by Purdy Creek, Golden Creek, Burchard Creek, and Wells Creek into the Umpqua River. The elevations in the area range from about 240 feet above sea level at the corner of sections 8, 9, 16 and 17, to about 1600 feet above sea level near the 1/4 section corner of section 4 only, on the north boundary of the township.</p>

T. 22 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The soil is generally a rocky clay loam from a few inches to several feet in depth, overlaying sandstone bedrock. The timber consists of fir, hemlock, alder, maple, cedar, and dogwood; the undergrowth consists of huckleberry, salmonberry, rhododendron, vine maple, poison oak, Oregon grape, ferns, and grass.

The magnetic declination is 19° East, as taken from the "SCOTTSBURG, ORE.," United States Geological Survey 7½ minute series quadrangle map, Provisional Edition, dated 1985.
