

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH, WEST, AND NORTH BOUNDARIES,
THE SUBDIVISIONAL LINES, AND BOUNDARIES OF DONATION LAND CLAIM
NOS. 50 AND 53, THE SUBDIVISION OF SECTIONS 7, 18, 21, 27 AND 35,
AND
THE AMENDED FIELD NOTES OF THE DEPENDENT RESURVEY OF
THE EAST ONE-HALF OF THE LINE BETWEEN SECTIONS 8 AND 17,
TOWNSHIP 28 SOUTH, RANGE 7 WEST,
OF THE
WILLAMETTE MERIDIAN
IN THE STATE OF OREGON.

EXECUTED BY

Bryan S. Seibold, Cadastral Surveyor

Robert J. Chappel, Cadastral Surveyor

Under Special Instructions dated March 12, 1991, approved March 13, 1991,
Supplemental Special Instructions dated July 9, 1991, approved
July 9, 1991, Second Supplemental Special Instructions dated
August 7, 1991, approved August 7, 1991, and Third Supplemental Special
Instructions dated May 28, 1992, and approved May 29, 1992,
which provided for the surveys included under Group No. 1585,
and Assignment Instructions dated March 21, 1991, July 16, 1991,
March 25, 1992, and June 9, 1992.

Survey commenced May 1, 1991

Survey completed May 26, 1994

T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of portions of the south, west, and north boundaries, subdivisional lines, and boundaries of Donation Land Claim Nos. 50 and 53, the subdivision of sections 7, 18, 21, 27, and 35, and the amended field notes of the dependent resurvey of a portion of the line between sections 8 and 17, township 28 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The south and west boundaries, the Sixth Standard Parallel South along the north boundary, and the subdivisional lines of T. 28 S., R. 7 W., were surveyed by Nathaniel Ford, U. S. Deputy Surveyor, in 1854.

The east boundary of T. 28 S., R. 8 W., the south boundary of T. 27 S., R. 7 W., establishing new corners south of those established by Ford for the Sixth Standard Parallel South, and the subdivision of T. 27 S., R. 7 W., were surveyed by Dennis Hathorn, U. S. Deputy Surveyor, in 1855.

Donation Land Claims in Tps. 27 and 28 S., R. 7 W., were surveyed by Elliott N. Bowman and Josiah A. Burnett, U. S. Deputy Surveyors, in 1855 and 1856.

The Sixth Standard Parallel South along the north boundary, the west boundary, and a portion of the subdivisional lines of T. 28 S., R. 7 W., the south boundary of T. 27 S., R. 7 W., and the east boundary of T. 28 S., R. 8 W., were resurveyed and T. 28 S., R. 7½ W., was subdivided by Fred Mensch, U. S. Cadastral Engineer, in 1924.

Portions of the subdivisional lines of T. 28 S., R. 7 W., and a portion of Donation Land Claim No. 47 were resurveyed by James E. Jelley, Cadastral Surveyor, in 1975.

A portion of the north boundary of T. 29 S., R. 7 W., was resurveyed by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, in 1981.

Portions of the subdivisional lines were resurveyed and section 9 was subdivided by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, in 1983 and 1984.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated March 12, 1991, Supplemental Special Instructions dated July 9, 1991, Second Supplemental Special Instructions dated August 7, 1991, and Third Supplemental Special Instructions dated May 28, 1992, for Group No. 1585. Oregon.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation.

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The DEEP-1 is composed of strontium encased in a color coded plastic container. The units are 1 inch in diameter, 2½ ins. long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the 1/4 section corner of sections 18 and 19, as determined from a tie to United States Coast and Geodetic Survey triangulation station "TENMILE 1942," is as follows:

Latitude 43° 07' 44.62" N. Longitude 123° 34' 08.60" W.

The geographic position (NAD 1927) of the 1/4 section corner of sections 21 and 28, as determined from a tie to Geodetic Control Station No. EC 41002, established by the Bureau of Land Management in 1989, is as follows:

Latitude 43° 06' 53.92" N. Longitude 123° 31' 50.68" W.

The geographic position (NAD 1927) of Angle Point No. 7, section 33, township 27 south, range 7 west, as determined from a tie to Geodetic Control Station No. EC 41169, established by the Bureau of Land Management in 1992, is as follows:

Latitude 43° 10' 15.50" N. Longitude 123° 32' 29.40" W.

The geographic position (NAD 1927) of the corner of sections 2, 3, 34, and 35, townships 28 and 29 south, range 7 west, as determined from a tie to Geodetic Control Station No. EC 41002, established by the Bureau of Land Management in 1989, is as follows:

Latitude 43° 05' 07.75" N. Longitude 123° 30' 08.77" W.

The mean magnetic declination is 18° East.

**Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the survey by Nathaniel Ford in 1854)

From the cor. of secs. 1, 2, 35, and 36, perpetuated by Jesse W. Cole, Deputy County Surveyor, in 1923, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office, Volume 3, pages 171 and 172, further perpetuated by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyor Office corner renewal file, T. 28 S., R. 7 W., No. 203, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S R S 35 S 36 7 ----- W S 2 S 1 T29S 1969</p> <p>from which the remains of bearing trees mkd. by Cole</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 71° E., 24½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A rotted, sawed, fir stump, 14 ins. diam., bears S. 7° W., 19 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A rotted, sawed, fir stump, 12 ins. diam., bears S. 64 3/4° W., 28½ lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 27½° W., 26½ lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A dead fir, 11 ins. diam., bears S. 55¼° E., 33 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 70¼° W., 115 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A madrone, 10 ins. diam., bears S. 39¼° E., 23 lks. dist., mkd. T29S R7W S1 BT.</p> <p>The corner is located S. 16° W., 0.08 chs. dist. from a fence corner, with 4 strand barbed wire fence extending N. and woven wire fence extending E.</p> <p>N. 89° 19' 00" W., bet. secs. 2 and 35.</p> <p>Ascend over SE. slope, through heavy timber and moderate undergrowth.</p> <p>0.80 Spur, slopes S. 55° W.; desc. over broken SW. slope.</p> <p>21.10 Ravine, drains S. 35° W.; asc. over broken S. slope.</p> <p>34.35 Spur, slopes S. 20° E.; desc. over broken SW. slope.</p> <p>39.355 The 1/4 sec. cor. of secs. 2 and 35, reestablished by Arthur Boyer, Deputy County Surveyor, in 1941, recorded in the Douglas County Surveyors Office, Volume 4, page 83, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 180, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S R7W S 35 1/4 ----- S 2 T29S 1961</p> <p>from which bearing trees mkd. by Boyer</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 19 3/4° E., 4 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 41° E., 19 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 00" W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>
19.735	<p>The W 1/16 sec. cor. of secs. 2 and 35, established by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file M33-57, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S S 35 R 1/16 ----- 7 S 2 W T29S 1969</p> <p>from which bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 75½° E., 13½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 4½° W., 31½ lks. dist., with healed blaze.</p> <p>The SE. bearing tree is also a fence corner, with woven wire fences extending N., S., and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 00" W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>
19.55	<p>McNabb Creek Road, graveled, 30 lks. wide, bears N. and S.</p>
19.750	<p>The cor. of secs. 2, 3, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set 2 ins. below ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

T28S R7W
S 34 | S 35
 S 3 | S 2
 T29S
 1981

from which reference monuments set by Jelley and Rogers

An iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, bears N. 44° E., 84 lks. dist., with brass cap mkd. RM S35 55.6' TO COR T28S R7W 1981 and an arrow pointing to the corner. (Record, N. 47½° E.)

An iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, bears S. 37° E., 105 lks. dist., with brass cap mkd. RM S2 69.3' TO COR T29S R7W 1981 and an arrow pointing to the corner.

An iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, bears S. 46° W., 10 lks. dist., with brass cap mkd. RM S3 6.6' TO COR T29S R7W 1981 and an arrow pointing to the corner.

An iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, bears N. 33° W., 10 lks. dist., with brass cap mkd. RM S34 6.6' TO COR T28S R7W 1981 and an arrow pointing to the corner.

The corner is located on the W. edge of McNabb Creek Road, in a woven wire fence extending N. and S.

From this point, the Bureau of Land Management, Geodetic Control Station No. EC 41002, at latitude 43° 06' 18.648" N., longitude 123° 34' 17.652" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N. 68° 45' 33" W., 300.177 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap, firmly set flush with the ground, in an irregular circle of concrete, 18 ins. diam., mkd. EC 41002 GPS 1989.

**Dependent Resurvey of a Portion of the West Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

(Restoring the survey by Nathaniel Ford in 1854,
and the resurvey by Fred Mensch in 1924)

Beginning at the cor. of secs. 7 and 18 only, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

| T28S
 | S 7
 | S 18
 R7W
 1924

from which an original bearing tree

**Dependent Resurvey of a Portion of the West Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">A fir, 46 ins. diam., bears S. 25° W., 38 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Mensch</p> <p style="text-align: center;">A maple, 18 ins. diam., bears N. 63½° E., 66 lks. dist., with healed blaze. (Record, N. 62° E.)</p> <p style="text-align: center;">A sawed fir stump, 38 ins. diam., bears S. 81° E., 54 lks. dist., with no marks visible on rotted stump.</p> <p>and a bearing tree mkd. by person(s) unknown</p> <p style="text-align: center;">A fir, 22 ins. diam., bears S. 44 3/4° E., 31 lks. dist., with healed blaze.</p> <p>N. 0° 28' 00" E., on the W. bdy. of sec. 7.</p> <p>Ascend over SE. slope, through heavy timber and moderate undergrowth.</p> <p>2.15 Spur, slopes E.; desc. over broken NE. slope.</p> <p>6.30 Abandoned dirt road, 15 lks. wide, bears N. 70° W. and S. 80° E.</p> <p>8.80 Creek, 3 lks. wide, course S. 60° E.; asc. over broken SE. slope.</p> <p>10.35 Dirt road, 15 lks. wide, bears N. 50° W. and S. 50° E.</p> <p>19.510 The S 1/16 sec. cor. of sec. 7 only, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1957, recorded in the Douglas County Surveyors Office map file No. M4-74, and is accepted as the corner; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 10 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> S 1/16 S 7 1991 </div> <p>from which</p> <p style="text-align: center;">A fir, 16 ins. diam., bears N. 10° E., 22½ lks. dist., mkd. S 1/16 S7 BT.</p> <p style="text-align: center;">A fir, 19 ins. diam., bears S. 45° E., 23 lks. dist., mkd. S 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 28' 30" E., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the West Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
6.790	<p>The 1/4 sec. cor. of sec. 7 only, T. 28 S., R. 7½ W., monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} 1/4 \\ S\ 7\ \\ R\ 7\frac{1}{2}\ \\ 1924 \end{array}$ </div> <p>from which bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 41° W., 19 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 5° W., 28 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 49' 00" E., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p>
8.30	<p>Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W., and top of ridge bearing same; desc. over NW. slope.</p>
12.705	<p>The 1/4 sec. cor. of sec. 7 only, monumented with an iron post, 1 in. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} 1/4 \\ S\ 7 \\ 1924 \end{array}$ </div> <p>from which bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 19° E., 42 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears S. 73° E., 52 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Randall W. Smith, Deputy County Surveyor, in 1994, recorded in the Douglas County Surveyors Office file CS 64/51</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 70½° E., 34½ lks. dist., with scribe marks 1/4 S7 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 16¼° E., 38 lks. dist., with scribe marks 1/4 S7 CS BT visible on open double blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 2° 10' 00" E., beginning new measurement.</p> <p>Descend over NW. slope.</p>
6.30	<p>Graveled road, 20 lks. wide, bears N. 55° E. and S. 55° W.</p>
19.200	<p>Point for the N 1/16 sec. cor. of sec. 7 only.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> N 1/16 S 7 1991 </p> <p>from which bearing trees mkd. during an administrative survey</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 84° E., 35 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 74° W., 8 lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 62° E., 30 lks. dist., mkd. N 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, a point established by an unofficial Bureau of Land Management administrative survey in 1976, bears North, 0.004 chs. dist., monumented with a steel fence post, firmly set.</p> <p>This point was not used during the course of this survey, the fence post was removed and reset alongside the stainless steel post, and new bearing and distances were taken to the bearing trees mkd. during the administrative survey.</p> <p>Descend over NW. slope.</p> <p>21.30 Creek, 5 lks. wide, course N. 50° E.; asc. over SE. slope.</p> <p>27.285 The cor. of secs. 6 and 7, T. 28 S., R. 7½ W., monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T28S S 6 S 7 R7½W 1924 </p> <p>from which a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7½ W., No. 7</p> <p style="padding-left: 40px;">A cedar, 18 ins. diam., bears N. 30° E., 6½ lks. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Larry E. Monrean, Deputy County Surveyor, in 1976, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7½ W., No. 15</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the West Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>A cedar, 13 ins. diam., bears S. 23° W., 99 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>A fir, 15 ins. diam., bears N. 28° W., 79 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 59' 30" E., beginning new measurement.</p> <p>Ascend over SE. slope.</p> <p>2.40 Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.</p> <p>7.95 Dirt road, 15 lks. wide, bears N. and S. 20° W.</p> <p>8.45 Ridge, bears N. 75° E. and S. 75° W.; desc. over NW. slope.</p> <p>11.115 The cor. of secs. 6 and 7, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T28S S 6 S 7 R7W 1924</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A fir snag, 25 ins. diam., bears N. 72° W., 12 lks. dist., with healed double blaze.</p> <p>and the remains of a bearing tree mkd. by Mensch</p> <p style="padding-left: 40px;">A roothole, bears N. 28° E., 22 lks. dist., with uprooted 15 in. diam. fir alongside, with healed blaze.</p> <p>and a bearing tree mkd. by Larry E. Monrean, Deputy County Surveyor, in 1976, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 233</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 80½° E., 73 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 61½° E., 35 lks. dist., mkd. T28S R7W S7 BT.</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">Dependent Resurvey of a Portion of the North Boundary, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr style="width: 80%; margin: 20px auto;"/> <p style="text-align: center;">(Restoring the survey by Dennis Hathorn in 1855, and the resurvey by Fred Mensch in 1924)</p> <hr style="width: 20%; margin: 10px auto;"/>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the North Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Beginning at the NE. cor. of sec. 5 only, identical with Angle Point No. 7, sec. 33, T. 27 S., R. 7 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">AP7 <u>S 33</u> S 5 R7W T28S 1924</p> <p>from which bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 25° W., 55 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone, 15 ins. diam., bears S. 56° W., 31 lks. dist., no marks visible on decayed, partially healed, single blaze. (Record, 33 lks.)</p> <p>The corner is located S. 68° W., 0.17 chs. dist. from a sawed fir stump fence corner post, 15 ins. diam., with woven wire fence extending S. and W.</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41169, at latitude 43° 10' 30.018" N., longitude 123° 30' 40.802" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N. 79° 38' 57" E., 123.943 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap, firmly set flush with the ground, with top mkd. EC41169 GPS 1992.</p> <p>S. 89° 34' 00" W., on the N. bdy. of sec. 5.</p> <p>Ascend over E. slope, through heavy timber and moderate undergrowth.</p>
2.660	<p>Angle Point No. 6, sec. 33, T. 27 S., R. 7 W., monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"><u>AP6</u> 1924</p> <p>from which the remains of a bearing tree mkd. by Mensch</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears N. 60° W., 7 lks. dist., with fragmentary scribe marks visible on partially healed lower blaze and healed upper blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 135</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears S. 86½° E., 48 lks. dist., with healed double blaze.</p>

**Dependent Resurvey of a Portion of the North Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">A fir, 17 ins. diam., bears S. 64 3/4° W., 38 lks. dist., with healed double blaze.</p> <p>The corner is located in a woven wire fence extending E. and W.</p> <hr/> <p>S. 89° 39' 30" W., on the N. bdy. of the Tp.</p> <p>Ascend over E. slope, through heavy timber and moderate undergrowth.</p> <p>3.60 Top of gradual ascent; begin descending over NW. slope.</p> <p>7.415 The cor. of secs. 32 and 33, identical with Angle Point No. 5, T. 27 S., R. 7 W., monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td></td><td style="text-align: center;">AP5</td><td></td></tr> <tr><td style="text-align: center;">T27S</td><td style="text-align: center;">R7W</td><td></td></tr> <tr><td style="text-align: center;">S 32</td><td style="text-align: center;"> S 33</td><td></td></tr> <tr><td colspan="3" style="text-align: center;">1924</td></tr> </table> </div> <p>from which a remaining original bearing tree</p> <p style="text-align: center;">A madrone, 25 ins. diam., bears N. 60½° W., 40 lks. dist., with healed blaze. (Record, N. 65° W.)</p> <p>and the remains of a bearing tree mkd. by Mensch</p> <p style="text-align: center;">A sawed partially decayed fir stump, 13 ins. diam., bears N. 66° E., 28 lks. dist., with scribe marks T27S R7W visible on open blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 132</p> <p style="text-align: center;">A madrone, 25 ins. diam., bears N. 42° E., 24½ lks. dist., with healed double blaze.</p> <p>The corner is located S. 77° W., 0.04 chs. dist. of a fence corner, with woven wire fence extending N. and W.</p> <hr/> <p>S. 89° 46' 30" W., on the N. bdy. of the Tp.</p> <p>Descend over NW. slope, through heavy timber and moderate undergrowth.</p> <p>0.25 Dirt road, 15 lks. wide, bears S. 15° E. and N. 15° W.</p> <p>2.10 Ravine, drains N. 25° W.; asc. over NE. slope.</p> <p>5.25 Spur, slopes N. 40° W.; desc. over NW. slope.</p> <p>14.35 Ravine, drains N. 20° W.; asc. over NE. slope.</p> <p>18.20 Ridge, bears N. 15° W. and S. 15° E.; desc. over broken NW. slope.</p>		AP5		T27S	R7W		S 32	S 33		1924		
	AP5												
T27S	R7W												
S 32	S 33												
1924													

**Dependent Resurvey of a Portion of the North Boundary,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
19.00	Woven wire fence, extends N. and S., also from this point, a fence corner bears South, 0.21 chs. dist., with same fence extending N. and W. from fence corner.
28.950	<p>The 1/4 sec. cor. of sec. 5 only, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 5 1924</p> <p>from which the remains of the bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A sawed oak stump, 13 ins. diam., bears S. 66° E., 22 lks. dist., with remains of a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 36° W., 46 lks. dist., with healed blaze.</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 140</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 50° E., 18 lks. dist., with healed double blaze.</p> <p>The corner is located in a woven wire fence extending E. and W.</p> <p>From this point, a point of which there is no record bears S. 88° 11' 30" W., 1.393 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 8 ins. above ground.</p> <p>From this same point, an angle point on the N. bdy. of the Tp. bears S. 89° 36' 00" W., 3.470 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. AP 1924, from which the original bearing trees:</p> <p style="padding-left: 40px;">A madrone, 30 ins. diam., bears S. 40° E., 44 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">An oak, 15 ins. diam., bears S. 61½° W., 34 lks. dist., with healed double blaze. (Record, S. 40° W.)</p> <p>and the remains of the bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A decayed pine stump, size indeterminate, bears N. 13½° E., 20 lks. dist., with scribe mark T visible on decayed blaze. (Record, N. 17° E.)</p> <p style="padding-left: 40px;">A sawed fir stump, 14 ins. diam., bears N. 35° W., 38 lks. dist., with healed blaze.</p> <p>The corner is located in a woven wire fence extending E. and W.</p> <hr style="width: 60%; margin-left: 0;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">(Restoring the survey by Nathaniel Ford in 1854, and the resurvey by Fred Mensch in 1924)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp. N. 0° 38' 00" E., bet. secs. 35 and 36.</p> <p>Ascend over SE. slope, through moderate timber and undergrowth.</p> <p>0.70 Spur, slopes S. 55° W.; desc. over broken NE. slope.</p> <p>36.880 The 1/4 sec. cor. of secs. 35 and 36, reestablished by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file M33-57, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S 1/4 S 35 S 36 R7W 1969</p> <p>from which bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A myrtle, 15 ins. diam., bears N. 38¼° E., 26 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears S. 83½° W., 34 lks. dist., with healed blaze.</p> <p>From this point, the cor. of secs. 25, 26, 35, and 36, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 79, bears N. 0° 40' 00" E., 36.885 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, bent over at ground level, with brass cap mkd. COUNTY SURVEYORS OFFICE T28S R7W S26 S25 S35 S36 1958, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">An oak, 30 ins. diam., bears N. 60° W., 65 lks. dist., no marks visible on opened blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 15 ins. diam., bears N. 80° E., 19½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">An oak, 15 ins. diam., bears S. 73 3/4° E., 21 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">The most easterly trunk of a double trunk oak, 13 ins. diam., bears S. 46 3/4° W., 70 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">The most easterly trunk of a double trunk oak, 16 ins. diam., bears West, 5½ lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin-left: 0;"/>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>From the cor. of secs. 26, 27, 34, and 35, perpetuated by Jesse W. Cole, Deputy County Surveyor, in 1924, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 91, further perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 82; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE <u>S27 S26</u> S34 S35 T28S R7W 1958</p> <p>An oak, 14 ins. diam., bears S. 63° W., 28½ lks. dist., with healed double blaze.</p> <p>An ash, 15 ins. diam., bears N. 15¼° W., 9 lks. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Byron</p> <p>An oak, 11 ins. diam., bears N. 28° E., 23 lks. dist., with healed double blaze.</p> <p>A fir, 17 ins. diam., bears S. 70° E., 44 lks. dist., with healed double blaze.</p> <p>N. 0° 15' 00" W., bet. secs. 26 and 27.</p> <p>Through creek bottom.</p> <p>0.25 Creek, 5 lks. wide, course S. 25° W.; asc. over SE. slope, through sparse timber and dense undergrowth.</p> <p>21.80 Ridge, bears N. 65° E. and S. 65° W.; desc. over N. slope.</p> <p>28.15 Dirt road, 20 lks. wide, bears N. 70° E. and N. 50° W.</p> <p>32.35 Dirt road, 15 lks. wide, bears E. and W.</p> <p>39.160 The ¼ sec. cor. of secs. 26 and 27, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 81; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE 1/4 S S 27 26 T28S R7W 1958</p> <p>from which the remains of an original bearing tree</p> <p>A roothole, bears N. 35° E., 105 lks. dist., with uprooted oak, 39 ins. diam., lying alongside, no marks visible on opened blaze.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>and a remaining bearing tree mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 34 ins. diam., bears N. 44½° W., 41½ lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears N. 32 3/4° E., 23½ lks. dist., mkd. 1/4 S26 BT.</p> <hr/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 86° 18' 00" W., bet. secs. 27 and 34.</p> <p>Through creek bottom.</p> <p>0.10 Creek, 5 lks. wide, course S. 25° W.; asc. over broken SE. slope.</p> <p>21.55 Spur, slopes S.; continue over broken rocky S. slope.</p> <p>22.685 Intersect the E. bdy. of Donation Land Claim No. 53, point for the crossing closing corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28S R7W S 27 C53 ----- CCC S 34 1993 </div> <p>from which</p> <p style="padding-left: 40px;">An oak, 20 ins. diam., bears N. 36° E., 9 lks. dist., mkd. T28S R7W S27 CCC BT.</p> <p style="padding-left: 40px;">An oak 16 ins. diam., bears S. 70° E., 29½ lks. dist., mkd. T28S R7W S34 CCC BT.</p> <p>Deposit a white 'DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Over broken rocky S. slope.</p> <p>30.15 Rocky spur, slopes S. 20° W.; desc. over steep W. slope.</p> <p>38.240 The 1/4 sec. cor. of secs. 27 and 34, perpetuated by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 205; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> COUNTY SURVEYORS OFFICE T28S R7W S 27 1/4 ----- S 34 1969 </div>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

from which the remains of the original bearing trees

A roothole, bears S. 41° W., 67 lks. dist., with uprooted and decayed oak alongside, size indeterminate, no marks visible.

An oak, 28 ins. diam., bears N. 35° W., 20 lks. dist., with scribe marks BT visible on opened blaze.

and bearing trees mkd. by Byron

A madrone, 14 ins. diam., bears N. 87° E., 22½ lks. dist., with scribe marks 1/4 S27 CS visible on open upper blaze and BT visible on open lower blaze.

An oak, 10 ins. diam., bears S. 54½° W., 33½ lks. dist., with healed double blaze.

From this point, the cor. of secs. 27, 28, 33, and 34, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 164, bears N. 86° 29' 00" W., 39.130 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above a mound of stone, 2½ ft. base, 1 ft. high, with brass cap mkd. COUNTY SURVEYORS OFFICE T28S R7W S28 S27 S33 S34 1961, from which an original bearing tree:

An oak, 37 ins. diam., bears S. 23° W., 334 lks. dist., no marks visible on opened blaze. (Record, S. 25° W.)

and bearing trees mkd. by Byron

An oak, 24 ins. diam., bears N. 67° E., 149 lks. dist., with healed double blaze.

An oak, 19 ins. diam., bears S. 67° E., 408 lks. dist., with healed double blaze.

An oak, 38 ins. diam., bears N. 32° W., 268 lks. dist., with healed double blaze.

From the cor. of secs. 21, 22, 27, and 28, perpetuated by Ben B. Irving, Deputy County Surveyor, in 1926, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 27, further perpetuated by James W. Byron, Deputy County Surveyor, in 1957, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 74; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T28S

S 21 | S 22

S 28 | S 27

R7W

1957

from which the remains of the bearing trees mkd. by Irving

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>An oak, 25 ins. diam., bears N. 86½° E., 201 lks. dist., with healed blaze.</p> <p>An oak, 42 ins. diam., bears S. 17° E., 291 lks. dist., with healed blaze.</p> <p>and the remains of the bearing trees mkd. by Byron</p> <p>A pine, 20 ins. diam., bears S. 66° W., 86 lks. dist., with healed blaze.</p> <p>A sawed fir stump, 22 ins. diam., bears N. 72° W., 113 lks. dist., with healed blaze.</p> <p>A roothole, bears N. 29 ¾° W., 260 lks. dist., with uprooted and partially decayed oak, 24 ins. diam., alongside, with fragmentary back scribing visible on partially decayed overgrowth.</p> <p>and a new bearing tree</p> <p>A fir, 6 ins. diam., bears N. 14° W., 16½ lks. dist., mkd. X BT.</p> <p>The corner is located in a fence corner, with woven wire fences extending E., W., and N.</p> <p>N. 0° 11' 00" E., bet. secs. 21 and 22.</p> <p>Ascend over broken SW. slope, through moderate timber and undergrowth.</p> <p>5.05 Spur, slopes S. 45° E.; desc. over NE. slope.</p> <p>8.50 Creek, 5 lks. wide, course S. 45° E.; asc. over SW. slope.</p> <p>19.590 Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16</p> <p>S 21 S 22</p> <p>1992</p> </div> <p>from which</p> <p>A fir, 18 ins. diam., bears N. 47 ¾° E., 55 lks. dist., mkd. S 1/16 S22 BT.</p> <p>A fir, 9 ins. diam., bears N. 72° W., 5½ lks. dist., mkd. S 1/16 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend over broken SW. slope.</p> <p>39.180 Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Drive an aluminum rod, 36 ins. long, 3/4 in. diam., 32 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T28S R7W 1/4 S 21 S 22 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 86 3/4° E., 80 lks. dist., mkd. 1/4 S22 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 27 3/4° W., 38 lks. dist., mkd. 1/4 S21 BT.</p> <p>From this point, a point established as the 1/4 sec. cor. of secs. 21 and 22 by Ben B. Irving, Deputy County Surveyor, in 1926, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 26, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 152, bears S. 32° 56' 30" W., 4.327 chs. dist.; monumented with an axle, 1 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by Byron:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 5 3/4° E., 38 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 2 3/4° W., 50 lks. dist., with healed blaze.</p> <p>This corner was rejected due to gross error and was not used in this survey.</p> <p>Ascend over broken SW. slope.</p>
58.770	<p>Point for the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, 18 ins. diam., with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 21 S 22 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 31° E., 70 lks. dist., mkd. N 1/16 S22 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 13¼° W., 70 lks. dist., mkd. N 1/16 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>From this point, a point established as the N 1/16 sec. cor. of secs. 21 and 22 by G. Robert Lecklider, Registered Professional Engineer No. 4079, in 1959, recorded in the Douglas County Surveyors Office map file M14-18, bears S. 32° 02' 00" W., 2.150 chs. dist.; monumented with an iron rod, ½ in. diam., firmly set, projecting 4 ins. above a collar of stone, from which bearing trees mkd. by Lecklider:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 59½° E., 9 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 21 ¾° W., 6 lks. dist., with healed double blaze.</p> <p>This corner was rejected due to improper control and was not used in this survey.</p> <p>Ascend over broken SW. slope.</p>
78.360	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S <u>S 16 S 15</u> S 21 S 22 R7W 1957</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A roothole, bears S. 29° E., 121 lks. dist., with down and decayed 22 in. diam. oak alongside, no marks visible on rotted open blaze.</p> <p>and the remains of bearing trees mkd. by Ben B. Irving, Deputy County Surveyor, in 1926</p> <p style="padding-left: 40px;">A fir snag, 17 ins. diam., bears N. 49½° E., 66½ lks. dist., with fragmentary scribe marks visible on opened blaze.</p> <p style="padding-left: 40px;">A fir stump, 32 ins. diam., bears S. 34° E., 73 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 16 ins. diam., bears N. 32° W., 65 lks. dist., with scribe marks 16 28S R7W BT visible on open blaze.</p> <p>and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1957</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 11° E., 59 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 4° W., 48 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears N. 12½° W., 14½ lks. dist., with healed double blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>and a bearing tree mkd. by Jelley in 1975</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 53° E., 50 lks. dist., with healed blaze. (Record, N. 54½° E.)</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 88° 23' 00" W., bet. secs. 21 and 28.</p> <p>Across broken S. slope, through moderate timber and undergrowth.</p> <p>24.00 Ravine, drains S. 10°E.; continue across broken S. slope.</p> <p>36.05 Dirt road, 20 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>39.200 The 1/4 sec. cor. of secs. 21 and 28, reestablished by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file M33-57, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S 21 1/4 ----- S 28 1969</p> <p>from which the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 77° E., 36½ lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 29 ins. diam., bears S. 64° E., 32½ lks. dist., no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 54° W., 58 lks. dist., mkd. 1/4 S28 BT.</p> <p>The corner is located in a fence corner, with woven wire fences extending E., W., and N.</p> <p>From this point, the Bureau of Land Management, Geodetic Control Station No. EC 41002, at latitude 43° 06' 18.648" N., longitude 123° 34' 17.652" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S. 71° 01' 46" W., 173.816 chs. dist. (mean bearing and sea level distance); monumented with an aluminum cap, firmly set flush with the ground in an irregular circle of concrete, 18 ins. diam., mkd. EC41002 GPS 1989.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 19' 00" W., beginning new measurement.</p> <p>Descend over SW. slope, through moderate timber and dense undergrowth.</p> <p>1.20 Creek, 5 lks. wide, course S. 30° E.; asc. over S. slope.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

<p>CHAINS</p> <p>19.605</p>	<p>The W 1/16 sec. cor. of secs. 21 and 28, established by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file, M33-57, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE S21 W1/16 ----- S28 1969</p> <p>from which the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 7° E., 27½ lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 22 ins. diam., bears S. 73½° W., 25½ lks. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 48 3/4° E., 26½ lks. dist., mkd. W1/16 S28 BT.</p> <p>From this point, the NE. property corner of Lot 5, identical with the NW. property corner of Lot 6, Homeland Acres, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1971, recorded in the Douglas County Surveyors Office map file, M79-24, bears S. 88° 12' 00" E., 5.120 chs. dist.; monumented with an iron rod, 5/8 in. diam., firmly set in a concrete cylinder, 6 ins. diam., projecting 1 in. above the concrete.</p> <p>The property corner is located at a fence corner, with woven wire fences extending N. and E.</p> <p style="text-align: center;">_____</p> <p>N. 88° 17' 00" W., beginning new measurement.</p> <p>Descend over broken S. slope.</p>
<p>19.600</p>	<p>The cor. of secs. 20, 21, 28 and 29, perpetuated by G. G. Stewart, Deputy County Surveyor, in 1922, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 21, further perpetuated by James W. Byron, Deputy County Surveyor, in 1956, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 63; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S R7W COR 20 21 SEC ----- 29 28 1956</p> <p>from which the remains of a bearing tree mkd. by Stewart</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">A down and dead oak, size indeterminate, bears S. 39° E., 58½ lks. dist., no marks visible on old face.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="text-align: center;">A fir, 20 ins. diam., bears N. 37½° E., 39 lks. dist., with healed double blaze.</p> <p style="text-align: center;">A sawed fir stump, 23 ins. diam., bears S. 37¼° W., 98 lks. dist., with healed lower blaze.</p> <p>and new bearing trees</p> <p style="text-align: center;">A fir, 13 ins. diam., bears S. 23° E., 21½ lks. dist., mkd. T28S R7W S28 BT.</p> <p style="text-align: center;">A fir, 10 ins. diam., bears S. 41° W., 64 lks. dist., mkd. T28S R7W S29 BT.</p> <p style="text-align: center;">A fir, 18 ins. diam., bears N. 70½° W., 81 lks. dist., mkd. T28S R7W S20 BT.</p> <p>Found an iron pipe, ½ in. diam., lying alongside the 1½ in. iron post.</p> <p>The corner is located at a fence corner, with woven wire fences extending E., W., and N.</p> <hr/> <p>N. 0° 38' 00" W., bet. secs. 20 and 21.</p> <p>Ascend over broken SW. slope, through moderate timber and undergrowth.</p>
19.300	<p>Point for the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S20 S21 1992</p> <p>from which</p> <p style="text-align: center;">A fir, 17 ins. diam., bears N. 7½° E., 80 lks. dist., mkd. S1/16 S21 BT.</p> <p style="text-align: center;">A fir, 16 ins. diam., bears N. 27 3/4° W., 63 lks. dist., mkd. S1/16 S20 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SW. slope.</p>
38.600	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate distance, there is no remaining evidence of the original corner.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W 1/4 S20 S21 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 71 3/4° E., 91 lks. dist., mkd. 1/4 S21 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 39° W., 2½ lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established as the 1/4 sec. cor. of secs. 20 and 21 by William C. Stiles, Registered Land Surveyor No. 432, in 1967, recorded in the Douglas County Surveyors Office map file, M32-76, bears S. 67° 10' 00" W., 0.206 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 4 ins. above ground, from which bearing trees mkd. by Stiles:</p> <p style="padding-left: 40px;">A madrone, 17 ins. diam., bears N. 43½° E., 29 lks. dist., with scribe marks S21 1/4 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 42½° W., 55 lks. dist., with healed blaze.</p> <p>This corner was rejected due to improper control and erroneous position and was not used in this survey.</p> <p>Ascend over broken SW. slope.</p> <p>51.30 Spur, slopes S. 40° W.; desc. over broken NW. slope.</p> <p>75.80 Spur, slopes S. 80° W.; desc. over NW. slope.</p> <p>77.200 The cor. of secs. 16, 17, 20 and 21, reestablished by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1984, recorded in the Douglas County Surveyors Office map file, RM3-62, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with plastic cap mkd. BAUGHMAN TECH SERV, from which bearing trees mkd. by Baughman:</p> <p style="padding-left: 40px;">A fir, 29 ins. diam., bears N. 10¼° E., 291 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. 69½° E., 24 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>An oak, 11 ins. diam., bears S. $53\frac{1}{4}^{\circ}$ W., 25 lks. dist., with fragmentary scribe marks visible on partially healed double blaze. This tree is Stiles' SW. bearing tree and was also scribed and used by Baughman.</p> <p>A fir, 15 ins. diam., bears N. $65\frac{1}{4}^{\circ}$ W., 95 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T28S</td> <td style="padding: 0 10px;">R7W</td> </tr> <tr> <td style="padding: 0 10px;">S17</td> <td style="padding: 0 10px;"> S16</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="padding: 0 10px;">S20</td> <td style="padding: 0 10px;"> S21</td> </tr> <tr> <td colspan="2" style="text-align: center;">1992</td> </tr> </table> </div> <p>No new accessories.</p> <p>The corner is located South, 0.02 chs. dist., of a seasonal creek.</p> <p>From this point, a point established as the cor. of secs. 16, 17, 20 and 21 by William C. Stiles, Registered Land Surveyor No. 432, in 1967, recorded in the Douglas County Surveyors Office map file, M32-76, bears S. $46^{\circ} 32' 30''$ E., 0.384 chs. dist.; monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, from which accessories mkd. by Stiles:</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ E., 15 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A 4 in. high "X" chiseled in a rock face, bears S. 47° E., 50 lks. dist.</p> <p style="padding-left: 40px;">A 4 in. high "X" chiseled in a rock face, bears S. $32\frac{1}{2}^{\circ}$ W., 53 lks. dist.</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears N. 77° W., 48 lks. dist., with healed blaze. This tree was also scribed and used by Baughman and contains 2 sets of blazes and scribes.</p> <p>Found a copper rod, $\frac{5}{8}$ in. diam., buried alongside the iron pipe.</p> <p>This corner was rejected due to erroneous position and was not used in this survey.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. $89^{\circ} 12' 00''$ W., bet. secs. 16 and 21.</p> <p>Over nearly level ground, through moderate timber and undergrowth.</p> <p>5.20 Spur, slopes S. 35° W.; asc. over broken SE. slope.</p> <p>29.75 Spur, slopes S. 25° E.; desc. over SW. slope.</p>	T28S	R7W	S17	S16	-----		S20	S21	1992	
T28S	R7W										
S17	S16										

S20	S21										
1992											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

39.755

The 1/4 sec. cor. of secs. 16 and 21, reestablished by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1984, recorded in the Douglas County Surveyors Office map file, RM3-62, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 6 ins. above ground, with plastic cap mkd. BAUGHMAN TECH SERV, from which bearing trees mkd. by Stiles in 1967 and used by Baughman:

A fir, 17 ins. diam., bears S. 12½° W., 26½ lks. dist., with healed blaze.

A fir, 18 ins. diam., bears N. 26½° W., 9 lks. dist., with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron rod, with brass cap mkd.

T28S R7W
 S16
1/4 -----
 S21
 1992

From this point, a point established as the 1/4 sec. cor. of secs. 16 and 21 by William C. Stiles, Registered Land Surveyor No. 432, in 1967, recorded in the Douglas County Surveyors Office map file, M32-76, bears S. 30° 21' 30" E., 0.109 chs. dist.; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 4 ins. above ground.

This corner was rejected and was not used in this survey.

From the cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 1½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE
T28S R7W
 S5 | S4

 S8 | S9
 1976

from which the remains of the bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1961

An oak, 7 ins. diam., bears N. 16½° E., 36 lks. dist., with healed double blaze. (Record, N. 19° E.)

An oak, 9 ins. diam., bears N. 39½° E., 41 lks. dist., with fragmentary scribe marks visible on partially healed upper blaze of double blaze. (Record, N. 41° E.)

A fir, 20 ins. diam., bears S. 5½° E., 86 lks. dist., with healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>and a bearing tree mkd. by Larry E. Monrean, Deputy County Surveyor, in 1976</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 65½° W., 40 lks. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>and a bearing tree mkd. by Rogers and Bishop</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 60½° W., 62 lks. dist., with healed double blaze.</p> <p>The corner is located North, 0.40 chs. dist. of a dirt road, 20 lks. wide, bears NE. and SW.</p> <p>N. 5° 18' 00" W., bet. secs. 4 and 5.</p> <p>Ascend over broken SE. slope, through heavy timber and moderate undergrowth.</p> <p>12.80 Abandoned dirt road, 15 lks. wide, bears N. 75° E. and S. 75° W.</p> <p>32.15 Ridge, bears N. 50° E. and S. 35° W.; desc. over N. slope.</p> <p>32.35 Dirt road, 15 lks. wide, bears N. 50° E. and S. 40° W.</p> <p>39.75 Dirt road, 15 lks. wide, bears N. 40° W. and S. 25° E.</p> <p>39.880 The 1/4 sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> 1/4 S5 S4 1924 </div> <p>from which bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A double trunk madrone, 33 ins. diam., bears N. 70° E., 6 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone, 16 ins. diam., bears N. 81° W., 33 lks. dist., with healed blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 4° 49' 00" W., beginning new measurement.</p> <p>Descend over NE. slope, through heavy timber and moderate undergrowth.</p> <p>23.25 Dirt road, 15 lks. wide, bears N. 35° W. and S. 35° E.</p> <p>36.405 The NE. cor. of sec. 5 only, identical with Angle Point No. 7, T. 27 S., R. 7 W.</p> <hr style="width: 80%; margin: 20px auto;"/> <p>From the 1/4 sec. cor. of secs. 17 and 18, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 159; monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">DOUGLAS COUNTY SURVEYORS OFFICE T28S R7W 1/4 S18 S17 1961</p> <p>from which a remaining original bearing tree</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 50° E., 41 lks. dist., with scribe marks 1/4 BT visible on a bark blaze. (Record, 45 lks.)</p> <p>and the remains of bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears S. 24¼° W., 4½ lks. dist., with fragmentary scribe marks visible on a bark blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 84° W., 11 lks. dist., no marks visible.</p> <p>N. 4° 02' 30" W., bet. secs. 17 and 18.</p> <p>Descend over NW. slope, through heavy timber and moderate undergrowth.</p> <p>6.85 Porter Creek, 10 lks. wide, course S. 70° E.; asc. over broken S. slope.</p> <p>10.45 Graveled road, 20 lks. wide, bears N. 80° E. and S. 80° W.</p> <p>19.530 Point for the N 1/16 sec. cor. of secs. 17 and 18.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N1/16 S18 S17 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 41 3/4° E., 7 lks. dist., mkd. N1/16 S17 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 52° W., 20 lks. dist., mkd. N1/16 S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken S. slope.</p> <p>39.060 The cor. of secs. 7, 8, 17 and 18, reestablished by Arthur Boyer, Registered Professional Engineer No. 1581, in 1957, recorded in the Douglas County Surveyors Office map file, M4-74, and is accepted as the corner; monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 12 ins. above ground, from which the remains of the bearing trees mkd. by Boyer:</p> <p style="padding-left: 40px;">A roothole, bears N. 77° E., 9 lks. dist., with uprooted 18 in. diam. fir alongside.</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>A madrone, 17 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ E., 14 lks. dist., with healed blaze.</p> <p>A roothole, bears S. 60° W., $9\frac{1}{2}$ lks. dist., with decayed uprooted 10 in. diam. fir snag alongside, no marks visible on a bark blaze.</p> <p>A fir, 17 ins. diam., bears N. 86° W., $16\frac{1}{2}$ lks. dist., with scribe marks S7 BT visible on a bark blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">T28S</td> <td style="padding: 0 10px;">R7W</td> </tr> <tr> <td style="padding: 0 5px;">S7</td> <td style="padding: 0 5px;"> S8</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td style="padding: 0 5px;">S18</td> <td style="padding: 0 5px;"> S17</td> </tr> <tr> <td colspan="2" style="text-align: center;">1991</td> </tr> </table> </div> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears N. 50° E., 41 lks. dist., mkd. T28S R7W S8 BT.</p> <p>A cedar, 11 ins. diam., bears S. 38° W., 43 lks. dist., mkd. T28S R7W S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron pipe alongside the stainless steel post.</p> <p>From this point, the 1/4 sec. cor. of secs. 8 and 17 bears S. $89^{\circ} 53' 00''$ E., 40.960 chs. dist., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above ground, with aluminum cap mkd. T28S R7W 1/4 S8 S17 1983, from which bearing trees mkd. by Virgil L. Broadwater, Registered Land Surveyor No. 682, in 1972:</p> <p>A fir, 12 ins. diam., bears S. $48\frac{1}{2}^{\circ}$ E., 31 lks. dist., with healed double blaze.</p> <p>A fir, 19 ins. diam., bears N. 70° W., 40 lks. dist., with healed double blaze.</p> <p>Found an iron pipe, $1\frac{3}{4}$ ins. diam., buried alongside the aluminum post.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. $84^{\circ} 57' 30''$ W., bet. secs. 7 and 18.</p> <p>Ascend over SE. slope, through heavy timber and moderate undergrowth.</p> <p>4.55 Ridge, bears N. 30° E. and S. 40° W.; desc. over NW. slope.</p> <p>17.70 Creek, 3 lks. wide, course S. 65° W.; asc. over broken SE. slope.</p> <p>20.575 Point for the E 1/16 sec. cor. of secs. 7 and 18.</p>	T28S	R7W	S7	S8	-----		S18	S17	1991	
T28S	R7W										
S7	S8										

S18	S17										
1991											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S7 E1/16 ----- S18 1991</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 6 ins. diam., bears N. 21° E., 40 lks. dist., mkd. E 1/16 S7 BT.</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S. 19¼° E., 17 lks. dist., mkd. E 1/16 S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SE. slope.</p> <p>38.00 Ridge, bears N. 30° E. and S. 30° W.; desc. over broken SW. slope.</p> <p>41.150 The 1/4 sec. cor. of secs. 7 and 18, reestablished by Arthur Boyer, Registered Professional Engineer No. 1581, in 1957, recorded in the Douglas County Surveyors Office map file, M4-74, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 168, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 20 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S R7W S7 1/4 ----- S18 1961</p> <p>from which the remains of the bearing trees mkd. by Boyer</p> <p style="padding-left: 40px;">A sawed rotted fir stump, 22 ins. diam., bears S. 4¼° W., 45 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A roothole, bears N. 41° W., 26 lks. dist., with uprooted 18 in. diam. fir alongside, with fragmentary scribe marks visible on a bark blaze.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears N. 58¼° E., 46 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 49¼° W., 43 lks. dist., with healed double blaze.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 85° 43' 00" W., beginning new measurement.</p> <p>Descend over broken SW. slope.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
20.540	<p>The W 1/16 sec. cor. of secs. 7 and 18, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1957, recorded in the Douglas County Surveyors Office map file, M4-74, and is accepted as the corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S7 W1/16 ----- S18 1991</p> <p>from which</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 38° E., 23 lks. dist., mkd. W1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 5° E., 35 lks. dist., mkd. W1/16 S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85° 40' 30" W., beginning new measurement.</p> <p>Ascend over broken SE. slope.</p>
6.15	Spur, slopes S. 65° W.; desc. over NW. slope.
12.50	Porter Creek, 5 lks. wide, course S. 60° W.; asc. over NE. slope.
22.395	The cor. of secs. 7 and 18 only.
	<hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 6° 04' 00" E., bet. secs. 7 and 8.</p> <p>Ascend over SE. slope, through heavy timber and moderate undergrowth.</p>
9.70	Spur, slopes S. 40° W.; desc. over NW. slope.
13.40	Ravine, drains S. 80° W.; asc. over SW. slope.
18.45	Spur, slopes S. 70° W.; desc. over NW. slope.
19.445	<p>The S 1/16 sec. cor. of secs. 7 and 8, established by Virgil L. Broadwater, Registered Land Surveyor No. 682, in 1972, recorded in the Douglas County Surveyors Office map file, M44-46, and is accepted as the corner; monumented with an iron pipe, 1 in. diam., firmly set, projecting 9 ins. above ground, from which the remains of bearing trees mkd. by Broadwater:</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>A sawed fir stump, 19 ins. diam., bears S. 87 3/4° E., 30 lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A fir, 14 ins. diam., bears S. 12½° W., 25 lks. dist., with healed double blaze.</p> <p>A fir, 14 ins. diam., bears N. 38 3/4° W., 29 lks. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by person(s) unknown</p> <p>A fir, 17 ins. diam., bears S. 49 3/4° E., 28 lks. dist., with healed double blaze.</p> <p>A fir snag, 5 ins. diam., bears S. 65° W., 10 lks. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S1/16 S7 S8 1991</p> <p>No new accessories.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the iron pipe alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6° 05' 30" E., beginning new measurement.</p> <p>Descend over NW. slope.</p> <p>3.65 Ravine, drains S. 75° W.; asc. over SW. slope.</p> <p>19.425 The 1/4 sec. cor. of secs. 7 and 8, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 166, further perpetuated by Randall W. Smith, Deputy County Surveyor, in 1994, recorded in the Douglas County Surveyors Office file, CS 64/51; monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS T28S R7W 1/4 S7 S8 OFFICE 1961</p> <p>from which the remains of the original bearing trees</p> <p>A rotted oak stump, size indeterminate, bears S. 30° E., 79 lks. dist., no mks visible. (Record, S. 50° E.)</p> <p>A madrone, 45 ins. diam., bears S. 78° W., 29 lks. dist., no marks visible on a partially burned out trunk. (Record, 27 lks.)</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>and the remains of the bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears S. 40° E., 22 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 14½° W., 23 lks. dist., with healed blaze. (Record, N. 17° W.)</p> <p>and bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 52° E., 13½ lks. dist., with scribe marks 1/4 S8 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 38½° W., 12½ lks. dist., with scribe marks 1/4 S7 CS BT visible on open double blaze.</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 64° W., 51 lks. dist., with scribe marks 1/4 S7 CS BT visible on open double blaze.</p> <p>Found an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above ground, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 43' 00" E., beginning new measurement.</p> <p>Ascend over SW. slope.</p> <p>1.05 Dirt road, 15 lks. wide, bears N. 25° W. and S. 25° E.</p> <p>1.85 Ridge, bears N. 80° W. and S. 80° E.; desc. over NW. slope.</p> <p>12.00 Spur, slopes N. 20° W.; desc. over broken NE. slope.</p> <p>19.485 Point for the N 1/16 sec. cor. of secs. 7 and 8.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding-left: 100px;"> N1/16 S7 S8 1991 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 12½° E., 54 lks. dist., mkd. N1/16 S8 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 83 3/4° W., 39 lks. dist., mkd. N1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located on the E. side of and against a sawed stump, 20 ins. diam. and 2½ ft. high.</p> <p>Descend over broken NE. slope.</p> <p>33.15 Ravine, drains E.; continue over nearly level ground.</p>
--------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
36.40	Dirt road, 15 lks. wide, bears N. 30° W. and S. 40° E.
37.90	Dirt road, 15 lks. wide, bears N. 50° W. and S. 40° E.
38.970	The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, and in a collar of stone, with brass cap mkd.
	T28S R7W S6 S5 ----- S7 S8 1924
	from which the remains of a bearing tree mkd. by Mensch
	A rotted fir stump, size indeterminate, bears N. 47° E., 24 lks. dist., with fragmentary scribe marks visible on open blaze.
	and accessories mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 149
	A yew, 20 ins. diam., bears N. 11½° E., 45 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
	A PK nail in the center of a 3 in. by 3 in. cross on a 7 ft. high by 6 ft. wide sandstone outcrop, bears N. 49¼° E., 43 lks. dist.
	and bearing trees mkd. by A. Victor Cangie, Deputy County Surveyor, in 1976, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 229
	A fir, 16 ins. diam., bears S. 2¼° E., 50 lks. dist., with healed blaze.
	A fir, 14 ins. diam., bears S. 46½° W., 106 lks. dist., with healed blaze.
	N. 85° 52' 00" W., bet. secs. 6 and 7.
	Descend over W. slope, through scattered timber and moderate undergrowth.
3.05	Creek, 4 lks. wide, course N.; asc. over NE. slope.
7.65	Abandoned dirt road, 15 lks. wide, bears N. 40° W. and SE.
9.25	Abandoned dirt road, 15 lks. wide, bears N. and S., and top of spur, slopes N.; desc. over broken NW. slope.
11.35	Abandoned dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
19.10	Creek, 2 lks. wide, course S. 15° E.; asc. over NE. slope.
21.60	Abandoned dirt road, 15 lks. wide, bears S. 10° E. and N. 10° W., and top of spur, slopes N. 10° W.; desc. over broken NW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS 21.715	<p>The E 1/16 sec. cor. of secs. 6 and 7, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1965, recorded in the Douglas County Surveyors Office file, CS 51/317, and is accepted as the corner; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 18 ins. above ground, from which a bearing tree mkd. by Boyer:</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 14½° E., 56 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">S6 E1/16 ----- S7 1991</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 53½° W., 36 lks. dist., mkd. E1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85° 49' 00" W., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
4.75	Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.
20.30	Ravine, drains N. 40° W.; asc. over NE. slope.
21.560	<p>The 1/4 sec. cor. of secs. 6 and 7, reestablished by Arthur Boyer, Registered Professional Engineer No. 1581, in 1958, recorded in the Douglas County Surveyors Office map file, M13-19, perpetuated by Arthur Boyer, Registered Professional Engineer No. 1581, in 1965, recorded in the Douglas County Surveyors Office file, CS 51/317, further perpetuated by A. Victor Cangie, Deputy County Surveyor, in 1976, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 228, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS CO. SURVEYOR T28S R7W 1/4 COR S6 ----- S7 1976</p> <p>from which bearing trees mkd. by Boyer in 1965</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 73½° E., 28 lks. dist., with healed double blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">A fir, 25 ins. diam., bears N. 20° W., 52 lks. dist., with healed double blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 85° 26' 00" W., beginning new measurement.</p> <p>Ascend over NE. slope.</p> <p>1.05 Spur, slopes N. 20° W.; desc. over broken NW. slope.</p> <p>11.50 East edge of beaver pond, bears N. 80° E. and S. 80° W.</p> <p>13.40 West edge of same beaver pond, bears N. 80° E. and S. 80° W.; asc. over broken SE. slope.</p> <p>20.80 Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.</p> <p>21.265 Point for the W 1/16 sec. cor. of secs. 6 and 7.</p> <p style="padding-left: 40px;">Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>S6 W1/16 ----- S7 1994</p> </div> <p>from which a bearing tree mkd. during the Administrative Survey</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 19° E., 36 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 46° E., 38 lks. dist., mkd. W1/16 S6 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by an unofficial Bureau of Land Management Administrative Survey in 1976, bears N. 56° 19' 00" E., 0.011 chs. dist., monumented with a steel fence post, firmly set.</p> <p>This point was not utilized during the course of this survey, the fence post was removed and reset alongside the stainless steel post and a new bearing and distance was taken to the bearing tree mkd. during the Administrative Survey.</p> <p>Ascend over broken SE. slope.</p> <p>29.25 Abandoned dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.</p> <p>35.55 Abandoned dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.</p> <p>37.30 Ridge, bears N. 60° E. and S. 60° W.; desc. over broken NW. slope.</p> <p>39.75 Dirt road, 15 lks. wide, bears N. 65° E. and S.</p>
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS 43.530	<p>The cor. of secs. 6 and 7, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Boundaries of Donation Land Claim No. 50, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the survey by Josiah A. Burnett and Elliott N. Bowman, U.S. Deputy Surveyors, in 1855-56)</p> <hr/> <p>From the SW. interior L cor. of Donation Land Claim No. 50, identical with the N.-NW. cor. of Donation Land Claim No. 53, perpetuated by Arthur Boyer, Registered Professional Engineer No. 1581, in 1947, recorded in the Douglas County Surveyors Office map file, M29-9, further perpetuated by Randall W. Smith, Deputy County Surveyor, in 1987, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 265; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYORS OFFICE T28S R7W S27 +----- NNW DLC 53 1987</p> <p>from which a bearing tree marked by Boyer</p> <p style="padding-left: 40px;">An oak, 28 ins. diam., bears S. 40° W., 227 lks. dist., no marks visible on opened blaze.</p> <p>and bearing trees mkd. by Smith</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 72 3/4° E., 75 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 32½° E., 75 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 50¼° W., 184 lks. dist., with healed double blaze.</p> <p>Found an iron pipe, 1 in. diam., buried alongside the iron post.</p> <p>The corner is located at a fence corner with barbed wire fence extending W. and woven wire fence extending S.</p> <p>N. 89° 54' 00" E., on the S. bdy. of Claim No. 50, a portion of which is identical with the N. bdy. of Claim No. 53.</p> <p>Over nearly level ground, through populated area.</p> <p>9.35 Asphalt road, 35 lks. wide, bears NE. and SW.</p> <p>11.10 Lookingglass Creek, 60 lks. wide, course N. 60° E.; continue over nearly level ground.</p>
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 50,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	
26.85	County Road No. 38 (Olalla Road), asphalt-surfaced, 35 lks. wide, bears N. 55° E. and S. 55° W.
40.055	Point for the NE. cor. of Donation Land Claim No. 53, hereinafter described; begin ascent over broken NW. slope.
49.030	Intersect the E. and W. center line of sec. 27. Point for the crossing closing cor. of the E. and W. center line of sec. 27 with the S. bdy. of Donation Land Claim No. 50, hereinafter described. From this point, the 1/4 sec. cor. of secs. 26 and 27 bears S. 85° 47' 00" E., 13.590 chs. dist.
52.290	Point for the SE. cor. of Donation Land Claim No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T28S R7W C50 S27 ----- 1993</div> from which <div style="margin-left: 40px;">A maple, 9 ins. diam., bears N. 75° W., 64 lks. dist., mkd. C50 BT.</div> <div style="margin-left: 40px;">The most southerly trunk of a triple trunk madrone, 10 ins. diam., bears N. 30 3/4° W., 17 lks. dist., mkd. C50 BT.</div> Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. <hr style="width: 50%; margin-left: 0;"/> N. 0° 14' 00" W., on the E. bdy. of Claim No. 50. Ascend over SW. slope, through moderate timber and undergrowth.
0.75	Spur, slopes N. 50° W.; and woven wire fence, extends N. 80° E. and S. 80° W.; desc. over steep NW. slope.
6.20	Bottom of steep descent; continue over nearly level ground.
10.00	County Road No. 38 (Olalla Road), asphalt-surfaced, 35 lks. wide, bears N. 25° E. and S. 35° W.
39.85	State Highway No. 42, asphalt-surfaced, 55 lks. wide, bears N. 70° E. and S. 70° W.
40.065	Point for the NE. cor. of Donation Land Claim No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner. Set a "PK" nail in the asphalt-surface of State Highway No. 42.

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 50,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>from which</p> <p style="padding-left: 40px;">An ash, 22 ins. diam., bears S. 6½° E., 290 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 64° E., 233.2 lks. dist., with brass cap mkd. RM C50 154 FT TO COR 1993 and an arrow pointing to the corner.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The reference monument is located in a woven wire fence extending N. 65° E. and S. 65° W.</p> <p>The NE. abutment of a concrete bridge spanning Lookingglass Creek, bears S. 70 3/4° W., 6.28 chs. dist.</p> <hr/> <p>N. 89° 54' 00" W., on the N. bdy. of Claim No. 50.</p> <p>Over level ground, through scattered brush and fields.</p> <p>8.75 Lookingglass Creek, 1 ch. wide, course N. 25° W.; continue over rolling ground, through scattered brush and fields.</p> <p>30.70 County Road No. 108 (Strickland Canyon Road), asphalt-surfaced, 40 lks. wide, bears N. 65° E. and S. 65° W.</p> <p>36.50 Graveled road, 20 lks. wide, bears N. 10° W. and S. 10° E.</p> <p>45.90 Creek, 2 lks. wide, course S. 30° E.; asc. over gradual broken SE. slope.</p> <p>59.75 Creek, 5 lks. wide, course S. 20° E.; asc. over gradual SE. slope.</p> <p>72.190 Point for the NW. cor. of Donation Land Claim No. 50, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.</p> <p>Set a stainlesssteel post, 28 ins. long, 2½ ins. diam., 32 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28S R7W S28 C55 ----- C50 1993 </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 72½° E., 359 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 17 ins. diam., bears S. 9½° E., 287 lks. dist., mkd. C50 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 50,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>The corner is located in an open field.</p> <hr/> <p>S. 0° 14' 00" W., on the W. bdy. of Claim No. 50.</p> <p>Over nearly level ground, through scattered brush and fields.</p> <p>24.90 State Highway No. 42, asphalt-surfaced, 55 lks. wide, bears N. 70° E. and S. 70° W.</p> <p>54.910 The SW. cor. of Donation Land Claim No. 50, identical with the most westerly NW. cor. of Donation Land Claim No. 53, and on the E. bdy. of Donation Land Claim No. 51, perpetuated by Arthur Boyer, Registered Professional Engineer No. 1581, in 1947, recorded in the Douglas County Surveyors Office map file, M29-9, further perpetuated by Herbert L. Northcraft, Registered Land Surveyor No. 750, in 1972, recorded in the Douglas County Surveyors Office map file, M44-41; monumented with an iron rod, 5/8 in. diam., firmly set flush with the ground, from which the remains of a bearing tree mkd. by Boyer:</p> <p style="padding-left: 40px;">A fir snag, 18 ins. diam., bears N. 23½° E., 9½ lks. dist., with scribe marks C 158 visible on open decaying blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C50 C51 ----- C53 1993</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 42° E., 41 lks. dist., mkd. C50 BT.</p> <p style="padding-left: 40px;">A maple, 13 ins. diam., bears S. 26½° E., 49 lks. dist., mkd. C53 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located at a fence corner with woven wire fences extending N., S., and E.</p> <hr/> <p>NOTE: The SE. cor. of Donation Land Claim No. 55, identical with the NE. cor. of Donation Land Claim No. 51, was searched for but not recovered.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of A Portion of the Boundaries of Donation Land Claim No. 53, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p style="text-align: center;">(Restoring the survey by Josiah A. Burnett and Elliott N. Bowman, U.S. Deputy Surveyors, in 1862)</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the NE. cor. of Donation Land Claim No. 53, on the S. bdy. of Donation Land Claim No. 50, determined by the compass rule method; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C50 ----- C53 S27 1993</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 0 3/4° W., 78 lks. dist., mkd. C53 BT.</p> <p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 30 3/4° W., 105 lks. dist., mkd. C53 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located South, 0.25 chs. dist. of a dirt road, 15 lks. wide, bears E. and W.</p> <p>S. 0° 05' 00" E., on the E. bdy. of Claim No. 53.</p> <p>Ascend over broken NW. slope, through heavy timber and moderate undergrowth.</p> <p>31.45 Ridge, bears N. 35° E. and S. 35° W.; desc. over broken SE. slope.</p> <p>38.685 Intersect the section line between secs. 27 and 34.</p> <p>Point for the crossing closing cor. of the section line between secs. 27 and 34 with the E. bdy. of Donation Land Claim No. 53, hereinbefore described.</p> <p>From this point, the 1/4 sec. cor. of secs. 27 and 34 bears N. 86° 18' 00" W., 15.555 chs. dist.</p> <p>44.970 Point for the SE. cor. of Donation Land Claim No. 53, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C53 S34 ----- 1993</p> <p>from which</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>An oak, 22 ins. diam., bears N. 80½° W., 44 lks. dist., mkd. C53 BT.</p> <p>A madrone, 7 ins. diam., bears N. 49 3/4° W., 16 lks. dist., mkd. C53 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located N. 84° W., 1.90 chs. dist. of a fence corner, with woven wire fences extending N. 75° E., S. 75° W., and S. 10° E.</p> <hr/> <p>N. 89° 53' 00" W., on the S. bdy. of Claim No. 53.</p> <p>Ascend over broken S. slope, through scattered trees and undergrowth.</p> <p>10.95 Rocky spur, slopes S. 20° W.; desc. over steep W. slope.</p> <p>38.60 County Road No. 38 (Olalla Road), asphalt-surfaced, 30 lks. wide, bears N. 20° W. and S. 20° E.</p> <p>40.75 Perron Creek, 5 lks. wide, course N. 30° W., continue over level ground.</p> <p>45.30 Olalla Creek, 70 lks. wide, course NW.; asc. over E. slope.</p> <p>69.15 Ridge, bears N. 10° E. and SW.; desc. over NW. slope.</p> <p>104.60 Bottom of descent; asc. over broken NE. slope.</p> <p>113.35 Dirt road, 20 lks. wide, bears N. and S.</p> <p>114.55 Dirt road, 20 lks. wide, bears N. 10° E. and S. 10° W.</p> <p>119.50 Graveled road, 20 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>119.830 Point for the SW. cor. of Donation Land Claim No. 53, at proportionate position, determined by the Compass Rule method; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28S R7W</p> <p>S33 C53</p> <p>-----</p> <p>1993</p> </div> <p>from which</p> <p>A fir, 9 ins. diam., bears N. 24° E., 8½ lks. dist., mkd. C53 BT.</p> <p>A fir, 11 ins. diam., bears N. 52¼° E., 91 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

NOTE: The NW. cor. of Donation Land Claim No. 52, was searched for but not recovered.

N. 0° 05' 00" E., on the W. bdy. of Claim No. 53.

Descend over NE. slope, through timber and dense undergrowth.

13.025

Point for the N.-SW. cor. of Donation Land Claim No. 53, determined by single proportionate measurement; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.

T28S R7W
 C51

S28 | C53
 1993

from which

A fir, 17 ins. diam., bears S. 78½° E., 72 lks. dist., mkd. C53 BT.

A fir, 4 ins. diam., bears S. 13° E., 45 lks. dist., mkd. X BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the SW. cor. of Donation Land Claim No. 51, perpetuated by J. W. Cole, County Surveyor, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 1, further perpetuated by George J. Wenderoth, Deputy County Surveyor, in 1946, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 103, further perpetuated by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file, M33-57, bears S. 89° 50' 00" W., 0.400 chs. dist.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T28S SW COR. DLC 51 R7W 1969, from which a remaining bearing tree mkd. by Wenderoth:

A fir, 25 ins. diam., bears N. 67° E., 47½ lks. dist., with healed double blaze.

and a bearing tree mkd. by Byron

A fir, 14 ins. diam., bears N. 12¼° W., 42½ lks. dist., with healed blaze.

N. 89° 50' 00" E., on the most southerly N. bdy. of Claim No. 53, identical with a portion of the S. bdy. of Claim No. 51.

**Dependent Resurvey of A Portion of the
Boundaries of Donation Land Claim No. 53,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Descend over NE. slope, through moderate timber and light undergrowth.</p>
15.90	Tenmile Creek, 30 lks. wide, course S.; continue over level ground.
41.80	Tenmile Creek, 30 lks. wide, course NE.; asc. over NW. slope.
59.670	<p>The SW. interior L cor. of Donation Land Claim No. 53, identical with the SE. cor. of Donation Land Claim No. 51, perpetuated by George J. Wenderoth, Deputy County Surveyor, in 1946, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 102, further perpetuated by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 162; monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T28S R7W C51 C53 ----- 1993</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears N. 36 3/4° E., 94 lks. dist., mkd. C53 BT.</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., bears S. 85¼° W., 35½ lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located South, 0.03 chs. dist. of a woven wire fence extending E. and W., and North, 0.48 chs. dist. of a dirt road, 15 lks. wide, bears N. 60° W. and S. 40° E.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 1° 47' 00" E., on the N. and S. center line of sec. 7.</p> <p>Ascend over S. slope, through heavy timber and moderate undergrowth.</p>
7.80	Ridge, bears E. and W.; desc. over N. slope.
12.70	Creek, 5 lks. wide, course N. 80° W.; asc. over S. slope.
19.325	Point for the center S 1/16 sec. cor. of sec. 7.

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S1/16 S7 C 1994</p> <p>from which bearing trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 61° E., 79 lks. dist., with scribe marks S1/16 S7 T28S R7W visible on opened blaze.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears N. 89 3/4° W., 24½ lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 64½° E., 16½ lks. dist., mkd. CS1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by person(s) unknown, bears N. 2° 19' 00" E., 0.074 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by person(s) unknown:</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 57° E., 83 lks. dist., with scribe marks S1/16 S7 T28S R7W visible on opened blaze.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears S. 73½° W., 27½ lks. dist., with healed blaze.</p> <p>This point was not utilized in this survey.</p> <p>Ascend over S. slope.</p> <p>19.75 Dirt road, 15 lks. wide, bears E. and W.</p> <p>21.55 Dirt road, 15 lks. wide, bears S. 80° E. and N. 55° W.</p> <p>26.35 Dirt road, 15 lks. wide, bears S. 80° E. and N. 80° W.</p> <p>35.90 Dirt road, 15 lks. wide, bears N. 85° W. and S. 85° E., also at top of ridge, bearing same; desc. over broken NW. slope.</p> <p>38.650 The center 1/4 sec. cor. of sec. 7, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1958, recorded in the Douglas County Surveyors Office map file M13-19, this position was used but not recorded by an unofficial Bureau of Land Management Administrative Survey in 1976, and is accepted as the corner; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 1 in. above ground, with a steel fence post set alongside, from which a bearing tree mkd. during the Administrative Survey:</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears N. 79° E., 32 lks. dist., with healed blaze.</p>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C1/4 S7 1991</p> <p>and new bearing trees</p> <p>A fir, 8 ins. diam., bears S. 23° E., 24½ lks. dist., mkd. C1/4 S7 BT.</p> <p>A fir, 12 ins. diam., bears S. 50½° W., 37 lks. dist., mkd. C1/4 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and reset a fence post alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 27' 00" E., beginning new measurement.</p> <p>Descend over broken NW. slope.</p>
19.250	<p>The center N 1/16 sec. cor. of sec. 7, established by Arthur Boyer, Registered Professional Engineer No. 1581, in 1958, recorded in the Douglas County Surveyors Office map file M13-19, this position was used but not recorded by an unofficial Bureau of Land Management Administrative Survey in 1976, and is accepted as the corner; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 2 ins. above ground, from which the remains of a bearing tree mkd. by Boyer:</p> <p style="padding-left: 40px;">A sawed fir stump, 26 ins. diam., bears S. 15½° W., 25 lks. dist., with scribe marks 1/16 S7 1581 BT visible on open double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <p style="text-align: center;">C N1/16 S7 C 1991</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 36° E., 39 lks. dist., mkd. CN1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 79° W., 70 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2° 07' 30" E., beginning new measurement.</p>

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	Descend over broken NW. slope.
4.35	Woven wire fence of outplanting site, 7½ ft. high, extends S. 20° E. and N. 20° W.
6.70	Woven wire fence of same outplanting site, 7½ ft. high, extends N. 70° E. and S. 70° W.
7.35	Graveled road, 20 lks. wide, bears E. and S. 55° W.
19.265	The 1/4 sec. cor. of secs. 6 and 7.
	<hr/>
	From the 1/4 sec. cor. of secs. 7 and 8.
	N. 85° 16' 30" W., on the E. and W. center line of sec. 7.
	Ascend over gradual S. slope, through heavy timber and dense undergrowth.
22.020	Point for the center E 1/16 sec. cor. of sec. 7.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	E1/16 C ----- C S7 1991
	from which
	A fir, 13 ins. diam., bears N. 12° E., 16½ lks. dist., mkd. CE1/16 S7 BT.
	A fir, 12 ins. diam., bears S. 84° W., 16 lks. dist., mkd. CE1/16 S7 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over gradual S. slope.
25.90	Ridge, bears N. 80° E. and S. 80° W.; desc. over NW. slope.
26.60	Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.
44.040	The center 1/4 sec. cor. of sec. 7.
	<hr/>
	N. 85° 18' 30" W., beginning new measurement.
	Descend over NW. slope.
18.05	Dirt road, 15 lks. wide, bears N. 85° W. and S. 65° E., and top of ridge bearing same; continue along top of ridge.
21.170	Point for the center W 1/16 sec. cor. of sec. 7.

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W1/16 C ----- C S7 1991</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 39½° W., 27 lks. dist., mkd. CW1/16 S7 BT.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 43½° W., 60 lks. dist., mkd. CW1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by an unofficial Bureau of Land Management Administrative Survey in 1976, bears S. 83° 57' 00" E., 0.237 chs. dist.; monumented with a steel fence post, firmly set, from which bearing trees mkd. during the Administrative Survey:</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 84¼° W., 95 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 27° W., 50 lks. dist., with healed blaze.</p> <p>This point was not utilized during the course of this survey, the fence post was removed and reset alongside the stainless steel post.</p> <p>Continue along top of ridge.</p> <p>25.60 Dirt road, 15 lks. wide, bears N. 80° E. and W.; also top of ridge, bears same; continue along ridge top.</p> <p>30.00 Begin descent over NW. slope.</p> <p>43.765 The 1/4 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 7.</p> <p>N. 1° 09' 00" E., on the N. and S. center line of the NE 1/4 of sec. 7.</p> <p>Ascend over S. slope, through heavy timber and dense undergrowth.</p> <p>1.80 Dirt road, 15 lks. wide, bears N. 80° E. and S. 70° W., and top of ridge bearing same; desc. over NW. slope.</p> <p>15.55 Abandoned dirt road, 15 lks. wide, bears S. 60° E. and N. 60° W.</p> <p>17.40 Ravine drains N. 30° W.; asc. over SW. slope.</p> <p>18.95 Spur, slopes NW.; desc. over broken NW. slope.</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
19.365	<p>Point for the NE 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NE 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE1/16 S7 1991</p> <p>from which a bearing tree mkd. during the Administrative Survey</p> <p style="padding-left: 40px;">The most westerly trunk of a 3 trunk madrone, 10 ins. diam., bears S. 71° E., 35 lks. dist., with marks 1/16 visible on the bark.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 50° W., 21 lks. dist., mkd. NE1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by an unofficial Bureau of Land Management Administrative Survey in 1976, bears South, 0.005 chs. dist.; monumented with a steel fence post, firmly set.</p> <p>This point was not utilized during the course of this survey, the fence post was removed and reset alongside the stainless steel post.</p> <p>Descend over broken NW. slope.</p>
38.730	<p>The E 1/16 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>N. 85° 33' 30" W., on the E. and W. center line of the NE 1/4 of sec. 7.</p> <p>Ascend over SE. slope.</p>
2.30	Spur, slopes N. 20° W.; desc. over broken NW. slope.
3.25	Abandoned dirt road, 15 lks. wide, bears N. 35° W. and S. 20° E.
4.80	Abandoned dirt road, 15 lks. wide, bears N. and S.
18.35	Abandoned dirt road, 15 lks. wide, bears N. 20° W. and S. 20° E.
20.35	Abandoned dirt road, 15 lks. wide, bears N. 40° E. and S. 30° W.
21.870	<p>The NE 1/16 sec. cor. of sec. 7.</p> <p>Descend over broken NW. slope.</p>
23.15	Creek, 2 lks. wide, course N.; asc. over NE. slope.

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
25.65	From this point, the SE. cor. of an outplanting site, 7½ ft. high, bears North, 0.015 chs. dist., with woven wire fences extending N. 20° W. and S. 80° E.
43.775	The center N 1/16 sec. cor. of sec. 7. <hr/>
	From the S 1/16 sec. cor. of secs. 7 and 8. N. 85° 08' 00" W., on the E. and W. center line of the SE 1/4 of sec. 7. Descend over NW. slope, through heavy timber and dense undergrowth.
16.95	Creek, 2 lks. wide, course S. 70° W.; asc. over SE. slope.
19.70	Spur, slopes S. 80° W.; desc. over broken S. slope.
42.590	The center S 1/16 sec. cor. of sec. 7. <hr/>
	From the W 1/16 sec. cor. of secs. 7 and 18. N. 0° 51' 30" E., on the N. and S. center line of the SW 1/4 of sec. 7. Ascend over S. slope, through heavy timber and dense undergrowth.
3.70	Ridge, bears N. 70° E. and S. 70° W.; desc. over NW. slope.
15.10	Creek, course N. 60° W.; asc. over SW. slope.
19.420	Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the SW 1/4. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd. SW1/16 S7 1994 from which a bearing tree mkd. by person(s) unknown An oak, 26 ins. diam., bears N. 78½° W., 30½ lks. dist., with healed double blazes. and a new bearing tree A fir, 7 ins. diam., bears S. 60° E., 38½ lks. dist., mkd. SW1/16 S7 BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. From this point, a point established by person(s) unknown, bears N. 22° 50' 00" E., 0.021 chs. dist., monumented with an iron rod, 5/8 in. diam., firmly set, projecting 14 ins. above ground, from which a bearing tree mkd. by person(s) unknown:

Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	An oak, 26 ins. diam., bears N. 89½° W., 31 lks. dist., with healed double blaze.
	This point was not utilized during the course of this survey.
	Ascend over S. slope.
19.65	Dirt road, 15 lks. wide, bears N. 85° E. and S. 75° W.
37.25	Dirt road, 15 lks. wide, bears N. 75° W. and S. 75° E.
38.835	The center W 1/16 sec. cor. of sec. 7.
	<hr/>
	From the center S 1/16 sec. cor. of sec. 7.
	N. 85° 28' 00" W., on the E. and W. center line of the SW 1/4 of sec. 7.
	Descend over gradual SW. slope.
20.855	The SW 1/16 sec. cor. of sec. 7.
	Descend over SW. slope.
22.20	Dirt road, 15 lks. wide, bears N. 80° E. and S. 80° W.
25.95	Ravine, drains S. 15° E.; asc. over broken SE. slope.
43.390	The S 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.
	<hr/>
	From the center W 1/16 sec. cor. of sec. 7.
	N. 1° 38' 00" E., on the N. and S. center line of the NW 1/4 of sec. 7.
	Over level ground.
0.10	Dirt road, 15 lks. wide, bears N. 85° W. and S. 85° E., and top of ridge bearing same; desc. over NW. slope.
14.80	Graveled road, 20 lks. wide, bears N. 80° E. and W.
19.225	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E. and W. center line of the NW 1/4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NW1/16 S7 1994
	from which
	A fir, 16 ins. diam., bears N. 21 3/4° E., 59 lks. dist., mkd. NW1/16 S7 BT.
	A fir, 11 ins. diam., bears S. 81½° E., 52 lks. dist., mkd. NW1/16 S7 BT.

**Subdivision of Section 7,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by an unofficial Bureau of Land Management Administrative Survey in 1976, bears S. 85° 43' 00" E., 0.120 chs. dist., monumented with a steel fence post, firmly set, from which a bearing tree mkd. during the Administrative Survey:</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 68 3/4° W., 30 lks. dist., no scribe marks visible on open double blaze.</p> <p>This point was not utilized during the course of this survey.</p> <p>Descend over NW. slope.</p>
35.60	Creek, 8 lks. wide, course N. 40° E.; asc. over SE. slope.
38.460	The W 1/16 sec. cor. of secs. 6 and 7.
<hr/>	
16.10	<p>From the center N 1/16 sec. cor. of sec. 7.</p> <p>N. 85° 20' 00" W., on the E. and W. center line of the NW 1/4 of sec. 7.</p> <p>Descend over gradual broken S. slope.</p>
21.105	<p>Graveled road, 20 lks. wide, bears N. 75° E. and S. 60° W.</p> <p>The NW 1/16 sec. cor. of sec. 7.</p> <p>Descend over gradual broken S. slope.</p>
42.15	Creek, 3 lks. wide, course N. 30° W.; continue over broken S. slope.
43.520	The N 1/16 sec. cor. of sec. 7 only, on the W. bdy. of the Tp.
<hr/>	
<p>Subdivision of Section 18, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 18 and 19, perpetuated by James W. Byron, Deputy County Surveyor, in 1961, from original evidence no longer in existence, recorded in the Douglas County Surveyors Office corner renewal file T. 28 S., R. 7 W., No. 161, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.</p>	
<p>COUNTY SURVEYORS OFFICE T28S R7W S18 1/4 ----- S19 1961</p>	
from which bearing trees mkd. by Byron	

Subdivision of Section 18,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 18 ins. diam., bears S. 36 3/4° W., 8½ lks. dist., with healed double blaze.</p> <p>A fir, 17 ins. diam., bears N. 32° W., 25½ lks. dist., with healed double blaze.</p> <p>From this point, U.S. Coast and Geodetic Survey triangulation station 'TENMILE,' bears S. 56° 21' 17" E., 42.216 chs. dist. (mean bearing and sea level distance); monumented with a brass cap cemented flush in solid rock, with top mkd. TENMILE 1942-1976.</p> <p>N. 3° 53' 30" W., on the N. and S. center line of sec. 18.</p> <p>Descend over broken NE. slope, through heavy timber and dense undergrowth.</p>
5.05	Ravine, drains N. 35° E.; asc. over SE. slope.
11.00	Spur, slopes N. 65° E.; desc. over NE. slope.
14.00	Ravine, drains N. 75° E.; asc. over SE. slope.
41.85	Spur, slopes S. 85° E.; desc. over NE. slope.
43.330	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C1/4 S18 1991</p> <p>from which</p> <p>A fir, 6 ins. diam., bears N. 35° E., 30 lks. dist., mkd. C1/4 S18 BT.</p> <p>A cedar, 18 ins. diam., bears S. 22° E., 17½ lks. dist., mkd. C1/4 S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Descend over NE. slope.</p>
57.55	Porter Creek, 5 lks. wide, course S. 70° E.; asc. over broken SW. slope.
62.580	<p>Point for the center N 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N1/16 S18 C 1991</p>

Subdivision of Section 18,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 51½° E., 95 lks. dist., mkd. CN1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 14° W., 47 lks. dist., mkd. CN1/16 S18 BT.</p> <p>Ascend over broken SW. slope.</p>
81.830	<p>The 1/4 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 84° 12' 00" W., on the E. and W. center line of sec. 18.</p> <p>Ascend over broken NE. slope, through heavy timber and moderate undergrowth.</p>
2.95	<p>Spur, slopes N. 5° E.; desc. over broken NW. slope.</p>
17.80	<p>Creek, 5 lks. wide, course N. 20° E.; asc. over broken SE. slope.</p>
20.665	<p>Point for the center E 1/16 sec. cor. of sec. 18.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E1/16 C ----- C S18 1991</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 24 3/4° E., 3½ lks. dist., mkd. CE1/16 S18 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 87 3/4° W., 25 lks. dist., mkd. CE1/16 S18 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over E. slope.</p>
41.330	<p>The center 1/4 sec. cor. of sec. 18.</p> <p>Ascend over broken SE. slope.</p>
44.80	<p>Ridge, bears N. 35° E. and S. 35° W.; desc. over NW. slope.</p>
59.85	<p>Creek, 5 lks. wide, course N. 30° E.; asc. over broken E. slope.</p>
86.475	<p>The 1/4 sec. cor. of sec. 18 only, on the W. bdy. of the Tp., monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p>

Subdivision of Section 18,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	T 1/4 S18 1924
	from which bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 167
	A fir, 15 ins. diam., bears N. 46 3/4° E., 25½ lks. dist., with healed double blaze.
	A cedar, 12 ins. diam., bears S. 66½° E., 38 lks. dist., with healed double blaze.
	<hr/> From the center E 1/16 sec. cor. of sec. 18.
	N. 3° 58' 00" W., on the N. and S. center line of the NE 1/4 of sec. 18.
	Ascend over SE. slope, through heavy timber and dense undergrowth.
1.40	Spur, slopes N. 80° E.; desc. over NE. slope.
5.10	Porter Creek, 10 lks. wide, course S. 60° E.; asc. over broken S. slope.
9.25	Dirt road, 15 lks. wide, bears N. 65° W. and S. 65° E.
19.385	Point for the NE 1/16 sec. cor. of sec. 18, at intersection with the E. and W. center line of the NE 1/4.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	NE1/16 S18 1991
	from which
	A fir, 7 ins. diam., bears S. 27° E., 48 lks. dist., mkd. NE1/16 S18 BT.
	A fir, 9 ins. diam., bears N. 33° W., 23 lks. dist., mkd. NE1/16 S18 BT.
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	Ascend over broken S. slope.
26.50	Spur, slopes S. 50° W.; continue over nearly level ground on a W. slope.
29.65	Spur, slopes N. 85° W.; desc. over NW. slope.
37.00	Ravine, drains S. 80° W.; asc. over SW. slope.
38.775	The E 1/16 sec. cor. of secs. 7 and 18.
	<hr/>

**Subdivision of Section 18,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>From the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>N. 84° 33' 30" W., on the E. and W. center line of the NE 1/4 of sec. 18.</p> <p>Ascend over broken S. slope.</p>
20.620	<p>The NE 1/16 sec. cor. of sec. 18.</p> <p>Ascend over broken S. slope.</p>
21.45	<p>Spur, slopes S. 20° E.; desc. over broken SW. slope.</p>
33.45	<p>Ravine, drains S. 15° W.; asc. over SE. slope.</p>
41.245	<p>The center N 1/16 sec. cor. of sec. 18.</p>
<hr/> <p>Subdivision of Section 21, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/>	
19.465	<p>From the 1/4 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 13' 00" W., on the N. and S. center line of sec. 21.</p> <p>Ascend over SW. slope, through moderate timber and undergrowth.</p> <p>Point for the center S 1/16 sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> C S1/16 S21 C 1992 </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears N. 54¼° E., 32½ lks. dist., mkd. CS1/16 S21 BT.</p> <p style="margin-left: 40px;">A fir, 17 ins. diam., bears N. 53½° W., 28 lks. dist., mkd. X BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SW. slope.</p>
38.930	<p>Point for the center 1/4 sec. cor. of sec. 21, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T28S R7W C1/4 S21 1992 </div>

Subdivision of Section 21,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A cedar, 9 ins. diam., bears S. 15° E., 48½ lks. dist., mkd. C1/4 S21 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 64½° W., 42 lks. dist., mkd. C1/4 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over broken SW. slope.</p>
76.90	Ridge, bears N. 75° E. and S. 75° W.; continue over nearly level ground.
77.820	The 1/4 sec. cor. of secs. 16 and 21.
	<hr/> <p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>N. 88° 47' 00" W., on the E. and W. center line of sec. 21.</p> <p>Descend over W. slope, through moderate timber and dense undergrowth.</p>
6.10	Creek, 5 lks. wide, course S.; asc. over SE. slope.
28.90	Spur, slopes SW.; desc. over broken W. slope.
39.475	The center 1/4 sec. cor. of sec. 21.
	Descend over broken W. slope.
41.85	Creek, 5 lks. wide, course S. 20° W.; asc. over broken E. slope.
59.215	Point for the center W 1/16 sec. cor. of sec. 21.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W1/16</p> <p>C ----- C</p> <p>S21</p> <p>1992</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 12 3/4° E., 23 lks. dist., mkd. CW1/16 S21 BT.</p> <p style="padding-left: 40px;">A madrone, 19 ins. diam., bears S. 41° E., 17½ lks. dist., mkd. CW1/16 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>Ascend over E. slope.</p>
59.95	Spur, slopes S. 20° W.; desc. over broken SW. slope.

Subdivision of Section 21,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
78.955	<p>The 1/4 sec. cor. of secs. 20 and 21.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>N. 88° 36' 00" W., on the E. and W. center line of the SE 1/4 of sec. 21.</p> <p>Descend over SW. slope, through heavy timber and moderate undergrowth.</p>
5.50	Creek, 5 lks. wide, course S. 10° E.; asc. over SE. slope.
17.25	Spur, slopes S. 10° W.; desc. over SW. slope.
25.50	Ravine, drains S. 25° E.; asc. over broken SE. slope.
35.65	Spur, slopes S. 10° E.; desc. over SW. slope.
39.340	<p>The center S 1/16 sec. cor. of sec. 21.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 21 and 28.</p> <p>N. 0° 25' 00" W., on the N. and S. center line of the SW 1/4 of sec. 21.</p> <p>Ascend over SW. slope, through heavy timber and moderate undergrowth.</p>
19.390	<p>Point for the SW 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the SW 1/4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW1/16 S21 1992</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 11 ins. diam., bears S. 4¼° E., 5½ lks. dist., mkd. SW1/16 S21 BT.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 60½° W., 14½ lks. dist., mkd. SW1/16 S21 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established by person(s) unknown, bears N. 30° 55' 30" E., 0.265 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 6 ins. above ground.</p> <p>This point was not utilized during the course of this survey.</p> <p>Ascend over S. slope.</p>
38.775	<p>The center W 1/16 sec. cor. of sec. 21.</p> <hr/>

Subdivision of Section 27,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>15.20 Ravine, drains N. 10° W.; continue descending over broken NW. slope.</p> <p>18.65 Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.</p> <p>38.50 County Road No. 38 (Olalla Road), asphalt-surfaced, 35 lks. wide, bears N. 55° E. and S. 55° W.; continue over nearly level ground, through scattered brush and fields.</p> <p>46.45 Lookingglass Creek, 75 lks. wide, course N. 70° E.; continue over nearly level ground.</p> <p>50.80 Asphalt-surfaced road, 35 lks. wide, bears N. 40° E. and S. 40° W.</p> <p>76.905 The 1/4 sec. cor. of secs. 27 and 28, reestablished by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file M33-57, perpetuated by Herbert L. Northcraft, Registered Land Surveyor No. 750, in 1972, recorded in the Douglas County Surveyors Office map file M44-41, and is accepted as the corner; monumented with an iron rod, 5/8 in. diam., firmly set 5 ins. below ground, from which bearing trees mkd. by Byron:</p> <p style="padding-left: 40px;">The most northerly trunk of a double trunk oak, 14 ins. diam., bears S. 12° E., 381 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">The most easterly trunk of a triple trunk ash, 25 ins. diam., bears N. 10 3/4° W., 142 lks. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 38 ins. in the ground, directly over the iron rod, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W 1/4 S28 S27 1993</p> <p>No new accessories taken.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located in an open field, West, 0.73 chs. dist. of a woven wire fence extending N. and S.</p> <p>From this point, the cor. of secs. 21, 22, 27 and 28, bears N. 0° 34' 00" E., 39.970 chs. dist.</p> <p>From this same point, the cor. of secs. 27, 28, 33 and 34, bears S. 0° 30' 00" W., 39.970 chs. dist.</p> <hr style="width: 50%; margin: 20px auto;"/> <p style="text-align: center;">Subdivision of Section 35, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr style="width: 50%; margin: 20px auto;"/>
--------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 35,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>N. 0° 42' 00" E., on the N. and S. center line of sec. 35.</p> <p>Ascend over broken SW. slope, through heavy timber and moderate undergrowth.</p> <p>16.25 Spur, slopes S. 80° W.; desc. over broken NW. slope.</p> <p>35.15 Spur, slopes N. 65° W.; desc. over NE. slope.</p> <p>37.055 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T28S R7W C1/4 S35 1992</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 42° E., 27½ lks. dist., mkd. C1/4 S35 BT.</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears S. 84 3/4° W., 38½ lks. dist., mkd. C1/4 S35 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>The corner is located South, 0.31 chs. dist. of a woven wire fence extending E. and W.</p> <p>Descend over NE. slope.</p> <p>49.25 County Road No. 125 (Hoover Hill Road), asphalt-surfaced, 45 lks. wide, bears N. 60° E. and S. 75° W.</p> <p>55.50 Perron Creek, dry, 5 lks. wide, course S. 85° W.; asc. over SW. slope.</p> <p>75.230 The 1/4 sec. cor. of secs. 26 and 35, reestablished by James W. Byron, Douglas County Surveyor, in 1969, recorded in the Douglas County Surveyors Office map file M33-57, and is accepted as the corner; monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S S26 1/4 ----- S35 R7W 1969</p> <p>from which bearing trees mkd. by Byron</p>
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Subdivision of Section 35,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS	
	<p>A madrone, 11 ins. diam., bears N. 21° E., 10½ lks. dist., with partial scribe marks visible on open blaze.</p> <p>A fir, 16 ins. diam., bears S. 7¼° W., 69 lks. dist., with healed blaze.</p> <p>The corner is located S. 30° W., 0.28 chs. dist. of a madrone tree fence corner, with woven wire fences extending N., S., and W., and S. 50° W., 0.19 chs. dist. of a steel fence post, with woven wire fences extending N., S., and E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>N. 89° 02' 00" W., on the E. and W. center line of sec. 35.</p> <p>Ascend over broken E. slope, through heavy timber and dense undergrowth.</p>
17.00	Spur, slopes N.; desc. over NW. slope.
31.40	Ravine, drains N. 20° W.; asc. over NE. slope.
39.325	The center 1/4 sec. cor. of sec. 35.
	Ascend over NE. slope.
40.90	Spur, slopes N. 20° W.; desc. over NW. slope.
59.110	Point for the center W 1/16 sec. cor. of sec. 35.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	W1/16 C ----- C S35 1992
	from which
	<p>A fir, 11 ins. diam., bears N. 19¼° E., 31 lks. dist., mkd. CW1/16 S35 BT.</p> <p>A cedar, 21 ins. diam., bears S. 69¼° E., 36½ lks. dist., mkd. CW1/16 S35 BT.</p>
	Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.
	The corner is located N. 82° E., 0.21 chs. dist. of a fence corner, with woven wire fences extending E., W., and S.
	Descend over W. slope.
66.40	Ravine, drains N. 15° W.; asc. over NE. slope.

Subdivision of Section 35,
T. 28 S., R. 7 W., Willamette Meridian, Oregon

CHAINS 78.895	<p>The 1/4 sec. cor. of secs. 34 and 35, perpetuated by Jesse W. Cole, Deputy County Surveyor, in 1915, recorded in the Douglas County Surveyors Office, field book 37, page 1, further perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyors Office corner renewal file, T. 28 S., R. 7 W., No. 83; monumented with an iron post, 1½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T28S R7W 1/4 S34 S35 1958</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">An oak stump, size indeterminate, bears N. 7½° E., 196 lks. dist., no marks visible. (Record, N. 10° E., 210 lks. dist.)</p> <p style="padding-left: 40px;">The most westerly trunk of a double trunk oak, 29 ins. diam., bears N. 7° W., 248 lks. dist., with partially healed, opened blaze. (Record, N. 5° W., 200 lks. dist.)</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears N. 73¼° E., 63 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">An oak, 27 ins. diam., bears N. 81° W., 9½ lks. dist., with healed double blaze.</p> <p>From this point, the cor. of secs. 26, 27, 34 and 35, bears N. 1° 07' 00" E., 39.435 chs. dist.</p> <p>From this same point, the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., bears S. 0° 34' 00" W., 37.510 chs. dist.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p> <p style="padding-left: 40px;">N. 0° 37' 00" E., on the N. and S. center line of the SW 1/4 of sec. 35.</p> <p>Ascend over broken SW. slope, through heavy timber and moderate undergrowth.</p>
10.75	Spur, slopes W.; desc. over broken NW. slope.
33.65	Ravine, drains N. 70° W.; asc. over SW. slope.
37.285	The center W 1/16 sec. cor. of sec. 35.
	<hr/> <p>Amended Field Notes of the Dependent Resurvey of the East One-Half of the Line Between Sections 8 and 17, T. 28 S., R. 7 W., Willamette Meridian, Oregon</p> <hr/>

**Amended Field Notes of the Dependent Resurvey of the
East One-Half of the Line Between Sections 8 and 17,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS	<p>The purpose of these amended field notes is to correct the erroneously marked monument and bearing trees at the E 1/16 sec. cor. of secs. 8 and 17, as shown in the official record of the 1983-84 Bureau of Land Management survey, approved February 15, 1985. The error was discovered by Bryan S. Seibold, Cadastral Surveyor, a field investigation of this corner verified that the error existed in the field, the monument and bearing trees were changed and those changes are reflected in the following amended field notes.</p> <p>These amended field notes are authorized by memorandum from the Chief, Branch of Cadastral Survey and Mapping Sciences, dated February 28, 1994, file 9630(942), a copy of which follows these returns.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89° 49' W., bet. secs. 8 and 17.</p> <p>Ascend over NE. slope, through heavy timber and dense undergrowth.</p> <p>1.05 Spur, slopes N. 40° W.; desc. over broken W. slope.</p> <p>20.48 Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> S8 E1/16 ----- S17 1983 </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 87½° E., 19 lks. dist., mkd. E1/16 S8 BT.</p> <p style="padding-left: 40px;">A cedar, 5 ins. diam., bears S. 50° W., 45 lks. dist., mkd. E1/16 S17 BT.</p> <p>20.55 Ravine, drains S. 45° W.; asc. over broken SE. slope.</p> <p>40.96 The 1/4 sec. cor. of secs. 8 and 17, reestablished by proportionate distance and recorded by Virgil L. Broadwater, Registered Land Surveyor No. 682, in 1972; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 8 ins. above the ground. There is no remaining evidence of the original corner. This position is accepted as the corner, from which bearing trees mkd. by Broadwater:</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. 48½° E., 31 lks. dist., with fragmentary scribe marks visible on a partially healed double blaze.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 70° W., 40 lks. dist., with healed double blaze.</p> <p>At the corner point</p>
--------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Amended Field Notes of the Dependent Resurvey of the
East One-Half of the Line Between Sections 8 and 17,
T. 28 S., R. 7 W., Willamette Meridian, Oregon**

CHAINS

Set an aluminum post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T28S R7W
 S8
1/4 -----
 S17
 1983

Deposit the iron pipe alongside the aluminum post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, oak, madrone, maple, hemlock, alder, and ash; undergrowth, poison oak, salal, wild grass, vine maple, arrowwood, hazel, fern and young timber.

GENERAL DESCRIPTION

The lands included in the foregoing resurvey are in hilly country located northerly and easterly of Tenmile, Oregon. The elevation ranges from approximately 650 feet above sea level near Lookingglass Creek in section 27, to about 1700 feet above sea level on the top of Hoover Hill in section 35.

The area is drained by Tenmile Creek, Lookingglass Creek, Porter Creek, Perron Creek, and numerous other small and seasonal drainages. The soil consists of a rocky clay in the upper elevations and a clay loam in the creek bottoms. The timber consists of fir, cedar, hemlock, alder, maple, oak, chinquapin, pine, ash, yew and madrone. The undergrowth is mainly salal, Oregon grape, manzanita, arrowwood, poison oak, vine maple and young timber.

Access is gained via State Highway No. 42, Coos Bay Wagon Road, and numerous county roads, with other paved, gravelled, and dirt roads branching from them into the areas.

No mineral deposits were noted along the lines resurveyed. The lands are used primarily for timber.

The average of a number of readings over the area gives a value of 18° East for the mean magnetic declination, with a range of 1° due to local attraction.