

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REMONUMENTATION AND REHABILITATION

OF CERTAIN CORNER POINTS,

TOWNSHIP 25 SOUTH, RANGE 4 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Wayne L. Rogers, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 13, 1979,

and approved July 17, 1979,

and Supplemental Special Instructions dated May 20, 1985,

and approved May 24, 1985

which provided for the surveys included under Group No. 1000,

and assignment instructions dated April 27, 1998.

Survey commenced April 27, 1998

Survey completed April 28, 1998

T. 25 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The following field notes describe the remonumentation and the rehabilitation of certain corner points, township 25 south, range 4 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group Number 1000, Oregon, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed" and "Rehabilitation of Corner Points, without Remonumentation, When Suitable Monumentation Exists."

The remonumentation and rehabilitation of corner points was made at the request of the Roseburg District Manager for the administrative purposes of the Bureau of Land Management.

The mean magnetic declination is $18\frac{1}{2}^{\circ}$ East.

**Subdivision of Section 13, T. 25 S., R. 4 W.,
Willamette Meridian, Oregon**

(Remonumenting a corner established by Irving Zirpel, Jr.,
Lynn M. Roseberry, and Harold D. Corbin, Cadastral
Surveyors, in 1957-58)

The center south 1/16 sec. cor. of sec. 13, determined at record bearing and distance from the remaining bearing tree by Zirpel, Roseberry, and Corbin, from which

A cedar, 24 ins. diam., bears S. 35° W., $150\frac{1}{2}$ lks. dist.,
with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 27 ins. in the ground, with brass cap mkd.

C
S 1/16 S 13
C
1998

from which a new bearing tree

A fir, 8 ins. diam., bears N. 75° E., 18 lks. dist., mkd. CS
1/16 S13 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Remonumentation and Rehabilitation of Certain Corner Points,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS	<p>Corner is located West, 4 lks. of a woven wire fence extending North and South.</p> <hr/> <p style="text-align: center;">(Rehabilitating certain corner points established by Irving Zirpel, Jr., Lynn M. Roseberry, and Harold D. Corbin, Cadastral Surveyors, in 1957-58)</p> <hr/> <p>The center 1/4 sec. cor. of sec. 13, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">C 1/4 S 13 1958</p> <p>from which the remains of bearing trees by Zirpel, Roseberry, and Corbin</p> <p style="padding-left: 40px;">A fir snag, 27 ins. diam., bears S. 41¾° E., 76 lks. dist., with a healed blaze. (Record, 74 lks.)</p> <p style="padding-left: 40px;">A roothole, bears N. 7½° W., 38½ lks. dist., with a down and decayed trunk alongside, with no marks visible.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 52½° E., 9½ lks. dist., mkd. C 1/4 S13 BT.</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 83° W., 255½ lks. dist., mkd. C 1/4 S13 BT.</p> <p>Corner is located East, 2 lks. of a woven wire fence extending North and South.</p> <hr/> <p>The center east 1/16 sec. cor. of sec. 13, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C C S 13 1958</p> <p>from which the remains of bearing trees by Zirpel, Roseberry, and Corbin</p>
--------	--

**Remonumentation and Rehabilitation of Certain Corner Points,
T. 25 S., R. 4 W., Willamette Meridian, Oregon**

CHAINS

A fir, 20 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ E., 88 lks. dist., with a healed blaze. (Record 76 lks. dist.)

A sawed and decayed fir stump, 14 ins. diam., bears S. 80° W., 7 lks. dist., with no marks visible. (Record S. $70\frac{1}{4}^{\circ}$ W.)

and a new bearing tree

A fir, 8 ins. diam., bears N. $38\frac{3}{4}^{\circ}$ W., $10\frac{1}{2}$ lks. dist., mkd. CE 1/16 S13 BT.