

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REHABILITATION OF THE CORNER OF SECTIONS 5, 6, 31 AND 32

ON THE SOUTH BOUNDARY OF

TOWNSHIP 28 SOUTH, RANGE 6 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Under Special Instructions dated July 13, 1979, approved July 17, 1979,
and Supplemental Special Instructions
dated May 20, 1985, approved May 24, 1985,
which provided for the rehabilitation included under Group No. 1000,
and assignment instructions dated May 15, 2000.

Commenced May 15, 2000

Completed May 15, 2000

T. 28 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes describe the Rehabilitation of the corner of sections 5, 6, 31 and 32 on the south boundary of township 28 south, range 6 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon. "Rehabilitation of Corners Points, Without Remonumentation, When Suitable Monuments Exist."

The rehabilitation of the corner of sections 5, 6, 31 and 32 on the south boundary of the township was for administrative purposes of the Bureau of Land Management.

Each new bearing tree has a 2½ inch X 1/4 inch magnetic nail (Mag Nail) driven at the base on the right side-center.

The mean magnetic declination as taken from U.S. Geological Survey Quadrangle map "Winston, OREG.", provisional edition 1987, is 19° 00' 00" East.

**Rehabilitation of the Corner of Sections 5, 6, 31 and 32
on the S. Bdy.,
T. 28 S., R. 6 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by Robert Elder,
U.S. Deputy Surveyor, in 1853, and remonumented by
Wayne L. Rogers, Cadastral Surveyor, in 1987)

The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp. monumented with an iron post, 2½ ins. diam firmly set, projecting 2 ins. above the ground, with brass cap mkd.

```

T 28 S R 6 W
  S 31 | S 32
        |
  S 6  | S 5
T 29 S R 6 W
      1987

```

from which the remains of an original bearing tree

A rotted and sawed fir stump, 36 ins. diam., bears
N. 46½° E., 34.3 ft. dist., with scribe marks T28S S32
visible on a opened blaze.

and the remains of a bearing tree by Springer

**Rehabilitation of the Corner of Sections 5, 6, 31 and 32
on the S. Bdy.,
T. 28 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 25 ins. diam., bears S. 71° E., 25.1 ft. dist., no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p>A fir, 36 ins. diam., bears N. 1¼° E., 28.4 ft. dist., with a healed double blaze.</p> <p>A root hole bears S. 41¼° W., 44.2 ft. dist., with a wind blown fir, 16 ins. diam., lying alongside with a healed double blaze.</p> <p>A root hole bears N. 86¼° W., 11.6 ft. dist., with a wind blown fir, 24 ins. diam., lying alongside with a healed double blaze.</p> <p>and the remains of a bearing tree mkd. by Rogers</p> <p>A root hole bears S. 52½° E., 11.6 ft. dist., with a wind blown fir, 26 ins. diam., lying alongside with scribe marks T29S R6W S5 BT visible on open blaze.</p> <p>and new bearing trees</p> <p>A maple, 11 ins. diam., bears N. 65½° E., 10.1 ft. dist., mkd. T28S R6W S32 BT.</p> <p>A fir, 24 ins. diam., bears S. 40½° E., 45.2 ft. dist., mkd. T29S R6W S5 BT.</p> <p>A fir, 13 ins. diam., bears S. 21° W., 26.0 ft. dist., mkd. T29S R6W S6 BT.</p> <p>Corner is located on a SE. slope.</p> <hr/>