

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REHABILITATION OF THE CLOSING CORNER

OF SECTIONS 3 AND 4 ONLY,

ON THE NORTH BOUNDARY OF

TOWNSHIP 30 SOUTH, RANGE 3 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated July 13, 1979, approved July 17, 1979,
and Supplemental Special Instructions dated May 20, 1985, approved
May 24, 1985, which provided for the rehabilitation included under
Group No. 1000, and assignment instructions dated September 25, 2000.

Commenced September 26, 2000

Completed September 26, 2000

T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation of the closing cor. of secs. 3 and 4 only, on the north boundary of township 30 south, range 3 west, Willamette Meridian, Oregon in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon.

The rehabilitation of the closing cor. of secs. 3 and 4 only, on the north boundary of the township was made for administrative purposes of the Bureau of Land Management.

The new bearing tree has a 2½ inch x ¼ inch magnetic nail (MAG-NAIL) driven at the base on the right side-center.

The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "MILO, OREG.", Provisional Edition 1986, is 18° 30' East.

**Rehabilitation of the Closing Corner of Sections 3 and 4 Only,
on the N. Bdy. of,
T. 30 S., R. 3 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by Lynn M. Roseberry,
Cadastral Surveyor, in 1967)

The closing cor. of secs. 3 and 4 only, on the N. bdy. of the tp., recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 30 S., R. 3 W., Point Identifier No. 400700, monumented with an iron post, 2½ ins diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

```

T 29 S R 3 W
  S 33
  -----
  S 4 | S 3
      | C
T 30 S R 3 W
      1967
  
```

from which the remains of an original bearing tree

A fir, 23 ins. diam., bears S. 49¾° E., 19.8 ft. dist., with a healed blaze. (This tree was originally mkd. as the SE. bearing tree for the original closing cor.)

and remains of a bearing tree mkd. by Gee

Rehabilitation of the Closing Corner of Sections 3 and 4 Only
on the N. Bdy. of,
T. 30 S., R. 3 W., Willamette Meridian, Oregon

FEET	
	<p>A sawed and tin capped fir stump, 16 ins. diam., bears S. $56\frac{1}{4}^{\circ}$ W., 39.9 ft. dist., with a healed blaze on the fallen trunk lying alongside. (This tree was mkd. as a new bearing tree for the original closing cor. Record, S. 51° W., 43.2 ft.)</p> <p>and a new bearing tree</p> <p>A fir, 25 ins. diam., bears S. $27\frac{1}{2}^{\circ}$ W., 102.5 ft. dist., mkd. T30S R3W S4 BT.</p> <hr/>