

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REHABILITATION OF THE 1/4 SECTION CORNER OF SECTIONS 8 AND 9,

AND

THE CORNER OF SECTIONS 4, 5, 8 AND 9,

TOWNSHIP 29 SOUTH, RANGE 2 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated July 13, 1979, approved July 17, 1979,
and Supplemental Special Instructions dated May 20, 1985, approved
May 24, 1985, which provided for the rehabilitation included under
Group No. 1000, and assignment instructions dated September 26, 2000.

Commenced September 27, 2000

Completed September 27, 2000

T. 29 S., R. 2 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation of the 1/4 section corner of sections 8 and 9 and the corner of sections 4, 5, 8 and 9, township 29 south, range 2 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon, "Rehabilitation of Corner Points, Without Remonumentation, When Suitable Monument Exists."

The rehabilitation of the section corner of sections 4, 5, 8 and 9, and the 1/4 section corner of sections 8 and 9 was made for administrative purposes of the Bureau of Land Management.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (MAG-NAIL) driven at the base on the right side-center.

The mean magnetic declination as taken from U.S. Geological Survey quadrangle maps "RED BUTTE, OREGON", Provisional Edition 1986 and "DEADMAN MOUNTAIN, OREGON", Provisional Edition 1989, is 18° East.

**Rehabilitation of the 1/4 Section Corner of Sections 8 and 9,
and the Corner of Sections 4, 5, 8, and 9,
T. 29 S., R. 2 W., Willamette Meridian, Oregon**

(Rehabilitating corners established by Elmer F. Strickler,
U.S. Transitman, in 1917)

The ¼ sec. cor. of secs. 8 and 9, perpetuated by John M. Powell, Frank Jones and Joe Brady, Douglas County Surveyors Office, in 1967, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 29 S., R. 2 W., Point Identifier No. 300540, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone 30 ins. diam., 8 ins. high, with brass cap mkd.

$\frac{1}{4}$
 |
 S 8 | S 9
 |
 1917

from which the remains of an original bearing tree

**Rehabilitation of the 1/4 Section Corner of Sections 8 and 9,
and the Corner of Sections 4, 5, 8, and 9,
T. 29 S., R. 2 W., Willamette Meridian, Oregon**

FEET

A decayed stump, 54 ins. diam., bears N. $11\frac{3}{4}^{\circ}$ W., 145.9 ft. dist., no scribe marks visible.

and bearing trees mkd. by Powell, Jones and Brady

A fir, 27 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ E., 35.6 ft. dist., with a healed blaze.

A fir, 25 ins. diam., bears N. 48° W., 6.4 ft. dist., with a healed blaze.

At the cor. point

Reset the iron post, 36 ins. long, 18 ins. in the ground, in a mound of stone, 30 ins. diam., to top of cap.

The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 29 S	R 2 W
S 5	S 4
S 8	S 9

1917

from which the remains of the original, bearing trees

A roothole bears N. 61° E., 18.5 ft. dist. No evidence remains of the trunk.

A roothole bears S. $74\frac{1}{2}^{\circ}$ E., 25.7 ft. dist., with fallen, decayed trunk, 16 ins. diam., lying alongside, no marks visible. (Record, 29.7 ft.)

A fir, 23 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 2.6 ft. dist., with a healed blaze.

A fir, 21 ins. diam., bears N. 35° W., 16.5 ft. dist., with a healed blaze.

and new bearing trees

A fir, 13 ins. diam., bears N. 60° E., 49.3 ft. dist., mkd. T29S R2W S4 BT.

Rehabilitation of the 1/4 Section Corner of Sections 8 and 9,
and the Corner of Sections 4, 5, 8, and 9,
T. 29 S., R. 2 W., Willamette Meridian, Oregon

FEET	<p>A fir, 20 ins. diam., bears S. 32° E., 30.6 ft. dist., mkd. T29S R2W S9 BT.</p> <hr/>
------	----------------------------------------------------------------------------------------------