

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF THE 1/4 SECTION CORNER
OF SECTIONS 5 AND 6

TOWNSHIP 31 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY


A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated July 13, 1979, approved July 17, 1979,
and Supplemental Special Instructions dated May 20, 1985, approved
May 24, 1985, which provided for the rehabilitation included
under Group No. 1000, and assignment instructions dated October 26, 2000.

Commenced October 26, 2000

Completed October 26, 2000

T. 31 S., R. 6 W., Willamette Meridian, Oregon

<p>FEET</p>	<p>The following field notes describe the rehabilitation of the 1/4 sec. cor. of secs. 5 and 6, township 31 south, range 6 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon, "Rehabilitation of Corner Points, Without Remonumentation, When Suitable Monument Exists."</p> <p>The rehabilitation of the 1/4 sec. cor. of secs. 5 and 6, for administrative purposes of the Bureau of Land Management.</p> <p>The new bearing tree has a 2½ inch x ¼ inch magnetic nail (MAG-NAIL) driven at the base on the right side-center.</p> <p>The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "NICKEL MTN., OREG.", Provisional Edition 1986, is 18° 30' East.</p>
	<p align="center">Rehabilitation of the 1/4 Section Corner of Sections 5 and 6, T. 31 S., R. 6 W., Willamette Meridian, Oregon</p> <hr/> <p align="center">(Rehabilitating a corner reestablished by John M. Jelley, Cadastral Surveyor, in 1965)</p> <hr/> <p>The ¼ sec. cor. of secs. 5 and 6, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 31 S R 6 W</p>  </div> <p>from which the remaining bearing tree mkd. by Jelley</p> <p>A fir, 20 ins. diam., bears N. 59° E., 19.6 ft. dist., with a healed blaze. (Record, 39.6 ft. dist.)</p> <p>and a new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 50° W., 33.1 ft. dist., mkd. ¼ S6 BT.</p> <p>Corner is located on the Jelley blaze line, and 50 ft. N. and 60 ft. E. of a graveled road, 25 ft. wide, which bears N. 50° W. and S. 50° E.</p>