

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

REMONUMENTATION OF THE CORNER OF SECTIONS 15, 16, 21 AND 22,

**TOWNSHIP 27 SOUTH, RANGE 3 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY**

***Timothy J. Moore, Cadastral Surveyor***

Under Special Instructions dated July 13, 1979, approved July 17, 1979,  
which provided for the remonumentation included under Group No. 1000,  
and assignment instructions dated November 16, 2000.

***Commenced November 16, 2000***

***Completed November 16, 2000***

**T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET

The following field notes describe the remonumentation of the corner of sections 15, 16, 21 and 22 of township 27 south, range 3 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, under Group No. 1000, Oregon, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of the corner of sections 15, 16, 21 and 22, was for administrative purposes of the Bureau of Land Management.

Bearings are reported based on the true meridian as determined by direct solar observations.

Each new bearing tree has a 2½ inch X 1/4 inch magnetic nail (Mag Nail) driven at the base on the right side-center.

The mean magnetic declination as taken from U.S. Geological Survey Quadrangle map "Lane Mountain Oreg.", provisional edition 1987, is 19° 00' 00" East

---

**Remonumentation of the Corner of Sections 15, 16, 21 and 22,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

---

(Remonumentation of a corner established by Samuel C. Flint,  
U.S. Deputy Surveyor, in 1882)

---

The cor. of secs. 15, 16, 21 and 22, determined at record bearing and distance from the remains of the original NE. bearing tree.

A roothole, with a high stumped wind blown fir snag, 36 ins. diam., alongside, bears N. 25° E., 14.5 ft. dist., with scribe marks 5 BT and other illegible marks visible on a weathered bark blaze face down.

A roothole, bears S. 70° E., 17.2 ft. dist.

A roothole, bears S. 26° W., 33 ft. dist. (Record, S. 22° W.)

A roothole, bears N. 65° W., 36.3 ft. dist.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

**Re monumentation of the Corner of Sections 15, 16, 21 and 22,  
T. 27 S., R. 3 W., Willamette Meridian, Oregon**

FEET

T 27 S R 3 W  
S 16 | S 15  
S 21 | S 22  
2000

from which new bearing trees

A fir, 20 ins. diam., bears N. 71° E., 27.9 ft. dist., mkd.  
T27S R3W S15 BT.

A fir, 6 ins. diam., bears S. 52½° E., 25.4 ft. dist., mkd.  
X BT.

A fir, 18 ins. diam., bears S. 20° W., 32.0 ft. dist., mkd.  
T27S R3W S21 BT.

A fir, 19 ins. diam., bears N. 58½° W., 27.1 ft. dist., mkd.  
T27S R3W S16 BT.

Deposit a magnet in a white plastic case at the base of the  
stainless steel post.

The corner is located on a S. slope.

---