

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF THE
CORNER OF SECTIONS 2, 3, 34 AND 35

TOWNSHIPS 28 AND 29 SOUTH, RANGE 9 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated July 13, 1979, approved July 17, 1979,
and Supplemental Special Instructions dated May 20, 1985, approved
May 24, 1985, which provided for the rehabilitation included
under Group No. 1000, and assignment instructions dated March 23, 2001.

commenced November 8, 2001

completed November 8, 2001

Tps. 28 and 29 S., R. 9 W., Willamette Meridian, Oregon

<p>FEET</p>	<p>The following field notes describe the rehabilitation of the cor. of secs. 2, 3, 34, and 35, Townships 28 and 29 South, Range 9 West, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon, "Rehabilitation of Corner Points, Without Remonumentation, When Suitable Monument Exists."</p> <p>The rehabilitation of the cor. of secs. 2, 3, 34, and 35 was for administrative purposes of the Bureau of Land Management.</p> <p>Each new bearing tree has a 2½ x ¼ inch magnetic nail (MAG-NAIL) driven at the base on the right side-center.</p> <p>The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "CAMAS VALLEY, OREGON", Provisional Edition dated 1990, is 18° East.</p>										
	<p align="center">Rehabilitation of the Corner of Sections 2, 3, 34, and 35, Tps. 28 and 29 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> <p align="center">(Rehabilitating a corner established by Dennis Hathorn, U.S. Deputy Surveyor in 1885 and remonumented by William W. Glenn, Cadastral Surveyor, in 1959)</p> <hr/> <p>The cor. of secs. 2, 3, 34, and 35, was rehabilitated but not recorded by L. LaFlamme for Georgia Pacific in 1986, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 28 S</td> <td>R 9 W</td> </tr> <tr> <td>S 34</td> <td> S 35</td> </tr> <tr> <td>S 3</td> <td> S 2</td> </tr> <tr> <td colspan="2">T 29 S</td> </tr> <tr> <td colspan="2">1959</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A sawed fir stump, 34 ins. diam., bears N. 38° E., 23.4 ft. dist., with no scribe marks visible. (Bark scribed in 1855, all of the bark is gone.)</p> <p>and remains of a bearing tree mkd. by LaFlamme</p> <p>A sawed cedar stump, 35 ins. diam., bears S. 86° W., 15.9 ft. dist., with scribe marks S34 BT 378 visible on a partially healed blaze.</p>	T 28 S	R 9 W	S 34	S 35	S 3	S 2	T 29 S		1959	
T 28 S	R 9 W										
S 34	S 35										
S 3	S 2										
T 29 S											
1959											

**Rehabilitation of the Corner of Sections 2, 3, 34, and 35,
Tps. 28 and 29 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>and new bearing trees</p> <p>A hemlock, 10 ins. diam., bears N. $1\frac{1}{2}^{\circ}$ E., 25.4 ft. dist., mkd. T28S R9W S35 BT.</p> <p>A hemlock, 14 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ W., 107.0 ft. dist., mkd. T29S R9W S3 BT.</p> <p>A hemlock, 8 ins. diam., bears N. 27° W., 42.8 ft. dist., mkd. T28S R9W S34 BT.</p> <p>There is no remaining evidence of bearing trees mkd. by Glenn due to logging activity.</p> <p>Corner is located 15 ft. N. of a dirt road at a yarder landing.</p> <hr/>