

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES  
OF THE  
REHABILITATION OF THE  
CORNER OF SECTIONS 31 AND 32 ONLY

**TOWNSHIP 29 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY**

***A. Bert Skeesick, Cadastral Surveyor***

Under Special Instructions dated July 13, 1979, approved July 17, 1979,  
and Supplemental Special Instructions dated May 20, 1985, approved  
May 24, 1985, which provided for the rehabilitation included  
under Group No. 1000, and assignment instructions dated October 16, 2001.

***commenced January 17, 2002***

***completed January 17, 2002***

**T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	<p>The following field notes describe the rehabilitation of the cor. of secs. 31 and 32 only, Township 29 South, Range 7 West, Willamette Meridian, Oregon, as provided for in the Special Instructions dated July 13, 1979, and Supplemental Special Instructions dated May 20, 1985, under Group No. 1000, Oregon, "Rehabilitation of Corner Points, Without Remonumentation, When Suitable Monument Exists."</p> <p>The rehabilitation of the cor. of secs. 31 and 32 only was for administrative purposes of the Bureau of Land Management.</p> <p>The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "TENMILE, OREGON", Provisional Edition, dated 1990, is 18° East.</p>				
	<p style="text-align: center;"><b>Rehabilitation of the Corner of Sections 31 and 32 Only, T. 29 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p style="text-align: center;">(Rehabilitating a corner established by Nathaniel Ford, U.S. Deputy Surveyor in 1855, and reestablished by Fred Mensch, U.S. Cadastral Engineer, in 1924)</p> <hr/> <p>The cor. of secs. 31 and 32 only, perpetuated by Ted C. Baker, Registered Professional Land Surveyor No. 2488, in 2000, recorded in the Douglas County Surveyor's Office, Map File No. M136-9 A &amp; B, and Record of Government Corners Renewed, T. 29 S., R. 7 W., Point Identifier No. 200100, monumented with an iron post, 2 ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 29 S</td> <td style="border-left: 1px solid black; padding: 0 5px;">R 7 W</td> </tr> <tr> <td style="padding: 0 5px;">S 31</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 32</td> </tr> </table> </div> <p style="text-align: center;">1924</p> <p>from which the remains of a bearing tree mkd. by Mensch</p> <p style="padding-left: 40px;">A sawed fir stump, 34 ins. diam., bears N. 70° E., 54.1 ft. dist., with a healed blaze.</p> <p>and bearing tree mkd. by Baker</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 36° W., 15.4 ft. dist., with scribe marks BT visible on partially opened blaze.</p> <p>and new accessory</p>	T 29 S	R 7 W	S 31	S 32
T 29 S	R 7 W				
S 31	S 32				

**Rehabilitation of the Corner of Sections 31 and 32 Only,  
T. 29 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">An aluminum rod, 36 ins. long, <math>\frac{3}{4}</math> in. diam., driven 33 ins. in the ground for a reference monument, bears N. <math>87^{\circ}</math> E., 38.8 ft. dist., with brass cap mkd. RM T29S R7W S32 38.8 FT TO COR 2002 and an arrow pointing to the corner.</p> <p>Drive a steel fencepost alongside cor.</p> <hr/>