

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY AND
SUBDIVISIONAL LINES AND THE
SUBDIVISION OF SECTION 7,

TOWNSHIP 31 SOUTH, RANGE 1 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Leonard E. Herzstein, Land Surveyor (U.S. Forest Service)

Under Special Instructions dated, March 12, 2002, approved, March 12, 2002,
which provided for the surveys included under Group No. 2013,
and Assignment Instructions dated March 13, 2002

Survey commenced May 27, 2002

Survey completed February 28, 2003

T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines and the subdivision of section 7, township 31 south, range 1 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The west boundary and a portion of the subdivisional lines were surveyed by Dennis Hathorn, U.S. Deputy Surveyor, in 1858.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated March 12, 2002, for Group No. 2013, Oregon.

The directions of the lines are based on the true meridian as determined by Global Positioning System (GPS) base lines and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on left side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (98)) of the corner of sections 1, 6, 7, and 12, as determined by a tie to geodetic control station "DREW", established in 1993 by National Geodetic Survey, is as follows:

Latitude: 42° 54' 06.55" N. Longitude: 122° 52' 58.93" W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEET	
	<p>Beginning at the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., perpetuated by Ben B. Irving, Deputy County Surveyor, in 1931, from original evidence no longer in existence, recorded in County Survey map file M1-38, and perpetuated by the Douglas County Surveyor's Office in 1966, recorded in County Survey file 54/28, and perpetuated by Jim Landrum, Deputy County Surveyor, in 1983, recorded in County Survey file 62/15, and further perpetuated by Maurice E. Farr, Registered Land Surveyor No. 1181, in 1984, recorded in County Survey file 62/15; monumented by a white oak corner tree, 7 ins. diam., mkd. by Irving in 1931, with healed blazes on four sides. From which the remains of original bearing tree</p> <p style="padding-left: 40px;">A roothole, bears N. 37° W., 12.7 ft. dist. (Record, N. 12° W., 10.6 ft.)</p> <p>and the remaining bearing tree mkd. by the Irving in 1931</p> <p style="padding-left: 40px;">A white oak, 8 ins. diam., bears S. 38¼° W., 8.0 ft. dist., with healed double blaze.</p> <p>and the remains of bearing trees mkd. by Landrum in 1983</p> <p style="padding-left: 40px;">A Douglas fir snag, 10 ins. diam., bears N. 44¼° E., 64.0 ft. dist., with scribe marks T31S R1W S7 BT, and a ¾ in. diam. brass washer with no marks visible nailed to base of blaze, visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 10 ins. diam., bears S. 61° E., 78.2 ft. dist., no scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A white oak, 9 ins. diam., bears N. 87¼° W., 9.2 ft. dist., with healed blaze.</p> <p>and a reference monument mkd. by Farr in 1984</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., bears N. 9° 29' E., 0.52 ft. dist., firmly set projecting 2 ins. above a 2 foot diam. mound of stone, with brass cap mkd. RM R2W T31S R1W S12 S7 S13 S18 LS 1181 1984</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A Douglas fir, 21 ins. diam., bears N. 55¼° E., 94.0 ft. dist., mkd. T31S R1W S7 BT.</p>

**Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEET													
	N. 0° 10' 00" E., between sections 7 and 12, on the W. bdy. of the Tp.												
48	Gravel road, 14 feet wide, bears E. and W.												
2666.85	The ¼ sec. cor. of secs. 7 and 12 perpetuated by Leonard E. Herzstein, Deputy County Surveyor, in 1980, recorded in County Survey file 61/11; monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above a 2 foot diam. mound of stone, with brass cap mkd.												
	DOUGLAS COUNTY SURVEYORS T 31 S												
	<table style="margin: auto;"> <tr> <td style="text-align: center;">R</td> <td></td> <td style="text-align: center;">R</td> </tr> <tr> <td style="text-align: center;">2</td> <td style="text-align: center;">S 12</td> <td style="text-align: center;">S 7</td> </tr> <tr> <td style="text-align: center;">W</td> <td style="text-align: center;"> </td> <td style="text-align: center;">W</td> </tr> <tr> <td></td> <td style="text-align: center;">1/4</td> <td></td> </tr> </table>	R		R	2	S 12	S 7	W		W		1/4	
R		R											
2	S 12	S 7											
W		W											
	1/4												
	1980												
	from which original bearing trees												
	<p>A Douglas fir, 37 ins. diam., bears N. 57° E., 19.6 ft. dist., with fragmentary scribe marks visible on bark blaze and no marks visible on a previously opened lower blaze. (Record, 20.5 ft. dist.)</p> <p>A Douglas fir, 32 ins. diam., bears N. 12° W., 23.1 ft. dist., no scribe marks visible on a previously opened bark face and lower blaze.</p>												
	<p>From this point, a point established by proportionate measurement for the ¼ sec. cor. of secs. 7 and 12, by Arthur Boyer, Registered Engineer No. 1581, in 1950, recorded in County Survey file 40/298 and subsequently perpetuated by the Douglas County Surveyor's Office in 1966, recorded in County Survey file 54/28; monumented with a maple, 7 ins. diam., mkd. by Boyer in 1950 with a healed blaze on E. and W. sides, bears S. 5° 46' 30" E., 7.47 ft. dist. From which bearing trees mkd. by Boyer in 1950</p>												
	<p>A Douglas fir, 13 ins. diam., bears N. 50¼° E., 14.0 ft. dist., with healed blaze.</p> <p>A maple, 8 ins. diam., bears N. 47½° W., 12.0 ft. dist., with healed blaze.</p>												
	and bearing tree and reference object mkd. by the County Surveyor in 1966												

**Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEEET	<p>A Douglas fir, 26 ins. diam., bears N. 2¼° E., 26.2 ft. dist., with healed double blaze.</p> <p>An iron post, 1½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. with a center punch, bears S. 46° 49' E., 0.47 ft. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 12' 00" W., beginning new measurement.</p>						
2683.94	<p>The cor. of secs. 1, 6, 7, and 12, reestablished by proportionate measurement by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1967, recorded in County Survey file 55/41 and map file M34-23. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2 ins. diam. iron post, firmly set, projecting 14 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>ORE L. S. 536</p> <p>T 31 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 12</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">R 2 W</td> <td style="padding: 0 5px;">R 1 W</td> </tr> </table> <p>1967</p> </div> <p>from which remains of bearing trees mkd. by Baughman in 1967</p> <p>A Douglas fir snag, 12 ins. diam., bears N. 10¼° E., 51.0 ft. dist., with healed blaze.</p> <p>A Douglas fir snag, 13 ins. diam., bears S. 88¼° E., 35.9 ft. dist., with healed blaze.</p> <p>An incense cedar, 17 ins. diam., bears S. 33¼° W., 15.9 ft. dist., with healed blaze.</p> <p>A ponderosa pine, 20 ins. diam., bears N. 36¼° W., 1.9 ft. dist., with healed blaze.</p> <p>and new bearing trees</p> <p>A ponderosa pine, 6 ins. diam., bears N. 59¼° E., 111.2 ft. dist., mkd. X BT.</p> <p>A black oak, 9 ins. diam., bears S. 59¼° E., 31.3 ft. dist., mkd. T31S R1W S7 BT.</p>	S 1	S 6	S 12	S 7	R 2 W	R 1 W
S 1	S 6						
S 12	S 7						
R 2 W	R 1 W						

**Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner point lies North, 6.0 feet of barbed wire fence corner, fences bear N., E. and W.</p> <p>From this point, the National Geodetic Survey B-Order geodetic station "DREW" bears S. 0° 19' 41" W. (mean bearing), 11709.80 ft. dist. (sea level), monumented with a standard NGS brass tablet, 3½ ins. diam., firmly set in a concrete cylinder, 8 ins. in diam., mkd. DREW.</p> <p>From this same point, a 1 in. diam. iron rod, loosely set, projecting 9 ins. above ground, established by person(s) unknown, bears S. 50° 35' E., 126.59 ft. dist.</p> <p>from which trees mkd. by person(s) unknown</p> <p style="padding-left: 40px;">An incense cedar, 27 ins. diam., bears N. 8½° E., 25.4 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 14 ins. diam., bears S. 54° E., 31.3 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 12 ins. diam., bears S. 46° W., 41.2 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 17 ins. diam., bears N. 39½° W., 18.0 ft. dist., with healed blaze.</p> <hr/> <p>N. 0° 09' 00" W., between sections 1 and 6.</p>
35	Gravel road, 14 feet wide, bears E. and W.
1225	Gravel driveway, 12 feet wide, bears S. 55° E. and N. 55° W and creek in culvert under driveway, 1 foot wide, course S. 55° W.
1345.58	The S 1/16 sec. cor. of secs. 1 and 6 established by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1967, recorded in County Surveyor map file M34-23, and perpetuated by Leonard E. Herzstein, Deputy County Surveyor, in 1980, recorded in County Survey file 61/11 and accepted as the corner; monumented with an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground and in a 2 foot diam. mound of stone, with brass cap mkd.

**Dependent Resurvey of a Portion of the West Boundary,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEET

from which the remaining original bearing tree

A black oak, 25 ins. diam., bears N. 60° W.,
16.3 ft. dist., with decayed face on a previously opened
blaze. (Record, 15.2 ft.)

and bearing trees mkd. by the County Surveyor in 1966

A Douglas fir, 16 ins. diam., bears N. 58½° E.,
19.6 ft. dist., with healed blaze.

A Douglas fir, 19 ins. diam., bears S. 56¼° W.,
9.9 ft. dist., with healed blaze.

Corner point lies East, 1.0 feet of barbed wire fence corner,
fences bear N., S. and W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

From the cor. of secs. 7, 8, 17, and 18, perpetuated by the
Douglas County Surveyor's Office in 1966, recorded in County
Survey file 54/28; monumented with a 1½ ins. diam. iron post,
firmly set, projecting 12 ins. above ground and in a 3 foot
diam. mound of stones, with a brass cap mkd.

COUNTY SURVEYORS OFFICE

T31S R1W

S7	S8
----	----

S18	S17
-----	-----

1966

from which the remaining original bearing tree

A black oak stump, 24 ins. diam., bears S. 55° W.,
64.3 ft. dist., no scribe marks visible on hollow open
blaze. (Record, 65.3 ft.)

and bearing trees mkd. by County Surveyor in 1966

A Douglas fir, 20 ins. diam., bears N. 47° E.,
26.0 ft. dist., with healed double blaze.

A Douglas fir stump, 15 ins. diam., bears S. 50° E.,
51.6 ft. dist., with healed double blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
	<p>A Douglas fir, 16 ins. diam., bears S. 38° W., 27.2 ft. dist., with healed double blaze.</p> <p>A madrone, 20 ins. diam., bears N. 59½° W., 16.7 ft. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>An incense cedar, 13 ins. diam., bears S. 23¾° E., 182.7 ft. dist., mkd. T31S R1W S17 BT.</p> <p>Corner point lies N., 4.0 feet of the remaining barbed wire fence corner, downed fences bear N. and E.</p> <p>S. 89° 14' 00" W., between sections 7 and 18.</p>
25	<p>Skid road, 12 feet wide, bears S. 45° E. and N. 45° W.</p>
2653.24	<p>The ¼ sec. cor. of secs. 7 and 18, reestablished by proportionate measurement by Jack A. Hoffbuhr, Registered Land Surveyor No. 222, in 1972, recorded in County Survey map file M42-80. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2½ in. diam. iron post, firmly set, projecting 3 ins. above ground and in a collar of stones, with brass cap mkd.</p> <p style="text-align: center;">T31S - R1W S 7 1/4 COR S 18 ORE.LIC.222 1972</p> <p>from which bearing trees mkd. by Hoffbuhr in 1972</p> <p>A Douglas fir, 15 ins. diam., bears S. 34° W., 37.1 ft. dist., with healed blaze.</p> <p>A Douglas fir, 13 ins. diam., bears N. 49° W., 39.1 ft. dist., with healed blaze.</p> <p>Corner point lies East, 50 feet from downed barbed wire fence, fence bears N. 8° E. and S. 8° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 18' 00" W., beginning new measurement.</p>
950	<p>Gravel road, 14 feet wide, bears N. 40° E. and S. 70° W., in a curve.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEEET					
1735	Trail, 4 feet wide, bears N. 22° W. and S. 22° E.				
2571	Gravel road, 14 feet wide, bears N. 22° W. and S. 22° E.				
2592.44	<p>The cor. of secs. 7, 12, 13, and 18, hereinbefore described.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 5, 6, 7, and 8, perpetuated by the Douglas County Surveyor's Office in 1966, recorded in County Survey file 54/28, and perpetuated by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-50; monumented with a 1½ ins. diam. iron post, firmly set, projecting 20 ins. above the ground, with a brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T31S R1W</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S6</td> <td style="padding: 2px 5px;">S5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S7</td> <td style="padding: 2px 5px;">S8</td> </tr> </table> <p>1966</p> </div> <p>from which the remains of the original bearing trees</p> <ul style="list-style-type: none"> A Douglas fir stump, 36 ins. diam., bears S. 70¾° W., 40.0 ft. dist., with healed blaze. (Record, S. 69° W., 38.9 ft.) A Douglas fir stump, 24 ins. diam., bears N. 71° W., 27.7 ft. dist., with scribe marks T3 R1W S6 visible on previously opened blaze. (Record and dist. to face 27.1 ft.) <p>and remaining bearing trees mkd. by County Surveyor in 1966</p> <ul style="list-style-type: none"> A white fir, 22 ins. diam., bears S. 83° E., 105.9 ft. dist., with healed double blaze. A maple, 17 ins. diam., bears S. 17° W., 61.7 ft. dist., with healed double blaze. A roothole, bears N. 84° W., 67.6 ft. dist., with decayed maple log alongside, no marks visible. <p>and bearing trees mkd. by Ruppert in 1977</p> <ul style="list-style-type: none"> A white fir, 20 ins. diam., bears N. 31¼° E., 187.2 ft. dist., with healed double blaze. 	S6	S5	S7	S8
S6	S5				
S7	S8				

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 1 W., Willamette Meridian, Oregon**

FEEET	<p>A Douglas fir, 32 ins. diam., bears N. 9¾° W., 155.5 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>S. 89° 00' 00" W., between sections 6 and 7.</p>
1220	<p>Gravel road, 10 feet wide, bears N. 42° E. and S. 44° W.</p>
2664.69	<p>The ¼ sec. cor. of secs. 6 and 7, reestablished by proportionate measurement by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1967, recorded in County Survey file 55/41 and map file M34-23. There is no remaining evidence of the original cor., therefore this position is accepted as the corner; monumented with a 2 in. diam. iron post, firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>ORE L.S. 536 T31S S 6 ----- 1/4 S 7 R1W 1967</p> </div> <p>from which bearing trees mkd. by Baughman in 1967 and altered on the plat in 1978</p> <p style="margin-left: 40px;">A Douglas fir, 25 ins. diam., bears N. 23¾° E., 22.5 ft. dist., with healed blaze.</p> <p style="margin-left: 40px;">A Douglas fir, 21 ins. diam., bears S. 45¼° E., 18.9 ft. dist., with healed blaze.</p> <p>From this point, a 1¼ ins. diam. iron axle with 3½ ins. diam. gear, firmly set, leaning southerly, projecting 14 ins. above ground, established by person(s) unknown, bears N. 80°47' 30" E., 79.06 ft. dist.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 88° 52' 30" W., beginning new measurement.</p>
1331.93	<p>The W 1/16 sec. cor. of secs. 6 and 7 established by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1967, recorded in County Survey map file M34-23 and perpetuated by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-60 and accepted as the corner; monumented with a 2 in. diam. iron post, firmly set, projecting 7 ins. above ground and in a collar of stones, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
	<p>ORE L.S. 536 T31S S 6 ----- W 1/16 S 7 R1W 1967</p>
	<p>from which bearing trees mkd. by Baughman in 1967</p> <p style="padding-left: 40px;">A Douglas fir, 22 ins. diam., bears N. 60° E., 52.0 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A black oak, 32 ins. diam., bears S. 25¼° E., 70.6 ft. dist., with scribe marks W1/16 S7 B visible on partially healed blaze.</p> <p>Corner point lies S. 70° E., 7.6 feet, of barbed wire fence corner, fences bear N. 70° E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 04' 00" W., beginning new measurement.</p>
605	Dirt road, 14 feet wide, bears N. and S.
655	South edge of a pond, bears N., 11 ft., the dimensions of which are 25 feet E. and W. by 18 feet N. and S.
710	Gravel road, 14 feet wide, bears N. 54° W. and S. 46° E., in a curve.
1267.58	The cor. of secs. 1, 6, 7, and 12, hereinbefore described.
	<hr style="width: 50%; margin: 0 auto;"/> <p>Subdivision of Section 7, T. 31 S., R. 1 W., Willamette Meridian, Oregon</p> <hr style="width: 50%; margin: 0 auto;"/>
	<p>From the ¼ sec. cor. of secs. 7 and 18.</p> <p>N. 0° 04' 00" E., on the N. and S. centerline of section 7.</p>
1336.67	The center S 1/16 sec. cor. of sec. 7, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-60 and accepted as the corner; monumented with a 2½ ins. diam. iron post, firmly set, projecting 6 ins. above ground and in a collar of stones, with brass cap mkd.

T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
	<p style="text-align: center;">T31S R1W C S 1/16 S7 C PLS 866 1977</p> <p>from which bearing trees mkd. by Ruppert in 1977</p> <p>A Douglas fir, 17 ins. diam., bears S. 25½° E., 12.6 ft. dist., with healed double blaze.</p> <p>A ponderosa pine, 24 ins. diam., bears S. 60° W., 61.0 ft. dist., with healed double blaze.</p> <p>A Douglas fir, 10 ins. diam., bears N. 76¼° W., 4.5 ft. dist., with healed double blaze.</p> <p>Corner point lies East, 34 feet from downed barbed wire fence, fence bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 02' 30" E., beginning new measurement.</p>
1337.03	<p>The center ¼ sec. cor. of sec. 7, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-60 and accepted as the corner; monumented with a 2½ ins. diam. iron post, firmly set, projecting 2 ins. above ground and in a collar of stones, with brass cap mkd.</p> <p style="text-align: center;">T31S R1W C1/4 . S7 PLS 866 1977</p> <p>from which bearing trees mkd. by Ruppert in 1977</p> <p>A Douglas fir, 15 ins. diam., bears S. 2° E., 43.0 ft. dist., with healed double blaze.</p> <p>A roothole, bears S. 85° W., 94.0 ft. dist., with incense cedar log, 24 ins. diam., alongside with scribe marks C1/4 S7 visible on partially healed double blaze.</p> <p>and a new bearing tree</p>

T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
1346.81	<p>A Douglas fir, 14 ins. diam., bears S. 76½° W., 41.1 ft. dist., mkd. C1/4 S7 BT.</p> <p>Corner point lies South, 3 feet of barbed wire fence, fence bears E. and W.</p> <hr/> <p>N. 0° 03' 30" E., beginning new measurement.</p> <p>The center N 1/16 sec. cor. of sec. 7, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-60 and accepted as the corner; monumented with a 2½ ins. diam. iron post, firmly set, projecting 3 ins. above ground and in a collar of stones, with brass cap mkd.</p> <div style="text-align: center;"> <p>T31S R1W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;">1 S7</p> <p style="margin-left: 60px;">N /16 </p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;">PLS 866</p> <p style="margin-left: 80px;">1977</p> </div> <p>from which bearing trees mkd. by Ruppert in 1977</p> <p>A Douglas fir, 27 ins. diam., bears N. 63° E., 20.7 ft. dist., with healed double blaze.</p> <p>A Douglas fir stump, 18 ins. diam., bears N. 26½° W., 18.2 ft. dist., with healed double blaze.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 11 ins. diam., bears N. 21¼° W., 11.3 ft. dist., mkd. CN1/16 S7 BT.</p> <p>From this point, a ½ ins. diam. iron pipe, firmly set, projecting 3 ins. above ground, established by person(s) unknown, bears N. 35° 24' E., 123.97 ft. dist.</p> <hr/> <p>N. 0° 03' 00" E., beginning new measurement.</p>
1345.34	<p>The ¼ sec. cor. of secs. 6 and 7, hereinbefore described.</p> <hr/> <p>From the ¼ sec. cor. of secs. 7 and 8, perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1960, recorded in County Survey file 51/142 and further perpetuated by William J.</p>

T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
	<p>Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map files M65-50 and M65-60; monumented with a 2½ ins. diam. iron post, firmly set, projecting 6 ins. above a collar of stones, with a brass cap mkd.</p> <p style="text-align: center;">T31S R1W W.W.M.</p> <p style="text-align: center;">1/4 S7 S8</p> <p style="text-align: center;">PLS 866 1977</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burnt ponderosa pine snag, 36 ins. diam., bears N. 35°E., 40.1 ft. dist., with fragmentary scribe marks and chaining notch visible on previously opened lower blaze. (Record and dist. to notch 38.9 ft.)</p> <p>and bearing trees mkd. by Markham in 1960</p> <p style="padding-left: 40px;">A ponderosa pine, 30 ins. diam., bears S. 44½° E., 46.4 ft. dist., with scribe marks ¼ visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 18 ins. diam., bears S. 54° W., 22.0 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 24 ins. diam., bears N. 87½° W., 32.7 ft. dist., with scribe marks BT visible on lower bark blaze and a healed blaze.</p> <p style="padding-left: 40px;">A black oak, 15 ins. diam., bears N. 7¼° W., 71.3 ft. dist., with healed double blaze.</p> <p>S. 88° 59' 00" W., on the E. and W. centerline of section 7.</p>
685	Gravel road, 14 feet wide, bears N. 6° E. and S. 6° W.
2655.31	The center ¼ sec. cor. of sec. 7, hereinbefore described.

	S. 88° 58' 30" W., beginning new measurement.
200	Gravel road, 14 feet wide, bears N. 27° W. and S. 27° E.
1324.48	The center W 1/16 sec. cor. of sec. 7, established by William J. Ruppert, Registered Land Surveyor No. 866, in 1977, recorded in County Survey map file M65-60 and accepted as the corner; monumented with a 2½ ins. diam. iron post, firmly set,

T. 31 S., R. 1 W., Willamette Meridian, Oregon

FEET	
	<p>projecting 5 ins. above ground and in a collar of stones, with brass cap mkd.</p> <p style="text-align: center;">T31S R1W W 1/16 C ————— C S7 PLS 866 1977</p> <p>from which bearing trees mkd. by Ruppert in 1977</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 18° W., 30.7 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A Douglas fir, 18 ins. diam., bears N. 49° W., 24.4 ft. dist., with healed double blaze.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 19' 30" W., beginning new measurement.</p>
770	Gravel road, 14 feet wide, bears N. 18° W. and S. 50° E., in a curve.
1262.82	The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands surveyed are located approximately 5 miles southeast of the town of Tiller, Oregon. Access is gained by way of Douglas County Road No. 1 (Tiller-Trail Highway), Forest Service Road No. 1610 (Devils Knob Road), various other Forest Service roads, and private driveways. Elevations range from about 2100 feet to 3150 feet above sea level.</p> <p>The soil is generally rocky clay. The area is drained by Dixon Creek, Joe Hall Creek, Burnt Creek, and Elk Creek. Timber consists of fir, pine, cedar, yew, white oak, and madrone, with undergrowth of consisting of vine maple, ceanothus, poison oak, and blackberry.</p> <p>No mineral deposits were noted along the lines surveyed. Springs and ponds were noted in several locations. The primary use of the area is residences, timber production, and livestock grazing.</p> <p>The mean of several number of observations of the magnetic declination is 17¼° East, with a range of ½° in local attraction.</p>