

FEET

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY
OF
A PORTION OF
THE SUBDIVISIONAL LINES,
TOWNSHIP 30 SOUTH, RANGE 9 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated March 15, 2001, approved March 16, 2001,
which provided for the surveys included under Group No. 1973,
and Assignment Instructions dated March 23, 2001.

Survey commenced May 10, 2001

Survey completed May 30, 2001

T. 30 S., R. 9 W., Willamette Meridian, Oregon

FEET	<p>The following field notes are those of the dependent resurvey of a portion of the subdivisional lines township 30 south, range 9 west of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>The east boundary and a portion of subdivisional lines were surveyed by Dennis Hathorn, U.S. Deputy Surveyor, in 1855.</p> <p>A portion of the east boundary and subdivisional lines were resurveyed and section 25 was subdivided by Dale T. Bedell, Wayne L. Rogers, and Boyd W. Peterson, Cadastral Surveyors, in 1986.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated March 15, 2001, for Group No. 1973, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.</p> <p>Each new bearing tree has a 2½ in. X ¼ in. magnetic nail (MAG-NAIL) driven at the base on the right side-center.</p> <p>The geographic position (NAD 1983 (91)) of the corner of sections 1, 6, 7, and 12 on the east boundary of the township, as determined from a tie to Geodetic Control Station No. 41304, established by the Bureau of Land Management in 2001, is as follows:</p> <p style="text-align: center;">Latitude: 42° 58' 54.39" N. Longitude: 123° 42' 07.92" W.</p> <hr style="width: 60%; margin-left: auto; margin-right: auto;"/>
------	---

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

FEET													
	<p>(Restoring the 1855 survey by Dennis Hathorn)</p> <hr style="width: 20%; margin: auto;"/>												
	<p>Beginning at the cor. of secs. 1, 6, 7, and 12 on the E. bdy. of the Tp., monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p>												
	<p>COUNTY SURVEYORS OFFICE T 30 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 10px;">R</td> <td style="border-right: 1px solid black; padding: 0 10px;">S1</td> <td style="padding: 0 10px;">S6</td> <td style="padding: 0 10px;">R</td> </tr> <tr> <td style="padding: 0 10px;">9</td> <td style="border-right: 1px solid black; border-bottom: 1px solid black; padding: 0 10px;"></td> <td style="border-bottom: 1px solid black; padding: 0 10px;"></td> <td style="padding: 0 10px;">8</td> </tr> <tr> <td style="padding: 0 10px;">W</td> <td style="border-right: 1px solid black; padding: 0 10px;">S12</td> <td style="padding: 0 10px;">S7</td> <td style="padding: 0 10px;">W</td> </tr> </table> <p>1958</p>	R	S1	S6	R	9			8	W	S12	S7	W
R	S1	S6	R										
9			8										
W	S12	S7	W										
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A root hole bears N. 53° E., 16.5 ft. dist., with decayed stump lying nearby, no marks visible.</p> <p style="padding-left: 40px;">A burnt snag, 35 ins. diam., bears S. 45° E., 37.3 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 25° E., 27.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 67° E., 15.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 6½° W., 38.2 ft. dist., with a healed blaze. (Record S. 8° W.)</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears N. 38° W., 44.9 ft. dist., with a healed blaze. (Record N. 36° W.)</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41304 determined by the NAVSTAR Global Positioning System, utilizing static carrier phase receivers, (see Control Data Sheet attached to these field notes following the General Description) bears S. 53° 35' 53" E., 869.47 ft. dist., (mean bearing and sea level distance) monumented with an alum. cap, 3¾ ins. diam., firmly set flush with the ground, with top mkd. EC 41304 GPS 2001.</p> <p>N. 89° 29' 53" W., bet. secs. 1 and 12, posting and blazing the true line.</p> <p>Descend over broken NW. slope.</p>												
1700	<p>Ravine, drains North; asc. over broken N. slope.</p>												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2140	Spur, slopes N. 15° E.; desc. over NW. slope.
2640.18	<p>Point for the ¼ sec. cor. of secs. 1 and 12 at proportionate dist.; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 30 S R 9 W S 1 1/4 ————— S 12 2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 4° E., 24.1 ft. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 63½° W., 30.8 ft. dist., mkd. 1/4 S1 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a point established as the ¼ sec. cor. of secs. 1 and 12, by Howard W. Johnstone, Registered Professional Land Surveyor No. 498 in 1988, recorded in the Douglas County Surveyor's Office, Map File No. 101-44, and Record of Government Corners Renewed, T. 30 S., R. 9 W., No. 144, bears N. 63° 57' 05" E., 74.45 ft. dist., monumented with a rebar, 5/8 in. diam., firmly set projecting 19 ins. above the ground, with aluminum cap marked, T30S RR R9W ¼ S1 S12 1988 LS498. This cor. was not correctly positioned and is not used in the course of this survey.</p> <p>Continue descent over NW. slope.</p>
4120	Ravine, drains N. 10° W., asc. over E. slope.
4145	Spur, slopes N. 10° W., desc. over W. slope.
4190	Ravine, drains N. 10° E., asc. over NE. slope.
5280.36	The cor. of secs. 1, 2, 11, and 12, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, from original evidence no longer in existence, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 30 S., R. 9 W., No. 11, further perpetuated by Vernon R. Tracy, Douglas County Surveyor's Office, in 1964, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 30 S., R. 9 W., No. 38, and recovered by Howard W. Johnstone, Registered Professional Land

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 30 S., R. 9 W., Willamette Meridian, Oregon**

FEET

Surveyor No. 498 in 1988, recorded in the Douglas County Surveyor's Office, Map File No. 101-44, and the Douglas County Surveyor's Record of Government Corners Renewed, T. 30 S., R. 9 W., No. 143; monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 30 S
S 2 | S 1

S11 | S12
R9W
1958

from which the remains of bearing trees mkd. by Byron

A sawed and decayed stump, 46 ins. diam., bears N. 86½° E., 18.0 ft. dist., with scribe marks T30S R9W S1 CS BT visible.

A cedar snag, 16 ins. diam., bears S. 67¼° E., 32.5 ft. dist., no marks visible.

and bearing tree mkd. by Tracy

A cedar, 23 ins. diam., bears N. 37½° W., 184.7 ft. dist., with a healed blaze.

and new bearing trees

A pine, 9 ins. diam., bears N. 80¾° E., 7.0 ft. dist., mkd. T30S R9W S1 BT.

A fir, 4 ins. diam., bears S. 36¼° E., 29.5 ft. dist., mkd. X BT.

A fir, 11 ins. diam., bears S. 32° W., 8.5 ft. dist., mkd. T30S R9W S11 BT.

A pine, 11 ins. diam., bears N. 14¼° W., 15.0 ft. dist., mkd. T30S R9W S2 BT.

T. 30 S., R. 9 W., Willamette Meridian, Oregon

FEET

GENERAL DESCRIPTION

The lands included in the foregoing survey are located in mountainous terrain, approximately 4.0 miles southwesterly from the community of Camas Valley, Oregon.

The elevation ranges from about 1700 feet above sea level at the corner of sections 1, 2, 11, and 12 to about 2000 feet above sea level at the corner of sections 1, 6, 7, and 12 on the E. bdy. of the Tp.

The area is drained by unnamed tributaries which flow northerly to the Middle Fork of the Coquille River.

Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

The soil is generally composed of rocky clay, with steep, crumbling rock slopes.

Access to the survey was made by paved and graveled roads branching from State Highway No. 42 and Buck Springs Road.

The mean magnetic declination for the area surveyed is 18° East, as shown on the "CHIPMUNK RIDGE, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1990.