

FEET

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A
PORTION OF THE WEST BOUNDARY AND SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTION 7,
TOWNSHIP 22 SOUTH, RANGE 4 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated January 24, 2002, approved
January 24, 2002, which provided for the surveys included under
Group No. 2002, and Assignment Instructions dated January 30, 2002.

Survey commenced January 30, 2002

Survey completed March 7, 2002

T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines and the subdivision of section 7, township 22 south, range 4 west, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855 to 1856, Harvey Gordon and Charles T. Gardner, U.S. Deputy Surveyors, surveyed the west boundary and a portion of the subdivisional lines.

In 1884, William P. Wright, U.S. Deputy Surveyor, surveyed a portion of the subdivisional lines.

In 1982, James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, resurveyed a portion of the subdivisional lines of T. 22 S., R. 5 W.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated January 24, 2002, for Group No. 2002, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ in. X ¼ in. magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (CORSS)) of the corner of sections 5, 6, 7, and 8, as determined by the NAVSTAR Global Positioning System (GPS), by direct occupation utilizing dual

T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET

frequency, carrier phase GPS receivers (see the Control Data Sheet attached to these field notes following the General Description), by the Bureau of Land Management, in 2002, is as follows:

Latitude: 43° 40' 41.270" N. Longitude: 123° 12' 24.958" W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Harvey Gordon
and Charles T. Gardner)

Beginning at the cor. of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., recovered by B.H. McGillicuddy, Professional Engineer No. 2066, in 1952, recorded in the Douglas County Surveyor's Office, Map File No. 1-40, perpetuated by James W. Byron, Douglas County Surveyors Office, in 1958, recorded in the Douglas County Surveyor's Office, C.S. File No. 49/59, recovered by Donald L. Peel, Oregon Professional Land Surveyor No. 752, in 1987, recorded in the Douglas County Surveyor's Office, Map File No. M105-27, and recovered by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M129-46, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 100500, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S			
S 12		S 7	
R 5 W	—	—	R 4 W
S 13		S 18	

1958

from which the remains of the original bearing trees

A fir snag, 21 ins. diam., bears S. 44° W., 62.7 ft. dist., with no marks visible.

A maple stump, 20 ins. diam., bears N. 41¾° W., 21.5 ft. dist., with healed blaze. (Record N. 37½° W., 21.1 ft.)

and remains of bearing trees mkd. by Byron

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	A cedar, 30 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ E., 8.2 ft. dist., with healed blaze.
	A sawed cedar stump, 38 ins. diam., bears S. $50\frac{1}{4}^{\circ}$ E., 5.2 ft. dist., with healed blaze.
	A fir snag, 7 ins. diam., bears S. $44\frac{1}{2}^{\circ}$ W., 8.0 ft. dist., with healed blaze.
	A yew, 12 ins. diam., bears N. 38° W., 16.9 ft. dist., with scribe marks 22S R5W 12 CS BT visible on partially healed blaze.
	and new bearing tree
	A fir, 22 ins. diam., bears S. 61° W., 37.8 ft. dist., mkd. T22S R5W S13 BT.
	Corner is located in a four-strand barbed wire fence, 1.0 ft. South of a fence corner with fences extending N., E., S., and W.
	N. $0^{\circ} 26' 49''$ E., bet. secs. 7 and 12.
	Descend over broken NW. slope.
495	Salt Creek, 6 ft. wide, course West; asc. broken E. slope.
560	Salt Creek Road, 12 ft. wide, bears N. 55° E. and S. 35° W.
2640.76	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., reestablished at proportionate measurement by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M132-5, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 100540. There is no remaining evidence of the original corner, therefore this point is accepted as the cor., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.
	T22S 1/4 R5W R4W S12 S7 PLS 1978 1999
	from which bearing trees mkd. by Baker

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET																						
	<p>A fir, 13 ins. diam., bears N. $38\frac{3}{4}^{\circ}$ E., 11.0 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 8 ins. diam., bears S. 61° E., 2.8 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>A fir, 8 ins. diam., bears N. $78\frac{1}{4}^{\circ}$ W., 15.2 ft. dist., with scribe marks S12 BT visible on partially healed blaze.</p> <p>A fir, 13 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 8.8 ft. dist., with scribe marks S12 1/4 BT visible on partially healed blaze. (Baker record, hemlock)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 24' 46''$ E., beginning new measurement.</p>																					
1321.52	<p>The N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., established by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M132-5, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td></td><td style="text-align: center;">T 22 S</td><td></td></tr> <tr><td></td><td style="text-align: center;">1/</td><td></td></tr> <tr><td style="text-align: center;">R 5 W</td><td style="text-align: center;"> </td><td style="text-align: center;">16 R 4 W</td></tr> <tr><td style="text-align: center;">S 12</td><td style="text-align: center;"> </td><td style="text-align: center;">S 7</td></tr> <tr><td></td><td style="text-align: center;"> </td><td></td></tr> <tr><td></td><td style="text-align: center;">LS 1978</td><td></td></tr> <tr><td></td><td style="text-align: center;">1999</td><td></td></tr> </table> </div> <p>from which bearing trees mkd. by Baker</p> <p>A fir, 12 ins. diam., bears S. $\frac{3}{4}^{\circ}$ E., 20.0 ft. dist., with scribe marks N 1/16 S7 BT visible on partially healed double blaze.</p> <p>A fir, 11 ins. diam., bears N. $66\frac{1}{4}^{\circ}$ W., 2.9 ft. dist., with illegible scribe marks visible on partially healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 23' 40''$ E., beginning new measurement, posting and blazing.</p>		T 22 S			1/		R 5 W		16 R 4 W	S 12		S 7					LS 1978			1999	
	T 22 S																					
	1/																					
R 5 W		16 R 4 W																				
S 12		S 7																				
	LS 1978																					
	1999																					
1321.29	<p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.</p>																					

**Dependent Resurvey of a Portion of the West Boundary,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET

COUNTY SURVEYORS OFFICE

T 22 S		
R S1		S6 R
5	— —	4
W S12		S7 W

1959

from which bearing trees mkd. by B.H. McGillicuddy, Professional Engineer No. 2066, in 1952, recorded in the Douglas County Surveyor's Office, Roll Map File No. 1-40, reported by Jelley and Rogers

A cedar, 31 ins. diam., bears N. 16° E., 46.9 ft. dist., with healed blaze.

A chinquapin, 18 ins. diam., bears S. 29½° E., 14.2 ft. dist., with healed blaze. (Record, S. 27¼° E.)

and bearing tree mkd. by James W. Byron, Douglas County Surveyors Office, in 1958, C.S. File No. 49/59, reported by Jelley and Rogers

A fir, 28 ins. diam., bears N. 63¾° W., 13.2 ft. dist., with healed blaze.

and bearing tree mkd. by Bruce A. Shaner, Oregon Professional Engineer No. 4906, in 1972, recorded in the Douglas County Surveyor's Office, Map File No. M42-68, reported by Jelley and Rogers

A hemlock, 28 ins. diam., bears S. 26° W., 112.4 ft. dist., with healed blaze.

and the remains of bearing trees mkd. by Jelley and Rogers

A fir, 15 ins. diam., bears S. 34½° E., 32.7 ft. dist., with healed blaze.

A fir stob, 14 ins. diam., bears S. 26¾° W., 21.4 ft. dist., with healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

(Restoring the 1855-56 survey by Harvey Gordon
and Charles T. Gardner)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET

From the cor. of secs. 7, 8, 17, and 18, perpetuated by O.F. Theil, Surveyor, in 1940, from evidence no longer in existence, recorded in the Douglas County Surveyor's Office, C.S. File No. 16/55, remonumented by James W. Byron, Douglas County Surveyors Office, in 1956, recorded in the Douglas County Surveyor's Office, Map File No. 2-32, perpetuated by Bruce Rogers, Douglas County Deputy Surveyor, in 1965, recovered by Donald L. Peel, Oregon Professional Land Surveyor No. 752, in 1992, recorded in the Douglas County Surveyor's Office, Map File No. M115-77, and perpetuated by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M132-16, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 04 W., Point Identifier No. 200500, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 22 S R 4 W

7	8
18	17

1956

from which the remains of bearing trees mkd. by Theil

A sawed and decayed fir stump, 18 ins. diam., bears N. 17° E., 6.3 ft. dist., with no marks visible.

A sawed and decayed fir stump, 39 ins. diam., bears S. 65° E., 27.6 ft. dist., with no marks visible.

A decayed fir stump, 14 ins. diam., bears N. 42½° W., 43.8 ft. dist., with no marks visible.

and remains of bearing trees mkd. by Byron

A decayed fir stump, 16 ins. diam., bears N. 42¼° E., 9.2 ft. dist., with no marks visible.

A sawed and decayed cedar stump, 30 ins. diam., bears S. 18° E., 84.5 ft. dist., with healed blaze.

and bearing trees mkd. by Rogers

A cedar, 31 ins. diam., bears N. 66¼° E., 57.4 ft. dist., with healed double blaze.

A fir, 20 ins. diam., bears N. 26° W., 29.1 ft. dist., with healed double blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	and bearing tree mkd. by Baker
	A fir, 21 ins. diam., bears S. 15¼° W., 43.2 ft. dist., with fragmentary scribe marks visible on partially healed blaze.
	and new bearing tree
	A fir, 13 ins. diam., bears S. 68¼° E., 31.2 ft. dist., mkd. T22S R4W S17 BT.
	Corner is located 2.5 ft. North of a fence corner with fences extending E., S., and W.
	S. 89° 18' 23" W., bet. secs. 7 and 18.
	Ascend over SE. slope.
930	Spur, slopes S. 25° E., and graveled road, 12 ft. wide, bears S. 25° E. and N. 60° W.; desc. over SW. slope.
1317.52	Point for the E 1/16 sec. cor. of secs. 7 and 18, not monumented.
2635.04	The ¼ sec. cor. of secs. 7 and 18, reestablished at proportionate measurement by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M132-16, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 140500. There is no remaining evidence of the original corner, therefore this point is accepted as the cor., monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.
	T 22 S R 4 W S 7 1/4 ——— S 18 PLS 1978 1999
	from which the remains of bearing trees mkd. by Baker
	A sawed fir stump, 18 ins. diam., bears N. 9¼° E., 27.3 ft. dist., with no marks visible.
	A fir, 22 ins. diam., bears S. 89¾° E., 60.6 ft. dist., with scribe marks S8 1/4 BT visible on partially healed blaze.
	A fir, 25 ins. diam., bears S. 80° W., 107.8 ft. dist., with scribe marks S8 visible on partially healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	<p style="text-align: center;">A sawed fir stump, 17 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ W., 26.6 ft. dist., with no marks visible.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $89^{\circ} 17' 53''$ W., beginning new measurement.</p> <p>Continue desc. over SW. slope.</p>
840	<p>Spur, slopes N. 75° W., desc. over NW. slope.</p>
1318.29	<p>The W 1/16 sec. cor. of secs. 7 and 18, established by Daniel W. Baker, Oregon Professional Land Surveyor No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Map File No. M132-16, and is accepted as the cor., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 4 W S 7 W 1/16 ----- S 18 PLS 1978 1999</p> <p>from which bearing trees mkd. by Baker</p> <p style="text-align: center;">A fir, 6 ins. diam., bears S. $76\frac{1}{4}^{\circ}$ E., 6.8 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="text-align: center;">A fir, 6 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ W., 3.9 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <hr style="width: 20%; margin: auto;"/>
115	<p>S. $89^{\circ} 16' 36''$ W., beginning new measurement.</p> <p>Continue desc. over NW. slope.</p> <p>Spring branch, 2 ft. wide, course N. 60° W.; asc. over NE. slope.</p>
1604.59	<p>The cor. of secs. 7, 12, 13, and 18 on the W. bdy. of the Tp., hereinbefore described.</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 7, 8, 17 and 18, hereinbefore described.</p> <p>N. $0^{\circ} 14' 32''$ E., bet. secs. 7 and 8.</p> <p>Over broken E. slope.</p>
1308.79	<p>Point for the S 1/16 sec. cor. of secs. 7 and 8.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Drive an aluminum rod, 72 ins. long, $\frac{3}{8}$ in. diam., 70 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 4 W</p> <p> S 1/16</p> <p> </p> <p> S 7 S 8</p> <p> </p> <p> 2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ E., 5.1 ft. dist., mkd. S 1/16 S8 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 19° W., 16.5 ft. dist., mkd. S 1/16 S7 BT.</p> <p>Begin posting and blazing.</p>
1505	Ravine, drains S. 80° E.; asc. E. slope.
2355	Spur, slopes N. 45° E.; desc. NE. slope.
2617.58	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8 at proportionate dist. There is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 4 W</p> <p> 1/4</p> <p> </p> <p> S 7 S 8</p> <p> </p> <p> 2002</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. $47\frac{3}{4}^{\circ}$ E., 28.8 ft. dist., mkd. 1/4 S8 BT.</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ W., 10.3 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
3500	Ravine, drains S. 30° E.; asc. SW. slope.
4940	Dirt road, 15 ft. wide, bears N. 80° E. and N. 80° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
4990	Graveled Road No. 22-4-8.0, 17 ft. wide, bears N. 35° E. and S. 25° W.
5070	Graveled Road No. 22-4-8.0, 18 ft. wide, bears S. 65° E. and N. 15° W.
5235.16	<p>The cor. of secs. 5, 6, 7, and 8, remonumented by Milo E. Godfrey, Douglas County Surveyors Office, in 1962, recorded in the Douglas County Surveyor's Office, C.S. File No. 49/42, recovered by Donald L. Peel, Oregon Professional Land Surveyor No. 752, in 1991 and 1992, recorded in the Douglas County Surveyor's Office, Map File Nos. M111-75 and M115-77, and recovered by Les Roberts, Oregon Professional Land Surveyor No. 1039, in 1994, recorded in the Douglas County Surveyor's Office, Map File No. M121-26, and recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 22 S., R. 4 W., Point Identifier No. 200600, monumented with an iron post, 1½ ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 22 S S 6 S 5 ----- S 7 S 8 R 4 W 1962</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears S. 82° E., 22.4 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed fir stump, 39 ins. diam., bears N. 88¾° W., 21.8 ft. dist., with healed blaze. (Record S. 89½° W.)</p> <p>and remains of bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 15¼° E., 36.3 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears S. 19½° E., 34.6 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 30 ins. diam., bears S. 9° W., 80.8 ft. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 73½° E., 100.9 ft. dist., mkd. T22S R4W S8 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A maple, 20 ins. diam., bears S. $15\frac{1}{4}^{\circ}$ W., 81.4 ft. dist., mkd. T22S R4W S7 BT.</p> <p>A fir, 23 ins. diam., bears N. 30° W., 38.7 ft. dist., mkd. T22S R4W S6 BT.</p> <p>From this point, an aluminum pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 6 ins. above ground, bears East, 2.0 ft. dist.</p> <hr/> <p>S. $89^{\circ} 47' 35''$ W., bet. secs. 6 and 7, posting and blazing.</p> <p>Descend broken SW. slope.</p>
1040	Spring branch, 2 ft. wide, course S. 9° W.; asc. broken SE. slope.
2085	Dirt road, 12 ft. wide, bears S. 26° E. and N. 26° W.
2285	Spur, slopes S. 30° W.; desc. steep W. slope.
2606.64	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist. There is no remaining evidence of the orig. cor.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 22 S R 4 W</p> <p> S 6</p> <p> 1/4 ———</p> <p> S 7</p> <p> 2002</p> </div> <p>from which</p> <p>A fir, 18 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ E., 44.1 ft. dist., mkd. 1/4 S6 BT.</p> <p>A fir, 14 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ W., 20.2 ft. dist., mkd. 1/4 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue posting and blazing.</p>
3909.96	<p>Point for the W 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 22 S R 4 W S 6 W 1/16 ——— S 7 2002
	from which
	A fir, 10 ins. diam., bears S. 5¼° W., 28.8 ft. dist., mkd. W 1/16 S7 BT.
	A fir, 14 ins. diam., bears N. 82° W., 35.3 ft. dist., mkd. W1/16 S6 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Begin posting and blazing.
4505	Salt Creek, 5 ft. wide, course S. 20° W.; asc. E. slope.
4595	Dirt road, 8 ft. wide, bears N. 36° E. and S. 22° W.
4795	Spur, slopes S. 5° E.; desc. SW. slope.
4830	Dirt road, 8 ft. wide, bears S. 30° E. and N. 30° W.
4940	Dirt road, 8 ft. wide, bears S. 65° E. and N. 65° W.
5150	Creek, 3 ft. wide, course S. 25° E.; asc. E. slope.
5539.11	The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., hereinbefore described.
<hr/> Subdivision of Section 7, T. 24 S., R. 7 W., Willamette Meridian, Oregon <hr/>	
	From the ¼ sec. cor. of secs 7 and 18, hereinbefore described.
	N. 0° 32' 31" E., on the N. and S. centerline of sec. 7.
	Over broken SW. slope.
740	Spur, slopes N. 68° W., and dirt road, 12 ft. wide, bears S. 68° E. and N. 68° W.; desc. steep N. slope.
1255	Ravine, drains N. 75° W.; asc. broken S. slope.
1314.11	Point for the center S 1/16 sec. cor. of sec. 7; not monumented.

**Subdivision of Section 7,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1925	Spur, slopes S. 70° W.; over broken W. slope.
2628.22	Point for the center ¼ sec. cor. of sec. 7, at the intersection with the E. and W. centerline. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;">T 22 S R 4 W C 1/4 S 7 2002</div> from which <div style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 28½° E., 4.4 ft. dist., mkd. C 1/4 S7 BT.</div> <div style="margin-left: 40px;">A fir, 10 ins. diam., bears N. 63¾° W., 24.4 ft. dist., mkd. C 1/4 S7 BT.</div> Deposit a magnet in a white plastic case at the base of the stainless steel post. Ascend steep SE. slope. Begin posting and blazing.
3520	Dirt road, 12 ft. wide, bears N. 68° E. and S. 68° W.
3540	Spur, slopes N. 78° W.; desc. steep NE. slope.
3940	Ravine, drains N. 52° W.; asc. SW. slope.
3943.03	Point for the center N 1/16 sec. cor. of sec. 7, not monumented.
4865	Spur, slopes S. 55° W., desc. NW. slope.
5257.84	The ¼ sec. cor. of secs. 6 and 7, hereinbefore described. <hr/>
	From the ¼ sec. cor. of secs 7 and 8, hereinbefore described. S. 89° 32' 00" W., on the E. and W. centerline of sec. 7. Ascend broken SE. slope.
1310.41	Point for the center E 1/16 sec. cor. of sec. 7. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.

Subdivision of Section 7,
T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET	
	E 1/16 C ————— C S 7 2002
	from which
	A fir, 14 ins. diam., bears N. 55° E., 30.9 ft. dist., mkd. CE 1/16 S7 BT.
	A fir, 12 ins. diam., bears S. 65½° E., 17.9 ft. dist., mkd. CE 1/16 S7 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Begin posting and blazing.
2130	Spur, slopes S. 5° W., and dirt road, 12 ft. wide, bears N. 20° E. and S. 5° W.; desc. steep W. slope.
2620.82	The center 1/4 sec. cor. of sec. 7, hereinbefore described.
	Discontinue posting and blazing.
2915	Ravine, drains S. 5° E.; asc. SE. slope.
3775	Spur, slopes S. 20° W., desc. NW. slope
3930.88	Point for the center W. 1/16 sec. cor. of sec. 7, not monumented.
5035	Salt Creek, 6 ft. wide, course S. 20° W.; asc. NE. slope.
5185	Dirt road, 10 ft. wide, bears N. 14° E. and S. 14° W.
5547.47	The ¼ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.
	<hr/>
	From the S. 1/16 sec. cor. of secs. 7 and 8, hereinbefore described.
	S. 89° 25' 10" W., on the calculated E. and W. centerline of the SE. ¼ of sec. 7, posting and blazing.
	Ascend broken E. slope.
1255	Spur, slopes N. 45° E.; desc. NW. slope.
1313.96	Point for the SE. 1/16 sec. cor. of sec. 7, at its calculated position.

**Subdivision of Section 7,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 7</p> <p style="text-align: center;">2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 54¼° E., 29.3 ft. dist., mkd. SE 1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 52° W., 21.5 ft. dist., mkd. SE 1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Cor. is located approx. 15 ft. E. of a dirt road, 12 ft. wide, bears N. 55° E., S. 55° W.</p> <hr/> <p>N. 0° 23' 32" E., on the calculated N. and S. centerline of the SE¼ of sec. 7, posting and blazing.</p> <p>Descend broken NE. slope.</p>
1105	Creek, 1 ft. wide. course N. 75° E.; asc. SE. slope.
1311.45	The center E 1/16 sec. cor. of sec. 7, hereinbefore described.
	<hr/> <p>From the N 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp., hereinbefore described.</p> <p>N. 89° 39' 56" E., on the calculated E. and W. centerline of the NW¼ of sec. 7, posting and blazing.</p> <p>Descend broken E. slope.</p>
670	Dirt road, 25 ft. wide, bears N. 10° E. and S. 10° W.
805	Salt Creek, 3 ft. wide, course S. 25° W.; asc. steep W. slope.
1455	Spur, slopes S. 30° W.; desc. SE. slope.
1622.65	Point for the NW 1/16 sec. cor. of sec. 7, at its calculated position.
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 7,
T. 22 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 22 S R 4 W NW 1/16 S 7 2002
	from which
	A fir, 12 ins. diam., bears N. 70¾° E., 6.1 ft. dist., mkd. NW 1/16 S7 BT.
	A fir, 14 ins. diam., bears N. 38¾° W., 17.4 ft. dist., mkd. SE 1/16 S7 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/>
	N. 0° 40' 59" E., on the calculated N. and S. centerline of the NW¼ of sec. 7, posting and blazing.
	Ascend broken SW. slope.
305	Spur, slopes West; desc. broken N. slope.
780	Creek, 1½ ft. wide, course N. 80° W., asc. SW. slope.
1050	Spur, slopes N. 85° W.; desc. NW. slope.
1317.76	The W 1/16 sec. cor. of secs. 6 and 7, hereinbefore described.
	<hr/>
	GENERAL DESCRIPTION
	The lands included in the foregoing survey are located in mountainous terrain, approximately 5.0 miles northeasterly from the community of Drain, Oregon. The survey lies approximately 0.3 mile westerly of Interstate Highway 5.
	The elevation ranges from about 400 ft. above mean sea level near the southwest section corner of section 7 to about 1129 ft. above mean sea level near the southeast 1/16 section corner of section 13.
	The westerly portion of sec. 7 is drained by Salt Creek, which flows southerly to Elk Creek. The easterly portion of sec. 7 drains into Thief Creek which flows southerly to Elk Creek.
	Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.

T. 22 S., R. 4 W., Willamette Meridian, Oregon

FEET

The soil is generally composed of rocky clay, with numerous basalt outcroppings and bluffs, and steep, crumbling rock slopes.

Access to the survey was made by graveled roads branching from State Highway No. 99 and Salt Creek Road.

The mean magnetic declination for the area surveyed is 19° East, as shown on the "CURTIN, OREG." 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1987.