

FEET

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

AND SUBDIVISIONAL LINES, AND

THE SUBDIVISION OF SECTIONS 3, 9, 11, 15, AND 33,

**TOWNSHIP 23 SOUTH, RANGE 4 WEST,**

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

**EXECUTED BY*****Timothy J Moore, Cadastral Surveyor******Robert H. Browning, Surveying Technician***

Under Special Instructions dated July 12, 2000, approved July 13, 2000,  
which provided for the surveys included under Group No. 1955,  
and Assignment Instructions dated July 26, 2000.

***Survey commenced July 26, 2000******Survey completed June 27, 2001***

**T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>The following field notes are those of the dependent resurvey of a portion of the north boundary and subdivisional lines, and the subdivision of sections 3, 9, 11, 15, and 33, township 23 south, range 4 west, of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this resurvey is as follows:</p> <p>The north boundary was surveyed by James E. Freeman, U.S. Deputy Surveyor, in 1851.</p> <p>A portion of the subdivisional lines were surveyed by Harvey Gordon and Charles T. Gardener, U.S. Deputy Surveyors, in 1855-56.</p> <p>A portion of the subdivisional lines were surveyed by William P. Wright, U.S. Deputy Surveyor, in 1884.</p> <p>A portion of the subdivisional lines were resurveyed, and certain original corner points were remonumented by C. Albert White and Donald R. Beck, Cadastral Surveyors, in 1963.</p> <p>A portion of the subdivisional lines were resurveyed by James E. Jelley, Cadastral Surveyor, in 1971.</p> <p>A portion of the south boundary and a portion of the subdivisional lines were resurveyed by James E. Jelley, Cadastral Surveyor, in 1976.</p> <p>A portion of the subdivisional lines were resurveyed and section 14 was subdivided by James E. Jelley, Cadastral Surveyor, in 1982.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated July 12, 2000, for Group No. 1955, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distance and direction have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot. The Standard Error of Unit Weight (SEUW) for a least squares adjustment of the survey data was checked to assure a value between 0.7 and 2.5. In addition, a post-adjustment comparison of the final adjusted measurements was also</p>

**T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

checked to assure a ratio not exceeding 1:4000. The comparison was done in the CHECKER routine of WinCMM, and is reported as the Precision After Orientation Correction.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ in. x ¼ in. magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983-91) of the ¼ sec. cor. of secs. 10 and 15, as determined by a tie to geodetic control station BM 24 1917, determined by the NAVSTAR Global Positioning System (GPS), (see the Control Data Sheet attached to these field notes following the General Description), by the Bureau of Land Management, in 2000, is as follows:

Latitude: 43° 34' 36.89" N.      Longitude: 123° 09' 25.64" W.

The geographic position (NAD 1983-91) of the ¼ sec. cor. of secs. 28 and 33, as determined by a tie to geodetic control station BM 24 1917, is as follows:

Latitude: 43° 32' 00.25" N.      Longitude: 123° 10' 37.35" W.

---

**Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

---

(Restoring the survey by James Freeman, in 1851)

---

Beginning at the ¼ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., perpetuated by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office map file No. M22-6, and further perpetuated by Donald L. Peel, Registered Professional Land Surveyor, No. 752, in 1988, recorded in the Douglas County Surveyor's Office, map file No. 106-59, further perpetuated by Harvey M. Christensen, Registered Professional Land Surveyor, No. 2603, in 1999, recorded in the Douglas County Surveyor's Office, map file No. 134-4, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 7 ins. above the ground, with brass cap cemented to top mkd.

**Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 22 S R 4 W S 34 1/4 ————— S 3 T 23 S PLS 752 1988
	from which the remaining original bearing tree
	A fir, 37 ins. diam., bears South, 72.6 ft. dist., with no marks visible on a opened blaze.
	and a bearing tree mkd. by Peel
	A fir, 17 ins. diam., bears N. 58° W., 13.4 ft. dist., with healed double blaze.
	and bearing trees mkd. by Christensen
	A fir, 15 ins. diam., bears N. 24½° E., 18.0 ft. dist., with scribe marks 1/4 S34 BT visible on partially healed blaze.
	A fir, 17 ins. diam., bears S. 76½° E., 35.0 ft. dist., with fragmentary scribe marks visible on partially healed blaze.
	From this point the cor. of secs. 2, 3, 34, and 35, restored by person(s) unknown, perpetuated by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, further perpetuated by Gregory Quibell, Deputy County Surveyor, in 1981, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500700, bears S. 89° 36' 46" E., 2642.88 ft. dist. There is no remaining evidence of the original corner, therefore this point is accepted as the corner, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, alongside a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above ground, from which bearing trees mkd. by person(s) unknown and reported by Haines
	A fir, 28 ins. diam., bears S. 62¾° E., 69.4 ft. dist., with healed double blaze.
	A fir, 26 ins. diam., bears S. 39¾° E., 71.0 ft. dist., with healed double blaze.
	and a bearing tree mkd. by Haines

**Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET						
	<p>An oak, 15 ins. diam., bears S. <math>74\frac{1}{4}^{\circ}</math> W., 33.5 ft. dist., with a healed blaze</p> <p>and an accessory by Quibell</p> <p>A power pole, No. 4-191, bears N. <math>33^{\circ}</math> W., 155.9 ft. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T 22 S R 4 W</td></tr> <tr><td>S 34   S 35</td></tr> <tr><td style="border-top: 1px solid black;">S 3   S 2</td></tr> <tr><td>T 23 S</td></tr> <tr><td>2001</td></tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post, and bury the iron pipe and the "T" shaped iron rod on north side of the stainless steel post.</p> <p>S. <math>89^{\circ} 20' 34''</math> W., bet. secs. 3 and 34, blazing and tagging.</p> <p>Ascend over gentle northerly slope.</p>	T 22 S R 4 W	S 34   S 35	S 3   S 2	T 23 S	2001
T 22 S R 4 W						
S 34   S 35						
S 3   S 2						
T 23 S						
2001						
85	Spur, slopes N. $15^{\circ}$ E.; desc. over NW. slope.					
325	Ravine, drains N. $20^{\circ}$ E., asc. over NE. slope.					
740	Spur, slopes N. $15^{\circ}$ W.; desc. over NW. slope.					
1655	Creek, 3 ft. wide, course N. $40^{\circ}$ E.; asc. over NE. slope.					
1795	Ravine, drains N. $80^{\circ}$ E., asc. over SE. slope.					
2621.20	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 10 ins. above the ground, with a 1 x 1 in. "T" shaped iron rod, and an iron pipe, 1 in. diam., firmly set, alongside, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr><td>T 22 S R 4 W</td></tr> <tr><td>S 33   S 34</td></tr> <tr><td style="border-top: 1px solid black;">S 4   S 3</td></tr> <tr><td>T 23 S</td></tr> <tr><td>1963</td></tr> </table> </div>	T 22 S R 4 W	S 33   S 34	S 4   S 3	T 23 S	1963
T 22 S R 4 W						
S 33   S 34						
S 4   S 3						
T 23 S						
1963						

**Dependent Resurvey of a Portion of the North Boundary,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

from which the remains of the remaining original bearing tree

A decayed fir stump, 27 ins. diam., bears N.  $42\frac{1}{2}^{\circ}$  E.,  
24.7 ft. dist., with no marks remaining. (Record N.  $40^{\circ}$  E.,  
25.1 ft. dist.)

and bearing trees mkd. by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400700

A cedar, 25 ins. diam., bears S.  $89^{\circ}$  E., 25.7 ft. dist., with a healed blaze.

A cedar, 34 ins. diam., bears N.  $14\frac{1}{2}^{\circ}$  W., 31.0 ft. dist., with a healed blaze.

and the remaining bearing tree mkd. by White and Beck

A maple, 34 ins. diam., bears S.  $16\frac{1}{4}^{\circ}$  E., 69.7 ft. dist., with a healed blaze. (Record, S.  $11^{\circ}$  E., 62.0 ft. dist.)

and a bearing tree mkd. by Harvey M. Christensen, Registered Professional Land Surveyor, No. 2603, in 1999, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No 400700

A fir, 11 ins. diam., bears S.  $27\frac{3}{4}^{\circ}$  W., 21.8 ft. dist., with scribe marks T23S R4W S4 BT visible on partially healed blaze.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

---

(Restoring the survey by Harvey Gordon and Charles T. Gardener, in 1855-56, the survey by William P. Wright, in 1884, the resurvey by C. Albert White and Donald R. Beck, in 1963, and the resurvey by James E. Jelley, in 1976)

---

From the cor. of secs. 11, 12, 13, and 14, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET						
	<table style="margin: auto;"> <tr><td>T 23 S R 4 W</td></tr> <tr><td>S 11   S 12</td></tr> <tr><td>-----</td></tr> <tr><td>S 14   S 13</td></tr> <tr><td>1971</td></tr> </table>	T 23 S R 4 W	S 11   S 12	-----	S 14   S 13	1971
T 23 S R 4 W						
S 11   S 12						
-----						
S 14   S 13						
1971						
	<p>from which a bearing tree mkd. by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 600500</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 23<math>\frac{3}{4}</math>° W., 75.2 ft. dist., with scribe marks S11 T23S R4W BT visible on the bark.</p> <p>and the remains of a bearing tree mkd. by Jelley</p> <p style="padding-left: 40px;">A roothole, bears N. 47° W., 9.6 ft. dist., alongside of which is the fir trunk, 11 ins. diam., with a healed blaze.</p> <p>and new reference monuments</p> <p style="padding-left: 40px;">An aluminum rod, 36 ins. long, <math>\frac{3}{8}</math> in. diam., set 33 ins. in the ground for a reference monument, bears S. 44° 22' 33" E., 19.9 ft. dist., with aluminum cap mkd. RM T23SR4W S13 19.9 FT TO COR 2001 and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An aluminum rod, 36 ins. long, <math>\frac{3}{8}</math> in. diam., set 32 ins. in the ground for a reference monument, bears S. 30° 32' 59" W., 19.4 ft. dist., with aluminum cap mkd. RM T23SR4W S14 19.4 FT TO COR 2001 and an arrow pointing to the corner.</p> <p>N. 0° 44' 50" E., bet. secs. 11 and 12, blazing and tagging.</p> <p>Ascend over gentle SW. slope.</p>					
910	Spur, slopes N. 55° W.; desc. over NW. slope.					
1309.20	The S 1/16 sec. cor. of secs. 11 and 12, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1963, recorded in the Douglas County Surveyor's Office, map file No. M26-80, subsequently recovered and utilized by Les D. Roberts, Registered Professional Land Surveyor, No. 1039, in 1997, recorded in the Douglas County Surveyor's Office, map file No. M127-80, monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 14 ins. above the ground, and is accepted as the cor., from which the remains of bearing trees mkd. by Haines					

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed and decayed fir stump, 36 ins. diam., bears N. <math>76\frac{3}{4}^{\circ}</math> E., 3.3 ft. dist., with scribe mark T visible on decayed face.</p> <p>A sawed and decayed fir stump, 34 ins. diam., bears S. <math>20\frac{3}{4}^{\circ}</math> W., 18.1 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 26 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W S 1/16 S 11   S 12 2001</p> <p>from which new bearing trees</p> <p>A fir, 9 ins. diam., bears S. <math>42\frac{1}{4}^{\circ}</math> E., 17.1 ft. dist., mkd. S1/16 S12 BT.</p> <p>A hemlock, 6 ins. diam., bears N. <math>79\frac{3}{4}^{\circ}</math> W., 18.5 ft. dist., mkd. S1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 46' 46''</math> E., beginning a new measurement, blazing and tagging.</p> <p>Descend over broken NW. slope, through second growth timber and dense undergrowth.</p> <p>405 Walker Creek, 6 ft. wide, course N. <math>65^{\circ}</math> W.; asc. over SW. slope.</p> <p>760 Dirt road, 12 ft. wide, bears N. <math>75^{\circ}</math> W. and S. <math>70^{\circ}</math> E.</p> <p>815 Spur, slopes S. <math>85^{\circ}</math> W.; desc. over NW. slope.</p> <p>1275 Creek, 3 ft. wide, course S. <math>60^{\circ}</math> W.; asc. over SE. slope.</p> <p>1308.23 The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 12, perpetuated from original evidence no longer in existence by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, further perpetuated by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, recorded in the Douglas County Surveyor's Office, records</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 600540, monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 5 ins. above the ground, with brass button, 1 in. diam., affixed to top, mkd. SURVEY POINT WILFORD N. HAINES 239 DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A maple snag, 16 ins. diam., bears S. 29¼° E., 14.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 46½° W., 14.4 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by Tracy</p> <p style="padding-left: 40px;">A cedar snag, 12 ins. diam., bears S. 86° E., 60.6 ft. dist., with scribe marks 1/4 S12 BT visible on partially healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W 1/4 S 11   S 12 2001</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. 8¼° E., 26.0 ft. dist., mkd. 1/4 S12 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post, and place the "T" shaped iron rod along east side of the stainless steel post</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 42' 06" W., beginning a new measurement, blazing and tagging.</p> <p>Ascend over SE. slope, through second growth timber and dense undergrowth.</p>
75	Graveled road, 12 ft. wide, bears N. 85° E. and S. 85° W.
340	Creek, 1 ft. wide, course N. 65° W.; asc. over SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1324.58	<p>The N 1/16 sec. cor. of secs. 11 and 12, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, determined at record distances from the remains of a bearing tree mkd. by Haines and a bearing tree mkd. by person(s) unknown, reported by Haines, and is accepted as the cor., from which the remains of a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A sawed fir stump, 60 ins. diam., bears N. 17½° E., 98.6 ft. dist., with scribe marks BT visible on the bark.</p> <p>and the remains of a bearing tree mkd. by person(s) unknown and reported by Haines</p> <p style="padding-left: 40px;">A decayed fir snag, 9 ins. diam., bears N. 50½° W., 16.0 ft. dist., with fragmentary scribe marks visible on decayed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S 11   S 12</p> <p>2001</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 64° E., 11.7 ft. dist., mkd. N1/16 S12 BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 0½° W., 63.7 ft. dist., mkd. N1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 33' 14" W., beginning a new measurement, blazing and tagging.</p> <p>Continue ascending over a broken SW. slope.</p>
1324.83	<p>The cor. of secs. 1, 2, 11, and 12, perpetuated from evidence no longer in existence by Oscar F. Theil, Deputy County Surveyor, in 1940, further perpetuated by Lester E. Calder, Registered Professional Engineer, No. 2149, in 1960, further perpetuated by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, further perpetuated by A. Victor Cangie, of the Douglas County Surveyor's</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

Office, in 1976, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No 600600, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S	
S 2	S 1
-----	
S 11	S 12
R 4 W	
CS 1976	
1965	

from which the remains of bearing trees mkd. by Theil

A fir, 40 ins. diam., bears S. 67¾° E., 16.0 ft. dist., with a healed double blaze.

A fir, 41 ins. diam., bears S. 52¼° W., 42.2 ft. dist., with a healed double blaze.

A fir snag, 37 ins. diam., bears N. 76° W., 10.6 ft. dist., with a healed double blaze.

and the remains of a bearing tree mkd. by Tracy

A sawed cedar stump, 25 ins. diam., bears N. 56° E., 174.8 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Cangie

A sawed and decayed fir stump, 12 ins. diam., bears N. 27° W., 79.5 ft. dist., with scribe marks 23S R4W S2 CS visible on partially healed blaze.

and new bearing trees

A fir, 6 ins. diam., bears N. 59¼° E., 20.2 ft. dist., mkd. X BT.

A fir, 11 ins. diam., bears N. 7½° W., 14.3 ft. dist., mkd. T23S R4W S2 BT.

Corner is located South, 2.0 ft. dist., of an unmaintained woven wire fence, fences extending east and west.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>From the cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 1½ ins. diam., firmly set, projecting 8 ins. above the ground, (with a 1 x 1 in. "T" shaped iron rod, firmly set, along side, projecting 10 ins. above the ground, by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, year unknown, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500400) with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 23 S S 15   S 14 ----- S 22   S 23 R 4 W 1963</p> <p>from which bearing trees mkd. by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No.. 500400</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 54½° E., 21.8 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 75° W., 5.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 49° W., 12.5 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 50° E., 38.4 ft. dist., mkd. T23S R4W S23 BT.</p> <p>N. 0° 05' 41" E., bet. secs. 14 and 15, blazing and tagging.</p> <p>Descend over broken North slope, along the East edge of a clear cut.</p>
160	Creek, 1 ft. wide, course S. 65° W.; asc. over South Slope.
460	Graveled road, 15 ft. wide, bears N. 85° E. and S. 85° W, also top of ridge, bears the same.
1005	Creek, 2 ft. wide, course N. 60° W.; asc. over SW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1316.37	<p>The S 1/16 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 15   S 14 1975</p> <p>from which bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 29½° E., 6.9 ft. dist., with a healed blaze. (Record, S. 28¼° E., 9.2 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 86° W., 8.7 ft. dist., with a healed blaze. (Record, S. 87° W., 7.3 ft. dist.)</p> <p>Discontinue blazing and tagging.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 05' 20" E., beginning a new measurement.</p> <p>Ascend a West slope, through a clear-cut.</p>
290	<p>Spur, slopes N. 50° W.; desc. over East Slope.</p>
1316.06	<p>The ¼ sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 15   S 14 T 23 S R 4 W 1976</p> <p>from which the remains of a bearing tree mkd. by Jelley</p> <p style="padding-left: 40px;">A sawed fir stump, 9 ins. diam., bears S. 21¼° W., 14.2 ft. dist., with a healed blaze.</p> <p>and new reference monuments</p> <p style="padding-left: 40px;">An aluminum finned rod, 36 ins. long, ¾ in. diam., 34 ins. in the ground for a reference monument, bears N. 35° 43' 01" E., 7.22 ft. dist., with aluminum cap mkd. T23SR4W RM 1/4 S14 7.2 FT. TO COR 2000, and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An aluminum finned rod, 36 ins. long, ¾ in. diam., 35 ins. in the ground for a reference monument, bears N. 54° 23' 06" W., 12.80 ft. dist., with aluminum cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>T23S R4W RM 1/4 S15 12.8 FT TO COR 2000, and an arrow pointing to the corner.</p> <p>Corner is located West, 23.0 ft. dist., of a graveled road, 20 ft. wide, bears N. 5° W. and S 10° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' 56" E., beginning a new measurement.</p> <p>Descend over broken NE. slope, through a clear-cut.</p>
80	Graveled road, 20 ft. wide, bears N. 30° W. and S. 20° E.
2629.58	<p>The cor. of secs. 10, 11, 14, and 15, monumented with a basalt stone, 12 x 10 x 8 ins. firmly set 10 ins. below the surface of the ground, with a 3/8 in. diam. x 8 ins. long iron spike plumbed over it from which a bearing tree mkd. and a reference monument established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, and records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500500</p> <p style="padding-left: 40px;">An oak, 43 ins. diam., bears S. 85½° E., 93.7 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A 1 x 1 in. "T" shaped iron rod, firmly set, 2 ins. below the ground for a reference monument, bears South, 1.99 ft. dist.</p> <p>and a bearing tree mkd. by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500500</p> <p style="padding-left: 40px;">An oak, 31 ins. diam., bears N. 77¼° E., 82.5 ft. dist., with healed blaze.</p> <p>and a reference monument by Jelley</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, bears S. 13° 30' 00" E., 30.36 ft. dist., with brass cap mkd. RM T23S R4W S14 1976 and an arrow pointing to the corner.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, the top flush with ground surface, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 23 S R 4 W S 10   S 11 ----- S 15   S 14 2001
	Deposit a magnet in a white plastic case at the base of the stainless steel post, and the stone and spike alongside.
	Corner is located south, 9.0 ft. of the center of a gravel driveway, 12 ft. wide, bears N. 70° W. and S. 55° E.
	<hr/> From the cor. of secs. 11, 12, 13, and 14.
	N. 89° 45' 42" W., bet. secs. 11 and 14, blazing and tagging.
	Descend over broken SW. slope, along the north edge of a clearcut.
125	Ravine, drains N. 70° W., asc. over NE. slope.
490	Spur, slopes N. 75° W.; desc. over NW. slope.
1324.90	Point for the E 1/16 sec. cor. of secs. 11 and 14.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	E 1/16 S 11 ----- S 14 2001
	from which
	A fir, 5 ins. diam., bears S. 62½° E., 19.6 ft. dist., mkd. X BT.
	A fir, 6 ins. diam., bears N. 86½° W., 12.7 ft. dist., mkd. E1/16 S11 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Discontinue blazing and tagging.
	Continue descending over NW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
2649.80	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, monumented with an iron post, 2<math>\frac{1}{2}</math> ins. diam., firmly set, projecting 10 ins. above the ground, with aluminum cap mkd.,</p> <p style="text-align: center;">T 23 S R 4 W  <math>\frac{1}{4}</math> <u>S 11</u>  S 14  1982</p> <p>from which the remains of a bearing tree mkd. by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 540500</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 32 ins. diam., bears S. 20<math>\frac{1}{4}</math><math>^{\circ}</math> W., 26.4 ft. dist., with a healed blaze. (Record, S. 15<math>^{\circ}</math> W.,)</p> <p>and the remains of a bearing tree mkd. by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 540500</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 14 ins. diam., bears N. 78<math>\frac{1}{2}</math><math>^{\circ}</math> W., 10.9 ft. dist., no marks visible. (Record, N. 84<math>^{\circ}</math> W.,)</p> <p>and the remains of bearing trees mkd. by Jelley</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 14 ins. diam., bears N. 24<math>^{\circ}</math> E., 17.1 ft. dist., no marks visible. (Record, N. 18<math>\frac{1}{4}</math><math>^{\circ}</math> E.)</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 7 ins. diam., bears S. 56<math>^{\circ}</math> E., 14.2 ft. dist., no marks visible. (Record, S. 64<math>\frac{3}{4}</math><math>^{\circ}</math> E.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 3<math>\frac{1}{4}</math><math>^{\circ}</math> W., 98.7 ft. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 88<math>\frac{1}{4}</math><math>^{\circ}</math> W., 38.2 ft. dist., mkd. 1/4 S11 BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>S. 89<math>^{\circ}</math> 55' 42" W., beginning a new measurement.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	Continue descending over broken NW. slope.
2629.93	The cor. of secs. 10, 11, 14, and 15.
	<hr/>
	N. 0° 04' 13" W., bet. secs. 10 and 11.
	Descend over NW. slope, through pasture lands.
270	Creek, 5 ft. wide, course West; asc. over SW. slope.
635	Spur, slopes S. 75° W.; desc. over NW. slope.
1320.40	The S 1/16 sec. cor. of secs. 10 and 11, established by Glen S. Baughman, Registered Professional Land Surveyor, No. 536, in 1978, recorded in the Douglas County Surveyor's Office, map file No. M65-71, and is accepted as the cor., monumented with an iron rod, 5/8 ins. diam., firmly set, 10 ins. below the ground, from which a bearing object referenced to by Baughman,
	A power pole, No. 5-32, bears S. 50¾° W., 152.1 ft. dist., (Baughman called this pole L1/74)
	At the corner point
	Drive an aluminum cap, 3½ ins. diam., onto the iron rod, 11 ins. below the ground, with top mkd.
	S 1/16 S 10   S 11 2001
	from which a new reference monument
	An aluminum rod, 36 ins. long, ¼ ins. diam., set 32 ins. in the ground for a reference monument, bears S. 55° 35' 19" E., 10.1 ft. dist., with aluminum cap mkd. RM S1/16 S11 2001 10.1 FT. TO COR and an arrow pointing to the corner.
	Corner is located N. 49¾° W., 10.6 ft. dist. from the corner of woven wire fences, fences extending south, east, and west.
	<hr/>
	N. 0° 02' 26" W., beginning a new measurement.
	Continue descending over a NW. slope, over pasture lands.
40	Power transmission line, bears, N. 30° E. and S. 30° W.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1321.92	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 11, at proportionate distance, there is no remaining evidence of the original cor., no monument set at the request of the private landowner.</p> <p>Continue descending over NW. slope, over pastureland.</p>
2315	Walker Creek, 3 ft. wide, course S. $70^{\circ}$ W.; asc. over SW. slope.
2643.84	<p>The N <math>\frac{1}{16}</math> sec. cor. of secs. 10 and 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, determined at record distances from Haines accessories and is accepted as the cor., from which a bearing tree and a bearing object mkd. by Haines,</p> <p style="padding-left: 40px;">A power pole, No. 59-4, bears North, 144.8 ft. dist.,</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears N. <math>61^{\circ}</math> W., 228.9 ft. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N <math>\frac{1}{16}</math></p> <p>S 10   S 11</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located North, 3.2 ft. dist. from the corner of woven wire fences, fences extending east and west.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 05' 29''</math> W., beginning a new measurement.</p> <p>Continue ascending over SW. slope, through pastureland.</p>
1255	Graveled road, 12 ft. wide, bears N. $80^{\circ}$ E. and S. $80^{\circ}$ W.
1322.57	The cor. of secs. 2, 3, 10, and 11, reestablished at proportionate measurement by Glen S. Baughman, Registered Professional Land Surveyor, No. 536, in 1978, recorded in the Douglas County Surveyor's Office, map file No. M65-71. Baughman used the information from the survey by Winford N. Haines, Registered Professional Land Surveyor No. 239, in 1961, recorded in Douglas County Surveyor's Office, map file No. M22-6 to reestablish this

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET																															
	<p>corner. Corner further perpetuated by Randall W. Smith, Deputy County Surveyor, in 1987, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500600. There is no remaining evidence of the original cor. therefore this point is accepted as the cor., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above a mound of stone, 3½ ft. base, 1½ ft. high, with brass cap mkd. T23S R4W WM S3 S2 S10 S11 1978 OLS536, from which reference monuments set by Baughman</p> <p style="padding-left: 40px;">An iron rod, 5/8 ins. diam., firmly set, projecting 3 ins. above the ground, bears S. 78° 28' 09" W., 96.7 ft. dist.</p> <p style="padding-left: 40px;">An iron rod, 5/8 ins. diam., firmly set, projecting 13 ins. below the ground, bears S. 83° 00' 42" E., 218.7 ft. dist.</p> <p>and a bearing tree and bearing objects mkd. and tied to by Smith</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 84¾° W., 160.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">The SE. cor. of a barn, bears N. 88¾° W., 29.2 ft. dist.</p> <p style="padding-left: 40px;">The NE. cor. of a barn, bears N. 21¼° W., 65.4 ft. dist.</p> <p>At the corner point, and at the landowners request.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T</td> <td style="padding: 0 5px;">23</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">R</td> <td style="padding: 0 5px;">4</td> <td style="padding: 0 5px;">W</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">3</td> <td style="border-left: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">2</td> <td></td> </tr> <tr> <td colspan="6" style="border-top: 1px solid black; height: 1px;"></td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">10</td> <td style="border-left: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">11</td> <td></td> </tr> <tr> <td colspan="6" style="text-align: center; padding-top: 5px;">2001</td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base and bury the iron pipe along the west side of the stainless steel post.</p> <hr style="border: 0.5px solid black; margin: 10px 0;"/> <p>From the cor. of secs. 1, 2, 11, and 12.</p> <p>N. 89° 40' 50" W., bet. secs. 2 and 11, blazing and tagging.</p> <p>Descend over broken NW. slope, through second growth timber and dense undergrowth.</p> <p>215 Graveled road, 12 ft. wide, bears N. 10° E. and S. 10° W.</p>	T	23	S	R	4	W	S	3		S	2								S	10		S	11		2001					
T	23	S	R	4	W																										
S	3		S	2																											
S	10		S	11																											
2001																															

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET									
1322.69	<p>The E 1/16 sec. cor. of secs. 2 and 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, and is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 11 ins. above the ground, with a brass button, 1 ins. diam., affixed to top, mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE., from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A decayed fir snag, 20 ins. diam., bears N. 8° E., 84.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 11 ins. diam., bears S. 82¾° W., 26.5 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="padding: 0 10px;">T 23 S</td> <td style="padding: 0 10px;">R 4 W</td> </tr> <tr> <td style="padding: 0 10px;">S 2</td> <td style="padding: 0 10px;">_____</td> </tr> <tr> <td style="padding: 0 10px;">E 1/16</td> <td style="padding: 0 10px;">S 11</td> </tr> <tr> <td></td> <td style="padding: 0 10px;">2001</td> </tr> </table> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 43½° E., 34.2 ft. dist., mkd. E1/16 S2 BT.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 56½° E., 14.1 ft. dist., mkd. E1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Discontinue blazing and tagging</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 89° 43' 56" W., beginning a new measurement.</p> <p>Continue descending over broken NW. slope, through second growth timber and dense undergrowth.</p>	T 23 S	R 4 W	S 2	_____	E 1/16	S 11		2001
T 23 S	R 4 W								
S 2	_____								
E 1/16	S 11								
	2001								
670	Graveled road, 12 ft. wide, bears N. 15° W. and S. 20° E.								

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1319.89	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11, reestablished at proportionate measurement by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, perpetuated by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, further perpetuated by Ken W. Hoffine, Registered Professional Land Surveyor, No. 2291, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 540600. There is no remaining evidence of the original corner, therefore this point is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 13 ins. above the ground, from which remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 18 ins. diam., bears S. <math>44\frac{1}{2}^{\circ}</math> W., 13.4 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 20 ins. diam., bears N. <math>82\frac{3}{4}^{\circ}</math> W., 15.8 ft. dist., with scribe marks T visible.</p> <p>and the remains of a bearing tree mkd. by Tracy</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 12 ins. diam., bears S. <math>22\frac{1}{4}^{\circ}</math> E., 25.2 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Hoffine</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. <math>32\frac{1}{4}^{\circ}</math> E., 55.3 ft. dist., with scribe marks S2 1/4 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 22 ins. diam., bears S. <math>87^{\circ}</math> E., 67.3 ft. dist., with scribe marks S11 1/4 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. <math>40\frac{3}{4}^{\circ}</math> W., 27.9 ft. dist., with scribe marks S11 1/4 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. <math>86\frac{1}{4}^{\circ}</math> W., 22.3 ft. dist., with scribe marks S2 1/4 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;">       T 23 S R 4 W              S 2        1/4 ———              S 11              2001     </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located South, 35.0 ft. dist., of a ravine, drains West.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 41' 10" W., beginning a new measurement.</p> <p>Continue descending over broken NW. slope, through second growth timber and dense undergrowth.</p>
460	Power transmission line, bears, N. 30° E. and S. 30° W.
2647.34	The cor. of secs. 2, 3, 10, and 11.
	<hr/> <p>N. 0° 01' 07" W., bet. secs. 2 and 3.</p> <p>Descend over gentle westerly slope.</p>
1319.57	Point for the S 1/16 sec. cor. of secs. 2 and 3, not monumented.
2639.14	<p>The ¼ sec. cor. of secs. 2 and 3, reestablished at proportionate measurement by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, perpetuated by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, further perpetuated by Gary L. Langlitz, of the Douglas County Surveyor's Office, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 500640. There is no remaining evidence of the original cor., therefore this point is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above the ground; (with a 1 x 1 in. "T" shaped iron rod firmly set, flush, along the south side., with brass button, 1 ins. diam., affixed to top, mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE), with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYORS T 23 S R 4 W S 3   S 2 1/4 1978</p> <p>from which the remains of a bearing tree mkd. by Haines</p> <p style="text-align: center;">A decayed fir stump, 22 ins. diam., bears S. 89¼° W., 74.3 ft. dist., no marks visible.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>and a bearing tree mkd. and a bearing object by Tracy</p> <p style="padding-left: 40px;">An oak, 11 ins. diam., bears S. <math>47\frac{3}{4}^{\circ}</math> W., 105.3 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A power pole, bears S. <math>7\frac{1}{2}^{\circ}</math> W., 26.0 ft. dist., with no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. <math>32\frac{3}{4}^{\circ}</math> E., 46.4 ft. dist., mkd. 1/4 S2 BT.</p> <p>Corner is located west, 14.0 ft. dist., from the corner of woven wire fences, fences extending north, south, and east.</p> <p>From this point, the cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., bears N. <math>0^{\circ} 00' 35''</math> W., 2649.91 ft. dist.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. <math>89^{\circ} 21' 59''</math> W., bet. secs. 15 and 22, blazing and tagging.</p> <p>Descend over broken NW. slope, through second growth timber and dense undergrowth.</p>
315	Ravine, drains S. $40^{\circ}$ W., asc. over SE. slope.
615	Spur, slopes S. $35^{\circ}$ W.; desc. over SW. slope.
1318.57	Point for the E 1/16 sec. cor. of secs. 15 and 22, not monumented.
2560	Ravine, drains N. $10^{\circ}$ E., asc. over NW. slope.
2637.14	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 4 ins. above the ground, (with an iron pipe, <math>1\frac{1}{2}</math> ins. diam., firmly set, projecting 12 ins. above the ground, along the east side), with brass cap mkd.</p> <p style="text-align: center;">S 15 1/4 ——— S 22 T 23 S R 4 W 1976</p> <p>from which bearing trees mkd. by Jelley</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET													
	<p>A fir, 10 ins. diam., bears N. <math>41\frac{3}{4}^{\circ}</math> E., 16.5 ft. dist., with a healed blaze.</p> <p>A fir, 6 ins. diam., bears S. <math>74^{\circ}</math> E., 27.4 ft. dist., with a healed blaze.</p> <p>Corner is located east, 19.5 ft. dist. from a corner of woven wire fences, fences extending N. <math>5^{\circ}</math> E. and S. <math>10^{\circ}</math> W.</p> <p>Discontinue blazing and tagging.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. <math>89^{\circ} 21' 59''</math> W., beginning new measurement.</p> <p>Ascend over NW. slope, through second growth timber and dense undergrowth.</p>												
70	Spur, slopes N. $15^{\circ}$ W.; desc. over SW. slope.												
805	Power transmission line, bears N. $25^{\circ}$ E. and S. $25^{\circ}$ W.												
1005	Power transmission line, bears N. $25^{\circ}$ E. and S. $25^{\circ}$ W.												
1220	Creek, 2 ft. wide, course S. $30^{\circ}$ W.; asc. over SE. slope.												
1360	Asphalt road, 30 ft. wide, bears N. $30^{\circ}$ E. and S. $30^{\circ}$ W.												
2636.94	<p>The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 3 ins. above the ground, (with geared axle, 1 ins. diam., firmly set alongside, projecting 4 ins. above the ground), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 23</td> <td style="padding: 0 5px;">S R</td> <td style="padding: 0 5px;">4 W</td> </tr> <tr> <td style="padding: 0 5px;">S 16</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 15</td> </tr> <tr> <td style="padding: 0 5px;">S 21</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">1976</td> </tr> </table> </div> <p>from which bearing trees mkd. by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400400</p> <p>An oak, 24 ins. diam., bears N. <math>21^{\circ}</math> E., 51.5 ft. dist., with a healed double blazed.</p> <p>An oak, 22 ins. diam., bears N. <math>14^{\circ}</math> W., 50.2 ft. dist., with a healed double blaze.</p>	T 23	S R	4 W	S 16		S 15	S 21		S 22	1976		
T 23	S R	4 W											
S 16		S 15											
S 21		S 22											
1976													

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>There are no suitable trees within limits in secs. 21 and 22.</p> <p>Corner is located north, 0.5 ft. dist. from the corner of woven wire fences, fences extending east, west, and south.</p> <hr/> <p>N. 0° 05' 04" E., bet. secs. 15 and 16.</p> <p>Ascend over broken SE. slope, through second growth timber and dense undergrowth.</p>
255	Spur, slopes N. 82° E.; desc. over NE. slope.
360	Ravine, drains N. 80° E., asc. over SE. slope.
585	Abandoned dirt road, 15 ft. wide, bears N. 75° W. and S. 75° E.
1410	Spur, slopes West; desc. over NW. slope.
2555	Bottom of descent, slopes SW.; asc. over SW. slope.
2595	Dirt road, 15 ft. wide, bears N. 40° E. and S. 20° W.
2656.64	<p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate distance, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 4 W</p> <p>1/4</p> <p>S 16   S 15</p> <p>2000</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 7 ins. diam., bears N. 53¾° E., 24.2 ft. dist., mkd. 1/4 S15 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 80¾° W., 17.6 ft. dist., mkd. 1/4 S16 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S. 85¾° E., 31.3 ft. dist., from the corner of woven wire fences, fences extending north and east.</p> <p>Ascend over SW. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
2985	Spur, slopes S. 55° W.; desc. over NW. slope.
5280	Creek, 1 ft. wide, course N. 80° W.; asc. over SW. slope.
5313.28	<p>The cor. of secs. 9, 10, 15, and 16, perpetuated by O. F. Thiel, year unknown, recorded in the Douglas County Surveyor's Office, CS File No. 61/5, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400500, monumented with an iron post, 1¼ ins. diam., loosely set, (reset iron post in place), projecting 16 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 23 S S 9   S 10 ----- S 16   S 15 R 4 W 1963</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 42 ins. diam., bears N. 48½° E., 42.4 ft. dist., with axe marks visible. (Record, N. 45° E., 42.9 ft. dist.)</p> <p style="padding-left: 40px;">A maple, 44 ins. diam., bears S. 24° W., 19.1 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Godfrey</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears N. 9¾° E., 112.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 40 ins. diam., bears N. 26¼° W., 92.9 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 52° W., 44.3 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">An alder, 13 ins. diam., bears S. 49° E., 25.1 ft. dist., bark scribed T23S R4W S15 BT.</p> <p>Corner is located in an unmaintained woven wire fence, with fences extending north, south, and west.</p> <hr style="width: 60%; margin-left: 0;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>S. 89° 55' 25" W., bet. secs. 10 and 15.</p> <p>Ascend over broken SE. slope.</p>
1770	<p>Asphalt road, 30 ft. wide, bears N. 20° E. and S. 20° E.</p>
2636.36	<p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate distance, there is no remaining evidence of the original cor.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 4 W</p> <p>1/4</p> <p>S 10</p> <hr style="width: 10%; margin: 0 auto;"/> <p>S 15</p> <p>2000</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 25½° W., 34.9 ft. dist., mkd. 1/4 S15 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 52¼° W., 32.5 ft. dist., mkd. 1/4 S10 BT.</p> <p>Deposit 2 mag nails at the base of the stainless steel post.</p> <p>Corner is located east, 13.0 ft. dist., of a woven wire fence, fences extending north and south.</p> <p>From this point, a point reestablished as the ¼ sec. cor. of secs. 10 and 15, by Glen S. Baughman, Registered Professional Land Surveyor, No. 536, in 1978, recorded in the Douglas County Surveyor's Office, Map File No. 65-71, bears N. 47° 40' 14" W., 14.60 ft. dist., monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd., T23SR4W WM 1/4 S10 S15 1978 OLS 536, from which bearing trees mkd. by Baughman</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 56½° W., 20.3 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 31½° W., 23.1 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>This point was not correctly positioned and is not utilized in the course of this survey.</p> <p>From this same point, benchmark "BM 24", established by the U.S. Geological Survey, in 1917, bears S. 17° 42' 37" E., 1218.91 ft. dist., (mean bearing and sea level dist.). The geographic position of this benchmark was determined by the NAVSTAR Global Positioning System, by the Bureau of Land Management, in 2000, monumented with an iron pipe, 3½ ins. diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd. Elevation Above Sea 955 Feet Datum 1917 BM 24.</p> <p>Ascend over SE. slope.</p>
3695	Ridge, bears N. 10° W. and S. 10° E.; desc. over broken SW. slope.
5272.72	The cor. of secs. 9, 10, 15, and 16.
	<hr/> <p>N. 0° 12' 12" W., bet. secs. 9 and 10, blazing and tagging.</p> <p>Ascend over broken SW. slope, through second growth timber and dense undergrowth.</p>
905	Spur, slopes West; desc. over broken NW. slope.
1230	Creek, 1 ft. wide, course N. 60° W.; asc. over SW. slope.
2315	Graveled road, 15 ft. wide, bears N. 10° E. and S. 60° W.
2663.76	<p>The ¼ sec. cor. of secs. 9 and 10, perpetuated from original evidence no longer in existence by Arthur Boyer, Deputy County Surveyor, in 1937, further perpetuated by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400540, monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 4 ins. above the ground, from which the remains of bearing trees mkd. by Boyer</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 35 ins. diam., bears S. 69° E., 25.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed fir snag, 9 ins. diam., bears S. 61¼° W., 47.3 ft. dist., with scribe marks 1/4 S9 BT visible (snag has been displaced).</p> <p>and the remains of bearing trees mkd. by Godfrey</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 19 ins. diam., bears S. <math>59\frac{3}{4}^{\circ}</math> E., 59.5 ft. dist., with a healed blaze.</p> <p>A sawed fir stump with tin cap, 27 ins. diam., bears S. <math>66\frac{3}{4}^{\circ}</math> W., 90.7 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W 1/4 S 9   S 10 2000</p> <p>from which a new bearing tree</p> <p>A fir, 22 ins. diam., bears S. <math>42\frac{1}{4}^{\circ}</math> W., 24.2 ft. dist., mkd. 1/4 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located in an unmaintained woven wire fence, fences extending north and south.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 12' 54''</math> W., beginning a new measurement, blazing and tagging.</p> <p>Ascend over broken SW. slope, through second growth timber and dense undergrowth.</p>
830	Spur, slopes S. $70^{\circ}$ W.; desc. over NW. slope.
960	Ravine, drains S. $85^{\circ}$ W., asc. over South Slope.
1125	Spur, slopes S. $65^{\circ}$ W.; desc. over NW. slope.
1317.12	The N 1/16 sec. cor. of secs. 9 and 10, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, recorded in the Douglas County Surveyor's Office, map file No. M24-42, monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 27 ins. above the ground, and is accepted as the cor., from which the remains of a bearing tree mkd. by Haines

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir stump, 16 ins. diam., bears S. <math>5\frac{1}{2}^{\circ}</math> W., 63.2 ft. dist., no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W N 1/16 S 9   S 10 2000</p> <p>from which new bearing trees</p> <p>A fir, 11 ins. diam., bears N. <math>31^{\circ}</math> E., 18.7 ft. dist., mkd. N1/16 S10 BT.</p> <p>A fir, 12 ins. diam., bears N. <math>86\frac{3}{4}^{\circ}</math> W., 34.8 ft. dist., mkd. N1/16 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base and the "T" shaped iron rod, bent in half, alongside the stainless steel post.</p> <p>Discontinue blazing and tagging.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>0^{\circ} 20' 09''</math> W., beginning a new measurement.</p> <p>Descend over NW. slope, through second growth timber and dense undergrowth.</p>
1235	Walker Creek, 8 ft. wide, course S. $40^{\circ}$ W.; asc. over SW. slope.
1319.49	<p>The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W S 4   S 3 <hr style="width: 20%; margin: 0 auto;"/>S 9   S 10 1963</p> <p>from which bearing trees mkd. by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, recorded in the Douglas County Surveyor's Office, record of government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400600,</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 18 ins. diam., bears N. 35° E., 11.2 ft. dist., with a healed blaze.</p> <p>A maple, 14 ins. diam., bears S. 3¾° W., 17.5 ft. dist., with a healed blaze. (Record, S. 5° W., 16.5 ft. dist.)</p> <p>A fir, 21 ins. diam., bears S. 59° W., 13.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 9 ins. diam., bears S. 17° E., 16.4 ft. dist., mkd. T23S R4W S10 BT.</p> <p>From this point, a point established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, as the cor. of secs. 3, 4, 9, and 10, bears S. 74° 42' 45" E., 3.86 ft. dist., recorded in the Douglas County Surveyor's Office, map file No. M24-42, monumented with a 1 X 1 in. "T" shaped iron rod, firmly set, projecting 12 ins. above the ground. This point was not properly positioned and is not utilized during the course of this survey.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>N. 89° 43' 34" W., bet. secs. 3 and 10.</p> <p>Ascend over broken NE. slope, through second growth timber and dense undergrowth.</p>
120	Asphalt road, 35 ft. wide, bears N. 5° E. and S. 5° W.
1240	Spur, slopes N. 50° W.; desc. over NW. slope.
1313.44	<p>The E 1/16 sec. cor. of secs. 3 and 10, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, monumented with a 1 x 1 ins. "T" shaped iron rod, firmly set, projecting 7 ins. above the ground, with brass button, 1 in. diam., affixed to top, mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE, and is accepted as the cor., from which the remains of bearing trees mkd. by Haines</p> <p>A decayed fir snag, 9 ins. diam., bears S. 61° W., 7.8 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A decayed fir snag, 15 ins. diam., bears N. <math>66\frac{3}{4}^{\circ}</math> W., 20.3 ft. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 25 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">S 3 E 1/16 ----- S 10 2001</p> <p>from which new bearing trees</p> <p>A fir, 7 ins. diam., bears N. <math>9\frac{1}{4}^{\circ}</math> E., 45.8 ft. dist., mkd. E1/16 S3 BT.</p> <p>A fir, 4 ins. diam., bears S. <math>70\frac{1}{4}^{\circ}</math> W., 42.9 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. <math>89^{\circ} 46' 34''</math> W., beginning a new measurement, blazing and tagging.</p> <p>Continue descending over NW. slope.</p>
505	Walker Creek, 10 ft. wide, course N. $20^{\circ}$ W.; asc. over NE. slope.
840	Spur, slopes North; desc. over NW. slope.
1040	Walker Creek, 10 ft. wide, course S. $70^{\circ}$ W.; across level creek bottom.
1260	Walker Creek, 10 ft. wide, course N. $10^{\circ}$ E.; asc. over NE. slope.
1318.41	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, perpetuated by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, subsequently recovered and utilized by Les Roberts Registered Professional Land Surveyor, No. 1039, in 1996, recorded in the Douglas County Surveyor's Office, record of government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 440600, monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above the ground, with brass button affixed to top, 1 in. diam., mkd., SURVEY POINT WILFORD N HAINES 239 DRAIN ORE, from which the remains of an original bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed and decayed fir stump, 50 ins. diam., bears S. 44° E., 18.0 ft. dist., with a healed blaze. (Record, S. 40° E., 17.2 ft. dist.)</p> <p>and the remaining bearing tree mkd. by Haines</p> <p>A fir, 23 ins. diam., bears N. 11¼° W., 63.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W S 3 1/4 _____ S 10 2001</p> <p>from which a new bearing tree</p> <p>A hemlock, 4 ins. diam., bears S. 54¾° E., 17.6 ft. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 53' 43" W., beginning a new measurement, blazing and tagging.</p> <p>Continue ascending over NE. slope.</p>
370	Spur, slopes N. 25° W.; desc. over NW. slope.
715	Walker Creek, 10 ft. wide, course West; across nearly level creek bottom.
1245	Walker Creek, 10 ft. wide, course N. 70° W.; asc. over NE. slope.
1670	Walker Creek, 10 ft. wide, course S. 80° W.; asc. over NE. slope.
1720	Spur, slopes North; desc. over NW. slope.
1755	Walker Creek, 10 ft. wide, course N. 40° W.; asc. over NE. slope.
2065	Spur, slopes N. 10° W.; desc. over NW. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
2545	Walker Creek, 20 ft. wide, course S. 60° W.; asc. over NE. slope.
2656.08	The cor. of secs. 3, 4, 9, and 10.
	<hr/>
	N. 0° 11' 09" E., bet. secs. 3 and 4, blazing and tagging.
	Ascend over broken SE. slope, through second growth timber and dense undergrowth.
255	Spur, slopes S. 20° E.; continue asc. over SW. slope.
720	Spur, slopes S. 40° W.; desc. over Westerly slope.
1316.49	The S 1/16 sec. cor. of secs. 3 and 4, monumented with an iron post, 2½ ins. diam., loosely set, (reset in place) projecting 12 ins. above the ground, with brass cap mkd.
	S 1/16 S 4   S 3 T 23 S R 4 W 1963
	from which the remains of bearing trees mkd. by White and Beck
	A fir, 37 ins. diam., bears S. 71¼° E., 21.1 ft. dist., with a healed blaze.
	A sawed fir stump, 24 ins. diam., bears S. 28½° W., 58.1 ft. dist., with a healed blaze.
	and a new bearing tree
	A fir, 11 ins. diam., bears S. 37½° W., 36.8 ft. dist., mkd. S1/16 S4 BT.
	Discontinue blazing and tagging
	<hr/>
	N. 0° 14' 31" E., beginning a new measurement.
	Continue descending over westerly slope.
30	Creek, 1.5 ft. wide, course S. 75° W.; asc. over SE. slope.
1318.24	The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, firmly set, projecting 6 ins. above the ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	$\frac{1}{4}$ S 4   S 3 T 23 S R 4 W 1963
	from which new reference monuments
	<p>An aluminum rod, <math>\frac{3}{4}</math> in. diam., 36 ins. long, set 36 ins. in the ground for a reference monument, bears S. <math>27^{\circ} 08' 07''</math> E., 28.8 ft. dist., with aluminum cap mkd. RM T23SR4W 1/4 S3 2001 28.8 FT. TO COR and an arrow pointing to the corner.</p> <p>An aluminum rod, <math>\frac{3}{4}</math> in. diam., 36 ins. long, set 36 ins. in the ground for a reference monument, bears S. <math>62^{\circ} 37' 48''</math> E., 40.8 ft. dist., with aluminum cap mkd. RM T23SR4W 1/4 S4 2001 40.8 FT. TO COR and an arrow pointing to the corner.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N. $0^{\circ} 13' 27''$ E., beginning a new measurement.
	Continue ascending over SE. slope.
1200	Dirt road, 12 ft. wide, bears N. $30^{\circ}$ W. and S. $40^{\circ}$ E.
1320.00	The N 1/16 sec. cor. of secs. 3 and 4, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 11 ins. above the ground, with brass cap mkd.
	N 1/16 S 4   S 3 T 23 S R 4 W 1963
	from which the remaining bearing tree mkd. by White and Beck
	<p>A fir, 20 ins. diam., bears N. <math>53^{\circ}</math> E., 97.0 ft. dist., with a healed blaze. (Record, N. <math>52\frac{1}{4}^{\circ}</math> E.)</p> <p>and a new bearing tree</p> <p>A fir, 11 ins. diam., bears N. <math>81^{\circ}</math> W., 9.4 ft. dist., mkd. N1/16 S4 BT.</p> <hr style="width: 20%; margin: 10px auto;"/>
	N. $0^{\circ} 16' 58''$ E., beginning a new measurement, blazing and tagging.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	Continue ascending over SE. slope.
685	Spur, slopes N. 55° E.; desc. over NE. slope.
1095	Ravine, drains N. 55° E., asc. over E. slope.
1315.59	The cor. of secs. 3, 4, 33, and 34 on the N. bdy. of the Tp.
	<hr/>
	From the cor. of secs. 9, 10, 15, and 16.
	S. 89° 18' 17" W., bet. secs. 9 and 16, blazing and tagging.
	Descend over a West slope, through second growth timber and dense undergrowth.
135	Creek, 1 ft. wide, course N. 65° W.; asc. over NE. slope.
325	Spur, slopes N. 5° W.; desc. over NW. slope.
585	Creek, 4 ft. wide, course N. 20° W.; asc. over NE. slope.
730	Spur, slopes N. 25° W.; desc. over NW. slope.
1344.24	Point for the E 1/16 sec. cor. of secs. 9 and 16.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<pre> T 23 S R 4 W       S 9 E 1/16 -----       S 16       2000 </pre>
	from which
	A fir, 22 ins. diam., bears N. 29° E., 26.2 ft. dist., mkd. E1/16 S9 BT.
	A fir, 30 ins. diam., bears S. 40¾° E., 7.4 ft. dist., mkd. E1/16 S16 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located North, 12.0 ft. dist., of an unmaintained woven wire fence, fences extending east and west.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	Discontinue blazing and tagging.
	Descend over NW. slope.
1750	Creek, 2 ft. wide, course N. 10° W.; asc. over NE. slope.
2005	Spur, slopes N. 30° W.; desc. over NW. slope.
2688.48	The ¼ sec. cor. of secs. 9 and 16, perpetuated from original evidence no longer in existence, by Arthur Boyer, County Surveyor, in 1938, further perpetuated by Milo E. Godfrey, Deputy County Surveyor, in 1963, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 340500, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 5 ins. above the ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 23 S S 9 1/4 ————— S 16 R 4 W 1963
	from which the remains of bearing trees mkd. by Boyer
	A fir snag, 23 ins. diam., bears N. 21° E., 42.4 ft. dist., with scribe marks 1/4 S visible.
	A sawed and decayed fir stump, 36 ins. diam., bears S. 69½° E., 44.6 ft. dist., with scribe marks BT visible.
	and new bearing trees
	A fir, 6 ins. diam., bears N. 76¾° E., 24.5 ft. dist., mkd. X BT.
	A fir, 9 ins. diam., bears S. 44° E., 25.2 ft. dist., mkd. 1/4 S16 BT.
	Corner is located N. 45° E., 6.0 ft. dist. from the corner of woven wire fences, unmaintained fences extending north, south and east.
	From the ¼ sec. cor. of secs. 8 and 9, restored at a recognized fence corner by Arthur Boyer, Douglas County Surveyor, in 1938, further perpetuated by James W. Byron, Deputy County Surveyor, in 1957, subsequently recovered and utilized by Ken Hoffine

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Registered Professional Land Surveyor, No. 2291, in 1998, recorded in the Douglas County Surveyor's Office, record of government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 300540. There is no remaining evidence of the original corner, therefore this point is accepted as the cor., monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above the ground, (with a basalt stone 7½ x 4 ins., firmly set along side, projecting 4 ins. above the ground, mkd. ¼), with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 23 S 1/4 S 8   S 9 R 4 W 1958</p> <p>from which the remains of a bearing tree mkd. by Boyer</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 80¼° W., 25.6 ft. dist., no marks visible.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A sawed fir stump, 27 ins. diam., bears N. 28¾° E., 40.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears N. 39½° W., 18.5 ft. dist., with a healed double blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 71½° E., 34.9 ft. dist., mkd. 1/4 S9 BT.</p> <p>Corner is located East, 1.0 ft. dist., from the corner of woven wire fences, fences extending north and west.</p> <p>N. 0° 11' 07" W., bet. secs. 8 and 9.</p> <p>Descend over NW. slope, through second growth timber and dense undergrowth.</p>
30	Creek, 1.5 ft. wide, course N. 30° W.; continue descending over NE. slope.
1310.50	The N 1/16 sec. cor. of secs. 8 and 9, established by Ken W. Hoffine, Registered Professional Land Surveyor, No. 2291, in 1998, recorded in the Douglas County Surveyor's Office, map file No. M128-60, and is accepted as the cor., monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 7 ins. above the ground, with aluminum cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	LONE ROCK TIMBER N 1/16 S 8   S 9 1998 PLS 2291
	from which bearing trees mkd. by Hoffine  A fir, 20 ins. diam., bears N. 77¼° E., 13.0 ft. dist., with a healed blaze.  A fir, 17 ins. diam., bears N. 7¾° W., 29.6 ft. dist., with a healed blaze.  <hr style="width: 20%; margin: auto;"/> N. 0° 11' 10" W., beginning a new measurement.  Descend over NE. slope.
1310.43	The cor. of secs. 4, 5, 8, and 9, perpetuated from original evidence no longer in existence, by H. L. Eppstein, Deputy County Surveyor, in 1938, further perpetuated by James W. Byron, Deputy County Surveyor, in 1957, further perpetuated by Vernon "Ray" Tracy, Deputy County Surveyor, in 1965, subsequently recovered and utilized by Ken W. Hoffine, Registered Professional Land Surveyor, No. 2291, in 1998, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 300600, monumented with an iron post, 1½ ins. diam., firmly set, projecting 16 ins. above the ground, with brass cap mkd.,  <div style="text-align: center;">             COUNTY SURVEYORS OFFICE              T 23 S              S 5   S 4  <hr style="width: 20%; margin: auto;"/>             S 8   S 9              R 4 W              1958           </div> from which the remaining bearing trees mkd. by Eppstein  An oak, 30 ins. diam., bears S. 18¾° E., 89.5 ft. dist., with a healed blaze.  An oak, 21 ins. diam., bears S. 34¾° W., 53.6 ft. dist., with a healed blaze.  and a bearing tree mkd. by Byron

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>An oak, 27 ins. diam., bears N. 50¾° E., 38.0 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Tracy</p> <p>An oak, 15 ins. diam., bears N. 12¼° W., 68.9 ft. dist., with a healed double blaze.</p> <hr/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89° 31' 15" W., bet. secs. 4 and 9.</p> <p>Descend a broken SW. slope, through second growth timber and dense undergrowth.</p>
140	Walker Creek, 10 ft. wide, course N. 35° W.; asc. over NE. slope.
1341.52	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 23 S R 4 W</p> <p>S 4</p> <p>E 1/16 ———</p> <p>S 9</p> <p>2000</p> </div> <p>from which</p> <p>A fir, 7 ins. diam., bears S. 69¼° E., 86.5 ft. dist., mkd. X BT.</p> <p>A fir, 10 ins. diam., bears S. 9¼° W., 78.8 ft. dist., mkd. E1/16 S9 BT.</p> <p>From this point, a point unofficially established as the E 1/16 sec. cor. of secs. 4 and 9, during the course of an administrative survey, by the Bureau of Land Management, in 1979, bears S. 23° 40' 30" W., 17.70 ft. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above the ground. This point is not utilized in the course of this survey, the iron pipe was removed and buried inside the stainless steel post.</p> <p>Ascend over NE. slope, begin blazing and tagging.</p>
1675	Elk Creek, 15 ft. wide, course N. 20° W.; asc. over NE. slope.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
2683.04	<p>The ¼ sec. cor. of secs. 4 and 9, perpetuated by Arthur Boyer, County Surveyor, in 1938, further perpetuated by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, recovered by Larry Monrean of the Douglas County Surveyor's Office, in 1984 and 1997, subsequently recovered by Les Roberts, Registered Professional Land Surveyor, No. 1039, in 1996, recorded in the Douglas County Surveyor's Office, record of government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 340600, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 5 ins. above the ground, (with a 1 x 1 in. "T" shaped iron rod, firmly set inside, projecting 1 in. above the iron pipe, with a brass disc 1 in. diam., affixed to top of "T" shaped rod, mkd., WILFORD N HAINES 239 SURVEY POINT DRAIN ORE), from which the remains of bearing trees mkd. by Boyer</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 62¼° W., 13.0 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed fir stump, 21 ins. diam., bears N. 1¾° W., 19.4 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the iron pipe and the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 23 S R 4 W</p> <p>S 4</p> <p>1/4 —————</p> <p>S 9</p> <p>2000</p> </div> <p>from which a new reference monument</p> <p style="padding-left: 40px;">A stainless steel post, 28 ins. long, 2½ ins. diam., set 25 ins. in the ground for a reference monument, bears N. 34° 04' 02" W., 85.35 ft. dist., with brass cap mkd. RM T23S R4W 1/4 S4 85.35 FT TO COR 2000 and an arrow pointing to the corner.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a point unofficially established as the ¼ sec. cor. of secs. 4 and 9, during the course of an administrative survey by the Bureau of Land Management, in 1979, bears S. 29° 15' 16" E., 36.81 ft. dist., monumented with an iron pipe, ½ in. diam., firmly set, projecting 6 ins. above the ground. This point</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>was not utilized during the course of this survey. From which the remains of bearing trees mkd. during the administrative survey</p> <p style="padding-left: 40px;">A sawed fir stump, 12 ins. diam., bears S. 20° W., 29.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A sawed cedar stump, 34 ins. diam., bears N. 19° W., 21.6 ft. dist., no marks visible.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 07' 01" W., beginning a new measurement, blazing and tagging.</p> <p>Ascend over NE. slope.</p>
505	Spur, slopes N. 10° W.; desc. over NW. slope.
590	Ravine, drains N. 30° W., asc. over NE. slope.
1095	Ridge, bears N. 5° W. and S. 5° E.; desc. over NW. slope.
1110	Dirt road, 13 ft. wide, bears N. 40° W. and S. 12° E.
1324.94	<p>The W 1/16 sec. cor. of secs. 4 and 9, established by Ken W. Hoffine, Registered Professional Land Surveyor, No. 2291, recorded in the Douglas County Surveyor's Office, Map File No. M128-60, and is accepted as the cor., monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, with aluminum cap mkd.</p> <p style="text-align: center;">LONE ROCK TIMBER</p> <p>See <span style="padding-left: 100px;">S 4</span></p> <p style="padding-left: 100px;">W 1/16 ———</p> <p>CS 65/72-26 <span style="padding-left: 100px;">S 9</span></p> <p>NEW BTs <span style="padding-left: 100px;">1998</span></p> <p style="padding-left: 100px;">PLS 2291</p> <p>from which a bearing tree mkd. by Hoffine</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 18° E., 37.4 ft. dist., with scribe marks W 1/16 S9 BT visible on open blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 63¾° W., 22.0 ft. dist., mkd. W1/16 S4 BT.</p> <p>From this point, a point unofficially established as the W 1/16 sec. cor. of secs 4 and 9, during the course of an administrative survey by the Bureau of Land Management, in 1979, bears S. 76° 40' 12" E., 21.90 ft. dist., monumented with an iron pipe, ½ in.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	diam., firmly set, projecting 4 ins. above the ground. This point was not utilized during the course of this survey.
	<hr/> S. 89° 06' 11" W., beginning a new measurement.
	Descend over broken NE. slope.
920	Graveled road, 20 ft. wide, bears N. 35° E. and S. 35° W.
1070	Asphalt road, 25 ft. wide, bears N. 25° W. and S. 10° E.
1324.69	The cor. of secs. 4, 5, 8, and 9.
<hr/> <b>Subdivision of Section 3, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b> <hr/>	
	From the ¼ sec. cor. of secs. 3 and 10.
	N. 0° 12' 00" W., on the N. and S. centerline of sec. 3.
	Descend over NE. slope.
170	Walker Creek, 10 ft. wide, course S. 70° W.; asc. over SE. slope.
1317.46	The center S 1/16 sec. cor. of sec. 3, established by Les D. Roberts, Registered Professional Land Surveyor, No. 1039, in 1996, recorded in the Douglas County Surveyor's Office, map file No. M125-29, and is accepted as the cor., monumented with an iron rod, 5/8 ins. diam., firmly set, in the root crown of the SW. bearing tree, with yellow plastic cap, 1½ ins. diam., mkd., Roberts PLS 1039, from which bearing trees mkd. by Roberts
	A fir, 15 ins. diam., bears S. 0½° E., 1.3 ft. dist., with partially healed double blaze.
	A fir, 14 ins. diam., bears S. 77½° W., 19.9 ft. dist., with partially healed double blaze.
	At the corner point
	Drive an aluminum cap, 3½ ins. diam., onto the iron rod, mkd.
	<div style="text-align: center;">             C              S 1/16   S 3              C              2001           </div>

**Subdivision of Section 3,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located S. 18½° W., 88.9 ft. dist., from the corner of woven wire fences, fences extending north, south, and west, and N. 51½° W., 32.8 ft. dist., from a second corner of woven wire fences, fences extending north and east.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 13' 07" W., beginning a new measurement.</p> <p>Continue ascending SE. slope.</p>
105	Spur, slopes S. 70° E.; desc. over NE. slope.
360	Ravine, drains S. 85° E., asc. over SE. slope.
940	Spur, slopes S. 50° W.; desc. over NW. slope.
1311.34	<p>Point for the center ¼ sec. cor. of sec. 3, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W C 1/4 S 3 2001</p> <p>from which a reference monument and a bearing tree</p> <p style="padding-left: 40px;">An aluminum rod, 1 in. diam., 36 ins. long, set 36 ins. in the ground for a reference monument, bears N. 43° 49' 27" E., 57.4 ft. dist., with aluminum cap mkd. RM T23SR4W C1/4 S3 2001 57.4 FT. TO COR and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 28¼° E., 97.4 ft. dist., mkd. C1/4 S3 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S. 61¼° W., 47.6 ft. dist. from the corner of woven wire fences, fences extending north, south, and east.</p> <p>Continue descending NW. slope.</p>
2615	Graveled road, 12 ft. wide, bears N. 70° E. and S. 80° W.
2646.27	The center N 1/16 sec. cor. of sec. 3, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No.

**Subdivision of Section 3,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>M22-6, recovered and utilized by Les D. Roberts, Registered Professional Land Surveyor, No. 1039, in 1996, recorded in the Douglas County Surveyor's Office, Map file No. M125-29, and is accepted as the cor., monumented with a 1 x 1 ins. "T" shaped iron rod, firmly set, projecting 6 ins. above the ground, from which the remains of a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A sawed oak stump, 20 ins. diam., bears N. 47¼° E., 9.8 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16   S 3 C 2001</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 21½° W., 43.3 ft. dist., mkd. CN1/16 S3 BT.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 79¼° W., 111.9 ft. dist., mkd. CN1/16 S3 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located S. 6¼° E., 29.8 ft. dist., from the corner of woven wire fences, fences extending south, east, and west, and S. 33° E., 31.3 ft. dist., from a second corner of woven wire fences, fences extending north and west.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' 34" E., beginning a new measurement, blazing and tagging.</p> <p>Continue descending over NW. slope.</p>
15	Graveled road, 16 ft. wide, bears N. 75° E. and S. 75° W.
668.91	The corner of woven wire fences, fences extending south and east, bears, East, 3.61 ft. dist.

**Subdivision of Section 3,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
669.68	From this point, an iron pipe, $\frac{1}{2}$ ins. diam., firmly set, flush with the ground, set by person(s) unknown, and not utilized in the course of this survey. bears East, 20.71 ft. dist.
1331.77	The $\frac{1}{4}$ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<hr/> From the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.  N. $89^{\circ} 58' 36''$ W., on the E. and W. centerline of sec. 3.  Descend over a SW. slope.
30	Graveled road, 30 ft. wide, bears North and South.
235	Creek, 3 ft. wide, course S. $30^{\circ}$ W.; asc. over SE. slope.
1294.22	From this point, the corner of woven wire fences, fences extending south, N. $10^{\circ}$ E. and east bears North, 14.2 ft. dist.
1320.13	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 3, no monument set.
1986.00	From this point, the corner of woven wire fences, fences extending east, south and N. $87\frac{3}{4}^{\circ}$ W., bears North, 17.3 ft. dist.
	Ascend over SE. slope.
2575.95	A woven wire fence, extending north and south.
2640.24	The center $\frac{1}{4}$ sec. cor. of sec. 3.
	Descend over Westerly slope.
5276.58	The $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	<hr/> From the E $\frac{1}{16}$ sec. cor. of secs. 3 and 10.  N. $0^{\circ} 10' 04''$ W., on the calculated N. and S. centerline of the SE $\frac{1}{4}$ of sec. 3, blazing and tagging.  Descend over NE. slope.
460	Walker Creek, 6 ft. wide, course S. $80^{\circ}$ W.; asc. over Westerly slope.
1317.95	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 3, at its calculated position.

**Subdivision of Section 3,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 3 2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 23 ins. diam., bears S. 31½° W., 13.5 ft. dist., mkd. SE1/6 S3 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 19¼° W., 30.7 ft. dist., mkd. SE1/16 S3 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located, N. 1° 42' 37" E., 29.45 ft. dist., from the corner of woven wire fences, fences extending north, south, and west.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89° 47' 51" W., on the calculated E. and W. centerline of the SE¼ of sec. 3, blazing and tagging.</p> <p>Descend over westerly slope.</p>
215	Creek, 2 ft. wide, course S. 5° W.; asc. over SE. slope.
522.83	A woven wire fence, extending east and west, thence South, 29.30 ft. dist., to a corner of woven wire fences, fences extending north, east, and west.
1319.07	The center S 1/16 sec. cor. of sec. 3.
	<hr/> <p>S. 89° 52' 26" W., on the E. and W. centerline of the SW¼ of sec. 3, blazing and tagging.</p> <p>Ascend over NE. slope.</p>
485	Top of ascent, slopes N. 10° W.; desc. over NW. slope.
2647.06	The S 1/16 sec. cor. of secs. 3 and 4.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 3.</p>

**Subdivision of Section 3,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	S. 89° 41' 51" W., on the E. and W. centerline of the NW¼ of sec. 3, blazing and tagging.
	Descend over NW. slope.
1400	Creek, 4 ft. wide, course N. 20° W.; asc. over NE. slope.
2625.95	The N 1/16 sec. cor. of secs. 3 and 4.
<hr/> <p><b>Subdivision of Section 9, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/>	
	From the ¼ sec. cor. of secs. 9 and 16.
	N. 0° 08' 18" W., on the N. and S. centerline of sec. 9.
	Descend over gentle N. slope.
1380	Elk Creek, 34 ft. wide, course N. 80° E.; asc. over S. slope.
2120	Graveled road, 10 ft. wide, bears East and S. 75° W.
2697.06	The center ¼ sec. cor. of sec. 9, established by Arthur Boyer, County Surveyor, in 1938, perpetuated by Rod B. Kimberling, of the Douglas County Surveyor's Office, in 1978, subsequently recovered and utilized by Ken Hoffine Registered Professional Land Surveyor, No. 2991, in 1998, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 340540, and is accepted as the cor., monumented with an iron post, 1¼ ins. diam., firmly set, projecting 4 ins. above the ground, in a mound of stone, 2½ ft. diam., to top, with brass cap mkd.
	DOUGLAS COUNTY SURVEYOR T 23 S R 4 W C 1/4 S 9 1978
	from which the remains of bearing trees mkd. by Boyer
	A cedar, 25 ins. diam., bears S. 84° E., 23.0 ft. dist., with a healed blaze.
	A decayed cedar stump, size indeterminate, bears S. 35° W., 14.3 ft. dist., with no marks visible.

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	and a bearing tree mkd. by Kimberling
	A fir, 13 ins. diam., bears N. 4¼° E., 10.0 ft. dist., with a healed double blaze.
	Corner is located south, 1.0 ft. dist., from the corner of woven wire fences, fences extending north and west.
	_____
	N. 0° 14' 09" W., beginning a new measurement, blazing and tagging.
	Ascend over moderate South slope.
350	Ridge, bears N. 70° W. and S. 70° E.; desc. over NE. slope.
1329.18	Point for the center N 1/16 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 23 S R 4 W C N 1/16   S 9 C 2000
	from which
	A fir, 9 ins. diam., bears S. 46¼° E., 41.4 ft. dist., mkd. CN1/16 S9 BT.
	A fir, 8 ins. diam., bears S. 36½° W., 37.9 ft. dist., mkd. CN1/16 S9 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Discontinue blazing and tagging.
	Descend over NE slope.
1375	Graveled road, 15 ft. wide, bears N. 80° W. and S. 80° E.
2658.36	The ¼ sec. cor. of secs. 4 and 9.
	_____
	From the ¼ sec. cor. of secs. 9 and 10.

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 89° 59' 08" W., on the E. and W. centerline of sec. 9.
	Descend over broken SW. slope, through second growth timber and dense undergrowth.
240	Graveled road, 12 ft. wide, bears N. 55° W. and S. 45° E.
1342.50	Point for the center E 1/16 sec. cor. of sec. 9.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	E 1/16 C ——— C S 9 2000
	from which
	A fir, 9 ins. diam., bears N. 73° E., 12.6 ft. dist., mkd. X BT.
	A fir, 9 ins. diam., bears S. 13¾° E., 13.9 ft. dist., mkd. CE1/16 S9 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this point, a point unofficially established as the center E 1/16 sec. cor. of sec. 9 during an administrative survey by the Bureau of Land Management, in 1979, bears N. 24° 04' 38" W., 0.15 ft. dist., monumented with an iron pipe, ½ ins. diam., firmly set, projecting 6 ins. above the ground. This point was not utilized during the course of this survey. Remove and deposit iron pipe inside stainless steel post.
	Begin blazing and tagging.
	Descend over SW. slope, blazing and tagging.
1590	Elk Creek, 25 ft. wide, course N. 35° E.; asc. over SE. slope.
1790	Graveled road, 12 ft. wide, bears N. 45° E. and S. 50° W.
2515	Spur, slopes South; desc. over SW. slope.
2685.00	The center ¼ sec. cor. of sec. 9.

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Discontinue blazing and tagging.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 55' 16" W., beginning a new measurement.</p> <p>Descend over broken SW. slope, through second growth timber and dense undergrowth.</p>
1326.04	<p>Point for the center W 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>W 1/16 C ——— C S 9 2000</p> </div> <p>from which</p> <p style="margin-left: 40px;">A cedar, 19 ins. diam., bears N. 36½° E., 10.4 ft. dist., mkd. CW1/16 S9 BT.</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears N. 76° W., 7.7 ft. dist., mkd. X BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located North, 2.5 ft. dist. of an unmaintained woven wire fence, fences extending east and west.</p> <p>Descend over SW. slope.</p>
2170	Asphalt road, 25 ft. wide, bears N. 20° W. and S. 35° E.
2650	Creek, 1½ ft. wide, course North; asc. over East Slope.
2652.08	<p>The ¼ sec. cor. of secs. 8 and 9.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89° 42' 15" W., on the E. and W. centerline of the NE¼ of sec. 9, blazing and tagging.</p> <p>Ascend over NE. slope, through second growth timber and dense undergrowth.</p>

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
125	Spur, slopes N. 30° W.; desc. over SW. slope.
1030	Dirt road, 15 ft. wide, bears N. 30° W. and S. 5° E.
1341.24	<p>The NE 1/16 sec. cor. of sec. 9, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1962, recorded in the Douglas County Surveyor's Office, map file No. M24-42, and is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 12 ins. above the ground, from which the remains of a bearing tree mkd. by Haines</p> <p style="padding-left: 40px;">A sawed cedar stump, 20 ins. diam., bears N. 17¾° E., 11.3 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 9 2000</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 54¾° E., 14.2 ft. dist., mkd. NE1/16 S9 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 25¼° E., 15.4 ft. dist., mkd. NE1/16 S9 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 20' 55" W., on the N. and S. centerline of the NE¼ of sec. 9, blazing and tagging.</p> <p>Ascend over broken SW. slope.</p>
400	Spur, slopes S. 55° W.; desc. over NW. slope.
1323.80	<p>The E 1/16 sec. cor. of secs. 4 and 9.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 9 and 16.</p>

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 10' 15" W., on the N. and S. centerline of the SE¼ of sec. 9, blazing and tagging.
	Descend over gentle NW. slope, through second growth timber and dense undergrowth.
2425	Creek, 1 ft. wide, course S. 55° W.; asc. over gentle SW. slope.
2680.48	The center E 1/16 sec. cor. of sec. 9.
<hr/>	
	From the center N 1/16 sec. cor. of sec. 9.
	S. 89° 30' 57" W., on the E. and W. centerline of the NW¼ of sec. 9, blazing and tagging.
	Ascend over gradual NE. slope.
300	Graveled road, 10 ft. wide, bears East and West.
635	Ridge, bears N. 10° W. and S. 10° E.; desc. over West Slope.
1325.74	The NW 1/16 sec. cor. of sec. 9, established by Ken W. Hoffine, Registered Professional Land Surveyor, No. 2291, in 1998, recorded in the Douglas County Surveyor's Office, map file No. M128-60, and is accepted as the cor., monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 6 ins. above the ground, with aluminum cap mkd.
	LONE ROCK TIMBER NW 1/16 S 9 1998 PLS 2291
	from which bearing trees mkd. by Hoffine
	A fir, 28 ins. diam., bears N. 61½° E., 18.4 ft. dist., with scribe marks NW1/16 S9 visible on partially healed blaze.
	A fir, 18 ins. diam., bears S. 39¾° E., 15.4 ft. dist., with scribe marks NW1/16 S9 BT visible on partially healed blaze.
	<hr/>
	N. 0° 12' 08" W., on the N. and S. centerline of the NW¼ of sec. 9, blazing and tagging.
	Ascend over gradual West slope.

**Subdivision of Section 9,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1319.98	<p>The W 1/16 sec. cor. of secs. 4 and 9.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 11, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the ¼ sec. cor. of secs. 11 and 14.</p> <p>N. 0° 02' 57" E., on the N. and S. centerline of sec. 11.</p> <p>Ascend over SW. slope.</p>
740	<p>Spur, slopes N. 50° W.; desc. over NW. slope.</p>
1313.30	<p>The center S 1/16 sec. cor. of sec. 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, and is accepted as the cor., monumented with a 1 x 1 ins. "T" shaped iron rod, firmly set, with brass button, 1 in. diam., affixed to the top, mkd., SURVEY POINT WILFORD N HAINES 239 DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed cedar stump, 27 ins. diam., bears N. 53° E., 6.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A decayed fir stump, 12 ins. diam., bears N. 20¼° W., 28.3 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>S 1/16</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;"> </p> <p>S 11</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;">2001</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 17¾° E., 37.8 ft. dist., mkd. CS 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 84¼° W., 25.8 ft. dist., mkd. CS 1/16 S11 BT.</p>

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located West, 0.4 ft. dist., from the corner of woven wire fences, fences extending north and east, and N. 49½° E., 3.5 ft. dist., of a mound of stone, 3½ x 1½ ft., reported by Haines.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' 09" E., beginning a new measurement, blazing and tagging.</p> <p>Descend over NW. slope.</p>
190	Walker Creek, 8 ft. wide, course N. 60° W.; asc. over SW. slope.
630	Spur, slopes N. 85° W.; desc. over NW. slope.
1311.34	<p>The center ¼ sec. cor. of sec. 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, and is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above the ground, with brass button, 1 ins. diam., affixed to top, mkd. SURVEY POINT WILFORD N HAINES 239 DRAIN ORE, from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears N. 30° E., 16.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 21 ins. diam., bears N. 22¼° W., 7.3 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W C 1/4 S 11 2001</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. 55½° W., 5.8 ft. dist., mkd. C1/4 S11 BT.</p>

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located in a woven wire fence, extending north and south.
	_____
	N. 0° 13' 09" E., beginning new measurement, blazing and tagging.
	Descend over NW. slope.
330	Creek, 4 ft. wide, course N. 60° W.; asc. over SW. slope.
425	Graveled road, 10 ft. wide, bears N. 70° W. and S. 70° E.
1095	Spur, slopes West; desc. over NW. slope.
1324.94	The center N 1/16 sec. cor. of sec. 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office, map file No. M22-6, and is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 5 ins. above the ground, with brass button, 1 in. diam., affixed to top, mkd., SURVEY POINT WILFORD N HAINES 239 DRAIN ORE, from which the remains of bearing trees mkd. by Haines
	A sawed and decayed fir stump, 22 ins. diam., bears S. 21° E., 48.8 ft. dist., with fragmentary scribe marks 11 visible on decayed blaze.
	A cedar, 30 ins. diam., bears S. 52½° W., 60.9 ft. dist., with a healed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.
	C N 1/16   S 11 C 2001
	from which a new bearing tree
	A fir, 19 ins. diam., bears N. 10½° W., 17.5 ft. dist., mkd. CN 1/16 S11 BT.

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located north, 0.7 ft. dist., from the corner of woven wire fences, fences extending south and east.
	_____
	N. 0° 13' 07" E., beginning a new measurement.
	Descend over NW. slope.
170	Creek, 3 ft. wide, course S. 65° W.; asc. over SW. slope.
1085	Spur, slopes S. 45° W.; desc. over NW. slope.
1319.38	The ¼ sec. cor. of secs. 2 and 11.
	_____
	From the ¼ sec. cor. of secs. 11 and 12.
	N. 89° 36' 20" W., on the E. and W. centerline of sec. 11.
	Descend over SW. slope.
420	Graveled road, 12 ft. wide, bears N. 80° E. and S. 70° W.
1341.03	Point for the center E 1/16 sec. cor. of sec. 11, not monumented.
	Descend over SW. slope.
2682.06	The center ¼ sec. cor. of sec. 11.
	_____
	N. 89° 41' 16" W., beginning a new measurement.
2634.54	The ¼ sec. cor. of secs. 10 and 11.
	_____
	From the center N 1/16 sec. cor. of sec. 11.
	S. 89° 35' 05" E., on the E. and W. centerline of the NE¼ of sec. 11, blazing and tagging.
	Ascend over SW. slope.
375	Spur, slopes S. 20° W.; desc. over SE. slope.
840	Ravine, drains S. 10° E., asc. over SW. slope.

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
1140	Spur, slopes S. 35° W.; desc. over SE. slope.
1332.07	<p>The NE 1/16 sec. cor. of sec. 11, established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1961, recorded in the Douglas County Surveyor's Office map file No. M22-6, and is accepted as the cor., monumented with a 1 x 1 in. "T" shaped iron rod, firmly set, projecting 6 ins. above the ground, with brass button, 1 in. diam., affixed to top, mkd., SURVEY POINT WILFORD N HAINES 239 DRAIN ORE., from which the remains of bearing trees mkd. by Haines</p> <p style="padding-left: 40px;">A sawed fir stump, 37 ins. diam., bears S. 6° E., 11.7 t. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed and decayed cedar stump, 11 ins. diam., bears S. 37¼° W., 9.3 ft. dist., with no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, directly over the "T" shaped iron rod, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 11 2001</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 45½° E., 24.8 ft. dist., mkd. NE 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 55½° E., 11.0 ft. dist., mkd. NE 1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located East, 0.6 ft. dist., from corner of unmaintained woven wire fences, fences extending west and north.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 18' 18" W., on the N. and S. centerline of the NE¼ of sec. 11, blazing and tagging.</p> <p>Ascend over SE. slope.</p>
695	Spur, slopes S. 50° W.; desc. over NW. slope.

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
895	Ravine, drains S. 85° W., asc. over SW. slope.
1322.87	The E 1/16 sec. cor. of secs. 2 and 11.
	<hr/> <p>From the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0° 24' 24" E., on the calculated N. and S. centerline of the SE¼ of sec. 11, blazing and tagging.</p> <p>Ascend over SW. slope.</p>
820	Spur, slopes N. 60° W.; desc. over NW. slope.
950	Ravine, drains N. 55° W., asc. over SW. slope.
1311.25	<p>Point for the SE 1/16 sec. cor. of sec. 11, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 11 2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 11¼° E., 17.0 ft. dist., mkd. SE 1/16 S11 BT.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 61¼° W., 43.1 ft. dist., mkd. SE 1/16 S11 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located south, 0.5 ft. dist., from a corner of unmaintained woven wire fences, fences extending west and south.</p> <p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 3 ins. above the ground, set by person(s) unknown, bears West, 0.70 ft. dist. This point is not utilized during the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 40' 21" W., on the calculated E. and W. centerline of the SE¼ of sec. 11, blazing and tagging.</p> <p>Descend over SW. slope.</p>

**Subdivision of Section 11,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
705	Ravine, drains N. 60° W., asc. over NE. slope.
870	Spur, slopes N. 30° W.; desc. over SW. slope.
1333.03	The center S 1/16 sec. cor. of sec. 11.
<hr/> <p><b>Subdivision of Section 15, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b></p> <hr/>	
	From the ¼ sec. cor. of secs. 15 and 22.
	N. 0° 05' 13" E., on the N. and S. centerline of sec. 15, blazing and tagging.
	Descend over NW. slope, through second growth timber and dense undergrowth.
190	Ravine, drains N. 85° W., asc. over SW. slope.
285	Graveled road, 15 ft. wide, bears N. 85° W. and East.
625	Spur, slopes West; desc. over NW. slope.
1322.26	Point for the center S 1/16 sec. cor. of sec. 15.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T23S R4W C S 1/16   S 15 C 2000
	from which
	A fir, 9 ins. diam., bears N. 24¼° E., 9.8 ft. dist., mkd. CS1/16 S15 BT.
	A fir, 8 ins. diam., bears S. 62° E., 7.0 ft. dist., mkd. X BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located west 26.6 ft. dist. from the corner of woven wire fences, fences extending N. 10° W. and S. 19° W.

**Subdivision of Section 15,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>From this point, a point unofficially established as the center S 1/16 sec. cor. of sec. 15, during an administrative survey by the Bureau of Land Management, in 1977, bears S. 25° 09' 51" W., 0.65 ft. dist., monumented with a steel fence post, inverted, firmly set, projecting 42 ins. above the ground. This point was not utilized during the course of this survey, from which bearing trees mkd. during the administrative survey.</p> <p style="padding-left: 40px;">An oak, 16 ins. diam., bears S. 49¼° E., 31.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears S. 77¼° W., 14.8 ft. dist., with a healed blaze.</p> <p>Discontinue blazing and tagging.</p> <p>Descend over NW. slope.</p>
1660	Power transmission line, bears, N. 30° E. and S. 30° W.
2145	Power transmission line, bears, N. 35° E. and S. 35° W.
2644.52	<p>Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W C 1/4 S 15 2000</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 70½° E., 45.7 ft. dist., mkd. C1/4 S15 BT.</p> <p style="padding-left: 40px;">A fir, 27 ins. diam., bears S. 18½° W., 162.7 ft. dist., mkd. C1/4 S15 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located East, 40.0 ft. dist., from a woven wire fence, fences extending N. 35° E. and S. 35° W.</p>
2660	Bottom of descent, slopes SW.; asc. over SE. slope.
3520	Asphalt road, 30 ft. wide, bears N. 35° E. and S. 30° W.

**Subdivision of Section 15,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
5287.69	The $\frac{1}{4}$ sec. cor. of secs. 10 and 15.
	<hr/>
	From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	S. $89^{\circ} 37' 44''$ W., on the E. and W. centerline of sec. 15.
	Ascend over NE. slope, through a clear-cut.
100	Spur, slopes N. $25^{\circ}$ W.; desc. over NW. slope, desc. over NW. slope.
1318.46	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 15, not monumented.
2055	Power transmission line, bears, N. $30^{\circ}$ E. and S. $30^{\circ}$ W.
2170	Power transmission line, bears, N. $30^{\circ}$ E. and S. $30^{\circ}$ W.
2636.92	The center $\frac{1}{4}$ sec. cor. of sec. 15.
	Descend over NW. slope.
2675	Bottom of descent, slopes SW.; asc. over SE. slope.
3600	Asphalt road, 30 ft. wide, bears N. $20^{\circ}$ E. and S. $20^{\circ}$ W.
4865	Spur, slopes S. $20^{\circ}$ W.; desc. over SW. slope.
5250	Dirt road, 15 ft. wide, bears N. $35^{\circ}$ E. and S. $20^{\circ}$ W.
5273.61	The $\frac{1}{4}$ sec. cor. of secs. 15 and 16.
	<hr/>
	From the S $\frac{1}{16}$ sec. cor. of secs. 14 and 15.
	S. $89^{\circ} 29' 38''$ W., on the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 15, blazing and tagging.
	Descend over SW. slope, along the N. edge of a fresh clear-cut.
355	Creek, 2 ft. wide, course N. $15^{\circ}$ E.; asc. over broken N. slope.
1318.57	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 15, at its calculated position.
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

**Subdivision of Section 15,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	SE 1/16 S 15 2000
	from which
	A fir, 16 ins. diam., bears S. 65¼° E., 15.0 ft. dist., mkd. SE1/16 S15 BT.
	A fir, 13 ins. diam., bears S. 7¾° W., 20.8 ft. dist., mkd. SE1/16 S15 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	Corner is located N. 12° W. 22 ft. dist., from the corner of woven wire fences, fences extending north and westerly.
	From this point, a point unofficially established as the SE 1/16 sec. cor. of sec. 15, during an administrative survey by the Bureau of Land Management, in 1977, bears N. 13° 15' 13" W., 0.80 ft. dist., monumented with a steel fence post, inverted, firmly set, projecting 40 ins. above the ground. This point was not utilized during the course of this survey.
	Ascend over broken NE. slope.
2210	Spur, slopes N. 10° W.; desc. over NW. slope.
2637.12	The center S 1/16 sec. cor. of sec. 15.
<hr/> <b>Subdivision of Section 33, T. 23 S., R. 4 W., Willamette Meridian, Oregon</b> <hr/>	
	From the ¼ sec. cor. of sec. 33 only, on the S. bdy. of the township, monumented with a brass tablet, firmly set, flush with rock ledge, mkd.
	T 23 S R 4 W 1/4 S 33 ----- T 24 S R 4 W 1976
	from which the remaining bearing tree mkd. by Jelley,
	A fir, 28 ins. diam., bears N. 11¾° W., 50.6 ft. dist., with a healed blaze. (Record, N. 5½° W., 49.5 ft. dist.)

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>There are no suitable trees within limits to NE.</p> <p>N. 0° 25' 58" W., on the N. and S. centerline of sec. 33.</p> <p>Descend over broken NE. slope, through second growth timber and dense undergrowth.</p>
1300	Graveled road, 20 ft. wide, bears N. 60° W. and S. 75° E.
1320.75	<p>Point for the center S 1/16 sec. cor. of sec. 33.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 23 S R 4 W</p> <p>C</p> <p>S 1/16   S 33</p> <p>C</p> <p>2000</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 38° W., 7.0 ft. dist., mkd. CS1/16 S33 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 2½° W., 66.1 ft. dist., mkd. CS1/16 S33 BT.</p> <p>From this point, a point unofficially established as the center S 1/16 sec. cor. of sec. 33, during an administrative survey by the Bureau of Land Management, in 1977, bears S. 19° 55' 45" W., 1.28 ft. dist., monumented with a steel fence post, inverted, projecting 42 ins. above the ground. This point was not utilized during the course of this survey.</p> <p>Descend over NE. slope,</p> <p>Begin blazing and tagging.</p>
2641.50	The center ¼ sec. cor. of sec. 33, established by Daniel W. Baker, Registered Professional Land Surveyor, No. 1978, in 1994, recorded in the Douglas County Surveyor's Office, map file No. M119-38, and is accepted as the cor., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above the ground and a brass cap, 2½ ins. diam., cemented to top of iron pipe, with brass cap mkd.

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 23 S R 4 W C 1/4 S 33 PLS 1978 1994
	from which the remains of bearing trees mkd. by Baker
	A fir, 19 ins. diam., bears N. 89° E., 7.6 ft. dist., with a healed double blaze.
	A fir, 26 ins. diam., bears S. 17½° E., 31.0 ft. dist., with a healed double blaze.
	A fir, 18 ins. diam., bears S. 79¾° W., 13.6 ft. dist., with a healed double blaze.
	A sawed fir stump, 19 ins. diam., bears N. 19¼° W., 21.1 ft. dist., with a healed double blaze.
	From this point, a point unofficially established as the center ¼ sec. cor. of sec. 33, during an administrative survey by the Bureau of Land Management, in 1977, bears S. 29° 20' 25" W., 1.24 ft. dist., monumented with fence post, inverted, projecting 40 ins. above the ground, from which the remains of a bearing tree reported during the administrative survey.
	A fir snag, 7 ins. diam., bears S. 62° W., 8.5 ft. dist., with no marks visible on open blaze.
	This point was not utilized during the course of this survey,
	Discontinue blazing and tagging.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 0° 28' 07" W., beginning a new measurement.
	Descend over NE. slope.
2640.93	The ¼ sec. cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above the ground, (with a 1 x 1 in. "T" shaped iron rod firmly set flush along side), with brass cap mkd.
	S 28 1/4 ————— S 33 T 23 S R 4 W 1976

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

from which the remains of an original bearing tree

A fir snag, 58 ins. diam., bears N. 15° E., 33.0 ft. dist.,  
with a healed blaze.

and a bearing tree mkd. by Frank O. Williams and Glen McChesney,  
for Weyerhaeuser Co., in 1976, recorded in the Douglas County  
Surveyor's Office, records of Government corners renewed,  
T. 23 S., R. 4 W., Point Identifier No. 340200

A madrone, 12 ins. diam., bears West, 21.4 ft. dist., with no  
marks visible. (Record, S. 88° W., 21.1 ft. dist.)

and bearing trees mkd. by Daniel W. Baker, Registered Professional  
Land Surveyor, No. 1978, in 1994, recorded in the Douglas County  
Surveyor's Office, map file No. M119-38

A fir, 9 ins. diam., bears S. 40½° W., 9.9 ft. dist., with a  
healed double blaze.

A fir, 7 ins. diam., bears N. 74½° W., 19.8 ft. dist., with  
a healed double blaze.

A fir, 11 ins. diam., bears N. 9¾° W., 40.3 ft. dist., with  
a healed double blaze.

Corner is located East, 0.4 ft. dist., from the corner of woven  
wire fences, fences extending north, south, and west.

From this point, Benchmark No. 24, bears N. 21° 02' 08" E.,  
15750.24 ft. dist., (mean bearing and sea level dist.),  
hereinbefore described.

---

From the ¼ sec. cor. of secs. 33 and 34, monumented with an iron  
post, 1¼ ins. diam., firmly set, flush with the ground, with brass  
cap mkd.

COUNTY SURVEYORS OFFICE

T 23 S  
S | S  
1/4 33 34  
R 4 W  
1965

from which bearing trees mkd. by Wilford N. Haines, Registered  
Professional Land Surveyor, No. 239, in 1960, recorded in the  
Douglas County Surveyor's Office, record of government corners  
renewed, T. 23 S., R. 4 W., Point Identifier No. 400140

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 12 ins. diam., bears S. <math>41\frac{3}{4}^{\circ}</math> E., 79.5 ft. dist., with a healed double blaze.</p> <p>A cedar, 26 ins. diam., bears N. <math>73\frac{3}{4}^{\circ}</math> W., 126.9 ft. dist., with a healed double blaze.</p> <p>and a reference monument by Jelley</p> <p>An iron post, <math>2\frac{1}{2}</math> ins. diam., projecting 2 ins. above the ground, bears S. <math>34^{\circ} 46' 47''</math> E., 18.5 ft. dist., with brass cap mkd. 1/4 S34 RM 1976 and an arrow pointing to the corner. (Record, S. <math>34\frac{1}{4}^{\circ}</math> E.)</p> <p>and bearing trees mkd. by Steven J. Flause, Deputy County Surveyor, in 1980, recorded in the Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400140</p> <p>A fir, 30 ins. diam., bears N. <math>5\frac{3}{4}^{\circ}</math> E., 113.2 ft. dist., with a healed blaze.</p> <p>A fir, 21 ins. diam., bears S. <math>74\frac{1}{2}^{\circ}</math> W., 142.5 ft. dist., with a healed blaze.</p> <p>and a bearing tree mkd. by Daniel W. Baker, Registered Professional Land Surveyor, No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, Douglas County Surveyor's Office, records of Government corners renewed, T. 23 S., R. 4 W., Point Identifier No. 400140</p> <p>A cedar, 9 ins. diam., bears S. <math>12^{\circ}</math> E., 36.7 ft. dist., with scribe marks S 1/16 BT visible on open blaze.</p> <p>S. <math>89^{\circ} 59' 24''</math> W., on the E. and W. centerline of sec. 33.</p> <p>Ascend over broken NE. slope.</p>
10	Graveled road, 20 ft. wide, bears N. $10^{\circ}$ E. and S. $10^{\circ}$ W.
1339.83	The center E 1/16 sec. cor. of sec. 33, established by Daniel W. Baker, Registered Professional Land Surveyor, No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, map file No. M132-20, and is accepted as the cor., monumented with an iron pipe, $2\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap cemented to top, with brass cap incorrectly mkd.

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	T 23 S R 4 W S 1/16 C ____C S 33 PLS 1978 1999
	<p>from which bearing trees mkd. by James A. Branch, Registered Professional Land Surveyor, No. 1138, in 1990, recorded in the Douglas County Surveyor's Office, map file No. M110-58, and used by Baker</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. <math>47\frac{3}{4}^{\circ}</math> E., 57.6 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. <math>12\frac{3}{4}^{\circ}</math> W., 57.7 ft. dist., with a healed double blaze.</p> <p>From this point, a point established by James A. Branch, Registered Professional Land Surveyor, No. 1138, in 1990, as the center E 1/16 sec. cor. of sec. 33, recorded in the Douglas County Surveyor's Office, map file No. M110-58, bears N. <math>76^{\circ} 00' 00''</math> W., 0.20 ft. dist., monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 4 ins. above the ground, with yellow plastic cap mkd., BRANCH ENG LS 1138. This point was established using improper control and is not utilized during the course of this survey.</p> <p style="text-align: center;">_____</p> <p>N. <math>89^{\circ} 56' 48''</math> W., beginning a new measurement.</p> <p>Ascend over broken NE. slope.</p>
1339.35	<p>The center <math>\frac{1}{4}</math> sec. cor. of sec. 33.</p> <p style="text-align: center;">_____</p> <p>S. <math>89^{\circ} 57' 28''</math> W., beginning a new measurement, blazing and tagging.</p> <p>Ascend over broken NE. slope.</p>
1550	<p>Spur, slopes N. <math>40^{\circ}</math> E.; across North slope.</p>
2669.23	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.</p>

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	$\frac{1}{4}$ S 32   S 33 T 23 S R 4 W 1976
	from which bearing trees mkd. by Jelley
	A fir, 18 ins. diam., bears N. $28\frac{1}{2}^{\circ}$ E., 10.6 ft. dist., with a healed blaze.
	A fir, 13 ins. diam., bears N. $73\frac{3}{4}^{\circ}$ W., 15.0 ft. dist., with a healed blaze.
	Corner is located West, 6.0 ft. dist., of a woven wire fence, fence extending north and south.
	<hr/> From the S $\frac{1}{16}$ sec. cor. of secs. 33 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above the ground, with brass cap mkd.
	S $\frac{1}{16}$ S 33   S 34 1976
	from which bearing trees mkd. by Jelley
	A fir, 7 ins. diam., bears S. $72^{\circ}$ E., 26.4 ft. dist., with a healed blaze.
	A fir, 17 ins. diam., bears N. $84^{\circ}$ W., 15.8 ft. dist., with a healed blaze.
	From this point, the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, bears N. $0^{\circ} 40' 20''$ W., 1320.78 ft. dist., hereinbefore described.
	N. $89^{\circ} 59' 25''$ W., on the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 33.
	Ascend over broken NE. slope.
70	Dirt road, 20 ft. wide, bears N. $25^{\circ}$ E. and S. $25^{\circ}$ W.
755	Dirt road, 20 ft. wide, bears N. $40^{\circ}$ W. and S. $40^{\circ}$ E.
1215	Dirt road, 20 ft. wide, bears N. $50^{\circ}$ E. and S. $80^{\circ}$ W.
1343.31	The SE $\frac{1}{16}$ sec. cor. of sec. 33, established by Daniel W. Baker, Registered Professional Land Surveyor, No. 1978, in 1999, recorded in the Douglas County Surveyor's Office, map file No. M132-20, and

**Subdivision of Section 33,  
T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET	
	<p>is accepted as the cor., monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap cemented to top, with brass cap mkd.</p> <p style="text-align: center;">T 23 S R 4 W SE 1/16 S33 PLS 1978 1999</p> <p>from which bearing trees mkd. by Baker</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 61¾° E., 10.5 ft. dist., with scribe marks SE1/16S33 visible on upper blaze and BT on the lower blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 42¼° E., 6.9 ft. dist., with scribe marks SE1/16S33 visible on upper blaze and BT on lower the blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89° 58' 05" W., beginning a new measurement.</p> <p>Ascend over broken SE. slope.</p>
25	Spur, slopes S. 5° W.; continue asc. over NE. slope.
405	Spur, slopes N. 65° E.; continue asc. over NE. slope.
1341.58	The center S 1/16 sec. cor. of sec. 33.

**T. 23 S., R. 4 W., Willamette Meridian, Oregon**

FEET

**General Description**

The lands included in the foregoing resurvey are located in Douglas County, approximately 10 miles southeast of the town of Yoncalla, Oregon. The terrain is mountainous, elevations range from approximately 650 feet above sea level, near the E 1/16 sec. cor. of secs. 4 and 9, to about 1650 feet above sea level, near the cor. of secs. 1, 2, 11, and 12.

The area is drained by numerous small and seasonal drainages flowing into Elk Creek. The timber consists of fir, cedar, hemlock, alder, maple, oak, chinquapin, pine, ash, yew, and madrone. The undergrowth is mainly scotch broom, salal, Oregon grape, manzanita, arrowwood, poison oak, vine maple, ferns, and young timber.

Access is by logging roads branching from Douglas County Road No. 7, "Elk Head Road".

No mineral deposits were noted along the lines resurveyed. The lands are used primarily for timber production.

The mean magnetic declination, as shown on the United States Geological Survey quadrangle map "SCOTTS VALLEY, OREG., PROVISIONAL EDITION", published in 1987, is 19° East.

---