

FEET

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
PORTIONS OF THE EAST BOUNDARY
AND SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTIONS 11 AND 13
TOWNSHIP 25 SOUTH, RANGE 2 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated April 16, 2001, approved April 17, 2001,
which provided for the surveys included under Group No. 1979,
and Assignment Instructions dated April 27, 2001.

Survey commenced May 31, 2001

Survey completed June 12, 2002

T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET	
	<p>The following field notes are those of the dependent resurvey of portions of the east boundary and subdivisional lines and the subdivision of sections 11 and 13, township 25 south, range 2 west of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1883, John A. McQuin, U.S. Deputy Surveyor, surveyed the south, east and west boundaries.</p> <p>In 1900, Hezekiah H. Johnson, U.S. Deputy Surveyor, resurveyed the south, east, and west boundaries and surveyed the subdivisional lines.</p> <p>In 1951 to 1963, Levi E. Tallett, Cadastral Engineer, and C. Albert White, Cadastral Surveyor, resurveyed portions of the east boundary and subdivisional lines.</p> <p>In 1962, Floyd A. Brooks, Cadastral Surveyor, remonumented certain original corner points.</p> <p>In 1972-75, Daniel L. Berry, Harvey E. Wofford, and G. Steven Popken, Cadastral Surveyors, and Glen S. Baughman, Registered Land Surveyor No. 536, resurveyed a portion of the south boundary and subdivisional lines, and subdivided sections 31 and 32.</p> <p>In 1978-80, James E. Jelley, Cadastral Surveyor, resurveyed a portion of the east boundary.</p> <p>In 1993, Wayne L. Rogers, Cadastral Surveyor, and Robert H. Browning, Surveying Technician, resurveyed a portion of the subdivisional lines.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated April 16, 2001, for Group No. 1979, Oregon.</p> <p>The survey was performed utilizing both conventional (directly measured angles and distances) and NAVSTAR Global Positioning System (GPS) satellite techniques. The GPS measurements utilized dual frequency, carrier phase GPS receivers. The baselines were computed in and adjusted by least squares analysis using Trimble Geomatics Office (TGO). The GPS position of the survey was executed in accordance with the "Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods" version 1.0, dated May 9, 2001, published by the United States Department of the Interior, Bureau of Land Management, and the United States Department of Agriculture, Forest Service.</p>

T. 25 S., R. 2 W., Willamette Meridian, Oregon

FEET

The directions of lines refer to the true meridian as determined by a combination of direct solar observations and GPS techniques and carried forward by sustained angulation using conventional survey techniques. Distances along the lines were derived through the use of electronic measuring equipment. Conventionally measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The Standard Error of Unit Weight for the least squares adjustment of the survey data fell between 0.7 and 2.5. In addition the ratio of the adjustments (residuals) to the original unadjusted measurements did not exceed 1:4000. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ in. X ¼ in. magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (91)) of the corner of sections 23, 24, 25, and 26, as determined by the NAVSTAR Geodetic Positioning System, utilizing dual frequency, carrier phase GPS receivers and National Geodetic Survey station "STEAM 1989" and Douglas County station "DAWNA 1980", is as follows:

Latitude: 43° 22' 23.65" N. Longitude: 122° 53' 38.09" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

(Restoring the 1883 survey by John A. McQuin,
the 1900 resurvey by Hezekiah H. Johnson,
and 1978-80 resurvey by James E. Jelley)

Beginning at the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<pre> T 25 S R 2 W S 25 ----- WM S 36 1975 </pre>
	<p>from which bearing trees mkd. by Johnson and reported by Jelley</p> <p>A fir, 54 ins. diam., bears S. 22¼° E., 20.5 ft. dist., with healed blaze. (Record, S. 26° E.)</p> <p>A fir, 14 ins. diam., bears S. 34° W., 42.9 ft. dist., with healed blaze. (Record, S. 25° W.)</p> <p>A fir, 14 ins. diam., bears N. 43° W., 20.8 ft. dist., with healed blaze. (Record, N. 35½° W.)</p> <p>and a bearing tree mkd. by V.R. Tracy, Douglas County Surveyor's Office, in 1967, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Point Identifier No. 700200, and reported by Jelley</p> <p>A fir, 21 ins. diam., bears S. 46½° W., 30.4 ft. dist., with healed blaze. (Record, S. 43° W.)</p> <p>N. 0° 14' 17" W., on the E. bdy. of sec. 25, posting and blazing.</p> <p>Ascend SE. slope.</p>
450	Ridge, bears East and West; desc. broken N. slope.
540	Graveled road, 16 ft. wide, bears N. 50° E. and S. 50° W.
2305	Creek, 4 ft. wide, course N. 50° E.; desc. broken NE. slope.
2320.62	<p>The true closing cor. of secs. 30 and 31, T. 25 S., R. 1 W., established by V.W. Hosford, Registered Land Surveyor No. 253, in 1950, shown on Plat of Survey by Larry J. Friar, Registered Land Surveyor No. 961, recorded in the Douglas County Surveyor's Office, Map File No. M70-70, remonumented by James D. Artman, Registered Land Surveyor No. 2268, in 1990, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Point Identifier No. 700233, monumented with an iron post, 2 ins. diam., firmly set in a collar of stone, 2 ft. diam. to top, with brass cap mkd.</p> <pre> T 25 S S 30 R CC 1 ----- W S 31 268 1990 </pre>

**Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which bearing trees mkd. by Hosford and reported by Jelley</p> <p>A hemlock, 22 ins. diam., bears N. $43\frac{1}{4}^{\circ}$ E., 18.6 ft. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, 19.8 ft.)</p> <p>A cedar, 32 ins. diam., bears S. $36\frac{1}{4}^{\circ}$ E., 32.7 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>From this point, the orig. closing cor. of secs. 30 and 31, T. 25 S., R. 1 W., bears N. $89^{\circ} 04' 05''$ E., 47.29 ft. dist., (record, East, 43.9 ft.) determined at record dist. from the remains of the original bearing trees</p> <p>A sawed cedar stump, 19 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ E., 29.7 ft. dist., with scribe marks BT visible on partially healed blaze. (Record, N. $62\frac{1}{2}^{\circ}$ E.)</p> <p>A roothole, bears S. 62° E., 26.4 ft. dist., with decayed fir stump lying alongside, with fragmentary scribe marks visible on open blaze. (Record, S. 51° E.)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 14' 17''$ W., beginning new measurement.</p>
365.93	<p>The $\frac{1}{4}$ sec. cor. of sec. 25 only, monumented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set, projecting 5 ins. above ground, with steel cap, no marks visible, from which the remains of bearing trees mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1950, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Point Identifier No. 700240, and reported by Jelley</p> <p>A roothole, bears S. $11\frac{1}{2}^{\circ}$ W., 58.1 ft. dist., with fallen fir trunk, 36 ins. diam., lying alongside, with healed blaze.</p> <p>A fir, 28 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ W., 37.6 ft. dist., with healed blaze.</p> <p>and new bearing tree</p> <p>A hemlock, 9 ins. diam., bears S. $15\frac{1}{4}^{\circ}$ W., 21.5 ft. dist., mkd. $\frac{1}{4}$ S25 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 12' 02''$ W., beginning new measurement, continue posting and blazing.</p> <p>Descend broken NE. slope.</p>

**Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1515	Spring branch, 2 ft. wide, course S. 88° E.; asc. broken SE. slope.
2410	Spur, slopes S. 55° E.; desc. NE. slope.
2685.35	The cor. of secs. 24 and 25 only, monumented with an iron post, 1½ ins. diam., firmly set, projecting 7 ins. above ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	DOUGLAS COUNTY SURVEYORS OFFICE T 25 S R S 24 R 2 ——— S 30 1 W S 25 W 1976
	from which the remains of bearing trees mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1950, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 11, and Map File No. 12-61, and reported by Jelley
	A fir stump, 31 ins. diam., bears S. 78½° W., 37.9 ft. dist., with scribe marks 25S R2 visible on partially healed blaze. (Record, 36.0 ft.)
	A fir stump, 30 ins. diam., bears N. 39° W., 16.5 ft. dist., with scribe marks S24 PS 53 visible on partially healed blaze.
	and bearing tree mkd. by L.E. Monrean, Deputy County Surveyor, in 1976, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Point Identifier No. 700300. Jelley reports this tree as being mkd. by Francis Ingram.
	A hemlock, 20 ins. diam., bears S. 47¾° W., 121.8 ft. dist., with healed double blaze. (Record, S. 50° W.)
	and new bearing tree
	A fir, 6 ins. diam., bears N. 9¾° W., 6.2 ft. dist., mkd. T25S R2W S24 BT.
	From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

**Dependent Resurvey of a Portion of the East Boundary,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<div style="text-align: center; margin-bottom: 20px;"> <p>T 25 S T 25 S</p> <p>S 13 </p> <p>----- S 19</p> <p>S 24 </p> <p>R 2 W R 1 W</p> <p>1978</p> </div> <p>from which the remains of a bearing tree mkd. by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1950 and 1957, recorded in the Douglas County Surveyor's Office, Map File No. 12-61, and the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Point Identifier No. 700400, and reported by Jelley</p> <p style="margin-left: 40px;">A sawed fir stump, 28 ins. diam., bears N. 34½° W., 19.1 ft. dist., with scribe marks T25S R2W S13 253 BT visible on open blaze.</p> <p>and bearing trees mkd. by Jelley</p> <p style="margin-left: 40px;">A fir, 16 ins. diam., bears S. 27° W., 5.6 ft. dist., with healed blaze. (Record, S. 32½° W., 6.3 ft.)</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 21¾° W., 15.2 ft. dist., with healed blaze.</p> <p>N. 0° 13' 30" W., on the E. bdy. of sec. 13.</p> <p>Descend broken NE. slope.</p> <p>1343.59 The S 1/16 sec. cor. of sec. 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>S 1/16 </p> <p>S 13 </p> <p>1978</p> </div> <p>from which bearing trees mkd. by Jelley</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears S. 65½° W., 22.1 ft. dist., with healed blaze.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 30½° W., 5.6 ft. dist., with healed blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 13' 30" W., beginning new measurement.</p>
------	--

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	(Restoring the 1900 survey by Hezekiah H. Johnson and the 1962 remonumentation by Floyd A. Brooks)

	From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., hereinbefore described.
	N. 83° 42' 57" W., bet. secs. 24 and 25, posting and blazing.
	Ascend NE. slope.
710	Spring branch, 2 ft. wide, course N. 70° E.
2270	Spur, slopes N. 40° E.; desc. gentle N. slope.
2691.24	The ¼ sec. cor. of secs. 24 and 25, monumented with an iron post, 2½ ins. diam., firmly set, flush with the ground, (with original stone buried alongside) with brass cap mkd.
	S 24 1/4 _____ S 25 T 25 S R 2 W 1962
	from which the remains of the original bearing trees
	A sawed cedar stump, 26 ins. diam., bears N. 38½° E., 7.6 ft. dist., with no marks visible on partially opened blaze. (Record, N. 36° E.)
	A decayed hemlock stump, size indeterminate, bears S. 59° W., 3.3 ft. dist., with no marks visible. (Record, S. 56° W.)
	and remains of a bearing tree mkd. by Brooks
	A sawed cedar stump, 13 ins. diam., bears N. 59½° W., 119.5 ft. dist., with scribe marks 1/4 S24 BT visible on open blaze.
	and new bearing trees
	A fir, 14 ins. diam., bears S. 63° W., 7.0 ft. dist., mkd. 1/4 S25 BT.
	A fir, 9 ins. diam., bears N. 6¾° W., 22.1 ft. dist., mkd. 1/4 S24 BT.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	S. 89° 23' 07" W., beginning new measurement, continue posting and blazing.
	Ascend broken NE. slope.
425	Spur, slopes N. 10° W.; desc. NW. slope.
1334.39	<p>The W 1/16 sec. cor. of secs. 24 and 25, established by V.W. Hosford, Registered Land Surveyor No. 253 in 1955, recorded in the Douglas County Surveyor's Office, Map File No. M16-5, and is accepted as the cor., monumented with an iron pipe, 1 in. diam., firmly set, projecting 10 ins. above ground, with no cap, and with 2½ x 2½ in. squared wood post, projecting 30 ins. above ground and steel fence post driven alongside, from which the remains of bearing trees mkd. by Hosford</p> <p style="padding-left: 40px;">A sawed stump with tin cap, species indeterminate 18 ins. diam., bears S. 46¾° E., 17.0 ft. dist., with no marks visible on open blaze.</p> <p style="padding-left: 40px;">A sawed stump with tin cap, species indeterminate 22 ins. diam., bears S. 3½° E., 19.3 ft. dist., with no marks visible on open blaze.</p> <p>At the corner point</p> <p>Drive an aluminum rod, 36 ins. long, ¾ in. diam., 31 ins. in the ground to point of refusal, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> T 25 S R 2 W S 24 W 1/16 ————— S 25 2001 </div> <p>Drive the iron pipe alongside the aluminum rod.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 23' 07" W., beginning new measurement.</p>
835	Graveled road, 15 ft. wide, bears N. 42° E. and S. 42° W.
1280	Graveled road, 15 ft. wide, bears N. 20° E. and South.
1335.56	The cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<pre> T 25 S R 2 W S 23 S 24 ----- ----- S 26 S 25 1962 </pre>
	<p>from which the remains of the original bearing trees</p> <p>A hemlock stump, 18 ins. diam., bears S. 25° E., 42.6 ft. dist., with healed blaze. (Record, 38.9 ft.)</p> <p>A roothole, bears S. 19° W., 9.2 ft. dist., with sawed and decayed hemlock stump pushed over alongside, no marks visible.</p> <p>A fallen hemlock, 32 ins. diam., bears N. 38° W., 10.5 ft. dist., with no marks visible on partially healed blaze. (Record, N. 28° W.)</p> <p>and remains of a bearing tree mkd. by Brooks</p> <p>A sawed cedar stump, 34 ins. diam., bears S. 6½° W., 27.7 ft. dist., with scribe marks BT visible on partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 62¼° E., 32.6 ft. dist., mkd. T25S R2W S24 BT.</p> <p>A hemlock, 5 ins. diam., bears S. 75° E., 14.2 ft. dist., mkd. T25S R2W S25 BT.</p> <p>A hemlock, 7 ins. diam., bears S. 11½° W., 32.8 ft. dist., mkd. T25S R2W S26 BT.</p> <p>From this point, National Geodetic Survey station "STEAM 1989" bears S. 75° 20' 40" E., 42,789.90 ft. dist. (mean bearing and sea level dist.), monumented with a brass disk set in concrete, buried 8 ins. below surface of parking area, in a monument well, mkd. OREGON PRIMARY GPS STATION STEAM 1989 and a triangle.</p> <hr/> <p>N. 0° 24' 16" E., bet. secs. 23 and 24, posting and blazing.</p> <p>Descend NW. slope.</p>
545	<p>Spring branch, 2 ft. wide, course N. 70° W.; asc. broken W. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1334.27	<p>The S 1/16 sec. cor. of secs. 23 and 24, established by V.W. Hosford, Registered Land Surveyor No. 253 in 1955, recorded in the Douglas County Surveyor's Office, Map File No. M16-5, and is accepted as the cor., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 16 ins. above ground, with no cap, from which the remains of bearing trees mkd. by Hosford</p> <p style="padding-left: 40px;">A sawed stump, species indeterminate, 68 ins. diam., bears S. 47° E., 27.2 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A roothole, bears N. 18° W., 15.1 ft. dist., with fallen trunk, species indeterminate, 62 ins. diam., lying alongside, no marks visible.</p> <p>At the corner point</p> <p>Cut the top 12 ins. off the top of existing iron pipe and set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over it, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <pre> T 25 S R 2 W S 1/16 S 23 S 24 2001 </pre> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 42° E., 8.4 ft. dist., mkd. S 1/16 S24 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 46° W., 8.7 ft. dist., mkd. S 1/16 S23 BT.</p> <p>Deposit a magnet in a white plastic case at base and bury the remainder of the iron pipe alongside the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 24' 16" E., beginning new measurement.</p>
745	Graveled road, 20 ft. wide, bears S. 52° E. and N. 52° W.
790	Graveled road, 12 ft. wide, bears S. 73° E. and N. 73° W.
1336.30	<p>The ¼ sec. cor. of secs 23 and 24, perpetuated by V.R. Tracy, Douglas County Surveyor's Office, in 1966, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 59. The uprooted monument set by Brooks in 1962 was recovered and reset by L.E. Monrean, Deputy County Surveyor, in 1976, recorded in the Douglas County</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 102, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>1/4</p> <p> </p> <p>S 23 S 24</p> <p> </p> <p>T 25 S R 2 W</p> <p>RESET 1976</p> <p>1962</p> </div> <p>from which the remains of a bearing tree mkd. by Tracy</p> <p style="padding-left: 40px;">A hemlock stump, 14 ins. diam., bears S. 44¾° E., 25.1 ft. dist., with healed blaze.</p> <p>and accessories mkd. by Monrean</p> <p style="padding-left: 40px;">A bridge spike driven into top of a fir stump, 61 ins. diam., bears S. 18½° E., 16.6 ft. dist., mkd. B02</p> <p style="padding-left: 40px;">A bridge spike driven into top of a fir stump, 61 ins. diam., bears S. 41¼° W., 32.6 ft. dist., mkd. B01</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 57¼° E., 18.1 ft. dist., mkd. 1/4 S24 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 29½° W., 24.6 ft. dist., mkd. 1/4 S23 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 25' 04" E., beginning new measurement, continue posting and blazing.</p> <p>Descend gentle NW. slope.</p> <p>1470 Descend steep N. slope.</p> <p>2170 Slope changes to broken NE. slope.</p> <p>2430 Graveled road, 10 ft. wide, bears N. 54° E. and S. 54° W.</p> <p>2627.99 The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET

T 25 S	R 2 W
S 14	S 13
S 23	S 24
1962	

from which the remains of an original bearing tree

A decayed fir stump, 21 ins. diam., bears N. 12° W.,
13.9 ft. dist., with healed blaze.

and remains of bearing trees mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1955, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index Nos. 20 and 24, reported by Brooks

A fir stump, 16 ins. diam., bears N. 31° E., 25.4 ft. dist.,
with healed blaze.

A fir stump, 18 ins. diam., bears S. 9½° E., 16.6 ft. dist.,
with healed blaze. (Record, 14.2 ft.)

A fir snag, 9 ins. diam., 20 ft. high, bears S. 52° W.,
18.5 ft. dist., with healed blaze.

and remains of a bearing tree mkd. by Brooks

A fir stump, size indeterminate, bears N. 59° E.,
52.1 ft. dist., with no marks visible. (Record, N. 57° E.)

and remains of bearing trees mkd. by Randall W. Smith and Stephen J. Flauser, Douglas County Surveyor's Office, in 1995, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 131

A dead hemlock, 8 ins. diam., bears N. 59° E.,
30.1 ft. dist., with scribe marks T25S R2W S13 CS BT
visible on unhealed double blaze.

A fir, 9 ins. diam., bears S. 65½° E., 21.2 ft. dist.,
with healed double blaze.

A fir, 23 ins. diam., bears S. 9° W., 27.7 ft. dist.,
with healed double blaze.

A fir, 6 ins. diam., bears N. 71° W., 25.7 ft. dist.,
with healed double blaze.

and new bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 6 ins. diam., bears N. 77° E., 10.5 ft. dist., mkd. T25S R2W S13 BT.</p> <p>A steel pipe, 4 ins. diam., projecting 28 ins. above ground, is alongside the iron post.</p> <hr/> <p>From the cor. of secs 13 and 24 only, on the E. bdy. of the Tp., hereinbefore described.</p> <p>N. 86° 45' 01" W., bet. secs. 13 and 24.</p> <p>Ascend broken NE. slope.</p>
815	Gravel road, 34 ft. wide, bears S. 70° E. and N. 70° W.
1322.77	<p>Point for the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 2 W</p> <p> S 13</p> <p>E 1/16 ———</p> <p> S 24</p> <p> 2002</p> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 16° E., 8.4 ft. dist., mkd. E 1/16 S13 BT.</p> <p>A fir, 17 ins. diam., bears S. 20½° E., 21.5 ft. dist., mkd. E 1/16 S24 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Begin posting and blazing.</p>
2645.54	<p>The ¼ sec. cor. of secs. 13 and 24, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 13</p> <p>1/4 ———</p> <p>S 24</p> <p>T 25 S R 2 W</p> <p> 1962</p> </div>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed, decayed fir stump, 30 ins. diam., bears S. 67¼° E., 15.8 ft. dist., with healed blaze. (Record, S. 58° E.)</p> <p style="padding-left: 40px;">A fir, 55 ins. diam., bears N. 13° W., 7.9 ft. dist., with healed blaze. (Record, N. 25° W.)</p> <p>and remains of bearing trees mkd. by Brooks</p> <p style="padding-left: 40px;">A sawed fir stump, 12 ins. diam., bears S. 49¼° W., 20.8 ft. dist., with a healed blaze. (Record, S. 48½° W., 21.8 ft.)</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears N. 38½° W., 12.9 ft. dist., with a healed blaze. (Record, N. 41° W., 12.2 ft.)</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. 78¼° W., 37.7 ft. dist., mkd. 1/4 S24 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89° 06' 28" W., beginning new measurement, continue posting and blazing.</p> <p>Ascend NE. slope.</p>
875	Spur, slopes N. 17° E.; desc. broken NW. slope.
1145	Gravel road, 20 ft. wide, bears N. 13° E. and S. 20° W.
1321.59	<p>The W 1/16 sec. cor. of secs. 13 and 24, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., determined at Hosford record bearing and distance from his bearing trees</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 30° E., 20.8 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 6° E., 7.7 ft. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	T 25 S R 2 W S 13 W 1/16 ——— S 24 2002
	Deposit a magnet in a white plastic case at the base of the iron post.
	Discontinue posting and blazing.
	—————
	N. 89° 02' 20" W., beginning new measurement.
	Descend broken NE. slope.
1050	Gravel road, 16 ft. wide, bears N. 35° E. and S. 38° W.
1322.06	The cor. of secs. 13, 14, 23, and 24, hereinbefore described.
	—————
	N. 0° 46' 59" E., bet. secs. 13 and 14.
	Descend broken NE. slope.
1332.00	Point for the S 1/16 sec. cor. of secs. 13 and 14, not monumented.
2664.00	The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.
	1/4 S 14 S 13 T 25 S R 2 W 1962
	from which the remains of an original bearing tree
	A decayed sawed fir stump, 42 ins. diam., bears N. 57¾° E., 9.0 ft. dist., with healed blaze. (Record, N. 54° E.)
	and remains of a bearing tree mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1955, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 23, reported by Brooks
	A decayed hemlock stump, 22 ins. diam., bears N. 27° W., 26.5 ft. dist., with scribe marks /4 S14 253 BT visible on partially healed blaze. (Record, N. 30½° W.)

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>and remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A decayed sawed hemlock stump, 10 ins. diam., bears N. 62° W., 23.0 ft. dist., with scribe marks 1/4 S14 BT visible on unhealed blaze. (Record, N. 66¼° W.)</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears S. 23½° E., 8.5 ft. dist., mkd. 1/4 S13 BT.</p> <p style="padding-left: 40px;">A hemlock, 13 ins. diam., bears N. 87¾° W., 35.3 ft. dist., mkd. 1/4 S14 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5° 51' 39" W., beginning new measurement.</p> <p>Descend broken NE. slope.</p>
1160	Gravel road, 20 ft. wide, bears S. 42° E. and N. 50° W.
1280.87	<p>The N 1/16 sec. cor. of secs. 13 and 14, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., perpetuated by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 18 ins. above ground, with no cap, from which the remains of a bearing tree mkd. by Hosford</p> <p style="padding-left: 40px;">A fallen decayed hemlock, 14 ins. diam., bears N. 35¾° E., 5.6 ft. dist., with fragmentary scribe marks visible on unhealed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, over the existing iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 2 W</p> <p style="padding-left: 40px;">N 1/16</p> <p style="padding-left: 40px;"> </p> <p style="padding-left: 20px;">S 14 S 13</p> <p style="padding-left: 40px;"> </p> <p style="padding-left: 40px;">2002</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 46¾° E., 9.0 ft. dist., mkd. N 1/16 S13 BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET									
	<p>A fir, 8 ins. diam., bears S. $68\frac{1}{4}^{\circ}$ W., 24.1 ft. dist., mkd. N 1/16 S14 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $5^{\circ} 49' 09''$ W., beginning new measurement, posting and blazing.</p> <p>Descend broken N. slope.</p>								
1279.22	<p>The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 10px;">T 25 S</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">R 2 W</td> </tr> <tr> <td style="padding: 0 10px;">S 11</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S 12</td> </tr> <tr> <td style="padding: 0 10px;">S 14</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;">S13</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 10px;">1962</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A sawed fir stump, 43 ins. diam., bears N. $16\frac{3}{4}^{\circ}$ E., 27.3 ft. dist., with healed blaze. (Record, N. $18\frac{1}{2}^{\circ}$ E., 28.4 ft.)</p> <p>A roothole bears S. 30° E., 11.9 ft. dist., with fallen fir trunk, 60 ins. diam., lying alongside, with healed blaze.</p> <p>A decayed fir stump, size indeterminate, bears S. $53\frac{3}{4}^{\circ}$ W., 25.7 ft. dist., with no marks visible. (Record, S. 57° W., 20.5 ft.)</p> <p>A decayed hemlock stump, size indeterminate, bears N. $75\frac{3}{4}^{\circ}$ W., 17.2 ft. dist., with fallen trunk, 22 ins. diam., lying alongside, with healed blaze. (Record, N. 72° W.)</p> <p>and bearing tree mkd. by Brooks</p> <p>A hemlock, 24 ins. diam., bears S. $60\frac{1}{4}^{\circ}$ W., 47.5 ft. dist., with healed blaze. (Record, S. 6° W.)</p> <p>and new bearing trees</p> <p>A fir, 6 ins. diam., bears N. 22° E., 11.5 ft. dist., mkd. T25S R2W S12 BT.</p>	T 25 S	R 2 W	S 11	S 12	S 14	S13	1962	
T 25 S	R 2 W								
S 11	S 12								
S 14	S13								
1962									

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock, 10 ins. diam., bears S. 21½° E., 32.1 ft. dist., mkd. T25S R2W S13 BT.</p> <p>A hemlock, 10 ins. diam., bears N. 48¼° W., 11.8 ft. dist., mkd. T25S R2W S11 BT.</p>
	<hr/> <p>From the ¼ sec. cor. of secs. 12 and 13, monumented with an iron post, 2½ ins. diam., firmly set, buried 8 ins. below ground, with brass cap mkd.</p> <p style="text-align: center;">S 12 1/4 ——— S 13 T 25 S R 2 W 1962</p> <p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, size indeterminate, bears S. 50¾° W., 12.5 ft. dist., with no marks visible. (Record, S. 54° W.)</p> <p>and remains of a bearing tree mkd. by Brooks</p> <p>A decayed hemlock stump, size indeterminate, bears S. 3° W., 28.4 ft. dist., with no marks visible. (Record, South)</p> <p>and a bearing tree mkd. by V.R. Tracy, Douglas County Surveyor's Office, in 1967, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 78</p> <p>A cedar, 32 ins. diam., bears S. 57¼° W., 50.8 ft. dist., with healed blaze.</p> <p>and bearing trees mkd. by Howard Johnstone, Oregon Registered Land Surveyor No. 498, in 1982, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 117</p> <p>A fir, 12 ins. diam., bears S. 19° E., 38.5 ft. dist., with healed blaze.</p> <p>A fir, 12 ins. diam., bears N. 88½° W., 24.9 ft. dist., with healed blaze.</p> <p>Cor. sits on edge of dry streambed, 5 ft. wide, with steel fence post driven alongside.</p> <p>N. 88° 54' 58" W., bet. secs. 12 and 13.</p> <p>Descend broken SW. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
485	Paved road, 16 ft. wide, bears S. 36° E. and N. 36° W.
1015	East Fork of Rock Creek, 15 ft. wide, course N. 10° W.; asc. broken N. slope.
1322.78	<p>The W 1/16 sec. cor. of secs. 12 and 13, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., monumented with a post hole, 4 ins. square, with rotted remains of wood post lying alongside, from which bearing trees mkd. by Hosford</p> <p style="padding-left: 40px;">A cedar, 30 ins. diam., bears N. 52½° E., 17.4 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears S. 68¾° W., 29.6 ft. dist., with scribe marks S13 S25 BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in the existing post hole, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T 25 S R 2 W</p> <p style="padding-left: 40px;">S 12</p> <p style="padding-left: 40px;">W 1/16 ———</p> <p style="padding-left: 40px;">S 13</p> <p style="padding-left: 40px;">2002</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88° 57' 10" W., beginning new measurement, posting and blazing.</p> <p>Ascend broken N. slope.</p>
815	Left bank of the East Fork of Rock Creek, bank bears N. 50° E. and S. 50° W.
1155	Left bank of the East Fork of Rock Creek, bank bears S. 37° E. and N. 37° W.
1321.54	<p>The cor. of secs. 11, 12, 13, and 14, hereinbefore described.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 23, 24, 25, and 26, hereinbefore described.</p> <p>S. 89° 20' 14" W., bet. secs. 23 and 26, posting and blazing.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	Descend broken NW. slope.
165	Creek, 6 ft. wide, course N. 54° W.; asc. NE. slope.
725	Spur, slopes N. 30° W.; desc. NW. slope.
1055	Graveled road, 12 ft. wide, bears N. 50° E. and S. 50° W.
2025	Graveled road, 16 ft. wide, bears N. 51° E. and S. 51° W.
2185	Spring branch, 1 ft. wide, course N. 10° W.
2672.36	<p>The ¼ sec. cor. of secs. 23 and 26, determined at record bearing and dist. from the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed hemlock stump, 14 ins. diam., bears S. 25° E., 20.5 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>and remains of a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A sawed hemlock stump, 26 ins. diam., bears S. 3° E., 46.2 ft. dist., with healed blaze.</p> <p>The corner point is located in creek. Not monumented.</p> <p>From this point, the witness cor. for the ¼ sec. cor. of secs. 23 and 26, established by Stephen J. Flause, Douglas County Surveyor's Office, in 1981, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 115, bears East, 10.00 ft. dist., monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">DOUGLAS COUNTY SURVEYOR T 25 S WC S 23 ←———— 1/4 S 26 R 2 W 1981</p> <p>from which bearing objects mkd. by Flause</p> <p style="padding-left: 40px;">A bridge spike driven into top of a fir stump, 48 ins. diam., bears N. 19° E., 6.4 ft. dist., mkd. WC B01.</p> <p style="padding-left: 40px;">A bridge spike driven into top of a fir stump, 48 ins. diam., bears S. 82½° E., 35.9 ft. dist., mkd. WC B02.</p> <p>and new bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET																													
	<p>A fir, 7 ins. diam., bears N. 28° E., 25.9 ft. dist., mkd. X BT.</p> <p>A cedar, 13 ins. diam., bears S. 30° W., 13.2 ft. dist., mkd. WC 1/4 S26 BT.</p> <p>A fir, 9 ins. diam., bears N. 39¼° W., 27.4 ft. dist., mkd. WC 1/4 S23 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 30' 39" W., beginning new measurement, continue posting and blazing.</p> <p>Ascend gentle NE. slope.</p>																												
15	Creek, 2 ft. wide, course N. 37° W.																												
925	Spur, slopes N. 5° E.; desc. steep NW. slope.																												
2085	Graveled road, 10 ft. wide, bears N. 21° E. and S. 21° W.																												
2682.79	<p>The cor. of secs 22, 23, 26, and 27, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 36, further perpetuated by Randall W. Smith, Stephen J. Flause and Terrie Franssen, Douglas County Surveyor's Office, in 1990, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 125, monumented with an iron post, 1½ ins. diam., firmly set, projecting 15 ins. above ground, in a mound of earth, 2 ft. diam., 6 ins. high, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td colspan="2" style="padding: 0 10px;">COUNTY</td> <td colspan="2" style="padding: 0 10px;">SURVEYORS</td> </tr> <tr> <td colspan="4" style="padding: 0 10px;">T 25 S</td> </tr> <tr> <td style="padding: 0 5px;">S 22</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 23</td> <td></td> </tr> <tr> <td colspan="4" style="text-align: center; padding: 0 10px;">-----</td> </tr> <tr> <td style="padding: 0 5px;">S 27</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 26</td> <td></td> </tr> <tr> <td colspan="4" style="padding: 0 10px;">R 2 W</td> </tr> <tr> <td colspan="2" style="padding: 0 10px;">OFFICE</td> <td colspan="2" style="padding: 0 10px;">1958</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p>A sawed pine stump with tin cap, 67 ins. diam., bears N. 39½° E., 41.9 ft. dist., with healed blaze. (Record, N. 37° E., 38.9 ft.)</p> <p>A sawed fir stump, 31 ins. diam., bears S. 23° E., 21.8 ft. dist., with healed blaze. (Record, S. 25° E., 23.1 ft.)</p>	COUNTY		SURVEYORS		T 25 S				S 22		S 23		-----				S 27		S 26		R 2 W				OFFICE		1958	
COUNTY		SURVEYORS																											
T 25 S																													
S 22		S 23																											

S 27		S 26																											
R 2 W																													
OFFICE		1958																											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET													
	<p>A sawed fir stump, 39 ins. diam., bears N. $42\frac{1}{4}^{\circ}$ W., 37.1 ft. dist., with healed blaze. (Record, N. 44° W., 38.9 ft.)</p> <p>and bearing tree mkd. by Byron</p> <p>A hemlock, 10 ins. diam., bears S. 83° W., 22.3 ft. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Smith, Flause and Franssen</p> <p>A double trunk hemlock, 14 ins. diam., bears S. $21\frac{1}{4}^{\circ}$ W., 24.4 ft. dist., with healed double blaze.</p> <p>A hemlock, 12 ins. diam., bears N. $40\frac{3}{4}^{\circ}$ W., 8.1 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p>												
	<hr/> <p>N. $1^{\circ} 18' 48''$ E., bet. secs. 22 and 23, posting and blazing.</p> <p>Descend broken NW. slope.</p>												
380	Spring branch, 1 ft. wide, course N. 10° W.; asc. steep SW. slope.												
560	Spur, slopes N. 69° W.; desc. NE. slope.												
1410	Dirt road, 10 ft. wide, bears N. 21° E. and S. 21° W.												
2375	Graveled road, 20 ft. wide, bears S. 29° E. and S. 65° W.												
2758.76	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 37, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 15 ins. above ground, in a mound of earth, 2 ft. diam., 6 ins. high, surrounded by a large truck tire, with brass cap mkd.</p> <div style="text-align: center;"> <table> <thead> <tr> <th>COUNTY</th> <th>SURVEYORS</th> </tr> </thead> <tbody> <tr> <td>T 25 S</td> <td></td> </tr> <tr> <td>1/4 S 22</td> <td> S 23</td> </tr> <tr> <td>COR</td> <td> </td> </tr> <tr> <td></td> <td>R 2 W</td> </tr> <tr> <td>OFFICE</td> <td>1958</td> </tr> </tbody> </table> </div> <p>from which the remains of an original bearing tree</p> <p>A roothole, bears N. $34\frac{1}{4}^{\circ}$ E., 15.8 ft. dist., with decayed cedar trunk lying alongside, no marks visible. (Record, N. 40° E.)</p>	COUNTY	SURVEYORS	T 25 S		1/4 S 22	S 23	COR			R 2 W	OFFICE	1958
COUNTY	SURVEYORS												
T 25 S													
1/4 S 22	S 23												
COR													
	R 2 W												
OFFICE	1958												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	and remains of bearing trees mkd. by Byron
	A fir stump, 60 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E., 39.2 ft. dist., with scribe marks S23 CS BT visible on unhealed blaze.
	A decayed hemlock stump, 16 ins. diam., bears S. $83\frac{3}{4}^{\circ}$ W., 39.5 ft. dist., with illegible scribe marks visible on partially healed double blaze.
	and a bearing tree mkd. by person(s) unknown
	A fir, 52 ins. diam., bears N. 50° W., 21.2 ft. dist., with letters MC and axe marks visible in the bark.
	and new bearing trees
	A hemlock, 12 ins. diam., bears N. $14\frac{1}{4}^{\circ}$ E., 19.5 ft. dist., mkd. 1/4 S23 BT.
	A fir, 8 ins. diam., bears S. 70° W., 29.1 ft. dist., mkd. 1/4 S22 BT.

	N. $0^{\circ} 08' 25''$ W., beginning new measurement, continue posting and blazing.
	Descend NE. slope.
135	Creek, 3 ft. wide, course N. 38° W.
255	Spur, slopes N. 63° W.; desc. steep N. slope.
340	Braided creekbed, 30 ft. wide, course N. 75° W.; asc. SW. slope.
2065	Graveled road, 16 ft. wide, bears N. 40° E. and S. 40° W.
2654.70	The cor. of secs. 14, 15, 22, and 23, perpetuated by Ben B. Irving, County Surveyor, in 1948, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 3, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 34, perpetuated by Randall W. Smith and Stephen J. Flause, Douglas County Surveyor's Office, in 1995, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 133, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	COUNTY SURVEYORS
	T 25 S S 15 S 14 ----- S 22 S 23 R 2 W OFFICE 1958
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A pine snag, 29 ins. diam., bears N. 39¼° E., 5.0 ft. dist., with healed blaze. (Record, N. 46° E., 4.0 ft.)</p> <p style="padding-left: 40px;">A pine snag, 34 ins. diam., bears N. 35° W., 13.0 ft. dist., with a burnt out blaze. (Record, 11.9 ft.)</p> <p>and remains of a bearing tree mkd. by Irving</p> <p style="padding-left: 40px;">A fir stump, 24 ins. diam., bears S. 27° W., 18.4 ft. dist., with healed blaze.</p> <p>and accessories mkd. by Smith and Flause</p> <p style="padding-left: 40px;">A chinquapin, 10 ins. diam., bears N. 80° E., 33.1 ft. dist., with scribe marks T25S R2W S14 CS BT visible on partially opened blaze.</p> <p style="padding-left: 40px;">A bridge spike driven into top of a fir stump, 32 ins. diam., bears S. 47½° W., 62.4 ft. dist., mkd. DCSO B01 1995.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 13° E., 90.0 ft. dist., mkd. T25S R2W S23 BT.</p> <p style="padding-left: 40px;">A yew, 6 ins. diam., bears N. 10½° W., 68.1 ft. dist., mkd. T25S R2W S15 BT.</p> <hr/> <p>From the cor. of secs. 13, 14, 23, and 24, hereinbefore described. N. 88° 52' 52" W., bet. secs. 14 and 23, posting and blazing. Ascend gentle E. slope.</p> <p>1230 Graveled road, 12 ft. lks. wide, bears N. 23° E. and S. 29° W.</p> <p>2055 Spur, slopes N. 30° E.; desc. NW. slope.</p> <p>2679.67 The ¼ sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with orig. stone buried alongside, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	S 14 1/4 ————— S 23 T 25 S R 2 W 1962
	<p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A roothole, bears S. 3° W., 21.1 ft. dist., with fallen hemlock trunk lying alongside, with healed blaze.</p> <p style="padding-left: 40px;">A roothole, bears N. 42° W., 11.9 ft. dist.</p> <p>and remains of the bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A roothole, bears N. 46° E., 21.1 ft. dist.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A cedar, 27 ins. diam., bears S. 66¾° W., 39.3 ft. dist., mkd. 1/4 S23 BT.</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 13½° W., 53.5 ft. dist., mkd. 1/4 S14 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 89° 49' 27" W., beginning new measurement, continue posting and blazing.</p> <p>Descend NW. slope.</p>
2655.72	<p>The cor. of secs. 14, 15, 22, and 23, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15, perpetuated by Ben B. Irving, County Surveyor, in 1948, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 2, perpetuated by V.R. Tracy, Douglas County Surveyor's Office, in 1967, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 83, perpetuated by Nick Juliano, Registered Logging Engineer No. 3449, in 1977, recorded in the Douglas County Surveyor's Office, Map File No. M62-74, monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	COUNTY SURVEYORS
	T 25 S S 10 S 11 ----- S 15 S 14 R 2 W OFFICE
	<p>from which an original bearing tree</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears S. 58¼° W., 22.4 ft. dist., with healed blaze. (Record, S. 56° W.)</p> <p>and the remains of bearing trees mkd. by Irving</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears S. 85° E., 51.7 ft. dist., with scribe marks T 5 R W S14 BT visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A cedar stump, 28 ins. diam., bears N. 81¼° W., 58.9 ft. dist., with scribe marks T25S R2W S10 CS visible on partially healed blaze.</p> <p>and bearing trees mkd. by Tracy</p> <p style="padding-left: 40px;">A hemlock, 26 ins. diam., bears N. 19° E., 56.1 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears S. 67½° W., 40.3 ft. dist., with healed double blaze.</p> <p>and bearing trees mkd. by Juliano</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 45° E., 46.8 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A cedar, 19 ins. diam., bears S. 11¾° W., 31.2 ft. dist., with healed blaze.</p> <p>N. 1° 33' 07" W., bet. secs. 10 and 11, posting and blazing.</p> <p>Descend NW. slope.</p>
375	Bottom of draw, drains West; asc. gentle SW. slope.
625	Spur, slopes N. 70° W.; desc. gentle W. slope.
995	End descent; over level river bottom.
1210	Rock Creek, 25 ft. wide, course S. 72° W.; continue over level river bottom.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1305	Asphalt road, 22 ft. wide, bears N. 66° E. and S. 70° W.
1960	Ascend SE. slope.
2663.63	<p>The ¼ sec. cor. of secs. 10 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <pre> 1/4 S 10 S 11 T 25 S R 2 W 1962 </pre> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A cedar stump, 18 ins. diam., bears S. 68¾° E., 35.6 ft. dist., with no marks visible. (Record, S. 64° E.)</p> <p style="padding-left: 40px;">A fir stump, 54 ins. diam., bears N. 56° W., 25.6 ft. dist., with healed blaze. (Record, N. 52° W., 26.4 ft.)</p> <p>and a bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 29½° E., 23.1 ft. dist., with healed blaze. (Record, S. 24½° E.)</p> <p>and bearing tree mkd. by person(s) unknown, reported by Nick Juliano, Registered Logging Engineer No. 3449, in 1977, recorded in the Douglas County Surveyor's Office, Map File No. M62-74,</p> <p style="padding-left: 40px;">A cedar, 41 ins. diam., bears S. 9¾° E., 16.6 ft. dist., with healed blaze.</p> <hr/> <p>From the ¼ sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with orig. stone lying alongside, and an iron pipe, 1½ ins. diam., driven alongside, with brass cap mkd.</p> <div style="text-align: center;"> <pre> S 15 1/4 ----- S 22 T 25 S R 2 W 1962 </pre> </div> <p>from which the remains of the original bearing trees</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A cedar snag, 10 ins. diam., bears S. 12° E., 21.1 ft. dist., with no marks visible on decayed blaze. (Record, S. 15° E.)</p> <p>A decayed hemlock stump, 26 ins. diam., bears N. 36° W., 4.6 ft. dist., with illegible scribe fragments lying alongside. (Record, N. 39° W.)</p> <p>and remains of a bearing tree mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1957, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 33, reported by Brooks</p> <p>A decayed hemlock snag, 29 ins. diam., bears S. 56° W., 21.8 ft. dist., with fragmentary scribe marks visible on open blaze and large X hacked into the bark on the side away from the corner. (Record, S. 54½° W.)</p> <p>and bearing trees mkd. by Randall W. Smith and Stephen J. Flause, Douglas County Surveyor's Office, in 1996, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 145</p> <p>A fir, 13 ins. diam., bears S. 21¾° E., 11.6 ft. dist., with healed double blaze.</p> <p>A fir, 6 ins. diam., bears S. 37° W., 22.9 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>A cedar, 10 ins. diam., bears N. 40¾° W., 7.7 ft. dist., with fragmentary scribe marks visible on partially healed double blaze.</p> <p>N. 89° 35' 19" W., bet. secs. 15 and 22, posting and blazing.</p> <p>Descend SW. slope.</p>
65	Graveled road, 20 ft. wide, bears S. 32° E. and N. 32° W.
200	Miller Creek, 5 ft. wide, course N. 32° W.; asc. steep NE. slope.
1345	Spur, slopes North; desc. broken NW. slope.
2647.76	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 2½ ft. base to top, with iron pipe, 2 ins. diam., driven alongside, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	T 25 S R 2 W S 16 S 15 ----- S 21 S 22 1962
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed hemlock stump, size indeterminate, bears S. $41\frac{3}{4}^{\circ}$ E., 18.2 ft. dist., with no marks visible. (Record, S. 45° E., 17.2 ft.)</p> <p>and remains of bearing trees mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1957, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 26, reported by Brooks</p> <p style="padding-left: 40px;">A hemlock snag, 11 ins. diam., bears N. $28\frac{3}{4}^{\circ}$ E., 25.7 ft. dist., with healed blaze. (Record, N. 27° E.)</p> <p style="padding-left: 40px;">A hemlock, 19 ins. diam., bears S. 21° W., 87.8 ft. dist., with healed blaze. (Record, S. 20° W.)</p> <p style="padding-left: 40px;">A cedar, 25 ins. diam., bears N. 43° W., 14.5 ft. dist., with healed blaze.</p> <p>and bearing tree mkd. by Brooks</p> <p style="padding-left: 40px;">A cedar, 35 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ E., 57.4 ft. dist., with healed blaze.</p> <hr/> <p>N. $0^{\circ} 02' 38''$ E., bet. secs. 15 and 16, posting and blazing.</p> <p>Descend broken NW. slope.</p> <p>890 Dirt road, 15 ft. wide, bears S. 82° E. and N. 82° W.</p> <p>1605 Spring branch, 1 ft. wide, course N. 50° W.</p> <p>2285 Graveled road, 16 ft. wide, bears N. 50° E. and S. 44° W.</p> <p>2445 Rock Creek, 30 ft. wide, course S. 44° W.; continue over level river bottom.</p> <p>2648.05 The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, perpetuated by Ben B. Irving, Douglas County Surveyor, in 1948, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 5, perpetuated by V.R. Tracy, Douglas County Surveyor's Office, in 1966 and again in 1973, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index Nos. 74 and 93, further</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET

perpetuated by Randall W. Smith and Stephen J. Flause, Douglas County Surveyor's Office, in 1995, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 130, monumented with an iron pipe, 1½ ins. diam., firmly set, buried 18 ins. below ground level, with a rebar, 5/8 in. diam., driven alongside, with brass cap mkd.

COUNTY	SURVEYORS
T 25 S	R 2 W
1/4 S 16	S 15
OFFICE	1973

from which bearing trees mkd. by Irving

A maple, 14 ins. diam., bears N. 46½° E., 40.5 ft. dist., with healed blaze.

A maple, 25 ins. diam., bears S. 84¼° W., 51.9 ft. dist., with healed blaze.

and bearing trees mkd. by Tracy

A maple, 24 ins. diam., bears N. 28° E., 31.2 ft. dist., with healed blaze.

A cedar, 30 ins. diam., bears S. 27¾° W., 109.0 ft. dist., with healed blaze.

From the cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 25 S	R 2 W
S 21	S 22
S 28	S 27
1962	

from which the remains of the original bearing trees

A hemlock, 30 ins. diam., bears N. 12½° E., 20.5 ft. dist., with healed blaze.

A decayed chinquapin stump, size indeterminate, bears S. 38° W., 9.2 ft. dist., no marks.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 37 ins. diam., bears N. 75° W., 39.7 ft. dist., with healed blaze. (Record, 35.0 ft.)</p> <p>and remains of bearing trees mkd. by Brooks</p> <p>A chinquapin, 13 ins. diam., bears S. 62° E., 30.4 ft. dist., with healed blaze.</p> <p>A decayed chinquapin stump, size indeterminate, bears S. 54½° W., 24.7 ft. dist., no marks.</p> <p>N. 89° 05' 42" W., bet. secs. 21 and 28, posting and blazing.</p> <p>Descend SW. slope.</p>
2697.00	<p>The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with original stone buried alongside, and an iron pipe, 2 ins. diam., driven alongside, with brass cap mkd.</p> <p style="text-align: center;">S 21 1/4 ----- S 28 T 25 S R 2 W 1962</p> <p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, size indeterminate, bears S. 25½° E., 31.0 ft. dist., with no marks visible.</p> <p>and remains of bearing trees mkd. by Arthur C. Boyer, Douglas County Surveyor, in 1943, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 1, and reported by Brooks</p> <p>A decayed fir stump, size indeterminate, bears N. 87° E., 19.8 ft. dist., with no marks visible.</p> <p>A decayed maple stump, size indeterminate, bears S. 14½° E., 34.6 ft. dist., with no marks visible.</p> <p>and remains of a bearing tree mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1957, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 28, and reported by Brooks</p> <p>A roothole, bears N. 61° W., 21.1 ft. dist.</p> <p>and remains of a bearing tree mkd. by Brooks</p> <p>A roothole, bears N. 50° W., 7.9 ft. dist.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET											
	and new bearing trees										
	A cedar, 10 ins. diam., bears N. 31½° E., 22.8 ft. dist., mkd. 1/4 S21 BT.										
	A hemlock, 14 ins. diam., bears S. 33½° E., 26.3 ft. dist., mkd. 1/4 S28 BT.										

	S. 89° 02' 35" W., beginning new measurement, continue posting and blazing.										
	Descend SW. slope.										
1085	Spring branch, 1 ft. wide, course S. 70° W.										
1710	Graveled road, 18 ft. wide, bears N. 48° E. and S. 42° W.										
2100	Graveled road, 24 ft. wide, bears S. 34° E. and N. 23° W.										
2255	Creek, 5 ft. wide, course N. 10° W.										
2272.23	The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, in a collar of stone, with an iron pipe, 2 ins. diam., driven alongside, with brass cap mkd.										
	<table style="margin: auto;"> <tr> <td>T 25 S</td> <td>R 2 W</td> </tr> <tr> <td>S 20</td> <td> S 21</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td>S 29</td> <td> S 28</td> </tr> <tr> <td colspan="2" style="text-align: center;">1962</td> </tr> </table>	T 25 S	R 2 W	S 20	S 21	-----		S 29	S 28	1962	
T 25 S	R 2 W										
S 20	S 21										

S 29	S 28										
1962											
	from which the remains of the original bearing trees										
	A cedar, 30 ins. diam., bears S. 45° E., 6.6 ft. dist., with healed blaze.										
	A sawed fir stump, size indeterminate, bears S. 13° W., 19.2 ft. dist., with scribe marks T25S R2W S29 visible on partially healed blaze.										
	and remains of bearing trees mkd. by V.W. Hosford, Registered Land Surveyor No. 253, in 1957, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 27, and reported by Brooks and Rogers										
	A hemlock, 21 ins. diam., bears S. 12° W., 60.1 ft. dist., with healed blaze. (Record, S. 13½° W.)										
	A broken top cedar, 29 ins. diam., bears West, 34.3 ft. dist., with healed blaze.										

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	and a bearing tree mkd. by Rogers
	A hemlock, 8 ins. diam., bears N. $80\frac{3}{4}^{\circ}$ E., 37.6 ft. dist., with healed blaze. (Record, fir, N. 81° E.)
	and new bearing tree
	A hemlock, 16 ins. diam., bears N. $28\frac{1}{4}^{\circ}$ W., 83.9 ft. dist., mkd. T25S R2W S20 BT.
	<hr/>
	N. $0^{\circ} 37' 00''$ E., bet. secs. 20 and 21, posting and blazing.
20	Creek, 5 ft. wide, course West; asc. SW. slope.
185	Graveled road, 22 ft. wide, bears S. 62° E. and N. 55° W.
720	Spur, slopes S. 83° W.; desc. NW. slope.
1575	Rock Creek, 20 ft. wide, course S. 24° W.; asc. gentle SE. slope.
2460	Asphalt road, 20 ft. wide, bears N. 58° E. and S. 58° W.
2655.56	The $\frac{1}{4}$ sec. cor. of secs 20 and 21, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	$\begin{array}{c} 1/4 \\ \\ \text{S } 20 \quad \quad \text{S } 21 \\ \\ \text{T } 25 \text{ S } \text{ R } 2 \text{ W} \\ 1962 \end{array}$
	from which the remains of an original bearing tree
	A decayed fir stump, 37 ins. diam., bears N. 89° E., 8.6 ft. dist., with scribe marks $1/4$ visible on partially opened blaze.
	and remains of accessories mkd. by Brooks
	A fir, 20 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ E., 25.1 ft. dist., with a healed blaze.
	A sawed fir stump, 42 ins. diam., bears N. 64° W., 36.6 ft. dist., with a healed blaze.
	A steel tube, $\frac{3}{8}$ ins. diam., firmly set, projecting 16 ins. above ground, bears West, 1.5 ft. dist.
	and new bearing tree

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 14 ins. diam., bears N. 37° W., 5.6 ft. dist., mkd. 1/4 S20 BT.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 20' 46" E., beginning new measurement, continue posting and blazing.</p> <p>Ascend SE. slope.</p>
1060	<p>Spur, slopes East; desc. NE. slope.</p>
1322.42	<p>The N 1/16 sec. cor. of secs. 20 and 21, established by Glenn S. Baughman, Registered Land Surveyor No. 536, in 1976, recorded in the Douglas County Surveyor's Office, Map File No. M56-35, and is accepted as the cor., monumented with an iron pipe, 2 ins. diam., firmly set, with no cap, from which bearing trees mkd. by Baughman</p> <p style="text-align: center;">A cedar, 24 ins. diam., bears S. 58° E., 35.7 ft. dist., with healed blaze.</p> <p style="text-align: center;">A fir, 25 ins. diam., bears S. 25° W., 12.3 ft. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, over existing iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 2 W</p> <p style="margin-left: 40px;">N 1/16</p> <p style="margin-left: 40px;"> </p> <p style="margin-left: 20px;">S 20 S 21</p> <p style="margin-left: 40px;"> </p> <p style="margin-left: 40px;">2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 16' 23" E., beginning new measurement, continue posting and blazing.</p> <p>Descend NE. slope.</p>
1165	<p>Creek, 2 ft. wide, course S. 48° E.; asc. steep S. slope.</p>
1320.45	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, 2½ ft. base, with brass cap mkd.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	<div style="text-align: center;"> <table style="margin: auto; border-collapse: collapse;"> <tr><td>T 25 S</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>R 2 W</td></tr> <tr><td>S 17</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>S 16</td></tr> <tr><td colspan="3" style="border-top: 1px solid black;"></td></tr> <tr><td>S 20</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>S 21</td></tr> <tr><td colspan="3" style="text-align: center;">1962</td></tr> </table> </div>	T 25 S		R 2 W	S 17		S 16				S 20		S 21	1962					
T 25 S		R 2 W																	
S 17		S 16																	
S 20		S 21																	
1962																			
	<p>from which an original bearing tree</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 48° W., 31.7 ft. dist., with healed blaze.</p> <p>and the remains of bearing trees mkd. by Brooks</p> <p style="padding-left: 40px;">A chinquapin, 14 ins. diam., bears N. 17¼° E., 11.2 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A dead hemlock, 15 ins. diam., bears S. 74½° E., 39.3 ft. dist., with a healed blaze. (Record, S. 77° E.)</p> <p style="padding-left: 40px;">A cedar, 23 ins. diam., bears S. 87° W., 35.6 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>and new bearing tree</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S. 29° E., 9.8 ft. dist., mkd. T25S R2W S21 BT.</p> <hr/> <p>From the cor. of secs. 15, 16, 21, and 22, hereinbefore described.</p> <p>N. 88° 42' 30" W., bet. secs. 16 and 21, posting and blazing.</p> <p>Descend broken NW. slope.</p>																		
1075	Graveled road, 12 ft. wide, bears S. 37° E. and N. 37° W.																		
1580	Creek, 8 ft. wide, course N. 75° E.; asc. NE. slope.																		
1895	Spur, slopes North; desc. NW. slope.																		
2652.09	The ¼ sec. cor. of secs. 16 and 21, monumented with an iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, in a collar of stone, with brass cap mkd.																		
	<table style="margin: auto; border-collapse: collapse;"> <tr><td>COUNTY</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>SURVEYORS</td></tr> <tr><td>T 25 S</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>S</td></tr> <tr><td>1/4 S 16</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td>21</td></tr> <tr><td>R 2 W</td><td style="border-left: 1px solid black; border-right: 1px solid black;"></td><td></td></tr> <tr><td></td><td></td><td>BLM</td></tr> <tr><td>OFFICE</td><td></td><td>1962</td></tr> </table>	COUNTY		SURVEYORS	T 25 S		S	1/4 S 16		21	R 2 W					BLM	OFFICE		1962
COUNTY		SURVEYORS																	
T 25 S		S																	
1/4 S 16		21																	
R 2 W																			
		BLM																	
OFFICE		1962																	

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which a bearing tree mkd. by Ben B. Irving, Douglas County Surveyor, in 1948, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 8, reported by Brooks</p> <p style="padding-left: 40px;">A cedar, 34 ins. diam., bears S. 35¼° W., 223.7 ft. dist., with healed blaze.</p> <p>and bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1960, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 41, reported by Brooks</p> <p style="padding-left: 40px;">A cedar, 38 ins. diam., bears N. 58° E., 65.3 ft. dist., with healed blaze.</p> <p>and bearing trees mkd. by Randall W. Smith and Stephen J. Flause, Douglas County Surveyor's Office, in 1995, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 136</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 30° E., 28.8 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 42° W., 27.0 ft. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 83° 51' 37" W., beginning new measurement, continue posting and blazing.</p>
50	Asphalt road, 20 ft. wide, bears S. 2° E. and N. 2° W.
400	Creek, 5 ft. wide, course S. 10° W.
795	Rock Creek, 20 ft. wide, course S. 30° E.; asc. steep NE. slope.
1240	Spur, slopes S. 50° E.; desc. broken S. slope.
2380.55	The cor. of secs. 16, 17, 20, and 21, hereinbefore described.
	<hr/> <p>Subdivision of Section 11, T. 25 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>
	<p>From the ¼ sec. cor. of secs 11 and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground, with brass cap mkd.</p>

**Subdivision of Section 11,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	S 11 1/4 ————— S 14 T 25 S R 2 W 1962
	from which the remains of an original bearing tree A cedar snag, 25 ins. diam., bears N. 10¼° W., 7.2 ft. dist., with healed blaze. (Record, N. 4° W.) and remains of a bearing tree mkd. by person(s) unknown, reported by Brooks A roothole, bears S. 62° W., 17.2 ft. dist. and a bearing tree mkd. by Brooks A cedar, 13 ins. diam., bears N. 5¼° E., 22.4 ft. dist., with healed blaze. (Record, N. 8° E.) and the remains of bearing trees mkd. by person(s) unknown, reported by Steven P. Ness, Registered Land Surveyor No. 811, in 1995, recorded in the Douglas County Surveyor's Office, Map File No. M123-3A&B A fir, 42 ins. diam., bears N. 46° W., 7.1 ft. dist., with cruiser marks visible in the bark. A sawed fir stump, 38 ins. diam., bears S. 82° E., 26.2 ft. dist., with healed blaze. and new bearing tree A hemlock, 9 ins. diam., bears S. 21¾° E., 10.8 ft. dist., mkd. 1/4 S14 BT. N. 2° 12' 38" E., on the N. and S. centerline of sec. 11, posting and blazing. Descend steep N. slope.
435	East Fork of Rock Creek, 30 ft. wide, course N. 50° W.; continue over level creek bottom.
805	Asphalt road, 20 ft. wide, bears S. 68° E. and N. 68° W.
950	Ascend broken SE. slope.

**Subdivision of Section 11,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1329.66	<p>The center S 1/16 sec. cor. of sec. 11, established by Steven P. Ness, Registered Land Surveyor No. 811, in 1995, recorded in the Douglas County Surveyor's Office, Map File No. M123-3A&B, and is accepted as the cor., monumented with an iron pipe, 1$\frac{3}{4}$ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 2 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 50px;">S 1/16 S 11</p> <p style="margin-left: 100px;">C</p> <p>1995 RPLS811</p> </div> <p>from which the remains of bearing trees mkd. by Ness</p> <p style="margin-left: 40px;">A sawed fir stump, 11 ins. diam., bears N. 42$\frac{1}{2}$$^{\circ}$ E., 21.4 ft. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 56$\frac{1}{2}$$^{\circ}$ W., 18.3 ft. dist., with healed double blaze.</p> <p>and new bearing tree</p> <p style="margin-left: 40px;">A fir, 6 ins. diam., bears S. 55$\frac{3}{4}$$^{\circ}$ W., 6.3 ft. dist., mkd. CS 1/16 S11 BT.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/> <p>N. 2$^{\circ}$ 12' 38" E., beginning new measurement.</p>
945	<p>Spur, bears N. 16$^{\circ}$ E. and S. 16$^{\circ}$ W.; desc. gentle NW. slope.</p>
1329.70	<p>The center $\frac{1}{4}$ sec. cor. of sec. 11, established by Steven P. Ness, Registered Land Surveyor No. 811, in 1995, recorded in the Douglas County Surveyor's Office, Map File No. M123-3A&B, at the intersection with the E. and W. centerline, and is accepted as the cor., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 25 S R 2 W</p> <p style="margin-left: 100px;">C1/4 S 11</p> <p>1995 RPLS811</p> </div> <p>from which bearing trees mkd. by Ness</p>

**Subdivision of Section 11,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 13 ins. diam., bears S. 39° E., 31.5 ft. dist., with healed double blaze.</p> <p>A fir, 12 ins. diam., bears S. 8° W., 23.0 ft. dist., with healed double blaze.</p> <p>A fir, 13 ins. diam., bears S. 78¾° W., 14.7 ft. dist., with healed blaze.</p> <p>A fir, 14 ins. diam., bears N. 4½° W., 82.7 ft. dist., with healed blaze.</p> <p>From this point the ¼ sec. cor. of secs. 2 and 11, bears N. 2° 12' 38" E., 2831.46 ft. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 2 ¼ ————— S 11 1951</p> <p>from which the remains of an original bearing tree</p> <p>A decayed fir stump, 39 ins. diam., bears N. 18¾° E., 32.0 ft. dist., with no marks visible. (Record, 30.4 ft.)</p> <p>and bearing trees mkd. by V.R. Tracy, Douglas County Surveyor's Office, in 1966, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 58</p> <p>A cedar, 22 ins. diam., bears S. 37½° E., 75.7 ft. dist., with healed double blaze.</p> <p>A fir, 28 ins. diam., bears N. 32½° W., 30.4 ft. dist., with healed blaze.</p> <p>and new bearing tree</p> <p>A fir, 11 ins. diam., bears S. 68¾° W., 9.0 ft. dist., mkd. 1/4 S11 BT.</p> <p>From this same point, the ¼ sec. cor. of secs. 11 and 12 bears S. 89° 14' 05" E., 2584.34 ft. dist., perpetuated by V.W. Hosford, Registered Land Surveyor No. 253, in 1957, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 25 S., R. 2 W., Index No. 29, further perpetuated by Steven P. Ness, Registered Land Surveyor No. 811, in 1995, recorded in the Douglas County Surveyor's Office, Map File No. M123-3A&B, and Douglas County Surveyor's Record of Government</p>

**Subdivision of Section 11,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>Corners Renewed, T. 25 S., R. 2 W., Index No. 140, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 10 ins. above ground, with no cap, from which the remains of the bearing trees mkd. by Hosford</p> <p style="padding-left: 40px;">A fir stump, 48 ins. diam., bears S. $65\frac{1}{4}^{\circ}$ E., 24.8 ft. dist., with scribe marks 25 3 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A cedar stump, 36 ins. diam., bears S. $71\frac{1}{2}^{\circ}$ W., 81.0 ft. dist., with healed blaze.</p> <p>and bearing trees mkd. by Ness</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ W., 25.0 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ W., 38.1 ft. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, over existing iron pipe, in a mound of earth and stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 25 S R 2 W</p> <p style="margin-left: 40px;">1/4</p> <p style="margin-left: 40px;"> </p> <p style="margin-left: 20px;">S 11 S 12</p> <p style="margin-left: 40px;"> </p> <p style="margin-left: 40px;">2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>NOTE: The center E 1/16 sec. cor. of sec. 11 was not searched for.</p> <hr style="width: 50%; margin-left: 0;"/> <p>N. $89^{\circ} 14' 05''$ W., on the E. and W. centerline of sec. 11, posting and blazing.</p> <p>Descend NW. slope.</p> <p>455 Graveled road, 15 ft lks. wide, bears N. 64° E. and S. 64° W.</p> <p>945 End descent; continue over level river bottom.</p> <p>1225 Graveled road, 10 ft lks. wide, bears N. 38° E. and S. 38° W.</p>

**Subdivision of Section 11,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
1695	Rock Creek, 20 ft. wide, course S. 28° W.; continue over level river bottom.
1840	Asphalt road, 20 ft. wide, bears N. 28° E. and S. 28° W.
2315	Dirt road, 12 ft. wide, bears S. 10° E. and N. 10° W.
2430	Ascend E. slope.
2819.40	The ¼ sec. cor. of secs. 10 and 11, hereinbefore described.
<hr/> <p>Subdivision of Section 13, T. 25 S., R. 2 W., Willamette Meridian, Oregon</p> <hr/>	
	From the ¼ sec. cor. of secs. 13 and 24, hereinbefore described.
	N. 2° 26' 47" W., on the N. and S. centerline of sec. 13.
	Descend broken NE. slope.
1311.39	The center S 1/16 sec. cor. of sec. 13, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., perpetuated by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 14 ins. above ground, with no cap, from which the remainins of bearing trees mkd. by Hosford
	A cedar snag, 17 ins. diam., bears N. 86¾° E., 19.1 ft. dist., with healed blaze.
	A decayed hemlock stump, 19 ins. diam., bears N. 59½° W., 34.8 ft. dist., with healed blaze.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. in the ground, over the existing iron pipe, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p>T 25 S R 2 W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;">S 1/16 S 13</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 100px;">2002</p>

**Subdivision of Section 13,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>from which new bearing trees</p> <p style="padding-left: 40px;">A cedar, 12 ins. diam., bears N. $57\frac{1}{4}^{\circ}$ E., 16.2 ft. dist., mkd. CS 1/16 S13 BT.</p> <p style="padding-left: 40px;">A hemlock, 9 ins. diam., bears S. $1\frac{3}{4}^{\circ}$ W., 12.4 ft. dist., mkd. CS 1/16 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $2^{\circ} 27' 18''$ W., beginning new measurement.</p> <p>Descend broken NE. slope.</p>
1315.88	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at the intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 25 S R 2 W C 1/4</p> <p style="text-align: center;">S 13 2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ E., 18.3 ft. dist., mkd. C 1/4 S13 BT.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ W., 42.3 ft. dist., mkd. C 1/4 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
1530	Gravel road, 20 ft. wide, bears S. 84° E. and N. 84° W.
2606.70	Point for the center N 1/16 sec. cor. of sec. 13, not monumented.
3475	East Fork of Rock Creek, 10 ft. wide, course S. 70° W., asc. broken S. slope.
3535	Paved road, 16 ft. wide, bears N. 70° E. and S. 82° W.
3897.52	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, hereinbefore described.

**Subdivision of Section 13,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	From the $\frac{1}{4}$ sec. cor. of sec. 13 only, on the E. bdy. of the Tp., hereinbefore described.
	N. $88^{\circ} 07' 31''$ W., on the E. and W. centerline of sec. 13.
	Descend broken W. slope.
210	Mace Creek, 15 ft. wide, course N. 40° W.; asc broken NE. slope.
1372.12	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 13, not monumented.
1995	Gravel road, 26 ft. wide, bears S. 34° E. and N. 46° W.
2744.24	The center $\frac{1}{4}$ sec. cor. of sec. 13, hereinbefore described.
3395	Spur, slopes N.; desc. broken NW. slope.
3955	Gravel road, 16 ft. wide, bears N. 34° E. and S. 34° W.
3992.03	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 13, not monumented.
4355	Spring branch, 1 ft. wide, course N. 6° E.; asc. broken NE. slope.
5239.82	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, hereinbefore described.
	<hr/>
	From the E $\frac{1}{16}$ sec. cor. of secs. 13 and 24, hereinbefore described.
	N. $1^{\circ} 19' 33''$ W., on the calculated N. and S. centerline of the SE $\frac{1}{4}$ of sec. 13, posting and blazing.
	Descend broken NE. slope
320	Gravel road, 20 ft. wide, bears S. 50° E. and N. 50° W.
1327.25	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 13, at its calculated position.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 S R 2 W SE $\frac{1}{16}$
	S 13 2002
	from which

**Subdivision of Section 13,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p>A hemlock, 9 ins. diam., bears S. 35½° E., 21.2 ft. dist., mkd. SE 1/16 S13 BT.</p> <p>A fir, 11 ins. diam., bears S. 66° W., 12.6 ft. dist., mkd. SE 1/16 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the iron post.</p> <hr/> <p>N. 87° 31' 18" W., on the calculated E. and W. centerline of the SE¼ of sec. 13, posting and blazing.</p> <p>Ascend broken NE. slope.</p>
590	Gravel road, 20 ft. wide, bears S. 33° E. and N. 33° W.
1347.09	The center S 1/16 sec. cor. of sec. 13, hereinbefore described.
	<hr/> <p>From the W 1/16 sec. cor. of secs. 13 and 24, hereinbefore described.</p> <p>N. 0° 46' 45" W., on the N. and S. centerline of the SW¼ of sec. 13, posting and blazing.</p> <p>Descend steep, broken NW. slope.</p>
1323.26	<p>The SW 1/16 sec. cor. of sec. 13, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., perpetuated by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 10 ins. above ground, with no cap, from which bearing trees mkd. by Hosford</p> <p>A cedar, 22 ins. diam., bears N. 66¼° E., 15.4 ft. dist., with healed blaze.</p> <p>A cedar, 22 ins. diam., bears S. 81° W., 24.3 ft. dist., with healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, over the existing iron pipe, with brass cap mkd.</p>
	<p>T 25 S R 2 W SW 1/16 S 13</p> <p>2002</p>

**Subdivision of Section 13,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	<hr/>
	S. 88° 30' 14" E., on the E. and W. centerline of the SW¼ of sec. 13, posting and blazing.
	Ascend steep NW. slope.
495	Spur, slopes North; desc. broken NE. slope.
1283.81	The center S 1/16 sec. cor. of sec. 13, hereinbefore described.
	<hr/>
	From the W 1/16 sec. cor. of secs. 12 and 13, hereinbefore described.
	S. 3° 59' 43" E., on the N. and S. centerline of the NW¼ of sec. 13, posting and blazing.
	Ascend broken NW. slope.
1287.77	The NW 1/16 sec. cor. of sec. 13, established by V.W. Hosford, Oregon Registered Land Surveyor No. 253, in 1953, recorded in the Douglas County Surveyor's Office, C.S. File Nos. 41/245A and 41/245b, and is accepted as the cor., determined at Hosford record bearing and distance from existing remains of bearing trees mkd. by Hosford
	A roothole, bears S. 20° W., 24.8 ft. dist., with fallen cedar trunk, size indeterminate, lying nearby, no marks visible.
	A sawed cedar stump, 25 ins. diam., bears N. 5¼° W., 14.0 ft. dist., with scribe marks S13 25 BT visible on unhealed blaze.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 25 S R 2 W NW 1/16 S 13
	2002
	from which new bearing trees
	A fir, 12 ins. diam., bears S. 67° E., 23.5 ft. dist., mkd. NW 1/16 S13 BT.

**Subdivision of Section 13,
T. 25 S., R. 2 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 18 ins. diam., bears S. 74° W., 12.8 ft. dist., mkd. NW 1/16 S13 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr/> <p>N. 88° 23' 00" W., on the E. and W. centerline of the NW¼ of sec. 13, posting and blazing.</p> <p>Descend broken NW. slope.</p>
855	Spring branch, 5 ft. wide, course N. 29° E.; asc. SE. slope.
1000	Spur, slopes N. 52° E.
1281.92	The N 1/16 sec. cor. of secs. 13 and 14, hereinbefore described.
	<p>GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in mountainous terrain, approximately 6.0 miles northeasterly from the community of Idleyld Park, Oregon.</p> <p>The elevation ranges from about 1050 ft. above sea level near Rock Creek to about 4000 ft. above sea level near the corner of sections 25 and 36 only on the E. bdy. of the Tp.</p> <p>The area is drained by Miller Creek and other tributaries which flow northwesterly to Rock Creek which flows southwesterly to the North Fork of the Umpqua River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>The soil is generally composed of rocky clay, with numerous basalt outcroppings and bluffs, and steep, crumbling rock slopes.</p> <p>Access to the survey was made by graveled roads branching from Rock Creek Road.</p> <p>The mean magnetic declination for the area surveyed is 18° East, as shown on the "HARRINGTON CREEK, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1989.</p>