

FEET

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF
PORTIONS OF THE SOUTH BOUNDARY AND SUBDIVISIONAL LINES
AND THE SUBDIVISION OF SECTION 32,
TOWNSHIP 29 SOUTH, RANGE 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated January 29, 2001, approved
January 30, 2001, which provided for the surveys included under
Group No. 1972, and Assignment Instructions dated March 23, 2001.

Survey commenced April 2, 2001

Survey completed May 23, 2001

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	
	<p>The following field notes are those of the dependent resurvey of portions of the south boundary and subdivisional lines and the subdivision of section 32, township 29 south, range 8 west of the Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the south boundary and subdivisional lines.</p> <p>In 1882, William H. Byars, U.S. Deputy Surveyor, resurveyed the south boundary of T. 29 S., R. 8 W., and surveyed the subdivisional lines of T. 30 S., R. 8 W.</p> <p>In 1965, Donald R. Beck, Cadastral Surveyor, resurveyed a portion of the south boundary and subdivisional lines and subdivided section 31.</p> <p>In 1973 to 1976, Charles E. Akin, Jr., and James E. Jelley, Cadastral Surveyors, and Bruce A. Shaner, Registered Land Surveyor No. 430, under Contract No. 52500-CT5-1117, resurveyed a portion of the south and west boundaries, a portion of the subdivisional lines, and subdivided sections 7 and 13.</p> <p>In 1985, Wayne L. Rogers, Lance J. Bishop, and James L. White, Cadastral Surveyors, resurveyed a portion of the subdivisional lines, and subdivided section 25, T. 30 S., R. 8 W.</p> <p>In 1989 to 1993, Dale T. Bedell and Bryan S. Seibold, Cadastral Surveyors, resurveyed portions of the north boundary and subdivisional lines, T. 30 S., R. 8 W.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated January 29, 2001, for Group No. 1972, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET

proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ in. X ¼ in. magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (91)) of the corner of sections 34 and 35 only, on the south boundary of the township, as determined by direct occupation (see the Control Data Sheet attached to these field notes following the General Description), by the Bureau of Land Management, in 2001, is as follows:

Latitude: 42° 59' 49.666" N. Longitude: 123° 37' 20.935" W.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

(Restoring the 1855 survey by Dennis Hathorn and the
1882 resurvey by William H. Byars)

Beginning at the cor. of secs. 34 and 35 only on the S. bdy. of the Tp., monumented with an iron post, 1½ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S R 8 W

S 34 | S 35

S 2

T 30 S

1970

from which the remains of an original bearing tree

A sawed fir stump, 33 ins. diam., 10 ft. high, bears
S. 43° E., 30.4 ft. dist., with a healed blaze.

and remains of bearing trees mkd. by the Douglas County Surveyor's Office, recorded in the Douglas County Surveyor's Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 500100

A roothole, bears N. 39¾° E., 20.8 ft. dist., with decayed trunk, size indeterminate, lying alongside, no marks visible.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 30 ins. diam., 6 ft. high, bears N. $29\frac{1}{2}^{\circ}$ W., 20.2 ft. dist., with illegible scribe marks visible on a burnt partially healed blaze. (Record, 19.5 ft.)</p> <p>and new bearing trees</p> <p>A cedar, 8 ins. diam., bears N. $31\frac{1}{4}^{\circ}$ E., 37.7 ft. dist., mkd. T29S R8W S35 BT.</p> <p>A fir, 5 ins. diam., bears S. $70\frac{1}{4}^{\circ}$ W., 33.4 ft. dist., mkd. T30S R8W S2 BT.</p> <p>S. $89^{\circ} 04' 47''$ W., on the S. bdy. of sec. 34.</p> <p>Descend over gentle SW. slope.</p>
30	Draw, drains S. 40° E., asc. over E. slope.
195	Graveled Road No. 29-8-1.0, 30 ft. wide, bears N. and S.
242.08	<p>The cor of secs. 2 and 3 only, T. 30 S., R. 8 W., perpetuated by the Douglas County Surveyor's Office, in 1970, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 30 S., R. 8 W., Point Identifier No. 476100, monumented with an iron post, $1\frac{1}{2}$ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 29 S R 8 W S 34</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">S 3 S 2 T 30 S 1970</p> <p>from which the remains of an original bearing tree</p> <p>A sawed fir stump, 46 ins. diam., bears N. 42° E., 21.1 ft. dist., with no marks visible.</p> <p>and remains of bearing trees mkd. by the Douglas County Surveyor's Office</p> <p>A cedar, 11 ins. diam., bears N. 4° E., 33.9 ft. dist., with a healed blaze.</p> <p>A cedar snag, 13 ins. diam., 8 ft. high, bears S. 75° E., 31.7 ft. dist., with scribe marks T30S R8W S2 CS on upper and BT visible on lower partially healed blazes.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A roothole bears S. 2° W., 11.5 ft. dist., with sawed stump, 33 ins. diam., lying alongside, with no marks visible.</p> <p>and remains of a unrecorded bearing tree mkd. by person(s) unknown</p> <p>A sawed cedar stump, 24 ins. diam., bears N. 9¼° E., 26.9 ft. dist., with an X mkd. in the bark and a healed blaze.</p> <p>and a new reference monument</p> <p>A rebar, 36 ins. long, 5/8 in. diam., driven 35 ins. in the ground for a reference monument, bears S. 65°14'09" E., 32.32 ft. dist., with alum. cap mkd. RM T30S R8W S2 32.32 FT TO COR 2001 and an arrow pointing to the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 12' 50" W., beginning new measurement, posting and blazing.</p>
745	<p>Spur, slopes North; desc. over NW. slope.</p>
1073.22	<p>The E. 1/16 sec. cor. of sec 34 only, established by Howard W. Johnstone, Registered Professional Land Surveyor No. 498, in 1979, recorded in the Douglas County Surveyor's Office, Map File No. 79-15, and is accepted as the cor.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">R8W SEC 34 E 1/16 1979 T29S LS498</p> <p>from which bearing trees mkd. by Johnstone</p> <p>A fir, 10 ins. diam., bears N. 59¾° E., 4.0 ft. dist., with a healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 10¼° W., 19.4 ft. dist., with a healed blaze.</p> <p>From this point, an unrecorded iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground with no cap, set by person(s) unknown, bears N. 17°48'30" E., 9.30 ft. dist. This point is not utilized in the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 10' 40" W., beginning new measurement, posting and blazing.</p>
75	<p>Draw, drains N. 32° E., asc. over steep NE. slope.</p>

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
540	Spur, slopes North; desc. over gentle NW. slope.
830	Dirt road, 15 ft. wide, bears N. 15° E. and S. 15° E.
885	Dirt road, 20 ft. wide, bears S. 50° E. and N. 50° W.
1314.27	<p>The ¼ sec. cor. of sec. 34 only, reestablished by Howard W. Johnstone, Registered Professional Land Surveyor No. 498, in 1979, recorded in the Douglas County Surveyor's Office, Map File No. 79-15, and the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 440100. There is no remaining evidence of the original corner, therefore this point is accepted as the cor.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 15 ins. above ground, with aluminum cap mkd.</p> <p style="text-align: center;">R8W SEC 34 1/4 S34 ONLY 1979 T29S LS498</p> <p>from which bearing trees mkd. by Johnstone</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 77° E., 41.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 42° E., 19.5 ft. dist., with a healed blaze.</p> <p>From this point, an unrecorded iron pipe, 1½ ins. diam., firmly set, projecting 6 ins. above ground with no cap, set by person(s) unknown, bears N. 12° 03' 31" E., 17.20 ft. dist. This point is not utilized in the course of this survey.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 89° 11' 25" W., beginning new measurement, posting and blazing.</p>
265	Draw, drains S. 20° W., asc. over broken SE. slope.
545	Spur, slopes S. 14° E; continue ascent over broken SE. slope.
1030	Ridge, bears N. 40° E. and S. 40° W.; desc. over NW. slope.
1314.26	The W. 1/16 sec. cor. of sec. 34 only, established by Howard W. Johnstone, Registered Professional Land Surveyor No. 498 in 1979, recorded in the Douglas County Surveyor's Office, Map File No. 79-15, and is accepted as the cor.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 8 ins. above ground, with aluminum cap mkd.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET																			
	R8W SEC 34 W 1/16 1979 T29S LS498																		
	from which bearing trees mkd. by Johnstone																		
	<p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 81¼° E., 14.3 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir, 14 ins. diam., bears S. 69° E., 16.0 ft. dist., with a healed blaze.</p>																		
	<hr style="width: 20%; margin: 0 auto;"/>																		
	S. 89° 11' 06" W., beginning new measurement, posting and blazing.																		
	Ascend over steep NE. slope.																		
152	Spur, slopes N. 54° W.; desc. over steep W. slope.																		
803	Dirt road, 12 ft. wide, bears N. 10° E. and S. 10° W.																		
1315.06	<p>The cor. of secs. 33 and 34 only, reestablished by Howard W. Johnstone, Registered Professional Land Surveyor No. 498 in 1979, recorded in the Douglas County Surveyor's Office, Map File No. 79-15, and the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 400100. There is no remaining evidence of the original corner, therefore this point is accepted as the cor.; monumented with a rebar, 5/8 in. diam., firmly set, projecting 14 ins. above ground, with aluminum cap mkd.</p>																		
	<table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td></td> <td style="text-align: center;">T 29 S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">33 34</td> <td style="text-align: center;">R</td> </tr> <tr> <td></td> <td style="text-align: center;">-----</td> <td style="text-align: center;">8</td> </tr> <tr> <td style="text-align: center;">1979</td> <td style="text-align: center;">3</td> <td style="text-align: center;">W</td> </tr> <tr> <td></td> <td style="text-align: center;">T 30 S</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">LS498</td> <td></td> </tr> </table>		T 29 S			33 34	R		-----	8	1979	3	W		T 30 S			LS498	
	T 29 S																		
	33 34	R																	
	-----	8																	
1979	3	W																	
	T 30 S																		
	LS498																		
	from which the remains of bearing trees mkd. by Johnstone																		
	<p style="margin-left: 40px;">A fir stump, 15 ins. diam., bears N. 29¼° E., 45.9 ft. dist., with a healed blaze.</p> <p style="margin-left: 40px;">A fir stump, 28 ins. diam., bears S. 20° E., 44.9 ft. dist., with fragmentary scribe marks visible on a charred partially healed blaze.</p>																		

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET										
	<p>A fir, 25 ins. diam., bears N. 59½° W., 16.0 ft. dist., with fragmentary scribe marks visible on a charred partially healed blaze.</p> <hr/> <p>N. 87° 45' 57" W., on the S. bdy of sec. 33, posting and blazing.</p> <p>Descend steep W. slope.</p>									
97.09	<p>The cor. of secs. 3 and 4, T. 30 S., R. 8 W., monumented with an iron post, 1½ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p> <p align="center">COUNTY SURVEYORS OFFICE T 29 S R 8 W S 33</p> <table border="1" data-bbox="841 808 998 919" style="margin-left: auto; margin-right: auto;"> <tr> <td style="border: none;">S 4</td> <td style="border: none;"> </td> <td style="border: none;">S 3</td> </tr> <tr> <td colspan="3" style="border: none; text-align: center;">T 30 S R 8 W</td> </tr> <tr> <td colspan="3" style="border: none; text-align: center;">1967</td> </tr> </table> <p>from which an original bearing tree</p> <p>A fir, 14 ins. diam., bears S. 50¾° E., 11.2 ft. dist., with a healed blaze. (Record, S. 52° E., 10.5 ft.)</p> <p>and a bearing tree mkd. by Boyer, recorded in the Douglas County Surveyor's Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 378100</p> <p>A fir, 20 ins. diam., bears S. 11¾° W., 23.0 ft. dist., with a healed blaze. (Record, S. 13° W., 24.4 ft.)</p> <p>and a bearing tree mkd. by Powell, recorded in the Douglas County Surveyors Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 378100</p> <p>A hemlock, 21 ins. diam., bears N. 8¾° E., 13.2 ft. dist., with a healed double blaze. (Record, fir, N. 7¾° E.)</p> <p>and a unrecorded bearing tree mkd. by person(s) unknown</p> <p>A fir, 13 ins. diam., bears N. 62¼° W., 26.9 ft. dist., with scribe marks T29 R8 S33 BT visible on unhealed blaze.</p> <p>From this point, a point established as the cor. of secs. 3 and 4 only, by Howard W. Johnstone, Registered Professional Land Surveyor No. 498 in 1979, recorded in the Douglas County Surveyor's Office, Map File No. 79-15, and Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier 378100, bears S. 2° 16' 09" E., 5.28 ft. dist. (record, S. 0° 15' E.), monumented with a rebar, 5/8 in. diam., firmly set projecting</p>	S 4		S 3	T 30 S R 8 W			1967		
S 4		S 3								
T 30 S R 8 W										
1967										

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	19 ins. above the ground with aluminum cap marked, T29S R8W 33 3 4 T30S 1979 LS498. This cor. was not correctly positioned and is not utilized in the course of this survey.

	S. 89° 07' 14" W., beginning new measurement, posting and blazing.
	Continue descent over steep W. slope.
230	Berry Creek, 9 ft. wide, course N. 30° W.; asc. over E. slope.
655	Spur, slopes N. 27° W.; desc. over NW. slope.
780	Ravine, drains N. 20° W., asc. over NE. slope.
855	Spur, slopes North; desc. over N. slope.
1145	Spring branch, 4 ft. wide, course N. 52° E.; asc. over E. slope.
2350	Ridge, bears N. 15° E. and S. 15° W.; desc. over NW. slope.
2531.00	Point for the ¼ sec. cor. of sec. 33 only at proportionate dist.; there is no remaining evidence of the original corner.
	<hr/>
	Note: The Byars survey contains a blunder and was rejected for proportioning longitudinally, in favor of the original Hathorn record. The Byars corner of sections 3 and 4 only along with the original Hathorn corner of sections 4, 5, 32, and 33 were utilized as control latitudinally.
	<hr/>
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 29 S R 8 W ¼ S 33 _____
	T 30 S R 8 W 2001
	from which
	A fir, 22 ins. diam., bears N. 37¾° E., 8.4 ft. dist., mkd. 1/4 S33 BT.
	A fir, 8 ins. diam., bears N. 79½° W., 24.2 ft. dist., mkd. 1/4 S33 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	Continue ascent over NW. slope.
3050	Graveled road, 15 ft. wide, bears N. 24° E. and S. 24° W.
4050	Spring branch, 3 ft. wide, course N. 30° W.; asc. over NE. slope.
4120	Spur, slopes N. 20° W.; desc. over steep NW. slope.
4920	Ravine, drains N. 40° W., asc. over NE. slope.
5159.02	The cor. of secs. 4, 5, 32, and 33 on the S. bdy. of the Tp., monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.
	COUNTY SURVEYORS OFFICE T 29 S R 8 W S 32 S 33 ----- S 5 S 4 T 30 S R 8 W 1958
	from which the remains of the original bearing trees
	A cedar, 31 ins. diam., bears S. 24° W., 19.8 ft. dist., with scribe marks 30 R8W 5 visible on a partially healed blaze.
	A madrone snag, size indeterminate, bears N. 50° W., 19.1 ft. dist., with no marks visible.
	and the remains of bearing trees mkd. by Boyer
	A fir, 37 ins. diam., bears N. 5½° E., 25.4 ft. dist., with scribe marks T29S R8W CS BT visible on a bark blaze.
	A fir snag, 61 ins. diam., bears S. 18° E., 50.0 ft. dist., with scribe marks S4 30/8 CS BT visible on a bark blaze. (Record, S. 10° E., 52.1 ft.)
	and the remains of a bearing tree mkd. by Byron, recorded in the Douglas County Surveyor's Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 300100.
	A decayed stump, 17 ins. diam., bears N. 36° W., 39.6 ft. dist., with no marks visible.
	and bearing trees mkd. by Bedell and Seibold
	A fir, 18 ins. diam., bears S. 37° E., 33.3 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.

**Dependent Resurvey of a Portion of the South Boundary,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET													
	<p>A fir, 23 ins. diam., bears N. 75° W., 89.1 ft. dist., with scribe marks R8W S32 BT visible on a partially healed blaze.</p> <p>Corner is located approx. 80 ft. E. of the end of a dirt road which bears N. and S.</p>												
	<hr/> <p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 29 S., R. 8 W., Willamette Meridian, Oregon</p> <hr/>												
	<p>(Restoring the 1855 survey by Dennis Hathorn</p> <hr style="width: 20%; margin: auto;"/>												
	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp. N. 0° 02' 10" E., bet. secs. 32 and 33, posting and blazing.</p> <p>Descend over N. slope.</p>												
680	Spring branch, 2 ft. wide, course S. 87° W.; asc. over S. slope.												
1145	Ridge, bears N. 86° E. and S. 86° W.; desc. over NE. slope.												
1490	Creek, 2 ft. wide, course S. 84° W.; asc. over moderate SW. slope.												
2115	Graveled road, 10 ft. wide, bears S. 61° E. and N. 61° W.												
2320	Spur, slopes N. 90° W.; desc. over gentle NW. slope.												
2637.56	<p>The ¼ sec. cor. of secs. 32 and 33, reestablished at proportionate dist. by Arthur Boyer, Douglas County Surveyor, in 1939, recorded in the Douglas County Surveyor's Office C.S. file 16/25, subsequently perpetuated by James W. Byron, Douglas County Deputy Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 300140. There is no remaining evidence of the original corner, therefore this point is accepted as the cor.; monumented with an iron post, 1½ ins. diam., firmly set, projecting 13 ins. above ground, with brass cap mkd.</p>												
	<p>COUNTY SURVEYORS OFFICE</p> <table style="margin: auto;"> <tr> <td style="text-align: center;">1/4 S</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S</td> </tr> <tr> <td style="text-align: center;">32</td> <td style="text-align: center;"> </td> <td style="text-align: center;">33</td> </tr> <tr> <td colspan="3" style="text-align: center;">T 29 S R 8 W</td> </tr> <tr> <td colspan="3" style="text-align: center;">1958</td> </tr> </table>	1/4 S		S	32		33	T 29 S R 8 W			1958		
1/4 S		S											
32		33											
T 29 S R 8 W													
1958													
	<p>from which the remains of bearing trees mkd. by Boyer</p>												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>A cedar, 45 ins. diam., bears N. 57½° E., 25.1 ft. dist., with scribe marks S33 T29 R8 CS BT visible on a partially healed blaze.</p> <p>A roothole bears S. 30¾° W., 14.8 ft. dist., with fallen sawed stump, 32 ins. diam., lying alongside, with no marks visible.</p> <p>and a bearing tree mkd. by Byron</p> <p>A fir, 21 ins. diam., bears S. 79° W., 17.2 ft. dist., with a healed double blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 00' 48" W., beginning new measurement, posting and blazing.</p> <p>Continue descent over N. slope.</p>
1170	Thompson Creek, 3 ft. wide, course N. 75° W.; asc. over moderate SW. slope.
2205	Ridge, bears N. 90° E. and N. 90° W.; desc. over N. slope.
2495	Spring branch, 2 ft. wide, course N. 40° W.; asc. over SW. slope.
2645.44	<p>The cor. of secs 28, 29, 32, and 33, perpetuated by H.L. Eppstein, Douglas County Surveyor, in 1931, from original evidence no longer in existence, further perpetuated by Howard W. Johnstone, Registered Professional Land Surveyor No. 498 in 1961, and further perpetuated by Ronald Geisler, Registered Professional Land Surveyor No. 1988, in 1986, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 300200; monumented with an iron pipe, 1¼ ins. diam., firmly set, projecting 6 ins. above ground, with no cap, from which the remains of bearing trees mkd. by Johnstone</p> <p>A cedar, 17 ins. diam., bears N. 46° E., 126.6 ft. dist., with scribe marks 29 R8W S28 on upper and BT visible on lower partially healed blazes.</p> <p>A cedar stob, 6 ins. diam., bears S. 25¼° E., 138.5 ft. dist., with scribe marks 33 on upper and BT visible on lower unhealed blazes.</p> <p>A fir, 15 ins. diam., bears S. 80° W., 51.8 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Geisler</p> <p>A fir, 21 ins. diam., bears S. 47° E., 28.5 ft. dist., with a healed double blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET													
	<p>A fir, 14 ins. diam., bears N. 67° W., 23.5 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the existing iron pipe, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 0 5px;">T 29</td> <td style="padding: 0 5px;">S R</td> <td style="padding: 0 5px;">8 W</td> </tr> <tr> <td style="padding: 0 5px;">S 29</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 28</td> <td></td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 0 5px;">S 32</td> <td style="border-left: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S 33</td> <td></td> </tr> <tr> <td></td> <td style="padding: 0 5px;">2001</td> <td></td> </tr> </table> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located 54 ft. S. and 73 ft. W. of Road No. 29-8-29.3, a gravel road 12 ft. wide, bears S. 51° E. and N. 51° W.</p> <hr/> <p>N. 89° 42' 23" W., bet. secs. 29 and 32, posting and blazing.</p> <p>Descend over moderate SW. slope.</p>	T 29	S R	8 W	S 29	S 28		S 32	S 33			2001	
T 29	S R	8 W											
S 29	S 28												
S 32	S 33												
	2001												
270	Spring branch, 2 ft. wide, course N. 54° W.												
1610	Graveled road, 10 ft. wide, bears N. 10° E. and S. 10° E.												
2145	Thompson Creek, 3 ft. wide, course N. 40° W.; asc. over NE. slope.												
2630.68	<p>The ¼ sec. cor. of secs. 29 and 32, reestablished by Arthur Boyer, Douglas County Surveyor, in 1939, recorded in the Douglas County Surveyor's Office, C.S. file 16\25 and further perpetuated by James W. Byron, Douglas County Deputy Surveyor, in 1958, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 240200. There is no remaining evidence of the original corner, therefore this point is accepted as the cor.; monumented with an iron pipe, 1 in. diam., firmly set flush with surface of Burma Road, with no cap, from which the remains of bearing trees mkd. by Boyer</p> <p style="padding-left: 40px;">A sawed fir stump, 32 ins. diam., bears N. 6¼° E., 55.9 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A decayed madrone stump, size indeterminate, bears S. 38° E., 118.8 ft. dist., with no marks visible.</p> <p>and bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 21 ins. diam., bears N. 11¼° E., 52.9 ft. dist., with a healed double blaze.</p>												

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 14 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ E., 56.9 ft. dist., with a healed double blaze.</p> <p>At the corner point</p> <p>Drive an aluminum cap, $3\frac{1}{2}$ ins. diam., on top of iron pipe, mkd.</p> <p style="text-align: center;">T 29 S R 8 W S 29 1/4 ————— S 32 2001</p> <p>from which</p> <p style="text-align: center;">The NW. cor. of a frame house, 20 X 50 ft., bears S. $\frac{1}{2}^{\circ}$ W., 164.3 ft. dist., long side bears south.</p> <p>Corner is buried 3 ins. below road surface.</p> <p style="text-align: center;">—————</p> <p>S. $88^{\circ} 27' 29''$ W., beginning new measurement, posting and blazing.</p> <p>Descend over gentle W. slope.</p>
445	Two strand utility line, bears S. 27° E. and N. 27° W.
521.82	<p>Property cor. established by Glenn S. Baughman, Registered Professional Land Surveyor No. 536, in 1974, recorded in the Douglas County Surveyor's Office, C.S. File No. 55/334-2, and now functions as an angle point on the line; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 7 ins. above ground, with no cap, from which a bearing tree mkd. by Baughman</p> <p style="text-align: center;">A madrone, 11 ins. diam., bears N. $73\frac{3}{4}^{\circ}$ E., 5.2 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>At the corner point</p> <p>Cement a brass cap, $3\frac{1}{2}$ ins. diam., on top of iron pipe, mkd.</p> <p style="text-align: center;">AP T 29 S R 8 W S 29 ————— S 32 2001</p> <p>Corner is located 8.0 ft. north of the intersection of barbed wire fences extending E., S., and W.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
1313.80	<p>The W 1/16 sec. cor. of secs. 29 and 32, established by person(s) unknown, and is accepted as the cor.; monumented with a drill steel, 1 in. diam., firmly set, projecting 2 ins. above ground, with no cap.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over the existing drill steel, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 8 W</p> <p>S 29</p> <p>W 1/16 —————</p> <p>S 32</p> <p>2001</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. 72½° E., 23.8 ft. dist., mkd. W 1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears S. 26½° E., 16.1 ft. dist., mkd. X BT.</p> <p>Corner is located at the intersection of barbed wire fences extending E., S. and W.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 46' 33" W., beginning new measurement.</p> <p>Continue descent over gentle W. slope.</p>
1314.83	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 8 W</p> <p>S 30 S 29</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 31 S 32</p> <p>1965</p> </div> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">An oak, 21 ins. diam., bears S. 76¾° E., 68.6 ft. dist., with no scribe marks visible on partially healed blaze. (Record, S. 75¼° E.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET

A sawed fir stump, 48 ins. diam., bears S. $8\frac{3}{4}^{\circ}$ W.,
116.8 ft. dist., with a healed blaze. (Record, S. 10° W.)

and the remains of a bearing tree mkd. by Cole, recorded in the
Douglas County Surveyor's Office, records of Government Corners
Renewed, T. 29 S., R. 8 W., Point Identifier No. 200200.

A fir stump, 27 ins. diam., bears S. 46° E., 28.4 ft. dist.,
with no marks visible.

and a bearing tree mkd. by Byron, recorded in the Douglas County
Surveyor's Office, records of Government Corners Renewed,
T. 29 S., R. 8 W., Point Identifier No. 200200.

A fir, 17 ins. diam., bears N. $57\frac{1}{4}^{\circ}$ E., 13.5 ft. dist., with
a healed double blaze. (Record, N. 59° E.)

and bearing trees mkd. by Beck

A fir, 20 ins. diam., bears S. $4\frac{1}{2}^{\circ}$ W., 93.0 ft. dist., with
a healed blaze. (Record, S. $5\frac{1}{2}^{\circ}$ W.)

A fir, 27 ins. diam., bears N. 65° W., 84.5 ft. dist., with
a healed double blaze.

Corner is located approx. 40 ft. E. of Buck Springs Road, at the
intersection of barbed wire fence, extending N., E., S., and W.

**Subdivision of Section 32,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

From the $\frac{1}{4}$ sec. cor. of sec. 32 only, on the S. bdy. of the Tp.,
monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set,
projecting 5 ins. above the ground, with brass cap mkd.

T 29 S R 8 W

$\frac{1}{4}$ S 32

T 30 S R 8 W

1993

from which bearing trees mkd. Bedell and Seibold

A hemlock, 6 ins. diam., bears N. $41\frac{1}{2}^{\circ}$ E., 35 ft. dist., with
illegible scribe marks visible on partially healed blaze.

A cedar, 18 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 29.0 ft. dist.,
with fragmentary scribe marks visible on partially healed
blaze.

**Subdivision of Section 32,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	<p>From this point, the $\frac{1}{4}$ sec. cor. of sec. 5 only on the south bdy. of the Tp., bears N. $89^{\circ} 35' 39''$ E., 45.10 ft. dist., monumented with a stainless steel post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. T29S R8W $\frac{1}{4}$ S5 T30S R8W 1993, from which the remains of bearing trees mkd. by Boyer, recorded in the Douglas County Surveyor's Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 239100</p> <p style="padding-left: 40px;">A cedar, 62 ins. diam., bears S. $76\frac{1}{4}^{\circ}$ E., 25.7 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A sawed cedar stump, 28 ins. diam., bears N. $10\frac{3}{4}^{\circ}$ W., 4.6 ft. dist., with fragmentary scribe marks visible on pieces of wood lying alongside.</p> <p>and bearing trees mkd. by Bedell and Seibold</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. 61° E., 21.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 22° W., 20.5 ft. dist., with a healed blaze.</p> <p>N. $0^{\circ} 16' 04''$ E., on the N. and S. centerline of sec. 32, posting and blazing</p> <p>Descend over broken NE. slope</p>
515	Spring branch, 2 ft. wide, course N. 5° W.
1345	Abandoned dirt road, 20 ft. wide, bears S. 84° E. and N. 84° W.
1515	Noah Creek, 6 ft. wide, course N. 75° W.; asc. over broken SW. slope.
2235	Spur, slopes N. 63° W.; desc. over gentle NE. slope.
2664.37	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 32, at intersection with the E. and W. centerline.</p> <p>Drive a rebar, 36 ins. long, $\frac{5}{8}$ in. diam., 30 ins. in the ground into a tree root, with aluminum cap, $2\frac{1}{2}$ ins. diam., mkd.</p> <p style="text-align: center;">T 29 S R 8 W C $\frac{1}{4}$ S 32 2001</p> <p>from which</p>

**Subdivision of Section 32,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
	A fir, 18 ins. diam., bears N. 62½° E., 3.4 ft. dist., mkd. C1/4 S32 BT.
	A fir, 16 ins. diam., bears S. 7¼° W., 4.1 ft. dist., mkd. C1/4 S32 BT.
	A stainless steel post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 42° 25' 59" W., 9.90 ft. dist., with brass cap mkd. RM T29S R8W C1/4 S32 9.90 FT TO COR 2001 and an arrow pointing to the corner.
	Descend broken NE. slope; discontinue posting and blazing.
3135	Dirt road, 10 ft. wide, bears S. 40° E. and N. 16° W., in a curve.
3300	Creek, 2 ft. wide, course N. 60° W.; asc. over broken SW. slope.
4420	Descend over gentle NW. slope.
5340.46	The ¼ sec. cor. of secs. 29 and 32.
	<hr/>
	From the ¼ sec. cor. of secs. 32 and 33.
	S. 89° 37' 45" W., on the E. and W. centerline of sec. 32.
	Descend over broken NW. slope.
285	Graveled road, 10 ft. wide, bears S. 17° E. and N. 17° W.
400	Graveled road, 16 ft. wide, bears N. 44° E. and S. 44° W.
670	Graveled road, 12 ft. wide, bears S. 60° E. and N. 60° W.
1505	Abandoned dirt road, 12 ft. wide, bears S. 24° E. and N. 24° W.
1795	Spring branch, 2 ft. wide, course N. 40° W.; asc. over NE. slope.
2565	Spur, slopes N. 48° W., and dirt road, 16 ft. wide, bears S. 58° E. and N. 48° W.; continue over flat slope.
2644.12	The center ¼ sec. cor. of sec. 32.
	Descend over broken SW. slope; begin posting and blazing.
3950	Noah Creek, 3 ft. wide, course N. 48° W.; asc. over moderate E. slope.
4485	Spur, slopes North; desc. over gentle NW. slope.

**Subdivision of Section 32,
T. 29 S., R. 8 W., Willamette Meridian, Oregon**

FEET	
5260.38	<p>The ¼ sec. cor. of secs. 31 and 32, monumented with an iron post, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> COUNTY SURVEYORS BLM 1965 1/4 S S 31 32 T 29 S R 8 W OFFICE 1958 </p> <p>from which bearing trees mkd. by Byron, recorded in the Douglas County Surveyor's Office, records of Government Corners Renewed, T. 29 S., R. 8 W., Point Identifier No. 200140</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 19° E., 12.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A cedar, 28 ins. diam., bears N. 55½° W., 40.9 ft. dist., with a healed blaze.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The lands included in the foregoing survey are located in mountainous terrain, approximately 3.0 miles southeasterly from the community of Camas Valley, Oregon.</p> <p>The elevation ranges from about 1200 feet above sea level near the northwest cor. of sec. 32 and Buck Springs Road to about 2200 feet above sea level near the south ¼ sec. cor. of sec. 34.</p> <p>The area is drained by Berry Creek, which flows northerly to the South Fork of the Umpqua River, and Thompson Creek and Noah Creek, which flow northwesterly to the Middle Fork of the Coquille River.</p> <p>Timber consists of fir, cedar, chinquapin, maple, madrone, and oak. Undergrowth consists of salal, vine maple, poison oak, Oregon grape, and fern.</p> <p>The soil is generally composed of rocky clay, with numerous basalt outcroppings and bluffs, and steep, crumbling rock slopes.</p> <p>Access to the survey was made by paved and graveled roads branching from State Highway No. 42 and Buck Springs Road.</p>

T. 29 S., R. 8 W., Willamette Meridian, Oregon

FEET	<p>The mean magnetic declination for the area surveyed is 18° East, as shown on the "CAMAS VALLEY, OREGON" 7½ minute series quadrangle map, Provisional Edition, prepared by the United States Geological Survey, in 1990.</p>
------	--