

FEET

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE
WEST BOUNDARY AND SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTION 7,

TOWNSHIP 33 SOUTH, RANGE 5 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY

Francis J Simon, Cadastral Surveyor

Under Special Instructions dated and approved May 11, 2001,
which provided for the surveys included under Group No. 1989,
and Assignment Instructions dated May 18, 2001.

Survey commenced July 9, 2001

Survey completed August 16, 2001

T. 33 S., R. 5 W., Willamette Meridian, Oregon

| | |
|------|--|
| FEET | <p>The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines, and the subdivision of section 7, township 33 south, range 5 west, Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1854, Butler Ives and George W. Hyde, U.S. Deputy Surveyors, surveyed the west boundary of the township.</p> <p>In 1855, Wells Lake and George W. Hyde, U.S. Deputy Surveyors, surveyed a portion of the subdivisional lines of T. 33 S., R. 6 W.</p> <p>In 1894, Edward F. Sharp, U.S. Deputy Surveyor, surveyed the subdivisional lines of the township.</p> <p>In 1966-67, Joseph S. Gawron, John M. Jelly, and Rollin D. Aanrud, Cadastral Surveyors, remonumented certain original corner points without survey.</p> <p>In 1974, Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors, remonumented certain original corner points without survey.</p> <p>In 1989-92, Terrence O. Nickerson, Cadastral Surveyor, resurveyed a portion of the north boundary (Seventh Standard Parallel South), a portion of the west boundary and subdivisional lines, and subdivided section 6.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated May 11, 2001, for Group No. 1989, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distances and directions have been adjusted by Cadastral Measurement Management (CMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot.</p> <p>Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Lost corners were reestablished and remonumented at</p> |
|------|--|

T. 33 S., R. 5 W., Willamette Meridian, Oregon

FEET

proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1927) of the corner of sections 5, 6, 7, and 8, calculated from record data to the ¼ section corner of sections 5 and 6, as shown on the official plat of survey accepted July 31, 1992, is as follows:

Latitude: 42° 43' 29.62" N. Longitude: 123° 19' 38.95" W.

**Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

(Restoring the survey by Butler Ives and George Hyde, in 1854)

Beginning at the corner of secs. 7, 12, 13, and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

| | |
|--------|-------|
| T 33 S | |
| R 6 W | R 5 W |
| S 12 | S 7 |
| ----- | |
| S 13 | S 18 |
| 1966 | |

from which the remaining original bearing tree

A cedar, 38 ins. diam., bears S. 70° W., 36.3 ft. dist., with scribe marks 33 13 visible on open upper blaze, and healed lower blaze.

and the remains of bearing trees mkd. by Gawron, Jelley, and Aanrud

A root hole, bears N. 30° E., 15.2 ft. dist., with a down fir alongside, 22 ins. diam., with healed blaze.

A cedar, 13 ins. diam., bears S. 35½° E., 37.3 ft. dist., with healed blaze. (Record, S. 37° E., 38.3 ft. dist.)

**Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>A sawed fir stump, 12 ins. diam., bears S. 50° W., 42.9 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 24 ins. diam., bears N. 61° W., 16.8 ft. dist., with no marks visible on partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 11 ins. diam., bears N. 41° E., 57.0 ft. dist., mkd. T33S R5W S7 BT.</p> <p>A fir, 11 ins. diam., bears N. 7° W., 55.9 ft. dist., mkd. T33S R6W S12 BT.</p> <p>N. 0° 06' 55" E., bet. secs. 7 and 12.</p> <p>Descend NW. slope, along E. edge of recently logged timber and W. edge of heavy timber.</p> |
| 1800 | <p>Speaker Road, asphalt surface, 20 ft. wide, bears N. 65° E. and S. 65° W.; ascend SE. slope, through medium timber.</p> |
| 2661.96 | <p>Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate distance, there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 6 W R 5 W 1/4 S 12 S 7 2001</p> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears N. 7½° E., 9.4 ft. dist., mkd. 1/4 S7 BT.</p> <p>A fir, 9 ins. diam., bears N. 89¾° W., 10.8 ft. dist., mkd. 1/4 S12 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend steep SE. slope, through heavy timber, marking and blazing the line.</p> |

**Dependent Resurvey of a Portion of the West Boundary,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | | | | | |
|---------|--|---|---|----|---|
| 3450 | Saddle in ridge, bears N. 40° E. and S. 40° W.; descend steep NW. slope. | | | | |
| 4500 | Sourdough Gulch, 2 ft. wide, drains S. 60° W.; ascend S. slope. | | | | |
| 5323.92 | <p>The cor. of secs. 1, 6, 7, and 12, perpetuated by the County Surveyor's Office in 1974, C.S. book 6, page 263, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYOR R 6 W R 5 W T 33 S</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1</td> <td style="padding: 0 5px;">6</td> </tr> <tr> <td style="border-right: 1px solid black; border-top: 1px solid black; padding: 0 5px;">12</td> <td style="border-top: 1px solid black; padding: 0 5px;">7</td> </tr> </table> <p>1974</p> </div> <p>from which remains of original bearing trees</p> <p style="padding-left: 40px;">A burned cedar stump, size indeterminate, bears N. 51° E., 21.8 ft. dist., with scribe marks BT visible on burned blaze.</p> <p style="padding-left: 40px;">A root hole, bears S. 53° E., 29.0 ft. dist., with dead and down oak alongside, size indeterminate, no marks visible.</p> <p>and bearing trees mkd. by the County Surveyor's Office</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 42° E., 24.4 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 73° E., 17.5 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone, 14 ins. diam., bears N. 81½° W., 15.1 ft. dist., with healed blaze point.</p> <p>From this point, a point established by H. W. Lawrence, Registered Professional Engineer No. 1543, in 1951, recorded survey no. 47-51, and not utilized in this survey or by the County Surveyor's Office, in 1974, bears N. 41° 00' 00" W., 1.55 ft. dist., from which a bearing tree mkd by Lawrence</p> <p style="padding-left: 40px;">A madrone, 10 ins. diam., bears S. 77¾° W., 11.8 ft. dist., with scribe marks BT visible on partially healed blaze.</p> <hr style="width: 60%; margin-left: 40px;"/> | 1 | 6 | 12 | 7 |
| 1 | 6 | | | | |
| 12 | 7 | | | | |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

FEET

(Restoring the survey by Edward F. Sharp, in 1894,
the remonumentation by Joseph S. Gawron, John M. Jelley,
and Rollin D. Aanrud, in 1965-67, the remonumentation by
Lynn M. Roseberry and Larry D. Evans, in 1974, and
the resurvey by Terrence O. Nickerson, in 1989-92)

From the cor. of secs. 7, 8, 17, and 18, perpetuated by Gerald V. Nygren, Registered Land Surveyor No. 1035, in 1991, recorded survey no. 86-91, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with a yellow plastic cap mkd. NYGREN LS 1035, (alongside is a basalt stone, 10 x 12 x 18 ins. with 4 grooves on one face) from which bearing trees mkd. by Nygren

A black oak, 8 ins. diam., bears N. $4\frac{3}{4}^{\circ}$ E., 43.4 ft. dist., with scribe marks T33S R5W S8 BT visible on partially healed double blaze.

A white oak, 6 ins. diam., bears S. 70° E., 3.1 ft. dist., with healed double blaze.

A triple trunk black oak, 7 ins. diam., bears S. 68° W., 29.3 ft. dist., with scribe marks T33S R5W S18 BT visible on partially healed blaze.

A white oak, 6 ins. diam., bears N. $73\frac{3}{4}^{\circ}$ W., 10.7 ft. dist., with illegible scribe marks visible on partially healed double blaze.

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, directly over iron rod, with brass cap mkd.

| | |
|--------|-------|
| T 33 S | R 5 W |
| S 7 | S 8 |
| S 18 | S 17 |
| 2001 | |

Deposit a magnet in a white plastic case at the base of the stainless steel post, and basalt stone alongside.

N. $89^{\circ} 49' 08''$ W., bet. secs. 7 and 18.

Descend steep W. slope, through scattered timber and moderate undergrowth.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|--|
| 1285.26 | Point for the E 1/16 sec. cor. of secs. 7 and 18. Not monumented. |
| 2570.52 | <p>The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, (alongside is a stone 10 x 5 ins. mkd. 1/4 on N. side) with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W S 7 1/4 ————— S 18 1966</p> <p>from which bearing trees mkd. by Gawron, Jelley, and Aanrud</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 74° E., 9.9 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears S. 34° E., 48.8 ft. dist., with healed blaze.</p> <hr/> <p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0° 05' 38" W., bet. secs. 7 and 8.</p> <p>Proceed along W. slope, through medium timber and light undergrowth.</p> |
| 1291.98 | Point for the S 1/16 sec. cor. of secs. 7 and 8, not monumented. |
| 2583.96 | <p>The ¼ sec. cor. of secs. 7 and 8, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W 1/4 S 7 S 8 1974</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 38 ins. diam., bears S. 15° E., 40.3 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A fir, 42 ins. diam., bears N. 11½° W., 25.1 ft. dist., with healed blaze.</p> <p>and bearing trees mkd. by Roseberry and Evans</p> |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>A fir, 15 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 37.6 ft. dist., with healed blaze.</p> <p>A fir, 41 ins. diam., bears S. 40° W., 17.5 ft. dist., with healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 42' 44''$ E., beginning new measurement.</p> <p>Descend steep NE. slope, through medium timber.</p> |
| 770 | <p>Speaker Road, asphalt surface, 20 ft. wide, bears N. 60° W. and S. 60° E.; ascend SW. slope, along E. edge of open pasture and W. edge of scattered timber.</p> |
| 797.88 | <p>A point established by Gary D. Kaiser, Registered Land Surveyor No. 803, in 2000, recorded survey no. 066-2000, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 2 ins. above ground, with a yellow plastic cap mkd. KAISER PLS 803.</p> |
| 1358.25 | <p>The N $\frac{1}{16}$ sec. cor. of secs. 7 and 8, established by Gerald V. Nygren, Registered Land Surveyor No. 1035, in 1991, recorded survey no. 86-91, and is accepted as the corner, monumented with an iron rod, $\frac{5}{8}$ in. diam., firmly set, projecting 2 ins. above ground, with a yellow plastic cap mkd. NYGREN LS 1035, from which bearing trees mkd. by Nygren</p> <p style="padding-left: 40px;">A black oak, 28 ins. diam., bears S. 25° E., 18.7 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A black oak, 6 ins. diam., bears N. $6\frac{3}{4}^{\circ}$ W., 54.6 ft. dist., with healed double blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron rod, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>N $\frac{1}{16}$</p> <p>S 7 S 8</p> <p>2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 44' 05''$ E., beginning new measurement.</p> |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|--|
| 1358.37 | <p>Ascend SW. slope, along E. edge of scattered timber and W. edge of heavy timber.</p> <p>The cor. of secs. 5, 6, 7, and 8, monumented with the original basalt stone, 8 x 8 ins., firmly set, projecting 6 ins. above ground, with 5 notches on the S. and E. edges, from which the remaining original bearing tree</p> <p style="padding-left: 40px;">A white oak, 13 ins. diam., bears S. 80½° E., 13.5 ft. dist., with healed blaze.</p> <p>and bearing trees and a reference monument mkd. by the County Surveyor's Office</p> <p style="padding-left: 40px;">A white oak, 14 ins. diam., bears N. 31° E., 37.3 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">An iron post, 1½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd. RM 1971 and an arrow pointing to the corner point, bears South, 1.0 ft. dist.</p> <p style="padding-left: 40px;">A black oak, 9 ins. diam., bears S. 25° W., 25.1 ft. dist., with healed blaze.</p> <p style="padding-left: 40px;">A cedar, 15 ins. diam., bears N. 88° W., 32.7 ft. dist., with healed double blaze.</p> <p>Woven wire and barbed wire fences, in poor repair, bear S. and W.</p> <hr/> <p>S. 89° 54' 43" W., bet. secs. 6 and 7.</p> <p>Ascend SE. slope, along N. bdy. of scattered timber and S. bdy. of heavy timber.</p> |
| 1338.75 | <p>The E 1/16 sec. cor. of secs. 6 and 7, established by Gary D. Kaiser, Registered Land Surveyor No. 803, in 2000, recorded survey no. 066-2000, and is accepted as the corner, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above ground, with a yellow plastic cap mkd. KAISER PLS 803, from which bearing trees mkd. by Kaiser</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears N. 58° E., 13.4 ft. dist., with scribe marks E1/16 TB visible on partially healed double blaze.</p> <p style="padding-left: 40px;">A madrone, 13 ins. diam., bears N. 40½° W., 18.2 ft. dist., with scribe marks E1/16 BT visible on partially healed double blaze.</p> |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron rod, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 6 E 1/16 ——— S 7 2001</p> </div> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 8 9° 53' 41" W., beginning new measurement.</p> <p>Ascend steep SE. slope, through heavy timber and light undergrowth.</p> |
| 1339.00 | <p>The ¼ sec. cor. of secs. 6 and 7, monumented with an iron post, 1½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>COUNTY SURVEYOR T 33 S R 5 W ¼ S 6 ————— 7 1974</p> </div> <p>from which bearing trees mkd. by the County Surveyor's Office, and reported by Nickerson</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 37½° E., 10.9 ft. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 12° E., 18.2 ft. dist., with healed double blaze.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88° 44' 55" W., beginning new measurement.</p> <p>Descend NW. slope, along N. edge of heavy timber and S. edge of dense undergrowth.</p> |
| 15 | <p>Abandoned logging road, 15 ft. wide, bears N. 20° E. and S. 20° W.</p> |
| 1620 | <p>Sourdough Gulch, 4 ft. wide, course S. 30° W.; ascend SE. slope.</p> |

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| 2254.07 | <p>The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">Subdivision of Section 7, T. 33 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>N. $0^{\circ} 50' 34''$ W., on the N. and S. centerline of sec. 7.</p> <p>Descend steep N. slope, through heavy timber.</p> |
| 910 | Board Tree Creek, dry, 8 ft. wide, drains N. 70° W. |
| 1314.40 | <p>Point for the center S $\frac{1}{16}$ sec. cor. of section 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C S $\frac{1}{16}$ S 7 C 2001</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 70° E., 32.9 ft. dist., mkd. CS$\frac{1}{16}$ S7 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. 12° E., 35.2 ft. dist., mkd. CS$\frac{1}{16}$ S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend slight SW. slope, through recently cut timber.</p> |
| 1500 | Center of Board Tree Creek Road, gravel surface, 12 ft. wide, bears NW. and SE. on curve. |
| 2628.80 | <p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 5 W C $\frac{1}{4}$ S 7 2001</p> </div> |

**Subdivision of Section 7,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 86° W., 24.2 ft. dist., mkd. C1/4 S7 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 61° W., 21.8 ft. dist., mkd. C1/4 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, the corner of woven wire fences, bears N. 68¾° W., 33 ft. dist., fences extend South and N. 60° E.</p> <p>Ascend SE. slope, through medium timber and light undergrowth.</p> |
| 2660 | Woven wire fence, bears N. 60° E. and SW. |
| 2690 | Center of Speaker Road, asphalt surface, 20 ft. wide, bears N. 60° E. and S. 60° W. |
| 2720 | Woven wire fence, bears N. 60° E. and S. 60° W.; enter recently cut timber. |
| 3958.55 | <p>Point for the center N 1/16 sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C N 1/16 S 7 C 2001</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 14° E., 21.9 ft. dist., mkd. CN1/16 S7 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 89° E., 46.1 ft. dist., mkd. CN1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend steep S. slope, through heavy timber and light undergrowth.</p> |
| 5200 | Spur, slopes S. 70° W.; descend NW. slope. |

**Subdivision of Section 7,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| 5288.30 | <p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p> <p>N. $88^{\circ} 50' 29''$ W., on the E. and W. centerline of sec. 7.</p> <p>Ascend steep NE. slope, through medium timber and moderate undergrowth.</p> |
| 1302.59 | <p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 7.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E $\frac{1}{16}$</p> <p>C ——— C</p> <p>S 7</p> <p>2001</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ E., 16.2 ft. dist., mkd. CE $\frac{1}{16}$ S7 BT.</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears S. $52\frac{1}{4}^{\circ}$ E., 5.8 ft. dist., mkd. CE $\frac{1}{16}$ S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Descend NW. slope, through recently cut timber.</p> |
| 2605.18 | <p>The center $\frac{1}{4}$ sec. cor. of sec. 7.</p> <p>Ascend slight SE. slope, through medium timber and light undergrowth.</p> |
| 2635 | <p>Woven wire fence, bears N. and S.</p> |
| 2690 | <p>Center of Speaker Road, asphalt surface, 20 ft. wide, bears N. 60° E. and S. 60° W.</p> |
| 3002 | <p>From this point, the center of a steel water tank, 8 ft. diam., 17 ft. tall, bears North, 4.30 ft. dist.</p> |
| 4903.91 | <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> |

**Subdivision of Section 7,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | <p>From the center E 1/16 sec. cor. of sec. 7.</p> <p>N. 0° 02' 55" W., on the N. and S. centerline of the NE¼ of sec. 7.</p> <p>Descend NW. slope, along E. edge of recently cut timber and W. edge of open pasture.</p> |
| 630 | Center of Speaker Road, asphalt surface, 20 ft. wide, bears N. 70° E. and S. 70° W. |
| 633.48 | <p>A point established by Gary D. Kaiser, Registered Land Surveyor No. 803, in 2000, recorded survey no. 066-2000, and is accepted as a point on line, this point will now function as witness point no. 1, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 3 ins. above ground, with a yellow plastic cap mkd. KAISER PLS 803.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., directly onto the iron rod, mkd.</p> <p style="text-align: center;">WP1 E S 7 E 2001</p> |
| 1343.88 | <p>Point for the NE 1/16 sec. cor. of sec. 7, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 7 2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 83¾° W., 26.4 ft. dist., mkd. NE1/16 S7 BT. Mag Nail left side-center.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 6¾° W., 31.0 ft. dist., mkd. NE1/16 S7 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> |

**Subdivision of Section 7,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|--|
| | Ascend SE. slope, along E. edge of heavy timber and W. edge of recently cut timber. |
| 2026.82 | <p>A point established by Gary D. Kaiser, Registered Land Surveyor No. 803, in 2000, recorded survey no. 066-2000, and is accepted as a point on line, this point will now function as witness point no. 2, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above ground, with a yellow plastic cap mkd. KAISER PLS 803.</p> <p>At the corner point</p> <p>Drive an aluminum cap, 2 ins. diam., directly onto the iron rod, mkd.</p> <div style="text-align: center;"> WP2 E S 7 E 2001 </div> |
| 2688.02 | <p>The E 1/16 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the NE 1/16 sec. cor. of sec. 7.</p> <p>N. 89° 28' 35" W., on the calculated E. and W. centerline of the NE¼ of sec. 7.</p> <p>Ascend E. slope, along N. edge of medium timber and S. edge of heavy timber.</p> |
| 1320.72 | <p>The center N 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 7.</p> <p>S. 0° 28' 18" E., on the calculated N. and S. centerline of the SE¼ of sec. 7.</p> <p>Ascend NW. slope, along E. edge of recently cut timber and W. edge of heavy timber.</p> |
| 1303.16 | <p>Point for the SE 1/16 sec. cor. of sec. 7, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |

**Subdivision of Section 7,
T. 33 S., R. 5 W., Willamette Meridian, Oregon**

| FEET | |
|---------|---|
| | SE 1/16 S 7 2001 |
| | from which |
| | A white oak, 18 ins. diam., bears N. 72¼° E., 36.6 ft. dist., mkd. SE1/16 S7 BT. |
| | A white oak, 21 ins. diam., bears N. 31¼° W., 24.5 ft. dist., mkd. SE1/16 S7 BT. |
| | Deposit a magnet in a white plastic case at the base of the stainless steel post. |
| | <hr/> |
| | N. 89° 19' 37" W., on the calculated E. and W. centerline of the SE¼ of sec. 7. |
| 990 | Center of Board Tree Creek Road, gravel surface, 12 ft. wide, bears NW. and SE. |
| 1293.88 | The center S 1/16 sec. cor. of sec. 7. |
| | <hr/> |
| | GENERAL DESCRIPTION |
| | The lands surveyed are located approximately three miles northeast of the town of Wolf Creek, Oregon. Access is gained by way of Speaker Road, Board Tree Creek Road, and private driveways. Elevation is approximately 1500 to 2400 feet above sea level. |
| | The soil in the area is composed generally of rocky clay. The area is drained by Board Tree Creek, Sourdough Gulch and Wolf Creek. Timber consists primarily of cedar, fir, madrone, pine, and white oak. |
| | No mining activity was noted along the lines surveyed. The land surveyed is used for timber production and residences. Past use has included ranching. |
| | The mean magnetic declination, as shown on United States Geological Survey 7½ minute quadrangle map "GOLDEN, OREG.," Provisional Edition, 1986, is 18½° East. |