

FEET

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

TOWNSHIP 26 SOUTH, RANGE 10 WEST,

THE DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY

AND SUBDIVISIONAL LINES,

AND THE SUBDIVISION OF SECTION 31,

TOWNSHIP 26 SOUTH, RANGE 9 WEST,

OF THE WILLAMETTE MERIDIAN,

IN THE STATE OF OREGON.

EXECUTED BY***Edith M. Forkner, Cadastral Surveyor***

Under Special Instructions dated January 4, 2002,
approved January 4, 2002, which provided for the surveys

included under Group No. 2005,

and Assignment Instructions dated January 18, 2002.

Survey commenced February 19, 2002***Survey completed February 4, 2003***

T. 26 S., R. 9 W., Willamette Meridian, Oregon

FEET	
	<p>The following field notes are those of the dependent resurvey of a portion of the east boundary of township 26 south, range 10 west, the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of section 31, township 26 south, range 9 west, Willamette Meridian, Oregon.</p> <p>The history of surveys pertaining to this survey is as follows:</p> <p>In 1896, Samuel W. Lackland, U.S. Deputy Surveyor, surveyed the east boundary and a portion of the subdivisional lines of township 26 south, range 10 west.</p> <p>In 1896-97, John W. Meldrum, U.S. Deputy Surveyor, surveyed the south boundary and the subdivisional lines, establishing closing corners on the west boundary of the township.</p> <p>In 1901, Robert C. Bonser, Compassman, retraced a portion of the south boundary.</p> <p>In 1972-77, Owen C. Chatters II and Jack W. Bowder, Cadastral Surveyors, resurveyed a portion of the south boundary and subdivisional lines and a portion of the east boundary of township 26 south, range 10 west.</p> <p>In 1983, Stephen J. Malloy, Cadastral Surveyor, resurveyed a portion of the south boundary.</p> <p>The survey was executed in accordance with the specifications set forth in the <u>Manual of Surveying Instructions, 1973</u>, and the Special Instructions dated January 4, 2002, for Group No. 2005, Oregon.</p> <p>The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. Measured distance and directions have been adjusted by Cadastral Measurement Management for Windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot. The Standard Error of Unit Weight (SEUW) for a least squares adjustment of the survey data was checked to assure a value between 0.7 and 2.5. In addition, a comparison of the adjustments (residuals) to the original unadjusted measurements was also checked to assure a ratio not exceeding 1:4000. This comparison was done in the CHECKER routine of WinCMM, and is reported as the Precision After Orientation Correction.</p>

T. 26 S., R. 9 W., Willamette Meridian, Oregon

FEET

The retracement data were thoroughly verified and only the true line field notes are given herein.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The geographic position (NAD 1983 (91)) of the ¼ section corner of section 31 only, on the south boundary of the township, as determined by the NAVSTAR Global Positioning System (GPS), by direct occupation, utilizing static, carrier phase GPS receivers (see the Control Data Sheet attached to these field notes following the General Description), is as follows:

Latitude: 43° 15' 28.826" N. Longitude: 123° 48' 49.516" W.

The geographic position (NAD 1983 (91)) of the ¼ section corner of section 34 only, on the south boundary of the township, as determined by the NAVSTAR GPS, by direct occupation, utilizing static, carrier phase GPS receivers (see the Control Data Sheet attached to these field notes following the General Description), is as follows:

Latitude: 43° 15' 28.828" N. Longitude: 123° 45' 15.984" W.

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon**

(Restoring the survey by Samuel W. Lackland in 1896
and the resurvey by Owen C. Chatters II and
Jack W. Bowder in 1972-77)

Beginning at the cor. of Tps. 26 and 27 S., R. 10 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground (alongside of which is the original sandstone, 16 x 10 x 7 ins., firmly set, projecting 8 ins. above ground, mkd. with 4 notches visible on the E. edge, also alongside is an aluminum pipe, 2 ins. diam., firmly set, projecting 14 ins. above ground), with brass cap mkd.

T 26 S		
R 10 W		T 27 S
S 36		R 9 W
		S 6
S 1		
T 27 S		
		1975

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon**

FEET																
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A burned cedar snag, 32 ins. diam., bears N. 5° E., 19.1 ft. dist., with axe marks X at head height. (Record, 17.2 ft. dist.)</p> <p>and the bearing trees mkd. by Chatters and Bowder</p> <p style="padding-left: 40px;">An alder, 16 ins. diam., bears S. 50½° W., 5.5 ft. dist., with no scribe marks visible on partially healed blaze. (Record, 6.9 ft. dist.)</p> <p style="padding-left: 40px;">A myrtle, 14 ins. diam., bears N. 30½° W., 24.8 ft. dist., with a healed blaze. (Record, N. 28½° W.)</p> <p>N. 0° 00' 02" W., on the E. bdy. of sec. 36, T. 26 S., R. 10 W.</p> <p>Descend over N. slope through medium timber and light undergrowth.</p>															
145	<p>Tioga Creek, 20 ft. wide, course E.; along nearly level land.</p>															
495.91	<p>The closing cor. of Tps. 26 and 27 S., R. 9 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground (alongside of which is an iron axle, ½ in. diam., firmly set, projecting 4 ins. above ground), with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">T 26 S</td> <td style="padding-left: 5px;">T 26 S</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">R 10 W</td> <td style="padding-left: 5px;">R 9W</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 36</td> <td style="padding-left: 5px;">S 31</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S 6</td> <td style="border-left: 1px solid black; padding-left: 5px;">CC</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">T 27 S</td> <td></td> </tr> </table> <p>1975</p> </div> <p>from which the bearing trees mkd. by Chatters and Bowder</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears N. 60° E., 35.0 ft. dist., with a healed blaze. (Record, N. 58½° E.)</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears S. 88½° E., 27.3 ft. dist., with a healed blaze. (Record, 28.4 ft. dist.)</p> <p>From this point, the original closing cor. of Tps. 26 and 27 S., R. 9 W., perpetuated by Theodore S. Ellingsen, Registered Land Surveyor No. 329, in 1963, and recorded in the Coos County Surveyor's Office, Map No. 16A60, and Bearing Tree Book 10, Page 205, from original evidence no longer in existence, bears N. 89° 59' 00" W., 8.58 ft. dist., monument missing, determined from the bearing tre mkd. by Ellingsen</p>	T 26 S	T 26 S		R 10 W	R 9W		S 36	S 31			S 6	CC		T 27 S	
T 26 S	T 26 S															
R 10 W	R 9W															
S 36	S 31															
	S 6	CC														
	T 27 S															

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon**

FEET

An alder, 18 ins. diam., bears S. 65° E., 27.7 ft. dist., with illegible scribe marks visible on bark.

From this same point, the S 1/16 sec. cor. of sec. 31 only, on the W. bdy. of T. 26 S., R. 9 W., bears N. 0° 04' 11" W., 1317.14 ft. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

| S 1/16
| S 31
1975

from which new bearing trees

A fir, 19 ins. diam., bears N. 69½° E., 55.7 ft. dist., mkd. S1/16 S31 BT.

A fir, 16 ins. diam., bears S. 45° E., 60.2 ft. dist., mkd. S1/16 S31 BT.

Set a white fiberglass post 3 ft. N. of the cor.

Corner is located on the E. edge of fir reproduction, edge bears N. 45° E. and S. 30° W.

From the ¼ sec. cor. of sec. 31 only, on the W. bdy. of T. 26 S., R. 9 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

| T 26 S
| R 9 W
| 1/4
| S 31
1975

from which the bearing trees mkd. by Chatters and Bowder

A fir, 9 ins. diam., bears N. 5½° E., 4.6 ft. dist., with a healed blaze. (Record, 5.9 ft. dist.)

A fir, 17 ins. diam., bears S. 19½° E., 17.7 ft. dist., with a healed blaze. (Record, 16.5 ft. dist.)

A red metal fence post bears south, 4½ ft. dist.

From this point, the S 1/16 sec. cor. of sec. 31 only, on the W. bdy. of T. 26 S., R. 9 W., bears S. 0° 00' 05" E., 1317.56 ft. dist., hereinbefore described.

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon**

FEET											
	N. 0° 00' 15" W., on the E. bdy. of sec. 36, marking and blazing the true line.										
	Ascend over SE. slope through medium timber and moderate undergrowth.										
860	Spur, slopes S. 55° W.; also E. end dirt road, 10 ft. wide, bears same; also SE. cor. logged area, edge bears N. and S. 55° W.; desc. over NW. slope along E. edge logged area.										
990	Bottom of descent, slopes NW.; asc. across W. slope.										
1445	Ridge, bears N. 40° W. and S. 30° E.; desc. over NE. slope.										
1615	NE. cor. logged area, edge bears N. 55° W. and S.; leave logged area.										
2010	Creek, 1 ft. wide, course S. 35° E.; asc. over SW. slope.										
2167.87	The cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, with top flush with the surface of the ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 26 S</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 26 S</td> </tr> <tr> <td style="padding-right: 10px;">R 10 W</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 9 W</td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 31</td> </tr> <tr> <td style="border-top: 1px solid black; padding-right: 10px;">S 36</td> <td style="border-left: 1px solid black;"></td> </tr> <tr> <td></td> <td style="text-align: center;">1975</td> </tr> </table>	T 26 S	T 26 S	R 10 W	R 9 W	S 25	S 31	S 36			1975
T 26 S	T 26 S										
R 10 W	R 9 W										
S 25	S 31										
S 36											
	1975										
	from which the remains of the original bearing trees										
	A decayed myrtle stump, size indeterminate, bears N. 37½° E., 33.0 ft. dist., no marks visible.										
	A decayed myrtle stump with sprout, size indeterminate, bears S. 51° W., 29.5 ft. dist., no marks visible. (Record, 31.7 ft. dist.)										
	A decayed myrtle stump, size indeterminate, bears N. 50° W., 29.7 ft. dist., no marks visible.										
	and the bearing trees mkd. by Chatters and Bowder										
	A fir, 20 ins. diam., bears S. 21° W., 36.3 ft. dist., with a healed blaze.										
	A fir, 35 ins. diam., bears N. 45¼° W., 63.7 ft. dist., with a healed blaze.										

**Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon**

FEET																
	<p>A steel fence post, projecting 2 ft. above ground, bears S. 14° E., 24.6 ft. dist.</p> <hr/> <p>N. 0° 09' 47" W., on the E. bdy. of sec. 25.</p> <p>Ascend over S. slope through medium timber and moderate undergrowth.</p>															
464.72	<p>The closing cor. of secs. 30 and 31, on the W. bdy. of T. 26 S., R. 9 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground (alongside of which is an aluminum pipe, 1 in. diam., firmly set, projecting 10 ins. above ground), with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding-right: 10px;">T 26 S</td> <td style="border-left: 1px solid black; padding-left: 5px;">T 26 S</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 10 W</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 30</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">S 25</td> <td style="border-left: 1px solid black; padding-left: 5px;">S 31</td> <td style="border-left: 1px solid black; padding-left: 5px;">CC</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 5px;">R 9 W</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="padding-top: 5px;">1975</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed myrtle stump, size indeterminate, bears N. 59° E., 11.2 ft. dist., with axe marks and open decayed blaze.</p> <p>and the remains of the bearing trees mkd. by Chatters and Bowder</p> <p style="padding-left: 40px;">A roothole bears N. 49° E., 49.8 ft. dist., alongside of which is a down fir, 23 ins. diam., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 31 ins. diam., bears S. 7° E., 15.8 ft. dist., with a healed blaze.</p> <p>and the remains of a bearing tree mkd. by person(s) unknown</p> <p style="padding-left: 40px;">A roothole bears N. 83¼° E., 22.1 ft. dist., alongside of which is a down double myrtle, 14 ins. diam., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 34½° E., 5.3 ft. dist., mkd. T26S R9W S30 BT.</p> <p>Corner is set against the S. side of a fir stump, 48 ins. diam., with a red metal fence post in center.</p> <hr/>	T 26 S	T 26 S		R 10 W	S 30		S 25	S 31	CC		R 9 W				1975
T 26 S	T 26 S															
R 10 W	S 30															
S 25	S 31	CC														
	R 9 W															
		1975														

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p align="center">(Restoring the survey by John W. Meldrum in 1896-97, the retracement by Robert C. Bonser in 1901, the resurvey by Owen C. Chatters II and Jack W. Bowder in 1972-77, and the resurvey by Stephen J. Malloy in 1983)</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of sec. 34 only, on the S. bdy. of the Tp., perpetuated by Weyerhaeuser Timber Co. (now Plum Creek Timber Co., located in Coos Bay), in 1954 from original evidence no longer in existence, subsequently perpetuated by Tony Hostetter, Registered Land Surveyor No. 1975, in 1996, and recorded in the Douglas County Surveyor's Office, Map No. M126-61, from original evidence no longer in existence, monumented with an iron pipe, $\frac{3}{4}$ ins. diam., firmly set, projecting 12 ins. above ground, from which the remains of a bearing tree marked by person(s) unknown, reported by Hostetter</p> <p align="center">A fir stump, 45 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 24.7 ft. dist., with a healed blaze.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p align="center">T 26 S R 9 W 1/4 S 34 <hr/>2002</p> <p>from which a new bearing tree</p> <p align="center">A hemlock, 22 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ W., 181.2 ft. dist., mkd. 1/4 S34 BT.</p> <p>No other trees available within limits.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner is located on the SE. cor. of timber, edge bears N. and W.; fir reproduction to S. and E. Corner is in a new skid road.</p> <p>N. $89^{\circ} 54' 46''$ W., on the S. bdy. of sec. 34.</p> <p>Descend over W. slope through medium timber and light undergrowth, on the N. edge of fir reproduction.</p>
905	Bottom of descent, slopes NW.; asc. over NE. slope; also NW cor.

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET						
	fir reproduction, edge bears E. and S. 15° W.					
945	Across nearly level land.					
1135	Descend over W. slope.					
1785	Dirt road, 10 ft. wide, bears N. 60° W. and S. 65° E.					
2321.57	True point for the closing corner of secs. 3 and 4, described in the field notes of the dependent resurvey of a portion of the subdivisional lines T. 27 S., R. 9 W., executed concurrently with this same group.					
	Descend over W. slope.					
2626.78	The cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T 26 S R 9 W</td> </tr> <tr> <td>S 33 S 34</td> </tr> <tr> <td style="border-top: 1px solid black;">S 4</td> </tr> <tr> <td>T 27 S</td> </tr> <tr> <td>1978</td> </tr> </table>	T 26 S R 9 W	S 33 S 34	S 4	T 27 S	1978
T 26 S R 9 W						
S 33 S 34						
S 4						
T 27 S						
1978						
	from which the remains of the original bearing trees					
	A sawed fir stump, 68 ins. diam., bears N. 42° E., 12.2 ft. dist., no marks visible. (Record, 13.9 ft. dist.)					
	A sawed fir stump, 68 ins. diam., bears S. 57½° E., 33.0 ft. dist., with scribe marks R9W BT visible on bark blaze. (Record, S. 12° E.)					
	A sawed fir stump, 62 ins. diam., bears S. 22° W., 17.1 ft. dist., with scribe marks T27S R9W visible on bark blaze. (Record, 19.1 ft. dist.)					
	and the bearing trees mkd. by Chatters and Bowder					
	A fir, 17 ins. diam., bears N. 10¾° E., 22.1 ft. dist., with a healed blaze. (Record, N. 30° E.)					
	A fir, 21 ins. diam., bears N. 56° W., 17.2 ft. dist., with a healed blaze. (Record, N. 60° W.)					
	From the closing cor. of secs. 5 and 6, on the N. bdy. of T. 27 S., R. 9 W., monumented with an iron post, 2½ ins. diam.,					

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>firmly set, with top flush with the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W S 32</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 6 S 5 T 27 S R 9 W CC 1983</p> <p>from which the bearing trees mkd. by Malloy</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 55$\frac{3}{4}$° E., 33.5 ft. dist., with a healed blaze. (Record, 34.3 ft.)</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 21° W., 12.5 ft. dist., with a healed blaze.</p> <p>From this point, the position of the original closing cor. of secs. 5 and 6 bears N. 0° 29' 04" E., 8.75 ft. dist., (record N. 0° 45' W., 8.91 ft. dist.), monumented with an aluminum post, 2 ins. diam., firmly set, projecting 24 ins. above the ground. There is no remaining evidence of the original corner.</p> <p>S. 89° 59' 27" W., on the S. bdy. of sec. 32.</p> <p>Descend over W. slope through medium timber and light undergrowth.</p>
230.43	<p>The cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., monumented with an iron post, 2$\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W S 31 S 32</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S 6 T 27 S 1973</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A decayed fir snag, 34 ins. diam., bears N. 34$\frac{1}{4}$° E., 93.4 ft. dist., no marks visible. (Record, N. 33° E., 89.8 ft. dist.)</p> <p style="padding-left: 40px;">A decayed fir snag, 31 ins. diam., bears S. 59$\frac{3}{4}$° E., 36.1 ft. dist., with no marks visible. (Record and to face, S. 54$\frac{1}{2}$° E., 35.0 ft. dist.)</p> <p style="padding-left: 40px;">A decayed fir snag, 49 ins. diam., bears S. 32$\frac{3}{4}$° W.,</p>

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>75.2 ft. dist., no marks visible.</p> <p>A cedar snag, 39 ins. diam., bears N. $72\frac{3}{4}^{\circ}$ W., 35.6 ft. dist., with a decayed burnt blaze.</p> <p>and the bearing trees mkd. by Theodore S. Ellingsen, Registered Land Surveyor No. 329, in 1963, reported by Malloy in 1983</p> <p>A fir, 34 ins. diam., bears N. 48° E., 48.2 ft. dist., with a healed blaze.</p> <p>A fir, 17 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ W., 15.8 ft. dist., no marks visible.</p> <p>and a bearing tree mkd. by person(s) unknown, reported by Malloy in 1983</p> <p>A fir, 36 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ E., 29.7 ft. dist., with a healed blaze. (Record, S. 36° E., 33.0 ft. dist.)</p> <hr/> <p>S. $89^{\circ} 51' 09''$ W., on the S. bdy. of sec. 31.</p> <p>Descend over W. slope through medium timber and moderate undergrowth.</p>
55	Creek, 3 ft. wide, course N.; asc. over E. slope.
310	Spur, slopes N. 15° E.; desc. over NW. slope.
930	Creek, 1 ft. wide, course N. 60° E.; asc. over NE. slope.
1088.04	<p>Point for the E 1/16 sec. cor. of sec. 6 only, on the N. bdy. of T. 27 S., R. 9 W.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, 6 ins. below the surface of a graveled road, with brass cap mkd.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">E 1/16 S 6 2002</p> <p>from which</p> <p>A cedar, 21 ins. diam., bears S. $59\frac{1}{4}^{\circ}$ E., 35.8 ft. dist., mkd. E1/16 S6 BT.</p> <p>A hemlock, 21 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ W., 121.6 ft. dist., mkd. E1/16 S6 BT.</p>

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Corner falls in center of graveled road, 14 ft. wide, bears N. 20° E. and S. 30° W.; also the NE. cor. of a logged area, edge bears S. and W.</p> <p>From this point, a point established as the E 1/16 sec. cor. of sec. 6 only, on the N. bdy. of T. 27 S., R. 9 W., by John Minor, Registered Land Surveyor No. 2052, in 1992, and recorded in the Coos County Surveyor's Office, Map No. 22B55, bears S. 87° 12' 17" E., 15.77 ft. dist. This point is not properly positioned and is not utilized in this survey, the monument was destroyed by road work, position determined at record bearing and distance from a bearing tree mkd. by Minor</p> <p style="padding-left: 40px;">A hemlock, one of three from the same base, 25 ins. diam., bears S. 7° E., 38.9 ft. dist., with scribe marks E1/16 S6 BT visible on partially healed blaze.</p> <p>Ascend over NE. slope, on the N. edge of logged area.</p>
1300	Top of ascent, slopes N. 30° E.; desc. over NW. slope.
1420	Bottom of descent, slopes NE.; asc. over NE. slope.
1480	Dirt road, 14 ft. wide, bears N. 70° E. and S. 70° W.
2235	Spur, slopes N. 20° E.; desc. over NW. slope.
2406.56	<p>Point for the ¼ sec. cor. of sec. 6 only, on the N. bdy. of T. 27 S., R. 9 W., at proportionate distance.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W ----- 1/4 S 6 T 27 S R 9 W 2002</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 6 ins. diam., bears N. 31½° E., 19.2 ft. dist., mkd. X BT.</p> <p>No other trees available within limits.</p> <p>Deposit a magnet in a white plastic case at the base of the</p>

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>stainless steel post.</p> <p>Corner is on the N. edge of a logged area, edge bears E. and W.; no suitable trees to the S.</p> <p>From this point, a point established as the $\frac{1}{4}$ sec. cor. of sec. 6 only, on the N. bdy. of T. 27 S., R. 9 W., by John Minor, Registered Land Surveyor No. 2052, in 1992, and recorded in the Coos County Surveyor's Office, Map No. 22B55, bears N. $89^{\circ} 13' 07''$ E., 4.17 ft. dist. This point is not properly positioned and is not utilized in this survey, monumented with an iron post, $1\frac{1}{4}$ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. LS 2052 T26S R9W $\frac{1}{4}$ S6 T27S R9W 1992, from which the remains of the bearing trees mkd. by Minor</p> <p style="padding-left: 40px;">An alder snag, 11 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ E., 5.2 ft. dist., with scribe marks $\frac{1}{4}$ S6 BT visible on bark.</p> <p style="padding-left: 40px;">An alder snag, 11 ins. diam., bears S. $33\frac{1}{2}^{\circ}$ W., 16.0 ft. dist., with scribe marks $\frac{1}{4}$ S6 BT visible on bark.</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears S. $89\frac{1}{4}^{\circ}$ W., 39.8 ft. dist., with scribe marks $\frac{1}{4}$ S6 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fallen alder, 20 ins. diam., bears NW., with scribe marks $\frac{1}{4}$ S6 BT visible on bark, no discernable roothole.</p> <p>Descend over NW. slope, on the N. edge of logged area.</p>
2530	Along nearly level land.
2659.77	<p>The $\frac{1}{4}$ sec. cor. of sec. 31 only, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W <u>1/4 S 31</u> 1975</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A hemlock stump, 45 ins. diam., bears N. 62° W., 20.5 ft. dist., with scribe marks 1/ BT visible on open blaze.</p> <p>and the bearing trees mkd. by Chatters and Bowder</p> <p style="padding-left: 40px;">An alder, 11 ins. diam., bears N. $45\frac{1}{4}^{\circ}$ E., 25.7 ft. dist.,</p>

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	with a partially healed blaze.
	An alder, 12 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ W., 7.9 ft. dist., no marks visible.
	From this point, a point established as the $\frac{1}{4}$ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., by Theodore S. Ellingsen, Registered Land Surveyor No. 329, in 1963, and recorded in the Coos County Surveyor's Office, Map No. 16A60, and Bearing Tree Book 10, Page 204, bears S. $71^{\circ} 20' 13''$ E., 13.65 ft. dist. (record, S. 73° E., 13.9 ft. dist.), monumented with an aluminum pipe, 2 ins. diam., firmly set, projecting 14 ins. above ground, from which a bearing tree mkd. by Ellingsen
	An alder, 15 ins. diam., bears S. 42° W., 15.2 ft. dist., no marks visible.

	N. $89^{\circ} 59' 57''$ W., beginning new measurement.
	Along nearly level land, on the N. edge of logged area.
325	The NW. cor. of a logged area, edge bears S. 60° W. and E.; leave logged area.
450	Tioga Creek, 50 ft. wide, course N. 60° E.; asc. over SE. slope.
855	Along nearly level land.
875	Graveled road, 8 ft. wide, bears N. 40° E. and S. 40° W.
975	Center graveled parking area, 60 ft. diam.
1320.35	The W $\frac{1}{16}$ sec. cor. of sec. 31 only, on the S. bdy. of the Tp., rehabilitated by John Minor, Registered Land Surveyor No. 2052, in 1991, and recorded in the Coos County Surveyor's Office, Bearing Tree Book 20, Page 140, monumented with an iron post, $\frac{3}{4}$ ins. diam., firmly set, with top 2 ins. below the surface of the ground, with brass cap mkd.
	W $\frac{1}{16}$ S 31

	1991 LS 2052
	from which the bearing trees mkd. by Chatters and Bowder
	A fir, 21 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 34.3 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the South boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 24 ins. diam., bears N. $81\frac{3}{4}^{\circ}$ W., 59.4 ft. dist., with a healed blaze.</p> <p>From this point, a point established as the W 1/16 sec. cor. of sec. 31 only, on the S. bdy. of the Tp., by Theodore S. Ellingsen, Registered Land Surveyor No. 329, in 1963, and recorded in the Coos County Surveyor's Office, Map No. 16A60, and Bearing Tree Book 10, Page 204, bears S. $80^{\circ} 15' 00''$ E., 8.91 ft. dist., monument missing, from which a bearing tree mkd. by Ellingsen</p> <p>An alder, 15 ins. diam., bears N. 21° W., 19.8 ft. dist., with scribe marks 16 visible on bark.</p> <hr/> <p>S. $89^{\circ} 59' 46''$ W., beginning new measurement.</p> <p>Along nearly level land.</p>
985	Creek, 1 ft. wide, course S. 30° E.; along nearly level land.
1116.21	The closing cor. of Tps. 26 and 27 S., R. 9 W., described in the field notes of the dependent resurvey of a portion of the east bdy. of T. 26 S., R. 10 W., hereinbefore described.
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 9 W., Willamette Meridian, Oregon</p> <hr/> <p>(Restoring the survey by John W. Meldrum in 1896-97 and the resurvey by Owen C. Chatters II and Jack W. Bowder in 1972-77)</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W 1/4 S 31 S 32 1972</p> <p>from which the bearing trees mkd. by Chatters and Bowder</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 20 ins. diam., bears N. $70\frac{3}{4}^{\circ}$ E., 31.0 ft. dist., with a healed blaze.</p> <p>A fir, 16 ins. diam., bears S. $60\frac{1}{4}^{\circ}$ W., 23.8 ft. dist., with a healed blaze.</p> <p>From this point, the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., bears S. $0^{\circ} 26' 13''$ E., 2628.97 ft. dist., hereinbefore described.</p> <p>N. $0^{\circ} 26' 36''$ W., bet. secs. 31 and 32.</p> <p>Ascend over SW. slope through medium timber and moderate undergrowth.</p>
155	The W. cor. of fir reproduction, edge bears N. and S. 20° E.; along W. edge fir reproduction.
270	Spur, slopes W.; desc. over NE. slope.
1225	Creek, $1\frac{1}{2}$ ft. wide, course N. 65° W.; asc. over SW. slope.
1312.06	The N 1/16 sec. cor. of secs. 31 and 32, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.
	<p>N 1/16</p> <p>S 31 S 32</p> <p>1972</p>
	<p>from which the remains of the bearing trees mkd. by Chatters and Bowder</p> <p>A hemlock stump, 26 ins. diam., bears N. 83° E., 50.1 ft. dist., with scribe marks N1/16 S visible on open blaze. (Record, 47.5 ft. dist.)</p> <p>A fir, 16 ins. diam., bears N. $54\frac{1}{4}^{\circ}$ W., 38.9 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 5 ins. diam., bears N. $88\frac{1}{2}^{\circ}$ E., 26.9 ft. dist., mkd. N1/16 S32 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 32' 35''$ W., beginning new measurement.</p> <p>Ascend over SW. slope along W. edge fir reproduction.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET											
150	Spur, slopes W.; desc. over NE. slope.										
555	Creek, 2 ft. wide, course N. 55° W.; asc. over SW. slope; also NW. cor. of fir reproduction, edge bears S. and S. 55° E., and SW. cor. logged area, edge bears N. and S. 55° E.; along W. edge logged area.										
695	The NW. cor. of logged area, edge bears S. and E., leave logged area.										
830	The SW. cor. of logged area, edge bears N. and E.; along W. edge logged area.										
1085	Spur, slopes W.; desc. over NW. slope.										
1315.47	<p>The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr> <td>T 26 S R 9 W</td> <td></td> </tr> <tr> <td>S 30</td> <td> S 29</td> </tr> <tr> <td colspan="2" style="border-top: 1px solid black;"></td> </tr> <tr> <td>S 31</td> <td> S 32</td> </tr> <tr> <td colspan="2" style="text-align: center;">1972</td> </tr> </table> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A decayed cedar stump, size indeterminate, bears S. 86¼° W., 77.9 ft. dist., no marks visible.</p> <p>and the remains of the bearing trees mkd. by Chatters and Bowder</p> <p style="padding-left: 40px;">A cedar stump, 41 ins. diam., bears S. 84° E., 57.1 ft. dist., no marks visible.</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S. 52¾° E., 28.7 ft. dist., with a healed blaze. (Record, 33.7 ft. dist.)</p> <p style="padding-left: 40px;">A myrtle, 11 ins. diam., bears S. 44½° W., 31.7 ft. dist., no scribe marks visible on decayed partially healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A fir, 19 ins. diam., bears N. 23° E., 63.4 ft. dist., mkd. T26S R9W S29 BT.</p> <p style="padding-left: 40px;">A maple, 15 ins. diam., bears N. 59½° W., 12.4 ft. dist., mkd. T26S R9W S30 BT.</p> <p>Corner is located at the NW. cor. of logged area, edge bears S.</p>	T 26 S R 9 W		S 30	S 29			S 31	S 32	1972	
T 26 S R 9 W											
S 30	S 29										
S 31	S 32										
1972											

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	and E.
	<hr/>
	S. 89° 40' 22" W., bet. secs. 30 and 31.
	Descend over NW. slope through medium timber and moderate undergrowth.
645	Top of waterfall, 60 ft. high, 3 ft. wide, creek course S. 40° W.; desc. over SW. slope.
970	Tioga Creek, 48 ft. wide, course N. 25° W.; asc. over NE. slope.
1120	Coos River Mainline Road, asphalt surface, 16 ft. wide, bears N. 45° W. and S. 15° E.
1390	Ascend along broken N. slope.
2210	Top of ascent, slopes N.; desc. over NW. slope.
2300	Bottom of descent, slopes N.; asc. over NE. slope.
2470	Spur, slopes N.; desc. over NW. slope.
2636.53	The ¼ sec. cor. of secs. 30 and 31, monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.
	T 26 S R 9 W S 30 1/4 ——— S 31 1976
	from which the remains of the original bearing trees
	A decayed myrtle stump, size indeterminate, bears N. 8° E., 40.9 ft. dist., no marks visible. (Record, N. 5½° E.)
	A decayed hemlock stump, size indeterminate, bears S. 45¾° W., 45.5 ft. dist., no marks visible. (Record, S. 48° W.)
	and the bearing trees mkd. by Chatters and Bowder
	A hemlock, 13 ins. diam., bears N. 57° E., 58.1 ft. dist., with a healed blaze.
	A fir, 23 ins. diam., bears S. 74¼° E., 35.6 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	Corner is partially under a fallen log, 48 ins. diam. <hr style="width: 20%; margin: 10px auto;"/>
	N. 89° 33' 02" W., beginning new measurement.
	Descend over NW. slope.
10	Creek, 1 ft. wide, course N.; asc. over NE. slope.
150	Creek, ½ ft. wide, course N. 75° E.; asc. over steep NE. slope.
430	Spur, slopes N.; desc. over NW. slope.
695	Creek, 3 ft. wide, course N. 20° E.; asc. over E. slope.
1380	Ascend over SE. slope.
1645	The SE. cor. of logged area, edge bears N. 40° W. and W.; along S. edge logged area.
2045	Top of ascent, slopes S.; desc. over SW. slope.
2135	Creek, dry, 1 ft. wide, course S. 30° E.; asc. over NE. slope.
2395	The SW. cor. of logged area, edge bears N. and E.; leave logged area.
2419.18	The closing cor. of secs. 30 and 31, on the W. bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the east bdy. of T. 26 S., R. 10 W., hereinbefore described.
<hr/> Subdivision of Section 31, T. 26 S., R. 9 W., Willamette Meridian, Oregon <hr/>	
	From the ¼ sec. cor. of sec. 31 only, on the S. bdy. of the Tp. N. 0° 11' 21" W., on the N. and S. center line of sec. 31.
	Along nearly level land through medium timber and moderate undergrowth.
310	Tioga Creek, 35 ft. wide, course N. 70° E.; along nearly level land.
1140	Tioga Tie Road, asphalt surface, 18 ft. wide, bears N. 80° E. and S. 65° W.

**Subdivision of Section 31,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET													
1318.32	<p>The center S 1/16 sec. cor. of sec. 31, established by John Minor, Registered Land Surveyor No. 2052, in 1994, and recorded in Coos County Surveyor's Office, Map No. 16B49, and is accepted as the corner, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border: none;"> <tr> <td style="padding: 0 10px;">C</td> <td style="border-left: 1px solid black; padding: 0 5px;">S 1/16</td> <td style="padding: 0 10px;">S 31</td> <td style="padding: 0 10px;">C</td> <td style="padding: 0 10px;">1994</td> <td style="padding: 0 10px;">1994</td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding: 0 5px;"> </td> <td></td> <td></td> <td></td> <td></td> </tr> </table> </div> <p>from which the bearing trees mkd. by Minor</p> <p style="padding-left: 40px;">A hemlock, 14 ins. diam., bears S. 58¼° E., 9.9 ft. dist., with illegible scribe marks visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears S. 69° W., 24.6 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 22 ins. diam., bears N. 13° W., 8.9 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 14' 18" W., beginning new measurement.</p> <p>Along nearly level land.</p>	C	S 1/16	S 31	C	1994	1994						
C	S 1/16	S 31	C	1994	1994								
110	Tioga Creek, 30 ft. wide, course S. 80° E.; asc. over S. slope.												
420	Spur, slopes N. 65° E.; desc. over N. slope.												
945	Tioga Creek, 40 ft. wide, course S. 50° W.; asc. over S. slope.												
1015	Spur, slopes E.; desc. over N. facing cliff, 30 ft. high.												
1025	Bottom of descent, slopes E.; asc. over SW. slope.												
1185	Spur, slopes W.; desc. over N. slope.												
1270.69	<p>A point established as a witness cor. to the center ¼ sec. cor. of sec. 31, by John Minor, Registered Land Surveyor No. 2052, in 1994, and recorded in Coos County Surveyor's Office, Map No. 16B49, and is accepted as the witness cor. to the center ¼ sec. cor., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.</p>												

**Subdivision of Section 31,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	T 26 S R 9 W WC C 1/4 S 31 1994 LS 2052
	<p>from which the bearing trees mkd. by Minor</p> <p>A roothole bears S. $72\frac{1}{2}^{\circ}$ E., 14.1 ft. dist., alongside of which is a down alder, 15 ins. diam., no marks visible.</p> <p>An alder, 21 ins. diam., bears S. 58° E., 46.5 ft. dist., with scribe marks C1/4 S31 BT visible on bark.</p> <p>An alder, 18 ins. diam., bears S. 56° W., 22.9 ft. dist., with scribe marks C1/4 S31 BT visible on bark.</p>
1317.32	<p>True point for the center $\frac{1}{4}$ sec. cor. of sec. 31, determined by extending the N. and S. center line through the witness cor. record distance from the witness cor., utilizing the record from Minor's survey, no permanent monument established.</p> <p>Corner falls in Tioga Creek, 40 ft. wide, course N. 80° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ} 13' 25''$ W., beginning new measurement.</p> <p>Ascend over broken W. slope.</p>
2612.47	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>S. $89^{\circ} 59' 54''$ W., on the E. and W. center line of sec. 31.</p> <p>Descend over SW. slope.</p>
455	Bench, bears N. and S., along nearly level land.
710	Descend over SW. slope.
1080	Descend over NW. slope.
2315	Coos River Mainline Road, asphalt surface, 18 ft. wide, bears N. 5° E. and S. 5° W.; also S. end of bridge over Tioga Creek.
2450	Enter Tioga Creek, 40 ft. wide, course N. 80° E.; thence in creek.

**Subdivision of Section 31,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
2649.23	<p>True point for the center $\frac{1}{4}$ sec. cor. of sec. 31.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S. $89^{\circ} 58' 21''$ W., beginning new measurement.</p> <p>Continue up Tioga Creek.</p>
200	Leave Tioga Creek, course N. 80° E.; asc. over SE. slope.
1000	Creek, dry, 1 ft. wide, course S. 40° E.; asc. over E. slope.
1314.98	Point for the center W $\frac{1}{16}$ sec. cor. of sec. 31, no permanent monument established.
1395	Spur, slopes S.; desc. over SW. slope.
1745	Dirt road, 13 ft. wide, bears N. 20° W. and S. 25° E.
1825	Enter marshy area, edge bears N. and S.; across shallow S. slope.
2045	Leave marshy area, edge bears N. and S.; ascend over SE. slope.
2275	Dirt road, 10 ft. wide, bears N. 30° E. and S. 30° W.
2428.10	<p>The $\frac{1}{4}$ sec. cor. of sec. 31 only, on the W. bdy. of the Tp.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the W $\frac{1}{16}$ sec. cor. of sec. 31 only, on the S. bdy. of the Tp.</p> <p>N. $0^{\circ} 06' 00''$ W., on the N. and S. center line of the SW$\frac{1}{4}$ of sec. 31.</p> <p>Ascend over shallow S. slope through medium timber and moderate undergrowth.</p>
240	Tioga Tie Road, asphalt surface, 16 ft. wide, bears E. and W.; ascend over S. slope.
875	Top of ascent, slopes E.; desc. over NE. slope.
1120	Creek, dry, 1 ft. wide, course S. 20° E.; asc. over SW. slope.
1317.65	<p>Point for the SW $\frac{1}{16}$ sec. cor. of sec. 31, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

**Subdivision of Section 31,
T. 26 S., R. 9 W., Willamette Meridian, Oregon**

FEET	
	SW 1/16 S 31 2002
	from which
	A fir, 16 ins. diam., bears S. 25° E., 26.3 ft. dist., mkd. SW1/16 S31 BT.
	A fir, 9 ins. diam., bears N. 9½° W., 33.8 ft. dist., mkd. SW1/16 S31 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this point, a point established as the SW 1/16 sec. cor. of sec. 31 by John Minor, Registered Land Surveyor No. 2052, in 1994, and recorded in Coos County Surveyor's Office, Map No. 16B49, bears N. 80° 19' 45" W., 1.73 ft. dist. This point was established utilizing erroneous control and is not utilized in this survey, monumented with an iron pipe, 2½ ins. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd. SW 1/16 1994 LS 2052, from which the bearing trees mkd. by Minor
	A fir, 22 ins. diam., bears N. 36½° E., 17.3 ft. dist., with a healed blaze.
	A fir, 12 ins. diam., bears S. 60° E., 9.0 ft. dist., with a healed blaze.
	A fir, 21 ins. diam., bears S. 81½° W., 11.2 ft. dist., with a healed blaze.
	<hr/>
	N. 89° 58' 00" E., on the E. and W. center line of the SW¼ of sec. 31.
	Ascend over SW. slope through medium timber and light undergrowth.
140	Top of ascent, slopes S.; desc. over SE. slope.
540	Descend over steep, rocky SE. slope.
820	Tioga Creek, 40 ft. wide, course N. 70° E.; along nearly level land.
1318.23	The center S 1/16 sec. cor. of sec. 31.
	<hr/>

T. 26 S., R. 9 W., Willamette Meridian, Oregon

FEET	GENERAL DESCRIPTION
	<p>The lands included in the foregoing survey are located in Coos County about 9 miles north-northeast of Sitkum, Oregon. Access is by way of Tioga Tie Road, Burnt Mountain Access Road, Coos River Mainline Road, and various logging roads that lead into the area.</p> <p>Elevations range from about 2400 feet above sea level on the line between sections 34 and 3, near the quarter corner of section 34 only, on the south boundary of the township, to about 600 feet above sea level on the line between sections 30 and 31, halfway between the quarter corner of sections 30 and 31 and the corner of sections 29, 30, 31, and 32. The soil is rocky clay.</p> <p>The area is drained by Burnt Creek, which flows westerly through the sections into Tioga Creek, which flows northerly through section 31, and their tributaries.</p> <p>The timber consists primarily of fir, hemlock, cedar, alder, myrtle, tan oak, maple, chinquapin, and madrone. Undergrowth consists of vine maple, salal, salmonberry, rhododendron, willow, poison oak, Oregon grape, blackberry, huckleberry, ferns, and grasses.</p> <p>There were no mineral deposits noted along the lines surveyed.</p> <p>The magnetic declination, as shown on the United States Geological Survey 7½ minute quadrangle map "TIOGA, OREGON," provisional edition 1990, is 18° east.</p>