

FEET

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE  
SOUTH BOUNDARY AND SUBDIVISIONAL LINES, AND THE  
SUBDIVISION OF SECTIONS 21, AND 32,  
**TOWNSHIP 26 SOUTH, RANGE 7 WEST,**  
OF THE WILLAMETTE MERIDIAN,  
IN THE STATE OF OREGON.

**EXECUTED BY*****Timothy J Moore, Cadastral Surveyor******Robert H. Browning, Surveying Technician***

Under Special Instructions dated May 31, 2001, approved May 31, 2001,  
which provided for the surveys included under Group No. 1990,  
and Assignment Instructions dated June 7, 2001.

***Survey commenced July 9, 2001******Survey completed September 12, 2002***

**T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

The following field notes are those of the dependent resurvey of a portion of the south boundary and subdivisional lines, and the subdivision of sections 21 and 32, township 26 south, range 7 west, of the Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

In 1855, Dennis Hathorn, U.S. Deputy Surveyor, surveyed the north, south, and west boundaries and a portion of the subdivisional lines.

In 1881, Addison R. and Samuel C. Flint, U.S. Deputy Surveyors, retraced the west boundary and portions of the north and south boundaries, and completed the subdivisional lines.

In 1959, Irving Zirpel Jr. and Leo J. Martin, Cadastral Surveyors, dependently resurveyed a portion of the west boundary and subdivisional lines.

In 1969, Lynn M. Roseberry, Cadastral Surveyor, dependently resurveyed a portion of the subdivisional lines.

In 1971-74, Peter A. Peterson, Daniel L. Berry, Gurdon S. Popken, and Harvey E. Wofford, Cadastral Surveyors, dependently resurveyed a portion of the south boundary and a portion of the subdivisional lines.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 31, 2001, for Group No. 1990, Oregon.

The directions of the lines are based on the true meridian as determined by direct solar observations and were carried forward by means of sustained angulation. All measurements along the lines were derived through the use of electronic measuring equipment. An analysis of the unadjusted field data assured a closure not exceeding 1:4000 in error. Measured distance and direction have been adjusted by Cadastral Measurement Management for windows (WinCMM), computer software that incorporates a least squares adjustment routine. The adjusted bearings and distances are reported to the nearest second and 0.01 foot

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. The retracement data were thoroughly verified and only the true line field notes are given herein.

**T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

Each new bearing tree has a 2½ in. X ¼ in. Magnetic nail (MAG-NAIL) driven at the base right side-center, unless otherwise described in the corner description.

The geographic position (NAD 1983 (98)) of the ¼ sec. cor. of secs. 19 and 30, as determined by a tie to geodetic control station No. EC 41308, established by the Bureau of Land Management, in 2001, (see the Control Data Sheet attached to these field notes following the General Description) is as follows:

Latitude: 43° 17' 12.57" N.      Longitude: 123° 34' 28.63" W.

The geographic position (NAD 1983 (98)) of the ¼ sec. cor. of secs. 21 and 28, as determined by a tie to geodetic control station No. EC 41309, established by the Bureau of Land Management, in 2001, (see the Control Data Sheet attached to these field notes following the General Description), is as follows:

Latitude: 43° 17' 13.53" N.      Longitude: 123° 32' 06.91" W.

---

**Dependent Resurvey of a Portion of the South Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the survey by Dennis Hathorn, in 1855, and the resurveys by Addison R. and Samuel C. Flint in 1881, and Peter A. Peterson, Daniel L. Berry, Gurdon S. Popken, and Harvey E. Wofford Cadastral Surveyors, in 1971-74)

Beginning at the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

T 26 S R 7 W		
S 32		S 33
S 5		S 4
		T 27 S
		1959

from which the remains of original bearing trees

A sawed fir stump, 33 ins. diam., bears N. 75¾° E., 11.9 ft. dist., with no marks visible, and a galvanized metal cap.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A sawed fir stump, 37 ins. diam., bears East, 51.5 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 20 ins. diam., bears N. 64° W., 29.7ft.dist., with no marks visible, and a galvanized metal cap.</p> <p>and the remains of a bearing tree mkd. by Zirpel and Martin</p> <p>A sawed fir stump, 28 ins. diam., bears S. 68½° W., 44.2ft.dist., with scribe marks T27S R7W S5 BT visible on partially healed blaze.</p> <p>and an accessory established by John Powell, Frank Jones, and W. Penley, of the Douglas County Surveyors Office, in 1970, recorded in the Douglas County Surveyors Office, corner renewal file No. T. 26 S., R. 7 W., Point Identifier No. 300100</p> <p>An iron rod, 5/8 ins. diam., firmly set, projecting 2 ins. above ground, bears N. 12° 25' 56" W., 23.6 ft. dist.</p> <p>and new bearing trees</p> <p>A fir, 9 ins. diam., bears N. 31½° E., 18.8 ft. dist., mkd. T26S R7W S33 BT.</p> <p>A fir, 10 ins. diam., bears S. 17½° E., 10.8 ft. dist., mkd. T27S R7W S4 BT.</p> <p>A fir, 13 ins. diam., bears S. 25¾° W., 24.4 ft. dist., mkd. T27S R7W S5 BT.</p> <p>A fir, 9 ins. diam., bears N. 19¾° W., 24.6 ft. dist., mkd. T26S R7W S32 BT.</p> <p>S. 89° 25' 52" W., bet. secs. 5 and 32, posting and blazing.</p> <p>Ascend over Easterly slope.</p>
95	Ridge, bears N. 10° E. and S. 30° W.; desc. over broken SW. slope.
135	Graveled road, 25 ft. wide, bears N. 5° E. and S. 5° W.
860	Ravine, drains N. 20° W., asc. over broken NE. slope.
1180	Spur, slopes N. 10° W.; desc. over broken NW. slope.

**Dependent Resurvey of a Portion of the South Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
1324.93	<p>The E 1/16 sec. cor. of secs. 5 and 32, monumented with a brass tablet, 3½ ins. diam., firmly set, flush in solid rock, mkd.</p> <p style="text-align: center;">S 32 E 1/16 ——— S 5 1974</p> <p>form which the remains of bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 41½° E., 52.1 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir snag, 8 ins. diam., bears S. 51½° E., 49.5 ft. dist., with scribe marks E 1/16 S5 BT visible on partially open blaze.</p> <p>and a bearing tree mkd. by Tony Hostetter, Registered Professional Land Surveyor, No. 1975, in 2001, unrecorded</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. 84¾° E., 37.3 ft. dist., with scribe marks S1/16 visible on partially healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 23' 13" W., beginning a new measurement.</p> <p>Descend over broken NW. slope.</p>
1327.38	<p>The ¼ sec. cor. of secs. 5 and 32, monumented with an iron pipe, 1¼ ins. diam., set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">COUNTY SURVEYORS OFFICE T 26 S R 7 W S 32 1/4 ——— S 5 T 27 S R 7 W 1961</p> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A sawed fir stump, 36 ins. diam., bears S. 58° E., 8.6 ft. dist., with no marks remaining.</p>

**Dependent Resurvey of a Portion of the South Boundary,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET

and the remains of a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1961, recorded in the Douglas County Surveyors Office, corner renewal file No. T. 26 S., R. 7 W., Point Identifier No. 240100

A roothole, bears N. 66° W., 134.0 ft. dist., with decayed fir trunk alongside, size indeterminate, with scribe marks 1/4 S32 CS BT visible on open double blaze.

and bearing trees mkd. by Peterson, Berry, Popken, and Wofford

A hemlock, 18 ins. diam., bears N. 19° E., 122.1 ft. dist., with a healed blaze.

A fir, 18 ins. diam., bears S. 10½° W., 30.7 ft. dist., with a healed blaze.

and bearing trees mkd. by Tony Hostetter, Registered Professional Land Surveyor, No. 1975, in 2001, recorded in the Douglas County Surveyors Office, corner renewal file No. T. 26 S., R. 7 W., Point Identifier No. 240100

A fir, 9 ins. diam., bears N. 65° E., 8.0 ft. dist., with scribe marks S32 1/4 BT visible on partially healed blaze.

A fir, 13 ins. diam., bears S. 5¼° E., 21.9 ft. dist., with scribe marks S5 1/4 BT visible on partially healed blaze.

---

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

---

(Restoring the survey by Dennis Hathorn, in 1855, and the resurveys by Addison R. and Samuel C. Flint, in 1881, Irving Zirpel Jr. and Leo J. Martin, in 1959, Lynn M. Roseberry, in 1967-69, and Peter A. Peterson, Dainiel L. Berry, Gurdon S. Popken, and Harvey E. Wofford, in 1971-74)

---

From the cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	T 26 S R 7 W S 21   S 22 <hr style="width: 50%; margin: 0 auto;"/> S 28   S 27 1974 1959
	<p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A stump hole, bears S. 16° E., 19.8 ft. dist., with madrone sprouts, 8 ins. diam., with no marks visible.</p> <p>and bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 14 ins. diam., bears N. 40½° E., 14.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears S. 89½° E., 6.9 ft. dist., with a healed blaze.</p> <p>and new bearing trees</p> <p style="padding-left: 40px;">A chinquapin, 5 ins. diam., bears S. 33° W., 11.8 ft. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 16¾° W., 7.3 ft. dist., mkd. T26S R7W S21 BT.</p> <p>Corner is located East of a mound of stone 3 ft. base, 2 ft. high, erected by Zirpel and Martin</p> <p>N. 0° 08' 40" W., bet. secs. 21 and 22, posting and blazing.</p> <p>Descend over broken NE. slope.</p>
1319.96	<p>The S 1/16 sec. cor. of secs. 21 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">           S 1/16            S 21   S 22            1974         </p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 85° E., 9.9 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p style="text-align: center;">A fir, 14 ins. diam., bears N. 87° W., 6.6 ft. dist., with a healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 04" 37" W., beginning a new measurement.</p> <p>Descend over broken NE. slope.</p>
1323.04	<p>The ¼ sec. cor. of secs. 21 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W 1/4 S 21   S 22 1974</p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="text-align: center;">A fir, 24 ins. diam., bears S. 32° E., 56.7 ft. dist., with a healed blaze.</p> <p style="text-align: center;">A fir, 24 ins. diam., bears S. 40° W., 63.0 ft. dist., with a healed blaze.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.</p> <p>N. 0° 21' 48" E., bet. secs. 32 and 33, posting and blazing.</p> <p>Ascend over SE. slope changing to a descend over NE. slope.</p>
850	<p>Asphalt road, in a curve, 24 ft. wide, bears N. 15° W. and S. 10° E.</p>
1329.65	<p>The S 1/16 sec. cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 32   S 33 1974</p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 20 ins. diam., bears N. 40° E., 15.8 ft. dist., with a healed blaze.</p> <p>A fir, 29 ins. diam., bears S. 44° W., 70.6 ft. dist., with a healed blaze.</p> <p>Discontinue posting and blazing.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 22' 35" E., beginning a new measurement.</p> <p>Descend over broken NW. slope.</p>
30	Dirt road, 12 ft. wide, bears N. 40° E. and S. 20° W.
1329.81	<p>The ¼ sec. cor. of secs. 32 and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 26 S R 7 W</p> <p>1/4</p> <p>S 32   S 33</p> <p>1974</p> </div> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p>A fir, 18 ins. diam., bears S. 32° E., 19.1 ft. dist., with a healed blaze.</p> <p>A fir, 28 ins. diam., bears S. 70¼° W., 38.9 ft. dist., with a healed blaze.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 26 S R 7 W</p> <p>S 29   S 28</p> <hr style="width: 20%; margin: 0 auto;"/> <p>S 32   S 33</p> <p>1974</p> </div> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p>A fir, 19 ins. diam., bears S. 5° E., 105.6 ft. dist., with a healed blaze.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 23 ins. diam., bears S. 32° W., 58.1 ft. dist., with a healed blaze.</p> <p>A fir, 20 ins. diam., bears N. 40¼° W., 85.1 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 7 ins. diam., bears N. 60° E., 7.5 ft. dist., mkd. T26S R7W S28 BT.</p> <p>N. 0° 16' 09" E., bet. secs. 28 and 29, posting and blazing.</p> <p>Descend over broken NW. slope.</p>
2205	Abandoned dirt road, 12 ft. wide, bears N. 10° W. and S. 20° E.
2430	Abandoned dirt road, 12 ft. wide, bears N. 35° W. and S. 5° E.
2658.55	The ¼ sec. cor. of secs. 28 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	<p>T 26 S R 7 W 1/4 S 29   S 28 1974</p>
	<p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p>A fir, 16 ins. diam., bears S. 30¾° E., 9.2 ft. dist., with a healed blaze.</p> <p>A fir, 19 ins. diam., bears N. 74½° W., 15.2 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 16' 34" E., beginning a new measurement, continue posting and blazing.</p> <p>Descend over NE. slope.</p>
1335	Creek, 2 ft. wide, course S. 60° W.; asc. over SW. slope.
2663.87	The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, loosely set, projecting 18 ins. above ground, reset in a mound of stone, 3½ ft. base, 1½ ft. high, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	T 26 S R 7 W S 20   S 21 ----- S 29   S 28 1959
	<p>from which a bearing object mkd. by Zirpel and Martin</p> <p style="padding-left: 40px;">A bedrock outcropping, bears S. 70° E., 7.6 ft. dist., chiseled X BO.</p> <p>and a bearing tree mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A madrone, 12 ins. diam., bears S. 39° W., 7.3 ft. dist., with no marks visible.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 47½° W., 75.3 ft. dist., mkd. T26S R7W S20 BT.</p> <p>No other suitable trees available in sec. 21, within limits.</p> <hr/> <p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89° 53' 07" W., bet. secs. 21 and 28, posting and blazing.</p> <p>Ascend over broken NE. slope.</p>
1215	Ridge, bears N. 25° W. and S. 25° E.; desc. over NW. slope.
1292.46	The E 1/16 sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 11 ins. above ground, with brass cap mkd.
	S 21 E 1/16 ——— S 28 1959
	<p>from which reference monuments set by Zirpel and Martin</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground for a reference monument, bears N. 12° 54' 46" E., 9.7 ft. dist., with brass cap mkd. E1/16 S21 RM 1959 and an arrow pointing to the corner. (Record, N. 15° E.)</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>An iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground for a reference monument, bears S. 13° 06' 26" W., 9.7 ft. dist., with brass cap mkd. E1/16 S28 RM 1959 and an arrow pointing to the corner. (Record, S. 15° W.)</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>N. 89° 55' 46" W., beginning a new measurement, continue posting and blazing.</p> <p>Continue desc. over broken NW. slope.</p>
200	Dirt road, 12 ft. wide, bears N. 45° W. and S. 25° E.
1110	Ravine, drains S. 65° W., asc. over SW. slope.
1301.28	The ¼ sec. cor. of secs. 21 and 28, monumented with an iron post, 2½ ins. diam., firmly set, projecting 9 ins. above ground, with brass cap mkd.
	<p>T 26 S R 7 W S 21 1/4 ————— S 28 1959</p>
	<p>from which reference monuments set by Zirpel and Martin</p> <p>An iron post, 2½ ins. diam., firmly set, projecting 3 ins. above the ground for a reference monument, bears S. 3° 21' 18" E., 7.4 ft. dist., with brass cap mkd. T26S R7W 1/4 S28 RM 1959 and an arrow pointing to the corner. (Record, South)</p> <p>An iron post, 2½ ins. diam., firmly set, projecting 9 ins. above the ground for a reference monument, bears N. 1° 25' 18" W., 7.4 ft. dist., with brass cap mkd. T26S R7W 1/4 S21 RM 1959 and an arrow pointing to the corner. (Record, North)</p> <p>From this point, the Bureau of Land Management Geodetic Control Station No. EC 41309, determined by the NAVSTAR Global Positioning System (GPS), utilizing static dual frequency, carrier phase receivers, (see the Control Data Sheet attached to these field notes following the General Description) bears N. 82° 25' 21" W., 1657.85 ft. dist., (mean bearing and sea level distance); monumented with an aluminum cap, 3½ ins. diam., firmly set, flush with the ground, with top mkd. EC41309 GPS 2001.</p> <hr style="width: 60%; margin: 10px auto;"/>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>From the E 1/16 sec. cor. of secs. 16 and 21, occupied by a fir, 18 ins. diam., with healed blazes on the North, South, and East faces, (drive a Mag-Nail South side center), from which bearing trees and a reference monument mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 26 ins. diam., bears N. 13½° E., 36.4 ft. dist., with a healed double blaze. (Record, N. 9° E., 35.6 ft. dist.)</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 83° E., 29.7 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set, projecting 5 ins. above the ground for a reference monument, bears S. 83° 00' 00" E., 19.8 ft. dist., with brass cap mkd. E1/16 S21 RM 1974 and an arrow pointing to the corner.</p> <p>N. 89° 22' 56" W., bet. secs. 16 and 21, posting and blazing.</p> <p>Ascend over SE. slope.</p>
275	Ridge, bears N. 5° E. and S. 5° W.; desc. over SW. slope, also gravelled road, 10 ft. wide, bears same.
825	Ravine, drains N. 65° W., asc. over NE. slope.
1288.89	<p>The ¼ sec. cor. of secs. 16 and 21, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W S 16 1/4 ————— S 21 1974</p> <p>from which the remains of bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 28 ins. diam., bears N. 51° E., 64.0 ft. dist., with a healed double blaze.</p> <p style="padding-left: 40px;">A decayed fir snag, 19 ins. diam., bears S. 39° W., 44.2 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears S. 3¾° E., 49.2 ft. dist., mkd. X BT.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>Corner is located at the base of a fir, 27 ins. diam.</p> <hr/> <p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>S. 89° 04' 06" W., bet. secs. 29 and 32, posting and blazing.</p> <p>Descend over broken NW. slope.</p>
1840	Dirt road, 10 ft. wide, bears S. 25° E. and N. 35° W.
1975	Dirt road, 12 ft. wide, bears S. 15° E. and N. 5° W.
2195	Hubbard Creek, 14 ft. wide, course N. 40° W.; asc. over NE. slope.
2643.36	<p>The ¼ sec. cor. of secs. 29 and 32, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W S 29 1/4 ————— S 32 1974</p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 21 ins. diam., bears N. 76° E., 30.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 74½° E., 35.6 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 02' 33" W., beginning a new measurement, continue posting and blazing.</p>
	Ascend over broken NE. slope.
235	An abandoned dirt road, 12 ft. wide, bears N. 30° E. and S. 45° W.
1370	Spur, slopes North; desc. over NW. slope.
2641.71	The cor. of secs. 29, 30, 31, and 32, monumented with an iron post, firmly set, projecting 6 ins. above ground, with brass cap mkd.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	T 26 S R 7 W S 30   S 29 ----- S 31   S 32 1974
	<p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears N. 41° E., 20.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A madrone, 11 ins. diam., bears S. 30° E., 49.5 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A madrone, 6 ins. diam., bears S. 53½° W., 25.1 ft. dist., with scribe marks 26S R7W S31 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 36° W., 48.2 ft. dist., with a healed blaze.</p> <p>From this point a point established by Wilford N. Haines, Registered Professional Land Surveyor, No. 239, in 1951, according to the narrative on the survey plat by Tony Hostetter, Registered Professional Land Surveyor No. 1975, in 1999, recorded in the Douglas County Surveyors Office, map file No. 134-63, monumented with an aluminum conduit pipe, ½ ins. diam., firmly set, projecting 15 ins. above ground, bears S. 40° 41' 23" W., 34.56 ft. dist., and is not utilized during the course of the Hostetter survey or this survey.</p> <hr/> <p>N. 0° 56' 30" E., bet. secs. 29 and 30, posting and blazing.</p> <p>Descend over broken NW. slope.</p> <p>1225 Creek, 6 ft. wide, course N. 70° E.; asc. over SE. slope.</p> <p>2270 Spur, slopes S. 85° E.; desc. over NW. slope.</p> <p>2636.99 The ¼ sec. cor. of secs. 29 and 30, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.</p>
	COUNTY SURVEYORS OFFICE T 26 S R 7 W 1/4 S 30   S 29 1957

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET																
	<p>from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A decayed fir stump, size indeterminate, bears N. 20° E., 8.6 ft. dist., with no marks remaining.</p> <p style="padding-left: 40px;">A decayed fir snag, 21 ins. diam., bears N. 30° W., 8.6 ft. dist., with no marks visible.</p> <p>and the remaining bearing tree mkd. by James W. Byron, County Surveyor, in 1957, recorded in the Douglas County Surveyors Office, corner renewal file, T. 26 S., R. 7 W., Point Identifier No. 200240</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. 27° E., 59.4 ft. dist., with a healed double blaze. (Record, fir snag)</p> <p>and bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 28½° E., 23.4 ft. dist., with a healed blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 54° W., 10.6 ft. dist., with a healed blaze.</p> <p>The Peterson, Berry, Popken, and Wofford record erroneously shows this brass cap as being marked 1959.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 06' 30" E., beginning a new measurement, continue posting and blazing.</p> <p>Continue descending over broken NW. slope.</p>															
2450	Creek, 1 ft. wide, course N. 40° E.; asc. over NE. slope.															
2646.40	<p>The cor. of secs. 19, 20, 29, and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="padding: 0 5px;">T 26 S R 7 W</td> <td></td> <td></td> </tr> <tr> <td style="padding: 0 5px;">S 19</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 20</td> </tr> <tr> <td colspan="3" style="border-top: 1px solid black; padding: 2px 0 2px 5px;"></td> </tr> <tr> <td style="padding: 0 5px;">S 30</td> <td style="border-left: 1px solid black; border-right: 1px solid black; padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 29</td> </tr> <tr> <td colspan="3" style="padding: 0 5px;">1974</td> </tr> </table> </div> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p>	T 26 S R 7 W			S 19		S 20				S 30		S 29	1974		
T 26 S R 7 W																
S 19		S 20														
S 30		S 29														
1974																

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>A fir, 14 ins. diam., bears N. 63½° E., 29.7 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 21° E., 23.1 ft. dist., with a healed blaze.</p> <p>A fir, 11 ins. diam., bears S. 53° W., 10.6 ft. dist., with a healed blaze.</p> <p>A fir, 12 ins. diam., bears N. 35½° W., 9.9 ft. dist., with a healed blaze.</p>
	<hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>S. 88° 34' 43" W., bet. secs. 20 and 29, posting and blazing.</p> <p>Descend over broken SW. slope.</p>
1220	Creek, 2 ft. wide, course N. 55° W.; asc. over NE. slope.
1780	Spur, slopes N. 10° W.; desc. over NW. slope.
1985	Creek, 1 ft. wide, course N. 15° W.; asc. over NE. slope.
2639.45	<p>The ¼ sec. cor. of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W S 20 1/4 ————— S 29 1974</p> <p>from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford</p> <p>A fir, 14 ins. diam., bears S. 65° W., 11.9 ft. dist., with a healed blaze.</p> <p>A fir, 14 ins. diam., bears N. 42° W., 16.8 ft. dist., with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88° 40' 03" W., beginning a new measurement, continue posting and blazing.</p> <p>Continue ascending over NE. slope.</p>

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
565	Spur, slopes N. 35° W.; desc. over NW. slope.
1645	Graveled road, 11 ft. wide, bears N. 10° E. and South.
1750	Hubbard Creek, 10 ft. wide, course N. 10° E.; asc. over SE. slope.
2230	Ridge, bears N. 25° E. and S. 30° W.; desc. over NW. slope.
2550	Creek, 1 ft. wide, course N. 35° E.; asc. over NE. slope.
2622.17	The cor. of secs. 19, 20, 29, and 30.
	N. 89° 28' 40" W., bet. secs. 19 and 30, posting and blazing.
	Ascend over broken NE. slope.
955	Spur, slopes N. 20° W.; continue asc. over broken NE. slope.
1275	Dirt road, 9 ft. wide, bears N. 50° W. and S. 45° E.
1590	Spur, slopes North; desc. over NW. slope.
2210	Bottom of descent, slopes N. 40° E.; asc. over SE. slope, also a dirt road, 12 ft. wide, bears N. 40° E. and S. 40° W.
2565	Spur, slopes S. 35° E.; desc. over SW. slope.
2627.92	The ¼ sec. cor. of secs. 19 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	T 26 S R 7 W S 19 1/4 ————— S 30 1974
	from which bearing trees mkd. by Peterson, Berry, Popken, and Wofford
	A fir, 11 ins. diam., bears N. 44° E., 19.5 ft. dist., with a healed blaze.
	A fir, 16 ins. diam., bears S. 67° W., 24.1 ft. dist., with a healed blaze.
	From this point, the Bureau of Land Management Geodetic Control Station No. EC 41308, determined by the NAVSTAR GPS, utilizing static dual frequency, carrier phase receivers, (see the Control

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET													
	Data Sheet attached to these field notes following the General Description) bears N. 67° 21' 16" E., 1084.90 ft. dist., (mean bearing and sea level distance); monumented with an aluminum cap, 3½ ins. diam., firmly set flush with the ground, with top mkd. EC41308 GPS 2001.												
	_____												
	N. 89° 30' 00" W., beginning a new measurement, continue posting and blazing.												
	Continue descending over broken SW. slope.												
1345	Creek, 3 ft. wide, course N. 55° W.; asc. over NE. slope.												
1975	Spur, slopes N. 20° W.; desc. over NW. slope.												
2615	Creek, 2 ft. wide, course N. 20° E.; asc. over NE. slope.												
2677.87	The cor. of secs. 19, 24, 25, and 30, on the W. bdy. of the township, monumented with an iron post, 2½ ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T 26 S</td></tr> <tr><td style="text-align: center;">R 8 W</td><td style="text-align: center;">R 7 W</td></tr> <tr><td style="text-align: center;">S 24</td><td style="text-align: center;">S 19</td></tr> <tr><td colspan="2" style="text-align: center;">-----</td></tr> <tr><td style="text-align: center;">S 25</td><td style="text-align: center;">S 30</td></tr> <tr><td colspan="2" style="text-align: center;">1959</td></tr> </table>	T 26 S		R 8 W	R 7 W	S 24	S 19	-----		S 25	S 30	1959	
T 26 S													
R 8 W	R 7 W												
S 24	S 19												
-----													
S 25	S 30												
1959													
	A mound of stone 3½ ft. base, 2.0 ft. high, is to the West.												
	from which the remains of bearing trees mkd. by Peterson, Berry, Popken, and Wofford												
	A stump hole, bears N. 15° E., 11.9 ft. dist., with decayed fir alongside, 9 ins. diam., with a healed blaze.												
	A fir, 13 ins. diam., bears S. 18° W., 20.1 ft. dist., with a healed blaze.												
	A fir, 11 ins. diam., bears N. 2¼° W., 26.3 ft. dist., with a healed blaze. (Record N. 6½° W., 26.7 ft. dist.)												
	and new bearing trees												
	A fir, 17 ins. diam., bears N. 68½° E., 30.5 ft. dist., mkd. T26S R7W S19 BT.												

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	A fir, 18 ins. diam., bears S. 72° E., 3.4 ft. dist., mkd. T26S R7W S30 BT.
	From the cor. of secs. 19, 20, 29, and 30.
	N. 0° 08' 16" E., bet. secs. 19 and 20, posting and blazing.
	Ascend over SE. slope.
445	Spur, slopes N. 20° W.; desc. over NW. slope.
995	Ravine, drains N. 20° E., continue desc. over NW. slope.
1095	Ravine, drains N. 25° E., asc. over SW. slope.
1615	Spur, slopes N. 30° E.; desc. over NE. slope.
1815	Ravine, drains N. 80° E., asc. over SE. slope.
2135	Spur, slopes N. 70° E.; desc. over NE. slope.
2265	Rock bluff, 15 ft. high, edge bears N. 60° E. and S. 60° W., continue descending over NE. slope.
2647.37	The ¼ sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.
	T 26 S R 7 W 1/4 S 19   S 20 1969
	from which the remains of the original bearing trees
	A sawed fir stump, 60 ins. diam., bears S. 69° E., 33.0 ft. dist., no marks visible.
	A sawed fir stump, 48 ins. diam., bears N. 23° W., 21.1 ft. dist., with a healed blaze.
	and bearing trees mkd. by Roseberry
	A fir, 14 ins. diam., bears N. 49° E., 19.5 ft. dist., no marks visible.
	A fir, 15 ins. diam., bears N. 55° W., 28.4 ft. dist., with a healed blaze.

**Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET											
	N. 0° 13' 23" E., beginning a new measurement, continue posting and blazing.										
	Continue descending over a NE. slope.										
135	Hubbard Creek, 12 ft. wide, course N. 80° W.; asc. over SW. slope.										
250	Graveled road, 10 ft. wide, bears N. 65° W. and S. 60° E.										
1275	Spur, slopes S. 85° W.; desc. over NW. slope.										
1385	Creek, 1 ft. wide, course N. 55° W.; asc. over NE. slope.										
2085	Dirt road, 14 ft. wide, bears N. 85° E. and S. 85° W.										
2115	Dirt road, 12 ft. wide, bears N. 70° E. and S. 70° W.										
2190	Ridge, bears N. 75° W. and S. 75° E.; desc. over North slope.										
2637.67	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.										
	<table style="margin: auto;"> <tr> <td>T 26 S R 7 W</td> <td></td> </tr> <tr> <td>S 18</td> <td>S 17</td> </tr> <tr> <td colspan="2" style="text-align: center;"> </td> </tr> <tr> <td>S 19</td> <td>S 20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1969</td> </tr> </table>	T 26 S R 7 W		S 18	S 17			S 19	S 20	1969	
T 26 S R 7 W											
S 18	S 17										
S 19	S 20										
1969											
	from which bearing trees mkd. by Roseberry										
	A fir, 16 ins. diam., bears N. 17¾° E., 46.9 ft. dist., with a healed blaze.										
	A fir, 16 ins. diam., bears S. 16° E., 18.5 ft. dist., with a healed blaze.										
	A fir, 15 ins. diam., bears S. 72½° W., 26.1 ft. dist., with a healed blaze.										
	A fir, 16 ins. diam., bears N. 52° W., 24.4 ft. dist., with a healed blaze.										
	<hr/> <p><b>Subdivision of Section 21, T. 26 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/>										
	From the ¼ sec. cor. of secs. 21 and 28.										

**Subdivision of Section 21,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 0° 03' 30" E., on the N. and S. centerline of sec. 21.
	Ascend over broken SW. slope.
550	Dirt road, 12 ft. wide, bears N. 55° W. and S. 70° E.
1325.69	Point for the center S 1/16 sec. cor. of sec. 21, not monumented.
1970	Ridge, bears N. 80° W. and S. 80° E.; desc. over NW. slope.
2651.38	Point for the center ¼ sec. cor. of sec. 21, at the intersection with the E. and W. centerline.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T 26 S R 7 W C 1/4 S 21 2001
	from which
	A fir, 6 ins. diam., bears S. 52½° E., 4.4 ft. dist., mkd. C1/4 S21 BT.
	A fir, 12 ins. diam., bears S. 76½° W., 2.8 ft. dist., mkd. C1/4 S21 BT.
	Deposit a magnet in a white plastic case at the base of the stainless steel post.
	From this point, a point unofficially established as the center ¼ sec. cor. of sec. 21 by the Bureau of Land Management, in 1978, during the course of an administrative survey, bears N. 23° 36' 23" E., 1.17 ft. dist., monumented with a galvanized iron pipe, ½ ins. diam., firmly set, projecting 4 ins. above ground. This point was not utilized during the course of this survey. Remove the iron pipe and place inside the stainless steel post, from which unmarked bearing trees referenced to in the administrative survey
	A fir, 12 ins. diam., bears S. 54¾° E., 12.4 ft. dist., with no marks visible.
	A fir, 13 ins. diam., bears N. 30¾° W., 2.1 ft. dist., with no marks visible.
	Descend over NW. slope.

**Subdivision of Section 21,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
5309.83	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 16 and 21.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22.</p> <p>N. <math>89^{\circ} 43' 17''</math> W., on the E. and W. centerline of sec. 21.</p> <p>Ascend over NE. slope.</p>
1292.82	<p>Point for the center E <math>\frac{1}{16}</math> sec. cor. of sec. 21.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E <math>\frac{1}{16}</math></p> <p>C ——— C</p> <p>S 21</p> <p>2001</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. <math>81^{\circ}</math> E., 4.2 ft. dist., mkd. CE <math>\frac{1}{16}</math> S21 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. <math>22\frac{3}{4}^{\circ}</math> W., 9.8 ft. dist., mkd. CE <math>\frac{1}{16}</math> S21 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>From this point, a point unofficially established as the center E <math>\frac{1}{16}</math> sec. cor. of sec. 21 by the Bureau of Land Management, in 1978, during the course of an administrative survey, bears N. <math>27^{\circ} 46' 59''</math> E., 1.03 ft. dist., monumented with an iron pipe, <math>\frac{3}{4}</math> ins. diam., firmly set, projecting 5 ins. above ground. This point was not utilized during the course of this survey. Remove the iron pipe and place inside the stainless steel post, from which unmarked bearing trees referenced to in the administrative survey</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears S. <math>2^{\circ}</math> E., 6.0 ft. dist., with no marks visible.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. <math>60^{\circ}</math> W., 5.3 ft. dist., with no marks visible.</p> <p>Ascend over NE. slope.</p>
2340	<p>Dirt road, 13 ft. wide, bears N. <math>35^{\circ}</math> W. and S. <math>35^{\circ}</math> E.</p>

**Subdivision of Section 21,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2365	Spur, slopes N. 10° W.; desc. over NW. slope.
2585.64	The center ¼ sec. cor. of sec. 21.  Descend over NW. slope.
2600	Ravine, drains North, asc. over NE. slope.
2670	Spur, slopes N. 10° W.; desc. over NW. slope.
3375	Ravine, drains North, asc. over NE. slope.
4505	Ridge, bears N. 10° W. and S. 10° E.; desc. over SW. slope.
5168.22	The ¼ sec. cor. of secs. 20 and 21, monumented with a brass tablet, 3½ ins. diam., firmly cemented flush in solid bedrock, mkd.  <div style="text-align: center;">           T 26 S R 7 W            1/4            S 20   S 21            1959         </div> from which bearing trees mkd. by Zirpel and Martin  <div style="margin-left: 40px;">             A fir, 25 ins. diam., bears S. 60° E., 51.5 ft. dist., with a healed blaze.               A fir, 22 ins. diam., bears N. 59¾° W., 92.6 ft. dist., with a healed blaze. (Record, N. 52° W., 92.4 ft.)           </div> <hr/> From the center E 1/16 sec. cor. of sec. 21.  N. 0° 01' 28" W., on the N. and S. centerline of the NE¼ of sec. 21, posting and blazing.  Descend over NE. slope.
570	Ravine, drains N. 85° E., asc. over SE. slope.
715	Spur, slopes N. 50° E.; desc. over NE. slope.
2650.84	The E 1/16 sec. cor. of secs. 16 and 21.  <hr/> From the S 1/16 sec. cor. of secs. 21 and 22.

**Subdivision of Section 21,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>N. 89° 46' 49" W., on the calculated E. and W. centerline of the SE¼ of sec. 21, posting and blazing.</p> <p>Ascend over broken NE. slope.</p>
1291.86	<p>Point for the SE 1/16 sec. cor. of sec. 21, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 21 2001</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 60¾° E., 7.3 ft. dist., mkd. SE 1/16 S21 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 37½° W., 11.9 ft. dist., mkd. SE 1/16 S21 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 07' 17" W., on the calculated N. and S. centerline of the SE¼ of sec. 21, continue posting and blazing.</p> <p>Descend over NE. slope.</p>
1324.38	<p>The center E 1/16 sec. cor. of sec. 21.</p> <hr/> <p style="text-align: center;"><b>Subdivision of Section 32, T. 26 S., R. 7 W., Willamette Meridian, Oregon</b></p> <hr/> <p>From the ¼ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. 0° 26' 34" E., on the N. and S. centerline of sec. 32.</p> <p>Descend over Westerly slope.</p>
1328.43	<p>Point for the center S 1/16 sec. cor. of sec. 32, not monumented.</p>
2280	<p>Hubbard Creek, 1½ ft. wide, course N. 10° E.; asc. over NE. slope.</p>

**Subdivision of Section 32,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
2656.86	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 32, at the intersection with the E. and W. centerline.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W C 1/4 S 32 2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears N. <math>25\frac{3}{4}^{\circ}</math> E., 22.4 ft. dist., mkd. C1/4 S32 BT.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. <math>46^{\circ}</math> W., 8.4 ft. dist., mkd. C1/4 S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <p>Ascend over NE. slope.</p>
5305.02	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 32.</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 32 and 33.</p> <p>S. <math>89^{\circ} 21' 05''</math> W., on the E. and W. centerline of sec. 32.</p> <p>Descend over broken NW. slope.</p>
1324.33	Point for the center E $\frac{1}{16}$ sec. cor. of sec. 32, not monumented.
2585	Hubbard Creek, $1\frac{1}{2}$ ft. wide, course N. $10^{\circ}$ E.; asc. over NE. slope.
2648.66	The center $\frac{1}{4}$ sec. cor. of sec. 32.
3280	Dirt road, 12 ft. wide, bears N. $30^{\circ}$ W. and S. $30^{\circ}$ E.
5297.09	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, monumented with an iron post, <math>2\frac{1}{2}</math> ins. diam., firmly set, projecting 5 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 7 W 1/4 S 31   S 32 1974</p>

**Subdivision of Section 32,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	<p>from which a bearing tree mkd. by Peterson, Berry, Popken, and Wofford</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. <math>10\frac{3}{4}^{\circ}</math> W., 46.2 ft. dist., with a healed blaze.</p> <p>and bearing trees mkd. by Tony Hostetter, Registered Professional Land Surveyor, No. 1975, in 1999, recorded in the Douglas County Surveyors Office, map file No. M134-63</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. <math>45\frac{1}{2}^{\circ}</math> E., 17.6 ft. dist., with fragmentary scribing visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears S. <math>53\frac{3}{4}^{\circ}</math> E., 6.9 ft. dist., with fragmentary scribing visible on partially healed blaze.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. <math>34\frac{1}{2}^{\circ}</math> W., 8.1 ft. dist., with fragmentary scribing visible on partially healed blaze.</p>
	<hr/> <p>From the E 1/16 sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp.</p> <p>N. <math>0^{\circ} 22' 48''</math> E., on the calculated N. and S. centerline of the SE<math>\frac{1}{4}</math> of sec. 32, posting and blazing.</p> <p>Descend over broken NE. slope.</p>
865	Ravine, drains N. $60^{\circ}$ W., asc. over SW. slope.
1328.52	<p>Point for the SE 1/16 sec. cor. of sec. 32, at its calculated position.</p> <p>Set a stainless steel post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 32 2002</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. <math>63\frac{1}{2}^{\circ}</math> E., 6.1 ft. dist., mkd. SE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. <math>46^{\circ}</math> W., 3.4 ft. dist., mkd. SE 1/16 S32 BT.</p> <p>Deposit a magnet in a white plastic case at the base of the stainless steel post.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>

**Subdivision of Section 32,  
T. 26 S., R. 7 W., Willamette Meridian, Oregon**

FEET	
	N. 89° 22' 55" E., on the calculated E. and W. centerline of the SE¼ of sec. 32, continue posting and blazing.
	Ascend over broken SW. slope changing to a broken NW. slope.
15	Dirt road, 14 ft. wide, bears N. 20° E. and S. 10° W, also top of ridge, bears the same.
1324.48	The S 1/16 sec. cor. of secs. 32 and 33.
<b>GENERAL DESCRIPTION</b>	
<p>The lands included in the foregoing survey are located about 25 miles southwesterly from Sutherlin, Oregon. The area is drained by Hubbard Creek, Elgaross Creek, and a number of small seasonal streams. Elevations range from about 1200 feet above mean sea level, near the ¼ sec. cor. of secs. 19 and 20, to about 2500 feet above mean sea level near the ¼ sec. cor. of secs. 31 and 32.</p>	
<p>Access is gained by way of Hubbard Creek Road, a paved and graveled road which extends westerly from Sutherlin, also by Callahan Road and numerous other logging and private roads.</p>	
<p>Soil consists of rock, clay, and sandy loam. There were a number of rock outcroppings and bluffs throughout the area.</p>	
<p>Timber in this area consists of fir, cedar, hemlock, oak, alder, madrone, maple, and chinquapin. Undergrowth consists of vine maple, hazel, ceanothus, fern, poison oak, salal, Oregon grape, arrowwood, huckleberry, salmonberry, and rhododendron.</p>	
<p>There were no mineral deposits along the lines resurveyed. The lands are used primarily for timber production.</p>	
<p>The mean magnetic declination, as shown on the United States Geological Survey 7½ minute quadrangle map "CALLAHAN, OREGON", provisional edition, published in 1990, is 18° East.</p>	