

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION AND/OR REMONUMENTATION
OF CERTAIN CORNER POINTS ON THE WEST
BOUNDARY AND SUBDIVISIONAL LINES,
TOWNSHIP 24 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 22, 2002,
approved February 22, 2002, which provided for the
remonumentation and/or rehabilitation included under Group No. 2000,
and Assignment Instructions dated June 30, 2003

Survey commenced June 30, 2003

Survey completed July 10, 2003

T. 24 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation and/or remonumentation of certain corner points on the west boundary and subdivisional lines, township 24 south, range 6 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2003, under Group No. 2000.

The rehabilitation and/or remonumentation of certain corner points, was made at the request of the Roseburg District Manager, for the administrative purposes of the Bureau of Land Management.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.

The mean magnetic declination, as taken from U.S. Geological Survey quadrangle map, "TYEE MOUNTAIN, OREG.", Provisional Edition, dated 1987, is 19° East.

**Rehabilitation of Certain Corner Points, West Boundary,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by
Williams R. Whipple, U.S. Deputy Surveyor, in 1893,
and reestablished by Joseph S. Gawron,
Cadastral Surveyor, in 1962)

The closing corner of sections 24 and 25 only, T. 24 S., R. 7 W. on the W. bdy. of T. 24 S., R. 6 W., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

	T 24 S	
	R 7 W	
	S 24	S 19
CC		
	S 25	
	1962	

from which the remaining bearing tree mkd. by Gawron

A fir, 32 ins. diam., bears N. 5° W., 26.7 ft. dist.,
with a healed blaze.

and a new bearing tree

**Rehabilitation of Certain Corner Points, West Boundary,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET							
	<p style="text-align: center;">A fir, 11 ins. diam., bears S. 60½° W., 31.0 ft. dist., mkd. T24S R7W S25 CC BT.</p> <p>The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade Global Positioning System (GPS) receiver (Trimble GEO Explorer 3) observation, is as follows:</p> <p style="text-align: center;">Latitude: 43° 27' 41.4" N. Longitude: 123° 27' 59.2" W.</p> <hr/> <p style="text-align: center;">(Rehabilitating a corner established by Joseph S. Gawron, Cadastral Surveyor, in 1962)</p> <hr/> <p>The S 1/16 sec. cor. of sec. 19 only, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="border: none; margin: auto;"> <tr> <td style="border: none;"> </td> <td style="border: none;">S 1/16</td> </tr> <tr> <td style="border: none;"> </td> <td style="border: none;">S 19</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">1962</td> </tr> </table> </div> <p>from which the remains of bearing trees mkd. by Gawron</p> <p style="text-align: center;">A root hole, bears N. 24° E., 136.6 ft. dist., with decayed fir trunk, 20 ins. diam., lying alongside, with a healed blaze.</p> <p style="text-align: center;">A fir, 30 ins. diam., bears S. 74° E., 57.4 ft. dist., with a healed blaze.</p> <p>and a new bearing tree</p> <p style="text-align: center;">A fir, 11 ins. diam., bears N. 32° E., 28.1 ft. dist., mkd. S 1/16 S19 BT.</p> <p>The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:</p> <p style="text-align: center;">Latitude: 43° 27' 53.8" N. Longitude: 123° 27' 59.3" W.</p> <hr/>		S 1/16		S 19		1962
	S 1/16						
	S 19						
	1962						

Rehabilitation or Remonumentation of Certain Corner
Points, Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

F E E T

(Rehabilitating a corner established by
Williams R. Whipple, U.S. Deputy Surveyor, in 1891,
and rehabilitated by Joseph S. Gawron,
Cadastral Surveyor, in 1962)

The cor. of secs. 17, 18, 19, and 20, monumented with a
sandstone, 14 x10 x 5 ins., firmly set 8 ins. in the ground,
mkd. F on W. face, with an iron post, 1½ ins. diam., firmly set,
projecting 12 ins. above ground, plumbed over the original
stone, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 18	S 17
S 19	S 20
T 24 S	R 6 W
1959	

from which the remains of original bearing trees

A roothole, bears S. 69° W., 89.1 ft. dist., with fir
trunk, 25 ins. diam., lying alongside, with no marks
visible.

A decayed madrone stump, size indeterminate, bears
S. 21° E., 42.9 ft. dist., with no marks visible.

and the remains of bearing trees mkd. by the Douglas County
Surveyor's Office, in 1959, recorded in the Douglas County
Surveyor's Record of Government Corners Renewed,
T. 24 S., R. 6 W., Point Identifier No. 200400, and reported by
Gawron

A dead madrone, 16 ins. diam., bears N. 51° E.,
45.5 ft. dist., with no marks visible.

A dead madrone, 15 ins. diam., bears S. 17½° E.,
66.0 ft. dist., with a healed blaze.

A dead madrone, 11 ins. diam., bears N. 18° W.,
35.6 ft. dist., with no marks visible.

and the remains of a bearing tree mkd. by Gawron

A dead madrone, 7 ins. diam., bears S. 45° W.,
51.5 ft. dist., with no marks visible. (Record,
S. 47° W.)

**Rehabilitation or Remonumentation of Certain Corner
Points, Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET	
	<p>and new bearing trees</p> <p>A fir, 14 ins. diam., bears N. 22¼° E., 26.2 ft. dist., mkd. T24S R6W S17 BT.</p> <p>A fir, 13 ins. diam., bears S. 7½° E., 14.4 ft. dist., mkd. T24S R6W S20 BT.</p> <p>A fir, 7 ins. diam., bears S. 54¾° W., 14.2 ft. dist., mkd. T24S R6W S19 BT.</p> <p>A fir, 10 ins. diam., bears N. 63½° W., 11.0 ft. dist., mkd. T24S R6W S18 BT.</p> <p>This cor. is located at the cor. of woven wire fences extending North, South, East, and West.</p> <p>The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:</p> <p>Latitude: 43° 28' 32.8" N. Longitude: 123° 26' 45.9" W.</p> <hr/> <p style="text-align: center;">(Remonumenting a corner established by Williams R. Whipple, U.S. Deputy Surveyor, in 1891)</p> <hr/> <p>The cor. of secs. 7, 8, 17, and 18, monumented with an X chiseled into solid sandstone bedrock, and the marks 7, 8, 17, and 18 visible around it, from which the remains of orig. bearing trees</p> <p>A decayed fir stump, size indeterminate, bears N. 18½° E., 42.9 ft. dist., with no marks visible.</p> <p>A sawed fir stump, 27 ins. diam., bears S. 33¾° E., 63.1 ft. dist., with a healed blaze. (Record, 66.7 ft.)</p> <p>A sawed fir stump, 27 ins. diam., bears S. 65¾° W., 60.7 ft. dist., with no marks visible. (Record, S. 58° W.)</p> <p>and the remaining bearing trees mkd. by the Douglas County Surveyor's Office, in 1959, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 24 S., R. 6 W., Point Identifier No. 200500</p>

**Rehabilitation or Remonumentation of Certain Corner
Points, Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon**

FEET

A madrone, 11 ins. diam., bears N. $8\frac{3}{4}^{\circ}$ E., 45.2 ft. dist., with a healed double blaze.

A fir, 25 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ W., 47.1 ft. dist., with a healed double blaze.

At the corner point

Set an alum. rod, 15 ins. long, $\frac{3}{4}$ in. diam., cemented 5 ins. into a drill hole, 1 in. diam., centered over the X in the sandstone bedrock, with an alum. cap mkd.

T 24 S	R 6 W
S 7	S 8
S 18	S 17
2003	

This cor. is located in center of a clearing, 120 ft. diam., on a moderate W. slope.

The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade GPS receiver (Trimble GEO Explorer 3) observation, is as follows:

Latitude: $43^{\circ} 29' 24.8''$ N. Longitude: $123^{\circ} 26' 46.1''$ W.
