

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF THE
CORNER OF SECTIONS 19, 20, 29, AND 30
TOWNSHIP 25 SOUTH, RANGE 3 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated February 22, 2002, approved
February 22, 2002, which provided for the
rehabilitation included under Group No. 2000, and
Assignment Instructions dated September 9, 2002.

Survey commenced September 12, 2002

Survey completed September 12, 2002

T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation of the cor. of secs. 19, 20, 29, and 30, township 25 south, range 3 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2002, under Group No. 2000, Oregon.

The rehabilitation of the cor. of secs. 19, 20, 29, and 30 was made at the request of the Roseburg District Manager for the administrative purposes of the Bureau of Land Management.


Each new bearing tree has a 2½ x ¼ inch magnetic nail (Mag-Nail) driven at the base on the right side-center, unless otherwise noted in the corner description.

The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "HINKLE CREEK, OREG.", Provisional Edition, dated 1987, is 19° East.

**Rehabilitation of the Corner of Sections
19, 20, 29, and 30,
T. 25 S., R. 3 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by
Labon H. Wheeler, U.S. Deputy Surveyor, in 1883,
and reestablished by Norman D. Price, Associate
Cadastral Engineer, in 1944)

The cor. of secs. 19, 20, 29, and 30, perpetuated by Milo E. Godfrey, Douglas County Surveyors Office, in 1963, recorded in the Douglas County Surveyors Record of Government Corners Renewed, T. 25 S., R. 3 W., Point Identifier No. 200300; monumented with an iron post, 2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.



1944

from which the remains of the bearing trees mkd. by Price.

A fir stump, 45 ins. diam., bears N. 80° E., 24.6 ft. dist., with no marks visible. (Record, 23.1 ft.)

Rehabilitation of the Corner of Sections
19, 20, 29, and 30,
T. 25 S., R. 3 W., Willamette Meridian, Oregon

FEET	
	<p>A fir stump, 52 ins. diam., bears S. 64¼° E., 29.0 ft. dist., with scribe marks S29 CS BT visible on open blaze. (Record, S. 74¼° E.) Note: Godfrey indicates this was a stump, 42 ins. diam., in 1963 and he rescribed it S20 CS BT.</p> <p>A roothole bears N. 88° W., 43.6 ft. dist., with fallen trunk, 42 ins. diam., species indeterminate, lying alongside, with a healed blaze. (Record, fir, N. 85° W.)</p> <p>and the remains of the bearing trees mkd. by Godfrey.</p> <p>A cedar, 21 ins. diam, bears S. 83½° W., 100.6 ft. dist., with healed blaze.</p> <p>A sawed fir stump, 26 ins. diam., bears N. 80° W., 108.7 ft. dist., with fragmentary scribe marks visible on a partially healed blaze.</p> <p>and new bearing trees</p> <p>A fir, 13 ins. diam., bears N. 63° E., 19.1 ft. dist., mkd. T25S R3W S20 BT.</p> <p>A fir, 16 ins. diam., bears S. 41¼° E., 39.5 ft. dist., mkd. T25S R3W S29 BT.</p> <p>A fir, 10 ins. diam., bears N. 61¼° W., 32.9 ft. dist., mkd. T25S R3W S19 BT.</p> <p>The geographic position (NAD 1983) of this cor., as determined by a differentially corrected, mapping grade direct GPS observation is as follows.</p> <p>Latitude: 43° 22' 36.29" N., Longitude: 123° 05' 22.57" W.</p> <hr/>