

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF
THE CORNER OF
TOWNSHIPS 29 AND 29½ SOUTH, RANGES 7 AND 8 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

A. Bert Skeesick, Cadastral Surveyor

Under Special Instructions dated February 22, 2002,
approved February 22, 2002, which provided for the
rehabilitation included under Group No. 2000,
and Assignment Instructions dated September 3, 2002

Survey commenced September 3, 2002

Survey completed September 3, 2002

Tps. 29 & 29½ S., Rs. 7 & 8 W., Willamette Meridian, Oregon

FEEET	<p>The following field notes describe the rehabilitation of the cor. of townships 29 and 29½ south, ranges 7 and 8 west, Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2002, under Group No. 2000, Oregon.</p> <p>The rehabilitation of the corner of townships 29 and 29½ south, ranges 7 and 8 west, was made at the request of the Roseburg District Manager for the administrative purposes of the Bureau of Land Management.</p> <p>Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag Nail) driven at the base on right side center, unless otherwise noted in the corner description.</p> <p>The mean magnetic declination as taken from U.S. Geological Survey quadrangle map "LIVE OAK MOUNTAIN, OREGON", Provisional Edition, dated 1990, is 18° East.</p> <hr/> <p style="text-align: center;">Rehabilitation of the Corner of Tps. 29 and 29½ S., Rs. 7 and 8 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Rehabilitating a corner established by Dennis Hathorn, U.S. Deputy Surveyor, in 1855, perpetuated by Fred Mensch, U.S. Cadastral Engineer, in 1924)</p> <hr/> <p>The cor. of Tps. 29 and 29½ S., Rs. 7 and 8 W., monumented with an iron post, 3 ins. diam., firmly set, flush with the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">T29S</td> <td style="padding: 2px 5px;">T29½S</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">R8W</td> <td style="padding: 2px 5px;">R7W</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 2px 5px;">S36</td> <td style="padding: 2px 5px;">S31</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px 5px;">1924</td> </tr> </table> <p>from which the remains of an orig. bearing tree</p> <p style="padding-left: 40px;">A sawed and decayed fir stump, 27 ins. diam., bears S. 1° W., 12.5 ft. dist., with healed blaze. (The marks had been obliterated by William. H. Byars, U.S. Deputy Surveyor, in 1883.)</p> <p>and the remains of bearing trees mkd. by Mensch</p> <p style="padding-left: 40px;">A decayed stump, size and species indeterminate, bears N. 59° E., 33.0 ft. dist., with no marks visible. (Record, fir)</p>	T29S	T29½S	R8W	R7W	S36	S31	1924	
T29S	T29½S								
R8W	R7W								
S36	S31								
1924									

Rehabilitation of the Corner of Tps. 29 and 29½ S.,
Rs. 7 and 8 W., Willamette Meridian, Oregon

FEET	
	<p>A fir snag, 29 ins. diam., bears N. 4° W., 27.1 ft. dist., with no scribe marks visible on opened blaze.</p> <p>and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, in 1962, recorded in the Douglas County Surveyor's Record of Government Corners Renewed, T. 29½ S., R. 7 W., Point Identifier No. 100100</p> <p>A fir snag, 15 ins. diam., bears N. 15° E., 33.7 ft. dist., with scribe marks 1/2 SR7W S31 CS BT visible on partially healed double blaze.</p> <p>A fir, 23 ins. diam., bears S. 72° W., 37.1 ft. dist., with healed double blaze.</p> <p>and new bearing trees</p> <p>A fir, 20 ins. diam., bears N. 45° E., 22.8 ft. dist., mkd. T291/2S R7W S31 BT.</p> <p>A fir, 10 ins. diam., bears N. 59½° W., 9.2 ft. dist., mkd. T29S R8W S36 BT.</p> <p>The geographic position (NAD 1983) of this cor. as determined by a differentially corrected, mapping grade GPS receiver, (Trimble GEO Explorer 3), observation, is as follows:</p> <p>Latitude: 42° 59' 50.87" North, Longitude: 123° 34' 59.06" West</p> <hr/>