

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

FIELD NOTES
OF THE
REHABILITATION OF CERTAIN
CORNER POINTS ON THE NORTH BOUNDARY AND SUBDIVISIONAL LINES,
TOWNSHIP 30 SOUTH, RANGE 6 WEST,
OF THE WILLAMETTE MERIDIAN,
IN THE STATE OF OREGON.

EXECUTED BY

Timothy J. Moore, Cadastral Surveyor

Robert H. Browning, Surveying Technician

Under Special Instructions dated February 22, 2002,
approved February 22, 2002,
which provided for the rehabilitation included under Group No. 2000,
and Assignment Instructions dated June 26, 2002.

Survey commenced June 26, 2002

Survey completed June 26, 2002

T. 30 S., R. 6 W., Willamette Meridian, Oregon

FEET

The following field notes describe the rehabilitation of certain corner points on the north boundary and subdivisional lines, township 30 south, range 6 west, of the Willamette Meridian, Oregon, as provided for in the Special Instructions dated February 22, 2002, under Group No. 2000, Oregon.

The rehabilitation of the certain corner points, was made at the request of the Roseburg District Manager, for the administrative purpose of the Bureau of Land Management.

Each new bearing tree has a 2½ inch x ¼ inch magnetic nail (Mag-Nail) driven at the base right side-center.

The mean magnetic declination as taken from U.S. Geological Survey quadrangle map, "WINSTON, OREG.", Provisional Edition, dated 1987, is 19° East

**Rehabilitation of a Certain Corner Point, North Boundary,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by Nathaniel Ford, U.S. Deputy Surveyor, in 1854, erroneously reestablished by Hans W. Thielsen and C. Albert White, Cadastral Surveyors, in 1958-59, and correctively reestablished by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, in 1980)

The 1/4 sec. cor. of sec. 4 only, on the N. bdy of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 7 ins. above ground, with brass cap mkd.

1/4 S 4
T 30 S R 6 W
1958
80

from which the remains of a bearing tree mkd. by Thielsen and White and reported by Jelley and Rogers

A fir snag, 18 ins. diam., bears S. 50° W., 38.6 ft. dist., with a healed blaze. (Record S. 55½° W., 37.3 ft.)

and a bearing tree not of record

A fir, 11 ins. diam., bears S. 34¾° E., 9.1 ft. dist., with a healed blaze.

**Rehabilitation of a Certain Corner Point, North Boundary,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

F E E T

and a new bearing tree

A fir, 8 ins. diam., bears S. 66° W., 11.5 ft. dist.,
mkd. 1/4 S4 BT.


The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR Global Positioning System (GPS), utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:

Latitude: 42° 59' 55.43" N., Longitude: 123° 24' 57.96" W.

**Rehabilitation of a Certain Corner Point, Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon**

(Rehabilitating a corner established by Addison R. Flint,
U.S. Deputy Surveyor, in 1855, and reestablished
by Lynn M. Roseberry, Cadastral Surveyor, in 1967)

The cor. of secs. 3, 4, 9, and 10, monumented with an iron post,
2½ ins. diam., firmly set, projecting 3 ins. above ground, with
brass cap mkd.



from which the remaining bearing trees mkd. by Roseberry

A fir, 34 ins. diam., bears N. 13½° E., 44.6 ft. dist., with
a healed blaze.

A fir, 21 ins. diam., bears N. 65¼° W., 82.7 ft. dist., with
a healed blaze. (Record 85.8 ft.)

and new bearing trees

A fir, 6 ins. diam., bears S. 78½° E., 26.6 ft. dist.,
mkd. T30S R6W S10 BT.

A fir, 12 ins. diam., bears S. 22¾° W., 33.1 ft. dist.,
mkd. T30S R6W S9 BT.

Rehabilitation of a Certain Corner Point, Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

FEET	<p>From this point, an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, reported by Roseberry, bears S. 31° 02' 00" E., 35.8 ft. dist. (Record, S. 31¼° E., 36.3 ft.)</p> <p>The geographic position (NAD 1983 (CORS)) of this cor. as determined by NAVSTAR GPS, utilizing dual frequency, carrier phase GPS receivers, (Trimble 5700), relative to the National Spatial Reference System, is as follows:</p> <p>Latitude: 42° 59' 05.80" N., Longitude: 123° 24' 23.01 W.</p> <hr/>
------	--